

LA-UR-04-5921

*Approved for public release;
distribution is unlimited.*

Title: MCNP5_RSICC_1.30

Author(s): MCNP Monte Carlo Team, X-5
Los Alamos National Laboratory

Submitted to:



Los Alamos National Laboratory, an affirmative action/equal opportunity employer, is operated by the University of California for the U.S. Department of Energy under contract W-7405-ENG-36. By acceptance of this article, the publisher recognizes that the U.S. Government retains a nonexclusive, royalty-free license to publish or reproduce the published form of this contribution, or to allow others to do so, for U.S. Government purposes. Los Alamos National Laboratory requests that the publisher identify this article as work performed under the auspices of the U.S. Department of Energy. Los Alamos National Laboratory strongly supports academic freedom and a researcher's right to publish; as an institution, however, the Laboratory does not endorse the viewpoint of a publication or guarantee its technical correctness.

Form 836 (8/00)

Patch to Update version MCNP5_RSICC_1.20 to version MCNP5_RSICC_1.30

X-5 Monte Carlo Team
Diagnostics Applications Group
Los Alamos National Laboratory

August 2004

This patch (patch-MCNP5_RSICC_1.20_to_1.30) updates the Radiation Safety Information Computational Center (RSICC) release of MCNP5 from version MCNP5_RSICC_1.20 to version MCNP5_1.30. The issues addressed by this patch as well as instructions on applying this patch are given below. This patch can be downloaded from:

www-xdiv.lanl.gov/x5/MCNP/mc/patch-MCNP5_RSICC_1.20_to_1.30

ISSUES

The following items list the new features, bug fixes and minor code improvements implemented in the new release. The T# or R# following the items are the tracking numbers for SQA purposes. Prior to being fixed, four of the following issues (bug fixes # 4, 9, 10, & 13) resulted in incorrect answers.

New Features:

- 1) Explicit 8 byte integer handling of nps and related variables. These modifications allow MCNP5 to read 8 byte integer values (.ie. from 2.4 billion to ~1E19) for certain input cards and to run these large number of histories. 8 Byte integer input is allowed for both entries on the NPS card, the ndp, ndm and dmmp entries on the PRDMP card, the seed, stride and hist entries on the RAND card, the nps and max keywords on the PTRAC card, the freq entry on the MPLOT card, and the DBUG keyword on the command line. T# 4904
- 2) Lattice Tally Enhancements. For very specific lattice geometry problems, where many tally features are not used, runtimes can be reduced by more than a factor of 100 by making simple assumptions about the tally routines. This functionality is most commonly used for voxel phantom geometries in problems which use F4 tally cards, DE DF cards and a single multiplier on the FM card to calculate dose or kerma throughout a voxel phantom. This new feature will automatically use the faster coding if the given criteria are met. Tally values will still track the slower version. This capability can be controlled with the SPDTL card. T# 5628
- 3) Improvements to the fmesh tally. Previously, the user had to specify the material on the FM card whose cross sections are used to calculate the mesh bin values. These cross sections were used for the entire mesh, even if the mesh covered several different materials in the geometry. Now, if you enter 0 as the material number for an FM card associated with the mesh tallies, MCNP will use the cross sections of the material in which the particle is traveling to calculate the bin values. Thus material dependent quantities that are computed with the use of the FM card (ie, neutron heating) can be calculated using mesh tallies that cover more than one material. T# 5588

- 4) Support for MPI on Mac OS X. The configuration file for Mac OS X systems (MCNP5/Source/config/Darwin.gcf) was enhanced to include options for compiling an MPI version of MCNP5 using LAM-MPI. T# 6015.

Bug Fixes:

- 1) Fixed bug in code sequence during cross-section interpolation. Does not affect regression test suite. Changes affect acecos.F90 R#
- 2) Fix mesh tally RUNTPE file read bug. Previous versions crash when using mesh tallies with a dose response function and limiting the number of dumps to 2. Changes affect src/fmesh_mod.F90. T# 5070
- 3) Decreased lower array index for IBNK to zero. Previous lower array index (1) caused MCNP5 to crash on some Windows PC systems. Reported by Ken Moy, DOE-NV. Changes affect src/imcn.F90, src/msgtsk.F90, and src/tpofil.F90 T# 5069
- 4) DXTRAN did not work properly if a DXTRAN sphere is located within repeated structure geometry (including lattices). Changes affect src/acegam.F90 src/brems.F90 src/collpn.F90 src/dxdiag.F90 src/dxtran.F90 src/dxtran_mod.F90 src/electr.F90 src/flaug.F90 src/hstory.F90 src/mgcoln.F90 src/startp.F90 src/summary.F90 src/ttbr.F90 src/ybbsp.F90 T# 4760
- 5) Change error message "CFS fetching no longer possible" to "cannot find xs library file specified in xsdir". Changes affect ffetch.F90 T# 5141
- 6) Make changes in dotcomm communications library to allow use with LAMPI. Changes affect dotcomm/include/dotcomm.h dotcomm/src/internals/dotcommi_binary_op.c dotcomm/src/internals/dotcommi_convert.c dotcomm/src/internals/dotcommi_mpi.h dotcomm/src/internals/dotcommi_sizeof.c
- 7) Change 'lock_var' to type i8knd to allow CONFIG='cheap omp' on some platforms. Changes affect src/smmp.F90 T# 5160
- 8) Fix crash when transformations are applied to RPP macrobodies. Change to src/oldcd1.F90 T# 5785
- 9) Fix mesh tally material number bug. In some cases, the incorrect material was being identified internal to the code when an FM card was used to modify a mesh tally. This would occur if a) the material specified on the FM card was not used in the problem geometry, and b) the material index number (the order number in the INP file) did not match the material number. Changes affect stuff.F90 fmesh_mod.F90 T# 5629
- 10) Fix bug with lin-lin interpolation with DE DF cards and mesh tallies. Previously, if lin-lin interpolation was used on the DE DF cards which were modifying mesh tallies, the tally results would be all zero. Changes affect src/fmesh_mod.F90 and src/nextit.F90. T# 6002.
- 11) Fix bug in error message tally number for mesh tallies. Correct tally numbers for mesh tallies are not printed in warning messages. Changes affect fmesh_mod. #T 5999.
- 12) Fix bug in Doppler broadening routine for sampling of momenta for slightly glancing interactions. T# 4965.
- 13) Fixed bug that caused incorrect mesh tallies results when used with an FM card that specifies an attenuator or special multiplier set. T#6016.
- 14) Removed the erroneous warning message stating that a transformation is not used if it is used only for a mesh tally. T# 6087.

- 15) Fixed a bug in the geometry plotter that caused the theta bin boundaries of the weight-window mesh to be plotted in the incorrect location. T# 6100

Minor Coding Improvements

- 1) Changed GNU make 'findstring' conflict of omp and Compaq. Use GNU make command 'filer' instead. Changes affect config/Windows_NT.gcf. T# 4941
- 2) Removed outdated preprocessor macro GKSSIM. Changes affect all config/*.gcf files and src/ginst.F90 src/gkssim.F90 src/main.F90 and src/pconst.F90. T# 4860
- 3) Removed outdated preprocessor macro QWIN LAHEY PCDOS. LAHEY Winteracter graphics package is no longer supported, and all MCNP5 plotting executables on any platform must be compiled with an X11 graphics library. Changes affect src/FILE.list src/getexm.F90 src/getxst.F90 src/gxsub.F90 src/isourc.F90 src/ixsdir.F90 src/keypro.F90 src/mc.c src/mcplot_module.F90 src/newcd1.F90 src/newcrd.F90 src/plotg.F90 src/sread.F90 src/stuff.F90 src/tallyh.F90 src/tekdrv.F90 src/track.F90 src/ttyint.F90 src/volume.F90 src/xsgen.F90. T# 4850
- 4) Changed !\$OMP ATOMIC directive to !\$OMP CRITICAL. Changes affect src/bankit.F90 src/errprn.F90 src/prlost.F90. T# 4921
- 5) Added several named constants to mcnp_params.F90. T# 4900
- 6) Changed some format statements from lpeX.Y to esX.Y
- 7) Added _dknd to some numeric constants.
- 8) Changed the parameter huge to huge_real to allow the use of Fortran 90 intrinsic function huge(). T# 4900
- 9) Removed pack and unpack string routines in src/internals/mpi.
- 10) Added nullify statements for allocated arrays. T# 5020
- 11) Explicitly calculate maximum record length for the MESHTAL file. T# 5304
- 12) Change non-standard control edit descriptor used in format statement in fmesh_mod. T# 5942.
- 13) Expanded Table 32 to provide additional information regarding FM cards used with mesh tallies. T# 6024.
- 14) Support for Intel Fortran 95, version 7.1 for Windows PCs. T# 6026

INSTALLATION INSTRUCTIONS

For best results apply this patch to an unmodified copy for the November, 2003 RSICC release of MCNP5 (MCNP5_RSICC_1.20). This patch may not work with a modified version of MCNP5_RSICC_1.20. To verify the version number of your copy of the MCNP5 source see the file MCNP5/Source/config/VC_info.gcf'. This file should contain the following:

```
# --- Automatically Generated Version Control Information file
# --- Thread Name
THREAD = MCNP5_RSICC
# --- Thread Version Number
THD_VERS = 1.20
```

After verifying that you have an unmodified copy of MCNP5_RSICC_1.20 perform the following steps to install the patch.

- 1) Verify that you have the GNU patch utility installed by issuing the command “patch –v”. You should see output that looks similar to the output below. Note the version may be different.

```
$ patch -v
patch 2.5.8
Copyright (C) 1988 Larry Wall
Copyright (C) 2002 Free Software Foundation, Inc.
```

This program comes with NO WARRANTY, to the extent permitted by law. You may redistribute copies of this program under the terms of the GNU General Public License. For more information about these matters, see the file named COPYING.

written by Larry Wall and Paul Eggert

- 2) Save the patch file “patch-MCNP5_RSICC_1.20_to_1.30” to the MCNP5 directory.
- 3) Change your working directory to the MCNP5 directory.
- 4) Apply the patch with the following command

```
$ patch -p1 < patch-MCNP5_RSICC_1.20_to_1.30
```

- 5) Rebuild the MCNP5 executable.
- 6) Run the Regression Test suite.

On Unix/Linux platforms, cd to the MCNP5/Testing/Regression directory, then
\$ make test1

On Windows PCs, cd to the MCNP5/Installation directory, then
> cleanup
> runprob

- 7) Compare to expected answers. Since the expected answer file templates are stored in a .tar file, they cannot be updated with the patch utility. The following differences in the output files are expected. No differences in the metal files should be present.

```
diff inp01o outp01
1987,1988c1987
< binary file inp01p written with 694 events
< from 100 histories.
---
> binary file inp01p written with 694 events from 100 histories.
```

```

diff inp02o outp02
2038,2039c2038
<  ascii file inp02p  written with      194 events
<                               from      194 histories.
---
>  ascii file inp02p  written with      194 events from      194 histories.

diff inp08o outp08
1258,1259c1258
<  ascii file inp08p  written with      0 events
<                               from      0 histories.
---
>  ascii file inp08p  written with      0 events from      0 histories.

Diff inp15o outp15
43,44d42
<  comment. lattice speed tally modifications will not be used.
<

diff inp16o outp16
109,110d108
<  comment. lattice speed tally modifications will not be used.
<

diff inp17o outp17
51,52d50
<  comment. lattice speed tally modifications will not be used.
<

diff inp18o outp18
1504,1505c1504
<  ascii file inp18p  written with      3 events
<                               from      3 histories.
---
>  ascii file inp18p  written with      3 events from      3 histories.

diff inp23o outp23
1261,1262c1261
<  ascii file inp23p  written with     253 events
<                               from      6 histories.
---
>  ascii file inp23p  written with     253 events from      6 histories.

diff inp24o outp24
81,82d80
<  comment. lattice speed tally modifications will not be used.
<

diff inp36o outp36
126c126
<    3      3  0.00000E+00  3.14159E+00
---
>    3      3  0.00000E+00  0.00000E+00  infinite
128c128
<    5      5  0.00000E+00  8.04248E+02
---
>    5      5  0.00000E+00  0.00000E+00  infinite

diff inp38o outp38
137,138d136
<  comment. lattice speed tally modifications will not be used.
<
573,575c571,573
<    1      1  0.00000E+00  1.25664E+05
<    2      2  0.00000E+00  0.00000E+00  asymmetric
<    3      3  0.00000E+00  0.00000E+00  asymmetric
---
>    1      1  0.00000E+00  1.88496E+05
>    2      2  0.00000E+00  4.80664E+04
>    3      3  0.00000E+00  4.80664E+04
585c583

```

```
< 13      13  0.00000E+00  0.00000E+00  asymmetric
---
> 13      13  0.00000E+00  0.00000E+00  infinite
```

```

# patch-MCNP5_RSICC_1.20_to_1.30 --- LA-UR-04-5921
#
# Patch to create MCNP5_RSICC_1.30 from MCNP5_RSICC_1.20
#
# USAGE
# -----
# To apply this patch to an unmodified copy of the November, 2003 RSICC
# release of MCNP5 (CCC-710), MCNP5_RSICC_1.20, follow the directions
# below.
#
# 1) Verify that you have the GNU patch utility installed by issuing
# the command "patch -v". You should see output that looks similar
# to the output below. Note that the version may be different.
#
# $ patch -v
# patch 2.5.8
# Copyright (C) 1988 Larry Wall
# Copyright (C) 2002 Free Software Foundation, Inc.
#
# This program comes with NO WARRANTY, to the extent permitted by law.
# You may redistribute copies of this program
# under the terms of the GNU General Public License.
# For more information about these matters, see the file named COPYING.
#
# written by Larry Wall and Paul Eggert
#
# 2) Make sure there are not carriage return (^M) characters in
# Source/dotcomm/src/dotcomm_pack.F90 and
# Source/dotcomm/src/internals/dotcommi_unpackstring.c
# The ^M characters may make the patch fail on some platforms.
# Simple editors such as vi or xemacs can be used to identify ^Ms and remove them.
# Some simple programs, such as to_unix or dos2unix will also work.
#
# 3) Save the patch file "patch-MCNP5_RSICC_1.20_to_1.30" to the MCNP5
# directory.
#
# 4) Change your working directory to the MCNP5 directory.
#
# 5) Apply the patch with the following command:
#
# $ patch -p1 < patch-MCNP5_RSICC_1.20_to_1.30
#
# 6) Recompile MCNP5.
#
# Note: This patch may fail if you have modified MCNP5.
# -----
#
Prereq: 1.20
diff -Naurd MCNP5/Source/config/VC_info.gcf MCNP5_new/Source/config/VC_info.gcf
--- MCNP5/Source/config/VC_info.gcf Wed Nov 5 17:23:12 2003
+++ MCNP5_new/Source/config/VC_info.gcf Thu Jul 22 15:06:14 2004
@@ -2,4 +2,4 @@
# --- Thread Name
THREAD = MCNP5_RSICC
# --- Thread Version Number
-THD_VERS = 1.20
+THD_VERS = 1.30
diff -Naurd MCNP5/Source/config/AIX.gcf MCNP5_new/Source/config/AIX.gcf
--- MCNP5/Source/config/AIX.gcf 2003-04-30 20:08:44.000000000 -0600
+++ MCNP5_new/Source/config/AIX.gcf 2004-07-22 15:06:14.000000000 -0600
@@ -57,7 +57,7 @@

# --- Plot option.
ifeq (plot,$(findstring plot,$(CONFIG)))
- DEF_PLOT ==-DPLOT -DMCPLOT -DGKSSIM -DXLIB
+ DEF_PLOT ==-DPLOT -DMCPLOT -DXLIB

ifeq (,$(premake))
PLOTLIBS = -lX11
diff -Naurd MCNP5/Source/config/Darwin.gcf MCNP5_new/Source/config/Darwin.gcf
--- MCNP5/Source/config/Darwin.gcf 2003-11-05 17:23:12.000000000 -0700

```



```

+++ MCNP5_new/Source/config/Darwin.gcf          2004-07-22 15:06:14.000000000 -0600
@@ -11,26 +11,30 @@
# Must have the Developers Toolkit + X11
#   installed.
#
-# As of 4/28/2003, this was only tested on a
-# PowerBook G4 running Mac OS X (10.2.4)
+#This was tested on a PowerBook G4 running
+# * Mac OS X 10.2.4
+# * Mac OS X 10.3
+#
+# For MPI version, use LAM-MPI (not MPICH)
+# See instructions at the end of this file.
#
#####

# -----COMPILER OPTIONS-----
-FPPmcpn := $(shell pwd)/../config/fpp
+FPPmcpn = $(CONFIG_DIR)/fpp

# --- Configuration
export CONFIG
ifeq (,$(CONFIG))
- CONFIG = cheap seq absoft gcc
+ CONFIG = cheap seq absoft gcc plot
endif
ifeq (default,$(CONFIG))
- CONFIG = cheap seq absoft gcc
+ CONFIG = cheap seq absoft gcc plot
endif

# Compilers
-FCOMPILER = ABSOFT
-CCOMPILER = gcc
+ FCOMPILER = ABSOFT
+ CCOMPILER = gcc

# --- path to cross-sections
ifeq (,$(DATAPATH))
@@ -39,31 +43,62 @@

# --- Plot option.
ifeq (plot,$(findstring plot,$(CONFIG)))
- DEF_PLOT = -DPLOT -DMCPLOT -DGKSSIM -DXLIB
+ DEF_PLOT = -DPLOT -DMCPLOT -DXLIB
+
+ ifeq (,$(premake))
+   PLOTLIBS = -L/usr/X11R6/lib -lX11
+ else
+   menuglib := $(subst lib,,$(menuglib))
+   menuglib := $(subst .so,,$(menuglib))
+   menuglib := $(subst .a,,$(menuglib))
+   PLOTLIBS = -L$(menugpath) -l$(menuglib)
+ endif
+
endif

##### ABSOFT with gcc #####

ifeq (ABSOFT,$(findstring ABSOFT,$(FCOMPILER)))

- ABSOFT    ?= '/Applications/Absoft'
- CCOMPILER ?= gcc
+ ABSOFT    = /Applications/Absoft

# --- Optimize/Debug options.
ifeq (debug,$(findstring debug,$(CONFIG)))
- FDEBUG = -g
- CDEBUG = -g
- FOPT   =
- COPT   =

```

```

+ FDEBUG =
+ CDEBUG =
+ FOPT = -g -Z1643 -Z1644 -B18 +B51 -et
+ COPT = -g -fno-common -malign-natural
else
FDEBUG =
CDEBUG =
- FOPT = -O1 -Z1643 -Z1644
- COPT =
+ FOPT = -O1 -Z1643 -Z1644 -B18 +B51 -et
+ COPT = -O1 -fno-common -malign-natural
endif

- INCLUDE_DIRS = -I'/usr/X11R6/include'
- PLOTLIBS = -L/usr/X11R6/lib -lX11
+ # --- Distributed Multiprocessing options
+ # --- MPI option.
+ ifeq (mpi,$(findstring mpi,$(CONFIG)))
+ MPICH_ROOT = /usr/local/lam
+ DOTCOMMROOT = ../dotcomm
+ DOTCOMM_INTERNAL = mpi
+ DMMP_NAME = -DDMMP_NAME=$Q$(EXEC)$Q
+ DEF_DMMP = -DMULTP -DMPI -DMPICH
+ INC_DMMP_INTERNAL=
+ INC_DMMP =
+ LIB_DMMP = -L$(DOTCOMMROOT)/src -ldotcomm
+ LIBDOTCOMM = $(DOTCOMMROOT)/src/libdotcomm.a
+ MOD_DMMP = -p ../../src
+ MPIO =
+ MPI = mpich
+ MPICH = -DMPICH
+ MPIFC=$(MPICH_ROOT)/bin/mpif77
+ MPICC=$(MPICH_ROOT)/bin/mpicc
+ else
+ MPIFC=$(FC)
+ MPICC=$(CC)
+ endif
+
+ INCLUDE_DIRS = -I/usr/X11R6/include

DEF_MACH = -DMACOSX -DABSOFT -DDEC -DCHEAP $(ROSSI)

@@ -71,9 +106,10 @@
PREPROCESS := yes
MISC = export ABSOFT; ABSOFT=$(ABSOFT);

- FC = $(MISC) $(ABSOFT)/BIN/f90
+ FC = $(MISC) $(ABSOFT)/bin/f90
FFLAGS = $(FDEBUG) $(FOPT) $(SMMP) $(MPIO) \
- -N11 -YEXT_NAMES=LCS -YEXT_SFX=_ -YCFRL=1
+ -YEXT_NAMES=LCS -YEXT_SFX=_ -YCFRL=1 \
+ -I../../src -I. -p . -p ../dotcomm/src
OBJF = .o
MOD_INC = -I

@@ -82,12 +118,11 @@
I = .f95

CPPFLAGS = $(DEFS)
- CFLAGS = -o $(<:..c=$(OBJC)) $(CDEBUG) $(COPT) $(WIN32)
+ CFLAGS = $(CDEBUG) $(COPT)
OBJC = .o
CC = /usr/bin/gcc
- WIN32 =

- LD = $(FC)
+ LD = $(MPIFC)
LDLFLAGS = $(FFLAGS) -lU77
OUT = -o #

@@ -95,6 +130,8 @@

```

```

endif

# --- some other setup stuff
+AR      = /usr/bin/ar
+ARFLAGS = -rvus
ECHO     = echo
RM       = /bin/rm
MV       = /bin/mv
@@ -104,3 +141,140 @@

export
# --- End of Make Include for Darwin
+
+#####
+#
+# Instructions for installing LAM-MPI & MCNP5 for
+# parallel processing on a Mac OS X cluster
+#
+#      F Brown, 5/26/2004
+#
+# Notes:
+#
+# 1) You must make sure that the options used for compiling
+#    & installing LAM-MPI and MCNP5 are consistent. The
+#    instructions below are for installing the LAM-MPI package
+#    (NOT MPICH) using the Absoft Fortran-90 compiler & gcc.
+#
+# 2) I tried using MPICH from the ANL website. While it
+#    installed correctly & passed tests, and linked OK with
+#    MCNP5, there were SIGBUS error interrupts when trying
+#    to execute. This problem has not yet been resolved.
+#    For now, it is necessary to use LAM-MPI rather than
+#    MPICH for parallel MCNP5 on Mac OS X clusters.
+#
+# 3) Our convention for compiling mixed Fortran & C is to
+#    set options so that external names for the linker are
+#    lower case with an appended underscore. The Fortran
+#    options for doing this with Absoft F90 must be included
+#    with the FFLAGS environment variable used in compiling
+#    LAM-MPI.
+#
+# 4) LAM-MPI does not support F90 directly, just F77 & C.
+#    There are utilities called mpif77 and mpicc, but not
+#    mpif90. This is OK for use with MCNP5, however, since
+#    all MPI calls are made through the "dotcomm" routines,
+#    which use C at the lowest level.
+#
+# 5) We use the Abssoft F90 compiler, not the F77 compiler,
+#    for both LAM-MPI and MCNP5. For LAM-MPI, the FC environment
+#    variable is set to point to the Absoft Fortran-90 compiler.
+#    Then, invoking mpif77 really uses Fortran-90, not Fortran-77.
+#
+# 6) I installed LAM-MPI using the script shown below into
+#    the directory /usr/local/lam. Note that this directory
+#    is hardwired into the MCNP5 config information above in
+#    this file. If you install LAM-MPI in a different location,
+#    you must change the variable MPICH_ROOT above in this file.
+#
+# 7) After installing LAM-MPI, I "booted" LAM-MPI
+#    with the command "lamboot -v". See the LAM-MPI documentation.
+#    Also, make sure that /usr/local/lam/bin is in your PATH.
+#
+# 8) These lines must be inserted into
+#    MCNP5/Source/dotcomm/include/dotcomm.h
+#    after line #162 (#include "mpi.h"):
+#
+#    #ifdef LAM_MPI
+#    /* ----- */
+#    /* if using LAM-MPI, must add defines for Fortran datatypes */
+#    /* ----- */
+#    #define MPI_2REAL          ((MPI_Datatype) &lam_mpi_double)

```

```

+# #define MPI_2INTEGER      ((MPI_Datatype) &lam_mpi_long_long_int)
+# #define MPI_REAL          ((MPI_Datatype) &lam_mpi_float)
+# #define MPI_INTEGER       ((MPI_Datatype) &lam_mpi_long_int)
+# #endif
+#
+# 9) Then, MCNP5 was compiled this way:
+#     cd MCNP5/Source
+#     make CONFIG='absoft gcc mpi plot cheap' NMPI=3 install
+#
+# This compiles the code & runs the tests with 3 MPI processes
+# (master + 2 slaves). There will be lots of minor diffs in
+# the output files, but mctal files will match exactly,
+# except for problems 21, 28, 33, 34, 41. See the notes
+# printed at the end.
+#
+# -----
+# #!/bin/bash
+# #####
+# # Install LAM-MPI for use with MCNP5 #
+# #####
+#
+# #
+# # location of tarfile for LAM-MPI,
+# # downloaded from http://www.lam-mpi.org/7.0/download.php
+# #
+# LAMMPI_TGZ="/Users/fbrown/mcnp/LAM-MPI/lam-7.0.6.tar.gz"
+#
+# #
+# # directory for creating lam-7.06 dir & building LAM-MPI
+# #
+# LAMMPI_WORK="/Users/fbrown/mcnp/LAM-MPI"
+#
+# #
+# # target directory for installing LAM-MPI
+# #
+# # Note: do the following BEFORE running this script:
+# #     sudo mkdir /usr/local/lam
+# #     sudo chown fbrown /usr/local/lam
+# #
+# LAMMPI_TARGET="/usr/local/lam"
+#
+# echo ".....un-tar lam-mpi....."
+# cd $LAMMPI_WORK
+# rm -rf lam-7.0.6
+# tar xfz $LAMMPI_TGZ
+#
+# cd lam-7.0.6
+#
+# echo ".....set environment variables for lam-mpi....."
+# export CC
+# CC=gcc
+#
+# export CFLAGS
+# CFLAGS="-fno-common -malign-natural"
+#
+# export CXX
+# CXX=g++
+#
+# export FC
+# FC=/Applications/Absoft/bin/f90
+#
+# export FFLAGS
+# FFLAGS="-O1 -YEXT_NAMES=LCS -YEXT_SFX=_ -YCFRL=1 -B18 +B51 -et"
+#
+# export PATH
+# PATH="$LAMMPI_TARGET/bin:$PATH"
+#
+# rm -rf $LAMMPI_TARGET/*
+#
+# echo ".....configure, make, & install lam-mpi....."

```

```

+#
+# ./configure --prefix=$LAMMPI_TARGET --with-rsh="ssh -x"
+#
+# make
+#
+# make install
+#
diff -Naurd MCNP5/Source/config/IRIX64.gcf MCNP5_new/Source/config/IRIX64.gcf
--- MCNP5/Source/config/IRIX64.gcf 2003-04-30 20:08:46.000000000 -0600
+++ MCNP5_new/Source/config/IRIX64.gcf 2004-07-22 15:06:14.000000000 -0600
@@ -55,7 +55,7 @@

# --- Plot option.
ifeq (plot,$(findstring plot,$(CONFIG)))
- DEF_PLOT = -DPLOT -DMCPLOT -DGKSSIM -DXLIB
+ DEF_PLOT = -DPLOT -DMCPLOT -DXLIB

ifeq (,$(premake))
POTLIBS = -lX11
diff -Naurd MCNP5/Source/config/Linux.gcf MCNP5_new/Source/config/Linux.gcf
--- MCNP5/Source/config/Linux.gcf 2003-11-05 17:23:12.000000000 -0700
+++ MCNP5_new/Source/config/Linux.gcf 2004-07-23 15:49:18.000000000 -0600
@@ -53,7 +53,7 @@

# --- Plot option.
ifeq (plot,$(findstring plot,$(CONFIG)))
- DEF_PLOT = -DPLOT -DMCPLOT -DGKSSIM -DXLIB
+ DEF_PLOT = -DPLOT -DMCPLOT -DXLIB

ifeq (,$(premake))
POTLIBS = -L/usr/X11R6/lib -lX11
@@ -176,7 +176,7 @@

ifeq (debug,$(findstring debug,$(CONFIG)))
CDEBUG = -g
- FDEBUG = -g
+ FDEBUG = -g
FOPT = -O0
else
FOPT = -O1 -tp px
@@ -288,10 +288,14 @@

ARCH=$(shell uname -m)
ifeq (,$(premake))
- ifeq (ia64,$(findstring ia64,$(ARCH)))
- FC=efc
+ ifeq (ifort,$(findstring ifort,$(shell which ifort)))
+ FC=ifort
else
FC=ifc
+ ifeq (ia64,$(findstring ia64,$(ARCH)))
+ FC=efc
+ else
+ FC=ifc
+ endif
endif
CC=gcc
ifeq (mpi,$(findstring mpi,$(CONFIG)))
@@ -303,11 +307,11 @@
ifeq (ia64,$(findstring ia64,$(ARCH)))
# Itanium
FOPT = -O0
- FFLAGS = $(FDEBUG) $(FOPT) $(SMMP) -fpp2 -W0 -C90 -Vaxlib -static-libcxa $(I8R8)
$(MPIO)
+ FFLAGS = $(FDEBUG) $(FOPT) $(SMMP) -fpp2 -W0 -Vaxlib -static-libcxa $(I8R8)
$(MPIO)
else
# i386 and up
FOPT = -O0
- FFLAGS = $(FDEBUG) $(FOPT) $(SMMP) -fpp2 -pc64 -W0 -C90 -Vaxlib -static-libcxa
$(I8R8) $(MPIO)

```

```

+   FFLAGS   = $(FDEBUG) $(FOPT) $(SMMP) -fpp2 -pc64 -W0 -Vaxlib -static-libcxa $(I8R8)
$(MPIO)
endif
  OBJF      = .o
  DEF_FCOMPILER= -DINTEL
diff -Naurd MCNP5/Source/config/OSF1.gcf MCNP5_new/Source/config/OSF1.gcf
--- MCNP5/Source/config/OSF1.gcf      2003-11-05 17:23:12.000000000 -0700
+++ MCNP5_new/Source/config/OSF1.gcf  2004-07-22 15:06:14.000000000 -0600
@@ -52,7 +52,7 @@

  # --- Plot option.
  ifeq (plot,$(findstring plot,$(CONFIG)))
-   DEF_PLOT = -DPLOT -DMCPLOT -DGKSSIM -DXLIB
+   DEF_PLOT = -DPLOT -DMCPLOT -DXLIB
  PLOTLIBS = -lX11
endif

diff -Naurd MCNP5/Source/config/SunOS.gcf MCNP5_new/Source/config/SunOS.gcf
--- MCNP5/Source/config/SunOS.gcf     2003-04-30 20:08:50.000000000 -0600
+++ MCNP5_new/Source/config/SunOS.gcf  2004-07-22 15:06:14.000000000 -0600
@@ -56,7 +56,7 @@

  # --- Plot option.
  ifeq (plot,$(findstring plot,$(CONFIG)))
-   DEF_PLOT = -DPLOT -DMCPLOT -DGKSSIM -DXLIB
+   DEF_PLOT = -DPLOT -DMCPLOT -DXLIB
  PLOTLIBS = -lX11
endif

diff -Naurd MCNP5/Source/config/Windows_NT.gcf MCNP5_new/Source/config/Windows_NT.gcf
--- MCNP5/Source/config/Windows_NT.gcf 2003-04-30 20:08:52.000000000 -0600
+++ MCNP5_new/Source/config/Windows_NT.gcf 2004-07-22 15:06:14.000000000 -0600
@@ -3,14 +3,15 @@
#####
#
# Fortran 90 compilers supported:
-# Compaq Fortran      (6.6b or higher)
-# Lahey Fortran 95    (5.7b or higher)
-# Absoft Fortran     (7.5 or higher)
+# Compaq Fortran      (6.6b only) [sequential, plotting, mpi, pvm]
+# Lahey Fortran 95    (5.7b or higher) [sequential, plotting]
+# Absoft Fortran     (7.5 or higher) [sequential, plotting]
+# Intel Fortran 95    (7.1 only)      [sequential, plotting]
#
# C Compilers supported
-# Microsoft C++      (cl)
-# GNU gcc
-# Fujitsu C/C++      (with Lahey Fortran90)
+# Microsoft C++      (cl) [sequential, plotting, mpi, pvm]
+# GNU gcc [sequential, plotting]
+# Fujitsu C/C++      (with Lahey Fortran90) [sequential, plotting]
#
#####
@@ -36,7 +37,11 @@
  ifeq (absoft,$(findstring absoft,$(CONFIG)))
    FCOMPILER = ABSOFT
  else
-   FCOMPILER = CVF
+   ifeq (intel,$(findstring intel,$(CONFIG)))
+     FCOMPILER = INTEL
+   else
+     FCOMPILER = CVF
+   endif
  endif
endif
endif
@@ -96,7 +101,7 @@

  # --- Plot option.
  ifeq (plot,$(findstring plot,$(CONFIG)))

```

```

- DEF_PLOT = -DPLOT -DMCPLOT -DGKSSIM -DXLIB
+ DEF_PLOT = -DPLOT -DMCPLOT -DXLIB
endif

##### CVF with either gcc or cl #####
@@ -162,7 +167,7 @@
Q      = '

# --- OpenMP threads option.
- ifeq (omp,$(findstring omp,$(CONFIG)))
+ ifeq (omp,$(filter omp,$(CONFIG)))
    SMMP      =
    DEF_SMMP = -DMULTT
endif
@@ -239,7 +244,7 @@

ifeq (ABSOFTE,$(findstring ABSOFTE,$(FCOMPILER)))

- ABSOFTE      ?= 'c:\Absoft80'
+ ABSOFTE      ?= '/cygdrive/c/Absoft80'
CCOMPILER ?= gcc

# --- Optimize/Debug options.
@@ -264,7 +269,8 @@
PREPROCESS := yes
MISC= export ABSOFTE; ABSOFTE=$(ABSOFTE);

- FC          = $(MISC) $(ABSOFTE)/BIN/f90
+ #FC         = $(MISC) $(ABSOFTE)/BIN/f90
+ FC          = /cygdrive/c/Absoft80/bin/f90
FFLAGS      = $(FDEBUG) $(FOPT) $(SMMP) $(MPIO)
OBJF        = .obj
MOD_INC     = -I
@@ -303,6 +309,94 @@

endif

##### INTEL with either gcc or cl #####
+
+ifeq (INTEL,$(findstring INTEL,$(FCOMPILER)))
+
+ # --- Optimize/Debug options.
+ ifeq (debug,$(findstring debug,$(CONFIG)))
+   FDEBUG = /Zi
+   CDEBUG = -g
+   FOPT = /Od /Ob0 /Qfp_port /Qpc64 /Op
+   COPT =
+ else
+   FDEBUG =
+   CDEBUG =
+   FOPT = /Od /Ob0 /nologo #/Ox will cause the regression test suite to fail!
+   COPT =
+ endif
+
+ # --- Include and Module search directories.
+ INCLUDE_DIRS = -I'..\X11R6\include'
+
+ # --- Location(s) for parts of the code in separate directories.
+ DEDXROOT = '..\dedx'
+ ifndef TESTING
+   DEDX_UNIT_TEST = -DDEDX_UNIT_TEST
+ endif
+ DEDX_UNIT_TEST_FLAG = $(DEDX_UNIT_TEST)
+ DEDX_LD_LIB_PATH = /LINK /LIBPATH:..\
+
+ # --- Plotting
+ PLOTLIBS = /LIBPATH:'..\X11R6\lib' X11.lib
+
+ # --- Machine dependent CPP flags.
+ #DEF_MACH = -DCVF -DDEC -DCHEAP $(ROSSI) -DDIRACCESS_RECL_WORDS $(WIN32)
+

```

```

+ PREPROCESS := yes
+ PREPROCESS :=
+
+ ifeq (,$(PREPROCESS))
+   FPP =
+   DEF_MACH = -DINTEL -DCHEAP $(ROSSI) -DDIRACCESS_RECL_WORDS -DWIN32 $(WIN32)
+   FPPFLAGS = /Qfpp2 $(DEFS)
+   ALL_FPPFLAGS = $(FPPFLAGS)
+   Q = \'#
+ else
+   FPP = $(FPPmcpn)
+   DEF_MACH = -DINTEL -DCHEAP $(ROSSI) -DDIRACCESS_RECL_WORDS -DWIN32 $(WIN32)
+   FPPFLAGS = $(DEFS) -s $(I)
+   ALL_FPPFLAGS = $(FPPFLAGS)
+   I = .for
+   DATAPATH := "$(shell echo "$(DATAPATH)" | sed -e 's/\\/\\\\/g')"
+   Q = \'#
+ endif
+
+
+ CFLAGS = $(CDEBUG) $(COPT)
+ CPPFLAGS= $(DEFS)
+ ifeq (gcc,$(findstring gcc,$(COMPILER)))
+   CC = /usr/bin/gcc
+   OBJC = .o
+   WIN32 =
+ endif
+ ifeq (cl,$(findstring cl,$(COMPILER)))
+   CC = cl
+   OBJC = .obj
+   WIN32 =
+ endif
+
+ # --- Compilers/Linker & options:
+ FC = ifl
+ Q2 = '
+ FFLAGS = $(FDEBUG) $(FOPT) $(SMMP) $(MOD_INC)$ (Q2) $(DEDXROOT)$ (Q2)
$(MOD_INC)$ (Q2) ..src$(Q2) $(MPIO) /FR /w90 /w95 /4Yportlib
+ OBJF = .obj
+ MOD_INC = -I
+
+ LIB_SFX =.a
+
+ LD = $(FC)
+ LDFLAGS = /nologo /link /heap:83886080 /stack:41943040 /largeaddressaware
+### should make heap & stack options /nodefaultlib:libc
+ OUT = /exe:# no trailing blanks
+
+ # --- OpenMP threads option.
+ ifeq (omp,$(filter omp,$(CONFIG)))
+   SMMP = /MT /Qfpp /Qopenmp /Qopenmp_report2
+   DEF_SMMP = -DMULTT
+ endif
+endif
+
+ # --- some other setup stuff for CYGWIN
+ ECHO = /usr/bin/echo
+ RM = /usr/bin/rm
+diff -Naurd MCNP5/Source/dotcomm/include/dotcomm.h
MCNP5_new/Source/dotcomm/include/dotcomm.h
--- MCNP5/Source/dotcomm/include/dotcomm.h 2003-04-30 20:08:54.000000000 -0600
+++ MCNP5_new/Source/dotcomm/include/dotcomm.h 2004-07-22 15:06:14.000000000 -0600
@@ -161,11 +161,22 @@

+ #include "mpi.h"
+
+ #define DOTCOMM_Datatype MPI_Datatype
+ #define DOTCOMM_Datatype int
+
+ #define DOTCOMM_Context MPI_Comm
+ #define DOTCOMM_Operation MPI_Op

```



```

#ifdef LAM_MPI
/* ----- */
/* if using LAM-MPI, must add defines for Fortran datatypes */
/* ----- */
#define MPI_2REAL          ((MPI_Datatype) &lam_mpi_double)
#define MPI_2INTEGER      ((MPI_Datatype) &lam_mpi_long_long_int)
#define MPI_REAL          ((MPI_Datatype) &lam_mpi_float)
#define MPI_INTEGER       ((MPI_Datatype) &lam_mpi_long_int)
#endif
+
+
/* Note that Fortran 90 users don't need DOTCOMM datatypes
   since F90 can "discover" types. */

diff -Naurd MCNP5/Source/dotcomm/src/dotcomm_bcast.F90
MCNP5_new/Source/dotcomm/src/dotcomm_bcast.F90
--- MCNP5/Source/dotcomm/src/dotcomm_bcast.F90      2003-04-30 20:09:00.000000000 -0600
+++ MCNP5_new/Source/dotcomm/src/dotcomm_bcast.F90  2004-07-22 15:06:14.000000000 -0600
@@ -127,7 +127,7 @@
        DOTCOMM_TYPE = DOTCOMM_CHARACTER
        CALL DOTCOMMI_BCAST( &
-         BUF, &
+         BUF(1), &
            COUNT, &
            DOTCOMM_TYPE, &
            ROOT_PE, &
@@ -207,7 +207,7 @@

        DOTCOMM_TYPE = DOTCOMM_INTEGER4
        CALL DOTCOMMI_BCAST( &
-         BUF, &
+         BUF(1), &
            COUNT, &
            DOTCOMM_TYPE, &
            ROOT_PE, &
@@ -287,7 +287,7 @@

        DOTCOMM_TYPE = DOTCOMM_INTEGER8
        CALL DOTCOMMI_BCAST( &
-         BUF, &
+         BUF(1), &
            COUNT, &
            DOTCOMM_TYPE, &
            ROOT_PE, &
@@ -367,7 +367,7 @@

        DOTCOMM_TYPE = DOTCOMM_REAL4
        CALL DOTCOMMI_BCAST( &
-         BUF, &
+         BUF(1), &
            COUNT, &
            DOTCOMM_TYPE, &
            ROOT_PE, &
@@ -447,7 +447,7 @@

        DOTCOMM_TYPE = DOTCOMM_REAL8
        CALL DOTCOMMI_BCAST( &
-         BUF, &
+         BUF(1), &
            COUNT, &
            DOTCOMM_TYPE, &
            ROOT_PE, &
diff -Naurd MCNP5/Source/dotcomm/src/dotcomm_pack.F90
MCNP5_new/Source/dotcomm/src/dotcomm_pack.F90
--- MCNP5/Source/dotcomm/src/dotcomm_pack.F90      2003-04-30 20:09:06.000000000 -0600
+++ MCNP5_new/Source/dotcomm/src/dotcomm_pack.F90  2004-07-22 15:06:14.000000000 -0600
@@ -121,7 +121,7 @@
        SUBROUTINE DOTCOMMI_PACK( BUF, COUNT, DOTCOMM_TYPE, IERR)
        USE DOTCOMM_CONST_MOD

```

```

!DEC$ ATTRIBUTES C, REFERENCE, ALIAS: 'DOTCOMMI_PACK' :: DOTCOMMI_PACK
- CHARACTER (LEN=*), DIMENSION (:), INTENT (IN) :: BUF
+ CHARACTER (LEN=*), INTENT (IN) :: BUF
  INTEGER (IDEF), INTENT (IN) :: COUNT
  INTEGER (IDEF), INTENT (OUT) :: IERR
  INTEGER (IDEF) :: DOTCOMM_TYPE
@@ -148,7 +148,7 @@
  DOTCOMM_TYPE = DOTCOMM_CHARACTER

  CALL DOTCOMMI_PACK ( &
-   BUF, &
+   BUF(1), &
  COUNT, &
  DOTCOMM_TYPE, &
  IERR )
@@ -222,7 +222,7 @@

  DOTCOMM_TYPE = DOTCOMM_INTEGER4
  CALL DOTCOMMI_PACK ( &
-   BUF, &
+   BUF(1), &
  COUNT, &
  DOTCOMM_TYPE, &
  IERR )
@@ -296,7 +296,7 @@

  DOTCOMM_TYPE = DOTCOMM_INTEGER8
  CALL DOTCOMMI_PACK ( &
-   BUF, &
+   BUF(1), &
  COUNT, &
  DOTCOMM_TYPE, &
  IERR )
@@ -370,7 +370,7 @@

  DOTCOMM_TYPE = DOTCOMM_REAL4
  CALL DOTCOMMI_PACK ( &
-   BUF, &
+   BUF(1), &
  COUNT, &
  DOTCOMM_TYPE, &
  IERR )
@@ -444,7 +444,7 @@

  DOTCOMM_TYPE = DOTCOMM_REAL8
  CALL DOTCOMMI_PACK ( &
-   BUF, &
+   BUF(1), &
  COUNT, &
  DOTCOMM_TYPE, &
  IERR )
diff -Naurd MCNP5/Source/dotcomm/src/dotcomm_recv.F90
MCNP5_new/Source/dotcomm/src/dotcomm_recv.F90
--- MCNP5/Source/dotcomm/src/dotcomm_recv.F90      2003-04-30 20:09:10.000000000 -0600
+++ MCNP5_new/Source/dotcomm/src/dotcomm_recv.F90  2004-07-22 15:06:14.000000000 -0600
@@ -139,7 +139,7 @@

  DOTCOMM_TYPE = DOTCOMM_CHARACTER
  CALL DOTCOMMI_RECV ( &
-   BUF, &
+   BUF(1), &
  COUNT, &
  DOTCOMM_TYPE, &
  SRCPE, &
@@ -225,7 +225,7 @@

  DOTCOMM_TYPE = DOTCOMM_INTEGER4
  CALL DOTCOMMI_RECV ( &
-   BUF, &
+   BUF(1), &
  COUNT, &

```

```

        DOTCOMM_TYPE, &
        SRCPE, &
@@ -397,7 +397,7 @@

        DOTCOMM_TYPE = DOTCOMM_REAL4
        CALL DOTCOMMI_RECV ( &
-        BUF, &
+        BUF(1), &
        COUNT, &
        DOTCOMM_TYPE, &
        SRCPE, &
@@ -483,7 +483,7 @@

        DOTCOMM_TYPE = DOTCOMM_REAL8
        CALL DOTCOMMI_RECV ( &
-        BUF, &
+        BUF(1), &
        COUNT, &
        DOTCOMM_TYPE, &
        SRCPE, &
diff -Naurd MCNP5/Source/dotcomm/src/dotcomm_send.F90
MCNP5_new/Source/dotcomm/src/dotcomm_send.F90
--- MCNP5/Source/dotcomm/src/dotcomm_send.F90      2003-04-30 20:09:10.000000000 -0600
+++ MCNP5_new/Source/dotcomm/src/dotcomm_send.F90  2004-07-22 15:06:14.000000000 -0600
@@ -135,7 +135,7 @@

        DOTCOMM_TYPE = DOTCOMM_CHARACTER
        CALL DOTCOMMI_SEND ( &
-        BUF, &
+        BUF(1), &
        COUNT, &
        DOTCOMM_TYPE, &
        DESTPE, &
@@ -221,7 +221,7 @@

        DOTCOMM_TYPE = DOTCOMM_INTEGER4
        CALL DOTCOMMI_SEND ( &
-        BUF, &
+        BUF(1), &
        COUNT, &
        DOTCOMM_TYPE, &
        DESTPE, &
@@ -307,7 +307,7 @@

        DOTCOMM_TYPE = DOTCOMM_INTEGER8
        CALL DOTCOMMI_SEND ( &
-        BUF, &
+        BUF(1), &
        COUNT, &
        DOTCOMM_TYPE, &
        DESTPE, &
@@ -393,7 +393,7 @@

        DOTCOMM_TYPE = DOTCOMM_REAL4
        CALL DOTCOMMI_SEND ( &
-        BUF, &
+        BUF(1), &
        COUNT, &
        DOTCOMM_TYPE, &
        DESTPE, &
@@ -479,7 +479,7 @@

        DOTCOMM_TYPE = DOTCOMM_REAL8
        CALL DOTCOMMI_SEND ( &
-        BUF, &
+        BUF(1), &
        COUNT, &
        DOTCOMM_TYPE, &
        DESTPE, &
diff -Naurd MCNP5/Source/dotcomm/src/dotcomm_unpack.F90
MCNP5_new/Source/dotcomm/src/dotcomm_unpack.F90

```

```

--- MCNP5/Source/dotcomm/src/dotcomm_unpack.F90      2003-04-30 20:09:12.000000000 -0600
+++ MCNP5_new/Source/dotcomm/src/dotcomm_unpack.F90 2004-07-22 15:06:14.000000000 -0600
@@ -119,7 +119,7 @@
SUBROUTINE DOTCOMMI_UNPACK (BUF, COUNT, DOTCOMM_TYPE, IERR)
  USE DOTCOMM_CONST_MOD
  !DEC$ ATTRIBUTES C, ALIAS: '_DOTCOMMI_UNPACK', REFERENCE :: DOTCOMMI_UNPACK
- CHARACTER (LEN=*), DIMENSION(:), INTENT(INOUT) :: BUF
+ CHARACTER (LEN=*), INTENT(INOUT) :: BUF
  INTEGER(IDEF), INTENT(IN) :: COUNT
  INTEGER(IDEF), INTENT(OUT) :: IERR
  INTEGER(IDEF) :: DOTCOMM_TYPE
@@ -144,7 +144,7 @@

DOTCOMM_TYPE = DOTCOMM_CHARACTER
CALL DOTCOMMI_UNPACK ( &
- BUF, &
+ BUF(1), &
COUNT, &
DOTCOMM_TYPE, &
IERR )
@@ -218,7 +218,7 @@

DOTCOMM_TYPE = DOTCOMM_INTEGER4
CALL DOTCOMMI_UNPACK ( &
- BUF, &
+ BUF(1), &
COUNT, &
DOTCOMM_TYPE, &
IERR )
@@ -292,7 +292,7 @@

DOTCOMM_TYPE = DOTCOMM_INTEGER8
CALL DOTCOMMI_UNPACK ( &
- BUF, &
+ BUF(1), &
COUNT, &
DOTCOMM_TYPE, &
IERR )
@@ -366,7 +366,7 @@

DOTCOMM_TYPE = DOTCOMM_REAL4
CALL DOTCOMMI_UNPACK ( &
- BUF, &
+ BUF(1), &
COUNT, &
DOTCOMM_TYPE, &
IERR )
@@ -440,7 +440,7 @@

DOTCOMM_TYPE = DOTCOMM_REAL8
CALL DOTCOMMI_UNPACK ( &
- BUF, &
+ BUF(1), &
COUNT, &
DOTCOMM_TYPE, &
IERR )
diff -Naurd MCNP5/Source/dotcomm/src/internals/mpi/dotcommmpi_binary_op.c
MCNP5_new/Source/dotcomm/src/internals/mpi/dotcommmpi_binary_op.c
--- MCNP5/Source/dotcomm/src/internals/mpi/dotcommmpi_binary_op.c      2003-04-30
20:09:32.000000000 -0600
+++ MCNP5_new/Source/dotcomm/src/internals/mpi/dotcommmpi_binary_op.c      2004-07-22
15:06:14.000000000 -0600
@@ -3,7 +3,11 @@
/*
/* Author: Richard Barrett; rbarrett@lanl.gov
/* Date: March 2002
-
+/* EDITED FOR LAMPI      SEPost 2-7-03 */
+/* Switch on operation with switch on datatype within each operation
+ case changed to elseif blocks because with LAMPI MPI_Datatype and
+ MPI_Op (and therefore DOTCOMM_Datatype and DOTCOMM_Operation) are

```

```

+     pointers instead of integers and cannot be basis for switches */
#include "dotcomm.h"

/* =====
@@ -37,11 +41,11 @@

    operation          Intent:          in
                        C               type: DOTCOMM_Operation
-                       The operation applied to the vector elements: \\
+                       The operation applied to the vector elements:

-                       \hspace*{.2in}{\tt DOTCOMM_OP_MAX}      \hspace*{.54in} Maximum.
-                       \hspace*{.2in}{\tt DOTCOMM_OP_MIN}      \hspace*{.55in} Minimum.
-                       \hspace*{.2in}{\tt DOTCOMM_OP_SUM}      \hspace*{.55in} Sum. \\
+                       DOTCOMM_OP_MAX      Maximum.
+                       DOTCOMM_OP_MIN      Minimum.
+                       DOTCOMM_OP_SUM      Sum.

                        See the User Guide for details.

@@ -106,158 +110,167 @@
/* ----- */
/* operate on the elements */
/* ----- */
- switch ( operation )
- {
-
-     case DOTCOMM_OP_MAX:
-         switch( datatype )
+ /*switch ( operation ) */
+ if (operation == DOTCOMM_OP_MAX) {
+     /* switch( datatype ) */
+     if (datatype == DOTCOMM_REAL8)
+     {
-         case DOTCOMM_REAL8:
-             for ( i = 0; i < count; i++ )
+             for ( i = 0; i < count; i++ )
+             {
+                 ((double*)dest)[i] = DOTCOMM_MAX( ((double*)src_a)[i],
+                                                     ((double*)src_b)[i] );
+             }
-             break;
+         }
-     }
-
-     case DOTCOMM_REAL4:
+ else if (datatype == DOTCOMM_REAL4)
+     {
+         for ( i = 0; i < count; i++ )
+         {
+             ((float*)dest)[i] = DOTCOMM_MAX( ((float*)src_a)[i],
+                                               ((float*)src_b)[i] );
+         }
-         break;
+     }
-     }
-
-     case DOTCOMM_INTEGER8:
+ else if (datatype == DOTCOMM_INTEGER8)
+     {
+         for ( i = 0; i < count; i++ )
+         {
+             ((long*)dest)[i] = DOTCOMM_MAX( ((long*)src_a)[i],
+                                              ((long*)src_b)[i] );
+         }
-         break;
+     }
-     }
-
-     case DOTCOMM_INTEGER4:
+ else if (datatype == DOTCOMM_INTEGER4)
+     {
+         for ( i = 0; i < count; i++ )
+         {
+             ((int*)dest)[i] = DOTCOMM_MAX( ((int*)src_a)[i],

```

```

                                ((int*)src_b)[i] );
-         }
+         break;
+     }

-     case DOTCOMM_CHARACTER:
+     else if (datatype == DOTCOMM_CHARACTER)
+     {
+         for ( i = 0; i < count; i++ )
+         {
+             ((char*)dest)[i] = DOTCOMM_MAX( ((char*)src_a)[i],
+                                             ((char*)src_b)[i] );
+         }
-         break;
+     }

-
-     default:
+     else
+     {
+         ierr = DOTCOMM_ERROR_INVALID_DATATYPE;
-         break;
+     }

-     } /* End datatype switch */
-     break;
+     /* End datatype switch */
+ }
+ else if (operation == DOTCOMM_OP_MIN) {

- case DOTCOMM_OP_MIN:
-     switch( datatype )
+     /* switch( datatype )*/
+     if (datatype == DOTCOMM_REAL8)
+     {
-     case DOTCOMM_REAL8:
+         for ( i = 0; i < count; i++ )
+         {
+             ((double*)dest)[i] = DOTCOMM_MIN( ((double*)src_a)[i],
+                                             ((double*)src_b)[i] );
+         }
-         break;
+     }

-     case DOTCOMM_REAL4:
+     else if (datatype == DOTCOMM_REAL4)
+     {
+         for ( i = 0; i < count; i++ )
+         {
+             ((float*)dest)[i] = DOTCOMM_MIN( ((float*)src_a)[i],
+                                             ((float*)src_b)[i] );
+         }
-         break;
+     }

-     case DOTCOMM_INTEGER8:
+     else if (datatype == DOTCOMM_INTEGER8)
+     {
+         for ( i = 0; i < count; i++ )
+         {
+             ((long*)dest)[i] = DOTCOMM_MIN( ((long*)src_a)[i],
+                                             ((long*)src_b)[i] );
+         }
-         break;
+     }

-     case DOTCOMM_INTEGER4:
+     else if (datatype == DOTCOMM_INTEGER4)
+     {
+         for ( i = 0; i < count; i++ )
+         {

```

```

                ((int*)dest)[i] = DOTCOMM_MIN( ((int*)src_a)[i],
                                                ((int*)src_b)[i] );
            }
-         break;
+         }

-     case DOTCOMM_CHARACTER:
+     else if (datatype == DOTCOMM_CHARACTER)
+     {
        for ( i = 0; i < count; i++ )
        {
            ((char*)dest)[i] = DOTCOMM_MIN( ((char*)src_a)[i],
                                                ((char*)src_b)[i] );
        }
-     break;
-
-
+     }

-     default:
+     else
+     {
        ierr = DOTCOMM_ERROR_INVALID_DATATYPE;
-     break;
+     }

-     } /* End datatype switch */
-     break;
+     /* End datatype switch */
+     }

-     case DOTCOMM_OP_SUM:
-     switch( datatype )
-     {
-     case DOTCOMM_REAL8:
+     else if (operation == DOTCOMM_OP_SUM) {
+     /* switch( datatype ) */
+     if (datatype == DOTCOMM_REAL8)
+     {
        for ( i = 0; i < count; i++ )
        {
            ((double*)dest)[i] = ((double*)src_a)[i] + ((double*)src_b)[i];
        }
-     break;
+     }

-     case DOTCOMM_REAL4:
+     else if (datatype == DOTCOMM_REAL4)
+     {
        for ( i = 0; i < count; i++ )
        {
            ((float*)dest)[i] = ((float*)src_a)[i] + ((float*)src_b)[i];
        }
-     break;
+     }

-     case DOTCOMM_INTEGER8:
+     else if (datatype == DOTCOMM_INTEGER8)
+     {
        for ( i = 0; i < count; i++ )
        {
            ((long*)dest)[i] = ((long*)src_a)[i] + ((long*)src_b)[i];
        }
-     break;
+     }

-     case DOTCOMM_INTEGER4:
+     else if (datatype == DOTCOMM_INTEGER4)
+     {
        for ( i = 0; i < count; i++ )

```

```

        {
            ((int*)dest)[i] = ((int*)src_a)[i] + ((int*)src_b)[i];
        }
-       break;
+       }

-       case DOTCOMM_CHARACTER:
+       else if (datatype == DOTCOMM_CHARACTER)
+       {
            for ( i = 0; i < count; i++ )
            {
                ((char*)dest)[i] = ((char*)src_a)[i] + ((char*)src_b)[i];
            }
-       break;
+       }

-       default:
+       else
+       {
            return DOTCOMM_ERROR_INVALID_DATATYPE;
-       } /* End datatype switch */
-       break;
-
-
-       default:
+       }
+       /* End datatype switch */
+       }
+       else {

            return DOTCOMM_ERROR_INVALID_OPERATION;

diff -Naurd MCNP5/Source/dotcomm/src/internals/mpi/dotcommmpi_convert.c
MCNP5_new/Source/dotcomm/src/internals/mpi/dotcommmpi_convert.c
--- MCNP5/Source/dotcomm/src/internals/mpi/dotcommmpi_convert.c      2003-04-30
20:09:32.000000000 -0600
+++ MCNP5_new/Source/dotcomm/src/internals/mpi/dotcommmpi_convert.c 2004-07-22
15:06:14.000000000 -0600
@@ -3,6 +3,10 @@
/*
/* Author: Richard Barrett; rbarrett@lanl.gov
/* Date: March 2002
+/* EDITED FOR LAMPI SEPost 2-7-03
+ Switch on dotcomm_op changed to elseif because with LAMPI
+ MPI_Datatype and therefore DOTCOMM_Datatype are pointers instead
+ of integers. Cannot switch on *dotcomm_op
*/

#include "dotcomm.h"

@@ -34,7 +38,7 @@
conversion          Intent:      in
                    C           type: const DOTCOMM_Conversions
                    The type of conversion.
-                   See DOTCOMM_Conversions (section \ref{DOTCOMM\_Convert\_enum})
page \pageref{DOTCOMM\_Convert\_enum})
+                   See DOTCOMM_Conversions
+                   for a listing of the possible conversion types.

Return Values
@@ -77,7 +81,7 @@
DOTCOMM_Operation
    *protocol_op;          /* protocol operation */

- DOTCOMM_Datatype
+ MPI_Datatype
    *protocol_datatype;   /* protocol datatype */

DOTCOMM_Operation
@@ -102,7 +106,7 @@
case DOTCOMM_TO_PROTOCOL_DATATYPE:

```



```

-     dotcomm_datatype      = (DOTCOMM_Datatype*)in;
-     protocol_datatype = (DOTCOMM_Datatype*)out;
+     protocol_datatype = (MPI_Datatype*)out;

-     if( *dotcomm_datatype == DOTCOMM_REAL8 )
-     {
@@ -194,28 +198,25 @@
-     dotcomm_op  = (DOTCOMM_Operation*)in;
-     protocol_op = (DOTCOMM_Operation*)out;

-     switch( *dotcomm_op )
-     {
-     case DOTCOMM_OP_MAX:
+     /* switch( *dotcomm_op ) */
+
+     if (*dotcomm_op == DOTCOMM_OP_MAX)
-     *protocol_op = MPI_MAX;
-     break;

-     case DOTCOMM_OP_MIN:
+     else if (*dotcomm_op == DOTCOMM_OP_MIN)
-     *protocol_op = MPI_MIN;
-     break;

-     case DOTCOMM_OP_SUM:
+     else if (*dotcomm_op == DOTCOMM_OP_SUM)
-     *protocol_op = MPI_SUM;
-     break;

-     default:
+     else
+     {
-     ierr = DOTCOMM_ERROR_BAD_PARAMETER;
-     DOTCOMM_ASSERT ( (ierr == DOTCOMM_OK), "bad parameter",
-     DOTCOMM_ERROR_BAD_PARAMETER );
-     break;
-     }
-     break;
+
+     break;
+
+     /* ----- */
+     /* DONE: DOTCOMM to protocol op */
+     /* ----- */
diff -Naurd MCNP5/Source/dotcomm/src/internals/mpi/dotcommmpi_mpi.h
MCNP5_new/Source/dotcomm/src/internals/mpi/dotcommmpi_mpi.h
--- MCNP5/Source/dotcomm/src/internals/mpi/dotcommmpi_mpi.h 2003-04-30 20:09:32.000000000
-0600
+++ MCNP5_new/Source/dotcomm/src/internals/mpi/dotcommmpi_mpi.h 2004-07-22
15:06:14.000000000 -0600
@@ -32,7 +32,7 @@
-
-     DOTCOMM_Conversions  conversion
-     );

- int dotcommmpi_sizeof ( DOTCOMM_Datatype datatype );
+ int dotcommmpi_sizeof ( int datatype );

-     /* ----- */
-     /* remove typesafe linkage if compiling under c++ */
diff -Naurd MCNP5/Source/dotcomm/src/internals/mpi/dotcommmpi_sizeof.c
MCNP5_new/Source/dotcomm/src/internals/mpi/dotcommmpi_sizeof.c
--- MCNP5/Source/dotcomm/src/internals/mpi/dotcommmpi_sizeof.c 2003-04-30
20:09:32.000000000 -0600
+++ MCNP5_new/Source/dotcomm/src/internals/mpi/dotcommmpi_sizeof.c 2004-07-22
15:06:14.000000000 -0600
@@ -37,7 +37,7 @@

-#define DOTCOMM_LOCATION "dotcommmpi_sizeof"

-int dotcommmpi_sizeof ( DOTCOMM_Datatype datatype )

```

```

+int dotcommpi_sizeof ( int datatype )
{
    /* ----- */
@@ -53,11 +53,11 @@

    if ( datatype == DOTCOMM_REAL8 )

-       sizeof_datatype = sizeof(double);
+       sizeof_datatype = 8;

    else if ( datatype == DOTCOMM_REAL4 )

-       sizeof_datatype = sizeof(float);
+       sizeof_datatype = 4;

    else if ( datatype == DOTCOMM_INTEGER8 )

@@ -66,11 +66,11 @@

    else if ( datatype == DOTCOMM_INTEGER4 )

-       sizeof_datatype = sizeof(int);
+       sizeof_datatype = 4;

    else if ( datatype == DOTCOMM_CHARACTER )

-       sizeof_datatype = sizeof(char);
+       sizeof_datatype = 1;

    else
    {
diff -Naurd MCNP5/Source/install MCNP5_new/Source/install
--- MCNP5/Source/install      2003-11-05 17:23:12.000000000 -0700
+++ MCNP5_new/Source/install  2004-07-23 15:49:01.000000000 -0600
@@ -236,32 +236,53 @@
    if [ "$GCC" = '' ]
    then GCC=''
    fi
-   if [ "$PGI" != '' ]
-   then {
-       menuf90=portland
-       menuf90path="$PGI/linux86/bin/pgf90"
-       menuccpath="$GCC"
-   }
-   elif [ -d "/usr/pgi" ]
-   then {
-       menuf90=portland
-       PGI=/usr/pgi
-       menuf90path="$PGI/linux86/bin/pgf90"
-       menuccpath="$GCC"
-   }
-   elif [ -d "/usr/local/pgi" ]
-   then {
+   menuf90path=`which pgf90`
+   if [ "$menuf90path" = '' ]
+   then
+       if [ "$PGI" = '' ]
+       then
+           -   "/usr/pgi-5.2" ]
+           then PGI=/usr/pgi-5.2
+       elif [ -d "/usr/local/pgi-5.2" ]
+       then PGI=/usr/local/pgi-5.2
+       elif [ -d "/opt/pgi-5.2" ]
+       then PGI=/opt/pgi-5.2
+       elif [ -d "/usr/pgi-5.1" ]
+       then PGI=/usr/pgi-5.1
+       elif [ -d "/usr/local/pgi-5.1" ]
+       then PGI=/usr/local/pgi-5.1

```

```

+     elif [ -d "/opt/pgi-5.1" ]
+     then PGI=/opt/pgi-5.1
+     elif [ -d "/usr/pgi" ]
+     then PGI=/usr/pgi
+     elif [ -d "/usr/local/pgi" ]
+     then PGI=/usr/local/pgi
+     elif [ -d "/opt/pgi" ]
+     then PGI=/opt/pgi
+     fi
+ fi
+
+ if [ -d "$PGI/linux86/5.2/bin" ]
+ then
+     menuf90path="$PGI/linux86/5.2/bin/pgf90"
+     elif [ -d "$PGI/linux86/5.1/bin" ]
+     then
+         menuf90path="$PGI/linux86/5.1/bin/pgf90"
+     elif [ -d "$PGI/linux86/bin/pgf90" ]
+     then
+         menuf90path="$PGI/linux86/bin/pgf90"
+     fi
+ fi
+
+ if [ "$menuf90path" != '' ]
+ then
+     menuf90=portland
+     PGI=/usr/local/pgi
+     menuf90path="$PGI/linux86/bin/pgf90"
+     menuccpath="$GCC"
+ }
+ else
+     menuf90path=`which pgf90`
+     menuccpath="$GCC"
+     if [ "$menuf90path" != '' ] && [ "$menuccpath" != '' ]
+     then menuf90=portland
+     fi
+ export menuf90
+ export menuf90path
+ export menuccpath
+ fi
}
#-----
@@ -336,43 +357,47 @@
# Use standard locations to identify a Fortran 95 compiler.
# Identify a C compiler to go with it.
FindINTELCCompiler () {
- ARCH=`uname -m`
- if [ "$ARCH" = 'ia64' ]
- then {
-     ARCH="ia64"
-     INTEL_FC="efc"
- }
- else
-     ARCH="ia32"
-     INTEL_FC="ifc"
- fi
-
- GCC=`which gcc`
- if [ "$GCC" = '' ]
- then GCC=''
- fi
- if [ -d "/opt/intel/compiler70" ]
- then {
-     menuf90=intel
-     menuf90path="/opt/intel/compiler70/$ARCH/bin/$INTEL_FC"
-     menuccpath="$GCC"
- }
+ else
+     menuf90path=`which ifort`
+

```

```

+ if [ "$menuf90path" = '' ]
+ then
+   ARCH=`uname -m`
+   if [ "$ARCH" = 'ia64' ]
-   then {
+   then
+     menuf90path=`which efc`
-   }
+   ARCH="ia64"
+   INTEL_FC="efc"
+   else
+     menuf90path=`which ifc`
+     ARCH="ia32"
+     INTEL_FC="ifc"
+   fi
-   export menuf90path
-   if [ "$menuf90path" != '' ]
-   then {
-     menuf90=intel
-     menuccpath="$GCC"
-   }
+   fi
+
+   if [ "$menuf90path" = '' ]
+   then
+     if [ -d "/opt/intel_fc_80/bin" ]
+     then
+       menuf90path="/opt/intel_fc_80/bin/ifort"
+     elif [ -d "/opt/intel/compiler70" ]
+     then
+       menuf90path="/opt/intel/compiler70/$ARCH/bin/$INTEL_FC"
+     fi
+   fi
+
+   if [ "$menuf90path" != '' ]
+   then
+     menuf90=intel
+     menuccpath="$GCC"
+     export menuf90
+     export menuf90path
+     export menuccpath
+   fi
+ }
+ #-----
+ # FindCompaqCompiler
diff -Naurd MCNP5/Source/src/acecas.F90 MCNP5_new/Source/src/acecas.F90
--- MCNP5/Source/src/acecas.F90      2003-04-30 20:10:00.000000000 -0600
+++ MCNP5_new/Source/src/acecas.F90  2004-07-22 15:14:40.000000000 -0600
@@ -48,7 +48,7 @@
! use the selected law to sample the energy (and possibly angle).
! if law samples without error, go to sample angle or coordinate
! transform as appropriate.
- colout(1,ls) = -huge
+ colout(1,ls) = -huge_float
lw = nint(xss(n))
iw = id-1+nint(xss(n+1))

@@ -415,7 +415,7 @@
! *****
! print debug information for cross-section table errors.
295 continue
- colout(1,ls) = huge
+ colout(1,ls) = huge_float

300 continue
call zaid(2,ht,ixl(1,iex))
@@ -427,11 +427,11 @@
& 5x, "law =",i3,5x, "energy out =",1pe12.4)
!$OMP END CRITICAL (PRINT_OUTPUT)

- if( colout(1,ls)==-huge ) then

```

```

+ if( colout(1,ls)==-huge_float ) then
  call expirx(1,'acecas','an inappropriate or non-existent law was selected.')
  elseif( colout(1,ls)<0. ) then
    call expirx(1,'acecas','emission energy was negative.')
- elseif( colout(1,ls)==huge ) then
+ elseif( colout(1,ls)==huge_float ) then
  call expirx(1,'acecas','faulty cross-section data.')
  elseif( colout(1,ls)>erg ) then
    call expirx(1,'acecas','emission energy exceeds incident energy.')
diff -Naurd MCNP5/Source/src/acecos.F90 MCNP5_new/Source/src/acecos.F90
--- MCNP5/Source/src/acecos.F90      2003-04-30 20:10:00.000000000 -0600
+++ MCNP5_new/Source/src/acecos.F90  2004-07-22 15:14:40.000000000 -0600
@@ -20,7 +20,7 @@
  ! find the cosine table by binary search on the energy table.
  if( ka==0 ) then
    ! isotropic case
-   acecos = 2.*rang()-1.
+   acecos = 2.0_dknd*rang()-one
    ixcos = 0
    return
  endif
@@ -38,32 +38,32 @@
    ib = ih
  endif
  enddo
-  !
+  !
  ! sample between adjoining tables by interpolation fraction.
  if( rang()*(xss(ib)-xss(ic)) < erg-xss(ic) ) ic=ib
  lm = nint(xss(ic+n))
  if( lm==0 ) then
    ! isotropic case
-   acecos = 2.*rang()-1.
+   acecos = 2.0_dknd*rang()-one
    ixcos = 0
    return
  elseif( lm>0 ) then
    ! sample from table of 32 equiprobable cosine groups.
-   t1 = rang()*32.
+   t1 = rang()*32._dknd
    kr = t1
    ixcos = ia-1+lm
    acecos = xss(ixcos+kr)+(t1-kr)*(xss(ixcos+kr+1)-xss(ixcos+kr))
    return
  endif
endif
-
+
  ! tabular probability angular distribution.
  k = ia-1-lm
  ixcos = -k
  jj = nint(xss(k))
  np = nint(xss(k+1))
  rn = rang()
-  !
+  !
  ! binary search of cumulative density function.
  ic = k+2*np+2
  ib = k+3*np+1
@@ -76,12 +76,17 @@
    ib = ih
  endif
  enddo
-  !
+  !
  fa = xss(ic-np)
  ca = xss(ic-2*np)
+  if ( jj /= 1 ) then
+  bb = (xss(ic-np+1)-fa)/(xss(ic-2*np+1)-ca)
+  if( bb /= zero ) then
+  acecos=ca+(sqrt(max(zero,fa**2+2.0_dknd*bb*(rn-xss(ic))))-fa)/bb

```

```

+     return
+   endif
+ endif
  acecos = ca+(rn-xss(ic))/fa
-   if( jj==1 ) return
-   bb = (xss(ic-np+1)-fa)/(xss(ic-2*np+1)-ca)
-   if( bb/=0. ) acecos=ca+(sqrt(max(zero,fa**2+2.*bb*(rn-xss(ic))))-fa)/bb
  return
+
+ end function acecos
diff -Naurd MCNP5/Source/src/acegam.F90 MCNP5_new/Source/src/acegam.F90
--- MCNP5/Source/src/acegam.F90      2003-04-30 20:10:04.000000000 -0600
+++ MCNP5_new/Source/src/acegam.F90  2004-07-22 15:14:40.000000000 -0600
@@ -4,6 +4,7 @@
  subroutine acegam
    ! generate and bank photons from a neutron collision.
    use mcnp_global
+   use dxtran_mod
    use mcnp_debug
    implicit real(dknd) (a-h,o-z)
    character(len=10) :: ht
@@ -85,7 +86,7 @@
    elseif( nww(2)==0 ) then
      t1 = max(gwt(icl),-gwt(icl)*wgt9(1))*fiml9(1,1)/(fiml(1)*sf)
    else
-     t1 = huge
+     t1 = huge_float
+     sw = wtfasv           ! use neutron wtfasv if erg or erg/tme photon imp
      if ( iets(2)==0 ) then
        sf = 1.
@@ -143,11 +144,7 @@
    es = erg
    vel = slite
    ncp = 0
-   idx = 0
-   do i = 1,ndx(2)
-     if( (xxx-dxx(2,1,i))**2+(yyy-dxx(2,2,i))**2+(zzz-dxx(2,3,i))**2<&
-       & dxx(2,5,i)) idx = i
-   enddo
+   idx = inside_dxtran_sphere()
    st = totm
    if( mcal/=2 ) wtfasv = 1.

diff -Naurd MCNP5/Source/src/acetot.F90 MCNP5_new/Source/src/acetot.F90
--- MCNP5/Source/src/acetot.F90      2003-04-30 20:10:06.000000000 -0600
+++ MCNP5_new/Source/src/acetot.F90  2004-07-22 15:14:40.000000000 -0600
@@ -6,6 +6,7 @@
    ! mm=1 for call from wtmult, otherwise zero.
    use mcnp_global
    use mcnp_debug
+   use erprnt_mod

    implicit real(dknd) (a-h,o-z)

diff -Naurd MCNP5/Source/src/addtfc.F90 MCNP5_new/Source/src/addtfc.F90
--- MCNP5/Source/src/addtfc.F90      2003-04-30 20:10:06.000000000 -0600
+++ MCNP5_new/Source/src/addtfc.F90  2004-07-22 15:14:40.000000000 -0600
@@ -30,15 +30,15 @@
    ! calculate the entries in the new line.
    ft = 0.
-   t = max(1,nps)
+   t = max(1_i8knd,nps)
    if( nsr==71 .and. kcz>=ikz ) t=nsrck*(kcz-ikz)
    call ra_kcheck( kcheck )
    call ra_lcheck( lsav, ldif )
    if( kcheck>0 .and. kcz>=lsav ) t=nsrck*(kcz-lsav)
    if( kc8 < 0 ) t=t+nsrck-wt0*nsa
    if( knrm /= 0 ) t=pax(1,1,1)
-   if( nsr == 6.and.nrrs >= nrss ) t=max(1,np1)
-   if( nsr == 6.and.nrrs < nrss ) t=max(1,npsr)

```

```

+ if( nsr == 6.and.nrrs >= nrss ) t=max(1_i8knd,np1)
+ if( nsr == 6.and.nrrs < nrss ) t=max(1_i8knd,np1)
if( t > .5 ) ft=1./t
npc(1)=nps

@@ -48,18 +48,18 @@
DO_140_1: do ital_tmp=1,ntal
  ital = ital_tmp
  it = ital+iper*ntal
-   tfc(1:6,1,it) = 0.
-   nhsd(ln,it) = 0
+   tfc(1:6,1,it) = zero
+   nhsd(ln,it) = 0_i8knd
  k = jptal(7,ital)+iper*mxfp
  t = tal(k+mxfp)
-   if( t==0. .or. ft==0. .or. tal(k+2*mxfp)<=0. ) cycle DO_140_1
+   if( t==0. .or. ft==0. .or. tal(k+2*mxfp)<=zero ) cycle DO_140_1
  tfc(2,1,it) = min(tal(k+2*mxfp)/t**2-ft,one)
-   if( tfc(2,1,it) <= 1.e-8 ) tfc(2,1,it)=0.
+   if( tfc(2,1,it) <= 1.e-8_dknd ) tfc(2,1,it)=zero
  tfc(2,1,it) = sqrt(tfc(2,1,it))
  if( iptal(4,2,ital)/=0 ) t=t/tds(iptal(4,2,ital)+&
    & iptal(4,3,ital)*(jtff(1,ital)-1)+jtff(4,ital))
  if( (jptal(2,ital)==6.or.jptal(2,ital)==7) .and. &
-    & jptal(4,ital)/=0 ) t=t*1.60219e-22
+    & jptal(4,ital)/=0 ) t=t*1.60219e-22_dknd
  tfc(1,1,it) = t*ft
  tfc(3,1,it) = (cts-cpk)*tfc(2,1,it)**2
  ! calculate and store the variance of the variance for tfc bin.
@@ -74,12 +74,12 @@
  if( tfc(3,1,it)/=0. ) tfc(3,1,it)=60./tfc(3,1,it)
  endif
endif
-   if( tfc(2,1,it)==0. ) tfc(3,1,it)=1.e30
+   if( tfc(2,1,it)==0. ) tfc(3,1,it)=1.e+30_dknd

  ! calculate slope (using a pareto) of tail of history tally pdf.
  ! the tail is defined as the extreme 5% with a minimum of 25
  ! history tallies for analysis to fit the pareto parameters.
-   if(nhds(ln-3,it)-nhds(1,it)-nhds(ln-5,it) < 500) cycle DO_140_1
+   if(nhds(ln-3,it)-nhds(1,it)-nhds(ln-5,it) < 500_i8knd) cycle DO_140_1

  ! check for the appearance of a bounded extreme tally value.
  if( shsd(lp,it)/shsd(lp-100,it) < 1.01 ) tfc(5,1,it)=10.
@@ -125,7 +125,7 @@
  ! store np and ts for later use in the prints.
  130 continue
  lk = ls+ks(ms)
-   nhsd(ln,it) = np
+   nhsd(ln,it) = int(np,i8knd)
  shsd(lp+2,it) = ts

  ! find pareto parameters that best fit the np extreme tallies.
diff -Naurd MCNP5/Source/src/avrwi.F90 MCNP5_new/Source/src/avrwi.F90
--- MCNP5/Source/src/avrwi.F90      2003-04-30 20:10:10.000000000 -0600
+++ MCNP5_new/Source/src/avrwi.F90  2004-07-22 15:14:40.000000000 -0600
@@ -5,6 +5,7 @@
  ! initialize weight window generator.
  use mcnp_global
  use mcnp_debug
+ use erprnt_mod

  implicit real(dknd) (a-h,o-z)

@@ -83,7 +84,7 @@
  if( ngww(i)>1 ) ig = 1
  if( wwg(9)/=0. ) cycle
  if( ngww(i)==1 ) ewwg(1+mgww(i)) = 100.
-   if( ngww(i)==1 .and. emx(i)<huge .and. emx(i)>100. ) ewwg(1+mgww(i)) = emx(i)
+   if( ngww(i)==1 .and. emx(i)<huge_float .and. emx(i)>100. ) ewwg(1+mgww(i)) = emx(i)
  if( ngww(i)==1 .and. wwg(8)/=0. ) ewwg(1+mgww(i)) = tco(i)

```

```

        enddo

diff  -Naurd MCNP5/Source/src/avrwwg.F90 MCNP5_new/Source/src/avrwwg.F90
---  MCNP5/Source/src/avrwwg.F90      2003-04-30 20:10:12.000000000 -0600
+++  MCNP5_new/Source/src/avrwwg.F90  2004-07-22 15:14:40.000000000 -0600
@@ -142,7 +142,7 @@
    if( nwgeoa==1 ) then
      do i = 1,3
        na = i
-       dr(i) = huge
+       dr(i) = huge_float
        if( dd(i)>0. ) dr(i) = (asm(na,mi(i))-dc(i))/vc(i)
        if( dd(i)<0. ) dr(i) = (asm(na,mi(i)-1)-dc(i))/vc(i)
      enddo
@@ -173,7 +173,7 @@
! radial (r)
na = 1
rv = vc(1)*dc(1)+vc(2)*dc(2)
- dr(1) = huge
+ dr(1) = huge_float
if( v/=0. ) then
  rs = dc(1)**2+dc(2)**2
  a = rv/v
@@ -194,7 +194,7 @@
180 continue
! axial (z)
na = 2
- dr(2) = huge
+ dr(2) = huge_float
if( vc(3)/=0. ) then
  if( vc(3)>=0. ) then
    dr(2) = (asm(na,mi(2))-dc(3))/vc(3)
@@ -207,7 +207,7 @@

! azimuthal (theta)
! if single azimuthal bin (ism(3)=2), point is always in it.
- dr(3) = huge
+ dr(3) = huge_float
if( ism(3)/=2 ) then
  na = 3
  rp = -vc(1)*dc(2)+vc(2)*dc(1)
@@ -219,7 +219,7 @@
  if( vn<0. ) then
    dr(3) = (st*dc(1)-ct*dc(2))/vn
    nf(3) = -1
-    if( dr(3)<=0. ) dr(3) = huge
+    if( dr(3)<=0. ) dr(3) = huge_float
  endif
  else
    t = asm(na,mi(3))
@@ -229,7 +229,7 @@
  if( vn>0. ) then
    dr(3) = (st*dc(1)-ct*dc(2))/vn
    nf(3) = 1
-    if( dr(3)<=0. ) dr(3) = huge
+    if( dr(3)<=0. ) dr(3) = huge_float
  endif
endif
endif
endif
diff  -Naurd MCNP5/Source/src/avrxyz.F90 MCNP5_new/Source/src/avrxyz.F90
---  MCNP5/Source/src/avrxyz.F90      2003-04-30 20:10:12.000000000 -0600
+++  MCNP5_new/Source/src/avrxyz.F90  2004-07-22 15:14:40.000000000 -0600
@@ -9,6 +9,7 @@

    use mcnp_global
    use mcnp_debug
+   use erprnt_mod

    implicit real(dknd) (a-h,o-z)

diff  -Naurd MCNP5/Source/src/bankit.F90 MCNP5_new/Source/src/bankit.F90

```



```

--- MCNP5/Source/src/bankit.F90      2003-11-05 17:23:12.000000000 -0700
+++ MCNP5_new/Source/src/bankit.F90  2004-07-22 15:14:40.000000000 -0600
@@ -54,7 +54,7 @@
    write(iuo,30) npstc
    if( ntasks<=1 .and. ltasks<=1 ) then
      write(jtty,30) npstc
-30    format( " bank is full. bank backup file is being created. nps =",i10)
+30    format( " bank is full. bank backup file is being created. nps =",i12)
    endif
    open(iub+ktask,form='unformatted',status='scratch')
  endif
@@ -63,9 +63,9 @@
  if( lsb==0 ) then
    lsb = 1

-    !$OMP ATOMIC
+    !$OMP CRITICAL      (UPDATE_VARCOM)
    nbov = nbov+1
-
+    !$OMP END CRITICAL  (UPDATE_VARCOM)
  endif

  ! Write the first half (one block) of bank to the backup file.
diff -Naurd MCNP5/Source/src/brems.F90 MCNP5_new/Source/src/brems.F90
--- MCNP5/Source/src/brems.F90      2003-04-30 20:10:18.000000000 -0600
+++ MCNP5_new/Source/src/brems.F90  2004-07-22 15:14:40.000000000 -0600
@@ -9,6 +9,7 @@
  ! ae = deflection cosine of electron over path segment d.

  use mcnp_global
+ use dxtran_mod
  use mcnp_debug

  implicit real(dknd) (a-h,o-z)
@@ -173,12 +174,8 @@
  ! bank the photon.
  vel = slite
  ncp = 0
-  idx = 0
+  idx = inside_dxtran_sphere()
  jsu = 0
-  do i=1,ndx(2)
-    if( (xxx-dxx(2,1,i))**2+(yyy-dxx(2,2,i))**2+&
-      & (zzz-dxx(2,3,i))**2 < dxx(2,5,i) ) idx=i
-  end do
  if( dbcn(20)/=0. ) then
    call bankit(16)
  endif
diff -Naurd MCNP5/Source/src/alcva.F90 MCNP5_new/Source/src/alcva.F90
--- MCNP5/Source/src/alcva.F90      2003-11-05 17:23:12.000000000 -0700
+++ MCNP5_new/Source/src/alcva.F90  2004-07-22 15:14:40.000000000 -0600
@@ -32,6 +32,7 @@
  endif
endif

+
  ! Do each appropriate surface of the current cell.
  vt = 0.
  ncrn = 0
diff -Naurd MCNP5/Source/src/celnbr.F90 MCNP5_new/Source/src/celnbr.F90
--- MCNP5/Source/src/celnbr.F90     2003-04-30 20:10:20.000000000 -0600
+++ MCNP5_new/Source/src/celnbr.F90  2004-07-22 15:14:40.000000000 -0600
@@ -16,7 +16,7 @@

  implicit real(dknd) (a-h,o-z)

-  character(len=10) :: ha
+  character(len=80) :: ha
  integer :: ii(3)
  ! Statement function: moved to end

```

```

diff -Naurd MCNP5/Source/src/celpar.F90 MCNP5_new/Source/src/celpar.F90
--- MCNP5/Source/src/celpar.F90      2003-04-30 20:10:20.000000000 -0600
+++ MCNP5_new/Source/src/celpar.F90  2004-07-22 15:14:40.000000000 -0600
@@ -7,6 +7,7 @@
    use mcnp_global
    use mcnp_debug
    use mcnp_input
+   use erprnt_mod

    implicit real(dknd) (a-h,o-z)

diff -Naurd MCNP5/Source/src/celsrf.F90 MCNP5_new/Source/src/celsrf.F90
--- MCNP5/Source/src/celsrf.F90      2003-04-30 20:10:22.000000000 -0600
+++ MCNP5_new/Source/src/celsrf.F90  2004-07-22 15:14:40.000000000 -0600
@@ -9,6 +9,7 @@
    use mcnp_global
    use mcnp_debug
    use mcnp_input
+   use erprnt_mod

    implicit real(dknd) (a-h,o-z)
    character hj(2,3)*10, hl*5, hp*130, hq*2, ht*4
@@ -51,7 +52,7 @@
    endif
    do ic=1, mxa
        do j=1, ndx(i)
-           if( dxcp(j,i,ic)==huge ) dxcp(j,i,ic)=dxcp(0,i,ic)
+           if( dxcp(j,i,ic)==huge_float ) dxcp(j,i,ic)=dxcp(0,i,ic)
        end do
        do j=0, ndx(i)
            dxcp(j,i,ic) = min(max(zero,dxcp(j,i,ic)),one)
@@ -334,13 +335,13 @@
    if( mxt>1 ) go to 518

    ! If one time, check if all the cell temperatures are the same.
-   tp = -huge
+   tp = -huge_float
    do ic=1, mxa
        if( fim(1,ic)==0. .or. mat(ic)==0 ) cycle
-       if( tp==-huge ) tp=tmp(ic)
+       if( tp==-huge_float ) tp=tmp(ic)
        if( tp/=tmp(ic) ) go to 518
    end do
-   if( tp==-huge ) then
+   if( tp==-huge_float ) then
        write(iuo,512)
    512 format(/ "    all materials are in zero importance cells.")
        return
diff -Naurd MCNP5/Source/src/chekcs.F90 MCNP5_new/Source/src/chekcs.F90
--- MCNP5/Source/src/chekcs.F90      2003-04-30 20:10:22.000000000 -0600
+++ MCNP5_new/Source/src/chekcs.F90  2004-07-22 15:14:40.000000000 -0600
@@ -6,6 +6,7 @@
    use mcnp_global
    use mcnp_debug
    use mcnp_input
+   use erprnt_mod

    implicit real(dknd) (a-h,o-z)
    integer :: iu(0:mxlv), il(0:mxlv), mu(0:mxlv), jm(0:mxlv), nu(0:mxlv)
diff -Naurd MCNP5/Source/src/chekit.F90 MCNP5_new/Source/src/chekit.F90
--- MCNP5/Source/src/chekit.F90      2003-04-30 20:10:22.000000000 -0600
+++ MCNP5_new/Source/src/chekit.F90  2004-07-22 15:14:40.000000000 -0600
@@ -11,6 +11,7 @@
    use mcnp_debug
    use mcnp_input
    use fmesh_mod
+   use erprnt_mod

    implicit real(dknd) (a-h,o-z)
    character(len=10) :: hs
@@ -655,7 +656,7 @@

```

```

case( 60 )
! >>>> source particle cutoff number                                nps
-   if( nsr==71 .and. iitm>0 ) call erprnt(2,2,0,0,0,0,1,&
+   if( nsr==71 .and. i8itm>0_i8knd ) call erprnt(2,2,0,0,0,0,1,&
& ' "nps card is ineffective in kcode problems."' )

case( 66 )
@@ -913,6 +914,7 @@
    if(hptr(mlc)=='event' .or. hptr(mlc)=='file' .or. hptr(mlc)=='type') go to 9010
    if(hptr(mlc)/='value' .and. hptr(mlc)/='tally' .and. &
& hptr(mlc)/='filter' .and. hptr(mlc)/='max' .and. iitm<0) go to 9010
+   if(hptr(mlc)=='max' .and. i8itm == 0_i8knd ) go to 9010
    if(hptr(mlc)=='cell' .and. namchg(1,iitm)==0)&
& call erprnt(2,1,1,iitm,0,0,0,0,' "ptrac cell entry ",i5," is not a valid
cell."')
    if(hptr(mlc)=='surface' .and. namchg(2,iitm)==0) call erprnt(2,1,1,iitm,0,0,0,0,&
diff -Naurd MCNP5/Source/src/chektr.F90 MCNP5_new/Source/src/chektr.F90
--- MCNP5/Source/src/chektr.F90      2003-04-30 20:10:24.000000000 -0600
+++ MCNP5_new/Source/src/chektr.F90  2004-07-22 15:14:40.000000000 -0600
@@ -7,6 +7,8 @@
    use mcnp_global
    use mcnp_debug
    use mcnp_input
+   use erprnt_mod
+   use fmesh_mod

implicit real(dknd) (a-h,o-z)

@@ -46,6 +48,11 @@
    if( mfl(3,j)==m .or. ktr(j)==i ) cycle DO_305
    end do
endif
+
+   do j=1,nmesh
+   if( fm(j)%itr == i ) cycle DO_305
+   enddo
+
    call erprnt(1,2,1,i,0,0,0,0,' "tr",i3, " card unused."')
end do DO_305

diff -Naurd MCNP5/Source/src/colinp.F90 MCNP5_new/Source/src/colinp.F90
--- MCNP5/Source/src/colinp.F90      2003-04-30 20:10:28.000000000 -0600
+++ MCNP5_new/Source/src/colinp.F90  2004-07-22 15:14:41.000000000 -0600
@@ -8,6 +8,8 @@
    use mcnp_global
    use mcnp_debug
    use mcnp_input
+   use erprnt_mod
+

implicit real(dknd) (a-h,o-z)

diff -Naurd MCNP5/Source/src/collpn.F90 MCNP5_new/Source/src/collpn.F90
--- MCNP5/Source/src/collpn.F90      2003-04-30 20:10:28.000000000 -0600
+++ MCNP5_new/Source/src/collpn.F90  2004-07-22 15:14:41.000000000 -0600
@@ -4,6 +4,7 @@
subroutine collpn
! generate and bank particles from a photonuclear collision.
    use mcnp_global
+   use dxtran_mod
    use mcnp_debug

implicit real(dknd) (a-h,o-z)
@@ -93,11 +94,7 @@
    wz = wg

! check if new particle is inside a dxtran sphere.
-   idx = 0
-   do nd=1,ndx(ipt)
-   if( (xxx-dxx(ipt,1,nd))**2+(yyy-dxx(ipt,2,nd))**2+&

```

```

-      & (zzz-dxx(ipt,3,nd))**2 < dxx(ipt,5,nd) )   idx=nd
-      end do
+      idx = inside_dxtran_sphere()

      ! the minimum weight is set by the dxtran weight cutoff.
      if( idx/=0 .and. wwp(ipt,5)>=0. ) then
@@ -120,7 +117,7 @@
      cycle DO_230
      endif
      ! minimum positive energy-dependent windows.
-      wl = huge
+      wl = huge_float
      wp = -1.
      do i=1,nww(ipt)
        wv = wwval(ipt,ic1,i,1,ix)
diff -Naurd MCNP5/Source/src/crit1_mod.F90 MCNP5_new/Source/src/crit1_mod.F90
--- MCNP5/Source/src/crit1_mod.F90 2003-04-30 20:10:32.000000000 -0600
+++ MCNP5_new/Source/src/crit1_mod.F90 2004-07-22 15:14:41.000000000 -0600
@@ -25,8 +25,9 @@
      use mcnp_input
      use ra1_mod
      use ra2_mod
-
-      implicit real(dknd) (a-h,o-z)
+      use erprnt_mod, only: erprnt
+
+      implicit real(dknd) (a-h,o-z)

      contains

@@ -326,8 +327,8 @@
      & " read from the srctp file named ",a8, ".")

      ! print 3 lines of information about the keff calculation.
-      write(iuo,50) ikz,kct,nsrck,min(kcz,ikz),min(nps,nskk),&
-      & max(0,kcz-ikz),max(0,nps-nskk)
+      write(iuo,50) ikz,kct,nsrck,min(kcz,ikz),min(nps,int(nskk,i8knd)),&
+      & max(0,kcz-ikz),max(0,i8knd,nps-int(nskk,i8knd))
      50 format( " the criticality problem was scheduled to skip",i4,&
      & " cycles and run a total of",i5, " cycles with nominally",i9,&
      & " neutrons per cycle."/ " this problem has run",i4,&
@@ -543,8 +544,8 @@

      ! find largest and smallest of each active cycle keff estimator.
      do j = 1,3
-      sk = huge
-      bk = -huge
+      sk = huge_float
+      bk = -huge_float
      do i = ikz+1,mk
        if( rkpl(j,i)>bk ) then
          bk = rkpl(j,i)
diff -Naurd MCNP5/Source/src/crit2_mod.F90 MCNP5_new/Source/src/crit2_mod.F90
--- MCNP5/Source/src/crit2_mod.F90 2003-04-30 20:10:32.000000000 -0600
+++ MCNP5_new/Source/src/crit2_mod.F90 2004-07-22 15:14:41.000000000 -0600
@@ -27,6 +27,7 @@
      use mcnp_debug
      use mcnp_input
      use ra2_mod
+      use erprnt_mod

      implicit real(dknd) (a-h,o-z)

@@ -558,6 +559,7 @@
      character(len=1) :: hs
      real(dknd) :: ci(2,3,3),cg(3),ea(4),os(3),o2(3,3),za(4),zk(3,1)
      integer :: nf(3)
+      integer(i8knd) :: ns

      if( nw/=2 ) then
        ! set up for calculation of the keffs with the largest values.

```

```

@@ -594,8 +596,8 @@
    enddo
  enddo
enddo
- ns = nps+nsa-nint(rkpl(18,kcz+1))
+ sd = huge
- ns = nps+nsa-nint(rkpl(18,kcz+1),i8knd)
+ sd = huge_float

! print the header for the keff table by cycles skipped.
write(iuo,70)
@@ -666,11 +668,11 @@
    o2(j,k) = o2(j,k)-rkpl(j,kcz+1-1)*rkpl(k,kcz+1-1)
  enddo
enddo
- ns = ns-nint(rkpl(18,kcz+1-1))
+ ns = ns-nint(rkpl(18,kcz+1-1),i8knd)
enddo DO_190

! print the cycle number for the minimum combined keff deviation.
- if( nc>0 ) write(iuo,200) kcz-nc,nc
+ if( nc>0 ) write(iuo,200) int(kcz,i8knd)-nc,nc
  200 format(2/," the minimum estimated standard deviation for the",&
    & " col/abs/tl keff estimator occurs with",i4, " inactive cycles",&
    & " and",i5, " active cycles.")
diff -Naurd MCNP5/Source/src/crtcze.F90 MCNP5_new/Source/src/crtcze.F90
--- MCNP5/Source/src/crtcze.F90      2003-04-30 20:10:32.000000000 -0600
+++ MCNP5_new/Source/src/crtcze.F90  2004-07-22 15:14:41.000000000 -0600
@@ -8,6 +8,7 @@
! mm=1 to do generated weight windows.
use mcnp_global
use mcnp_debug
+ use erprnt_mod

implicit real(dknd) (a-h,o-z)

@@ -41,7 +42,7 @@
  i1 = ic
  i2 = ic
  w1 = 0.
- w2 = huge
+ w2 = huge_float
  do js=abs(lca(ic)),abs(lca(ic+1))-1
    if( abs(lja(js)) > 1000000 ) cycle
    ij = 0
diff -Naurd MCNP5/Source/src/dbmin.F90 MCNP5_new/Source/src/dbmin.F90
--- MCNP5/Source/src/dbmin.F90      2003-04-30 20:10:34.000000000 -0600
+++ MCNP5_new/Source/src/dbmin.F90  2004-07-22 15:14:41.000000000 -0600
@@ -12,7 +12,7 @@

implicit real(dknd) (a-h,o-z)

- dbmin = huge
+ dbmin = huge_float
  ic = icl
  x0 = xxx
  y0 = yyy
diff -Naurd MCNP5/Source/src/dddiag.F90 MCNP5_new/Source/src/dddiag.F90
--- MCNP5/Source/src/dddiag.F90      2003-04-30 20:10:34.000000000 -0600
+++ MCNP5_new/Source/src/dddiag.F90  2004-07-22 15:14:41.000000000 -0600
@@ -36,7 +36,7 @@
  write(iuo,60) t4,int(ddn(j,id)),t1,ddn(j+9,id)*fpi,t2
end do
if( ddg(1,id)<0. ) then
- write(iuo,60) huge,int(ddn(9,id)),1.,ddn(18,id)*fpi,1.
+ write(iuo,60) huge_float,int(ddn(9,id)),1.,ddn(18,id)*fpi,1.
  60 format(1pe19.5,i15,0pf20.5,1pe19.5,0pf15.5)
  else
    write(iuo,70) int(ddn(9,id)),1., ddn(18,id)*fpi,1.
@@ -47,7 +47,7 @@
write(iuo,80) ddn(20,id)*fpi,ddn(21,id),t, int(ddn(23,id))

```

```

80 format(/ " average tally per history =",lpe12.5,12x,"largest score =",e12.5/&
& " (largest score)/(average tally) =",e12.5,6x,&
- & "nps of largest score =",i9)
+ & "nps of largest score =",il2)
write(iuo,90)
90 format(/ " score contributions by cell"/8x, "cell",4x, "misses",&
& 6x, "hits",4x, "tally per history",4x, "weight per hit")
diff -Naurd MCNP5/Source/src/den1.F90 MCNP5_new/Source/src/den1.F90
--- MCNP5/Source/src/den1.F90 2003-04-30 20:10:36.000000000 -0600
+++ MCNP5_new/Source/src/den1.F90 2004-07-22 15:14:41.000000000 -0600
@@ -12,6 +12,7 @@
! particles in various substances", phys rev b, 26, 6067(1982).
use mcnp_global
use mcnp_debug
+ use erprnt_mod

implicit real(dknd) (a-h,o-z)

diff -Naurd MCNP5/Source/src/den2.F90 MCNP5_new/Source/src/den2.F90
--- MCNP5/Source/src/den2.F90 2003-04-30 20:10:36.000000000 -0600
+++ MCNP5_new/Source/src/den2.F90 2004-07-22 15:14:41.000000000 -0600
@@ -8,6 +8,7 @@
! this routine solves eqs. (5) and (6) of sternheimer (1982).
use mcnp_global
use mcnp_debug
+ use erprnt_mod

implicit real(dknd) (a-h,o-z)

diff -Naurd MCNP5/Source/src/Depends MCNP5_new/Source/src/Depends
--- MCNP5/Source/src/Depends 2003-04-30 20:09:58.000000000 -0600
+++ MCNP5_new/Source/src/Depends 2004-07-22 15:14:40.000000000 -0600
@@ -9,10 +9,10 @@
acedel$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
acefc$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
acefpt$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF) dynamic_arrays$(OBJF)
-acegam$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
+acegam$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF) dxtran_mod$(OBJF)
acenu$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
acetbl$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
-acetot$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
+acetot$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF) erprnt$(OBJF)
action$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
adtdfc$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF) ra2_mod$(OBJF)
amatrx$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
@@ -21,9 +21,9 @@
avrcl$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
avrnm$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
avrout$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF) rmc_mod$(OBJF)
-avrwi$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
+avrwi$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF) erprnt$(OBJF)
avrww$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
-avrxyz$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
+avrxyz$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF) erprnt$(OBJF)
axis$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF) mcnp_input$(OBJF)
backup$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
bankit$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
@@ -32,18 +32,22 @@
binval$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
brang$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
brem$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
-brems$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
+brems$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF) dxtran_mod$(OBJF)
broadn$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
calcps$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
calcva$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF) mcnp_input$(OBJF)
celnbr$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF) dynamic_arrays$(OBJF)
mcnp_plot$(OBJF)
-celpar$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF) mcnp_input$(OBJF)
-celsrf$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF) mcnp_input$(OBJF)
+celpar$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF) mcnp_input$(OBJF) \

```

```

+          erprnt$(OBJF)
+celsrf$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF) mcnp_input$(OBJF) \
+          erprnt$(OBJF)
+  cgsdci$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
-chekcs$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF) mcnp_input$(OBJF)
+chekcs$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF) mcnp_input$(OBJF) \
+          erprnt$(OBJF)
+  chekit$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF) mcnp_input$(OBJF) \
-          ral_mod$(OBJF) fmesh_mod$(OBJF)
-chektr$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF) mcnp_input$(OBJF)
+          ral_mod$(OBJF) fmesh_mod$(OBJF) erprnt$(OBJF)
+chektr$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF) mcnp_input$(OBJF) \
+          erprnt$(OBJF) fmesh_mod$(OBJF)
+  chkcel$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
+  chksrc$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
+  chqcel$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF) mcnp_input$(OBJF)
@@ -51,48 +55,53 @@
+  colidk$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF) ral_mod$(OBJF)
+  colidn$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF) ral_mod$(OBJF)
+  colidp$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
-  colinp$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF) mcnp_input$(OBJF)
-  collpn$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
+  colinp$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF) mcnp_input$(OBJF) \
+          erprnt$(OBJF)
+collpn$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF) dxtran_mod$(OBJF)
+  confid$(OBJF) : mcnp_params$(OBJF) mcnp_debug$(OBJF)
+  covar$(OBJF) : mcnp_params$(OBJF) mcnp_debug$(OBJF)
+  cprinp$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF) mcnp_input$(OBJF)
+  crit1_mod$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF) crit2_mod$(OBJF) \
-          mcnp_input$(OBJF) ral_mod$(OBJF) ra2_mod$(OBJF)
-  crit2_mod$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF) ra2_mod$(OBJF)
+          mcnp_input$(OBJF) ral_mod$(OBJF) ra2_mod$(OBJF) erprnt$(OBJF)
+crit2_mod$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF) ra2_mod$(OBJF) \
+          erprnt$(OBJF)
+  crspro$(OBJF) : mcnp_params$(OBJF) mcnp_debug$(OBJF)
-  crtcze$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
+crtcze$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF) erprnt$(OBJF)
+  dbmin$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
+  dddet$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
+  dddiag$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
+  dddlev$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
-  den1$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
-  den2$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
+  den1$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF) erprnt$(OBJF)
+  den2$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF) erprnt$(OBJF)
+  dmmp$(OBJF) : $(LIBDOTCOMM) mcnp_params$(OBJF) mcnp_debug$(OBJF)
+  dopplerp$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF) mcnp_random$(OBJF)
+  dosef$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
-  dotrcl$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF) mcnp_input$(OBJF)
+  dotrcl$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF) mcnp_input$(OBJF) \
+          erprnt$(OBJF)
+  dunlev$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
-  dxdiag$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
-  dxtran$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
+  dxtran_mod$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
+  dynamic_arrays$(OBJF) : dmmp$(OBJF) mcnp_debug$(OBJF)
+  echkcl$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
-  electr$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF) fmesh_mod$(OBJF)
+  electr$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF) fmesh_mod$(OBJF) \
+          dxtran_mod$(OBJF)
+  emaker$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
+  ephcom$(OBJF) : dmmp$(OBJF) mcnp_params$(OBJF)
-  eqpbbn$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF) mcnp_input$(OBJF)
+  eqpbbn$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF) mcnp_input$(OBJF) \
+          erprnt$(OBJF)
+  erf2$(OBJF) : mcnp_params$(OBJF) mcnp_debug$(OBJF)
+  ergimp$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
+  erprnt$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
+  errprn$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
+  escat$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
+  esloss$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF) mcnp_landau$(OBJF)

```

```

-etsplt$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
+etsplt$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF) erprnt$(OBJF)
eventp$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF) ral_mod$(OBJF)
-exemes$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF) dmmp$(OBJF)
+exemes$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF) dmmp$(OBJF) \
+
  erprnt$(OBJF)
  exmg$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
  expire$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF) dmmp$(OBJF) gxsub$(OBJF)
  expirx$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
-expung$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
+expung$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF) erprnt$(OBJF)
extran$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
  fastdr$(OBJF) : mcnp_params$(OBJF) mcnp_debug$(OBJF)
  ffetch$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
@@ -100,44 +109,56 @@
  findlv$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
  finpht$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
  fixcom$(OBJF) : dmmp$(OBJF) mcnp_params$(OBJF) racom$(OBJF)
-flaug$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
+flaug$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF) dxtran_mod$(OBJF)
  fmesh_mod$(OBJF) : mcnp_global$(OBJF) messages$(OBJF) mcnp_params$(OBJF) \
-
  mcnp_iofiles$(OBJF) mcnp_data$(OBJF) mcnp_debug$(OBJF)
+
  mcnp_iofiles$(OBJF) mcnp_data$(OBJF) mcnp_debug$(OBJF) \
  erprnt$(OBJF)
  forcol$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
  fshort$(OBJF) : mcnp_params$(OBJF) mcnp_debug$(OBJF)
  getexm$(OBJF) : mcnp_debug$(OBJF)
  getidt$(OBJF) : mcnp_params$(OBJF) mcnp_debug$(OBJF)
  getpar$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
  getxs$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
-getxst$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF) dynamic_arrays$(OBJF)
+getxst$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF) dynamic_arrays$(OBJF) \
+
  erprnt$(OBJF)
  ginst$(OBJF) : mcnp_debug$(OBJF)
  gmgnw$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
  gkssim$(OBJF) : mcnp_plot$(OBJF) mcnp_debug$(OBJF)
  gxsub$(OBJF) : mcnp_global$(OBJF) mcnp_plot$(OBJF) gkssim$(OBJF) mcnp_debug$(OBJF)
  hpsort$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
  hstory$(OBJF) : mcnp_global$(OBJF) smmp$(OBJF) ral_mod$(OBJF) fmesh_mod$(OBJF) \
-
  rmc_mod$(OBJF) mcnp_debug$(OBJF)
-igeom$(OBJF) : mcnp_global$(OBJF) mcnp_input$(OBJF) mcnp_debug$(OBJF)
+
  rmc_mod$(OBJF) mcnp_debug$(OBJF) dxtran_mod$(OBJF)
+igeom$(OBJF) : mcnp_global$(OBJF) mcnp_input$(OBJF) mcnp_debug$(OBJF) \
+
  erprnt$(OBJF)
  imcn$(OBJF) : mcnp_global$(OBJF) mcnp_input$(OBJF) crit1_mod$(OBJF) \
  ral_mod$(OBJF) ra2_mod$(OBJF) \
  fmesh_mod$(OBJF) rmc_mod$(OBJF) mcnp_debug$(OBJF)
-inpert$(OBJF) : mcnp_global$(OBJF) mcnp_input$(OBJF) mcnp_debug$(OBJF)
+inpert$(OBJF) : mcnp_global$(OBJF) mcnp_input$(OBJF) mcnp_debug$(OBJF) \
+
  erprnt$(OBJF)
  inter$(OBJF) : mcnp_global$(OBJF) mcnp_plot$(OBJF) mcnp_debug$(OBJF)
  intsec$(OBJF) : mcnp_global$(OBJF) mcnp_input$(OBJF) mcnp_debug$(OBJF)
-ipbc$(OBJF) : mcnp_global$(OBJF) mcnp_input$(OBJF) mcnp_debug$(OBJF)
+ipbc$(OBJF) : mcnp_global$(OBJF) mcnp_input$(OBJF) mcnp_debug$(OBJF) \
+
  erprnt$(OBJF)
  isheet$(OBJF) : mcnp_global$(OBJF) mcnp_plot$(OBJF) mcnp_debug$(OBJF)
  isos$(OBJF) : mcnp_random$(OBJF) mcnp_params$(OBJF) mcnp_debug$(OBJF)
-isourc$(OBJF) : mcnp_global$(OBJF) mcnp_input$(OBJF) crit1_mod$(OBJF) mcnp_debug$(OBJF)
-issrc$(OBJF) : mcnp_global$(OBJF) mcnp_input$(OBJF) mcnp_debug$(OBJF)
-itally$(OBJF) : mcnp_global$(OBJF) mcnp_input$(OBJF) mcnp_debug$(OBJF) fmesh_mod$(OBJF)
+isourc$(OBJF) : mcnp_global$(OBJF) mcnp_input$(OBJF) crit1_mod$(OBJF) mcnp_debug$(OBJF)
\
+
  qttyin$(OBJF)
+issrc$(OBJF) : mcnp_global$(OBJF) mcnp_input$(OBJF) mcnp_debug$(OBJF) \
+
  erprnt$(OBJF)
+itally$(OBJF) : mcnp_global$(OBJF) mcnp_input$(OBJF) mcnp_debug$(OBJF) \
+
  fmesh_mod$(OBJF) erprnt$(OBJF)
+
  italpr$(OBJF) : mcnp_global$(OBJF) mcnp_input$(OBJF) mcnp_debug$(OBJF)
-items$(OBJF) : mcnp_global$(OBJF) mcnp_input$(OBJF) mcnp_debug$(OBJF)
-iwtwnd$(OBJF) : mcnp_global$(OBJF) mcnp_input$(OBJF) mcnp_debug$(OBJF)
-ixsdir$(OBJF) : mcnp_global$(OBJF) mcnp_input$(OBJF) mcnp_debug$(OBJF)

```



```

+items$(OBJF) : mcnp_global$(OBJF) mcnp_input$(OBJF) mcnp_debug$(OBJF) \
+
+iwtrnd$(OBJF) : mcnp_global$(OBJF) mcnp_input$(OBJF) mcnp_debug$(OBJF) \
+
+ixsdir$(OBJF) : mcnp_global$(OBJF) mcnp_input$(OBJF) mcnp_debug$(OBJF) \
+
jbin$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
jdecod$(OBJF) : mcnp_global$(OBJF) mcplot_module$(OBJF) mcnp_plot$(OBJF) \
-
gxsub$(OBJF) mcnp_debug$(OBJF)
-
jsourc$(OBJF) : mcnp_global$(OBJF) mcnp_input$(OBJF) mcnp_debug$(OBJF)
+
gxsub$(OBJF) mcnp_debug$(OBJF) qttyin$(OBJF)
+
jsourc$(OBJF) : mcnp_global$(OBJF) mcnp_input$(OBJF) mcnp_debug$(OBJF) \
+
erprnt$(OBJF)
kdarg$(OBJF) : mcnp_params$(OBJF) mcnp_debug$(OBJF)
kdata$(OBJF) : mcnp_debug$(OBJF)
keypro$(OBJF) :
@@ -154,12 +175,15 @@
mcplot_module$(OBJF) crit1_mod$(OBJF) \
crit2_mod$(OBJF) ral_mod$(OBJF) ra2_mod$(OBJF) gxsub$(OBJF) \
mcnp_debug$(OBJF)
-
mapmaz$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
-
mbody$(OBJF) : mcnp_global$(OBJF) mcnp_input$(OBJF) mcnp_debug$(OBJF)
-
mbodyo$(OBJF) : mcnp_params$(OBJF) mcnp_debug$(OBJF)
+
mapmaz$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF) qttyin$(OBJF) \
+
erprnt$(OBJF)
+
mbody$(OBJF) : mcnp_global$(OBJF) mcnp_input$(OBJF) mcnp_debug$(OBJF) \
+
erprnt$(OBJF)
+
mbodyo$(OBJF) : mcnp_params$(OBJF) mcnp_debug$(OBJF) erprnt$(OBJF) \
+
erprnt$(OBJF)
mbodyp$(OBJF) : mcnp_global$(OBJF) mcnp_input$(OBJF) mcnp_debug$(OBJF)
-
mbodyr$(OBJF) : mcnp_params$(OBJF) mcnp_debug$(OBJF)
-
mbodyys$(OBJF) : mcnp_params$(OBJF) mcnp_debug$(OBJF)
+
mbodyr$(OBJF) : mcnp_params$(OBJF) mcnp_debug$(OBJF) erprnt$(OBJF) erprnt$(OBJF)
+
mbodyys$(OBJF) : mcnp_params$(OBJF) mcnp_debug$(OBJF) erprnt$(OBJF) erprnt$(OBJF)
mcnp_data$(OBJF) : mcnp_params$(OBJF) mcnp_debug$(OBJF)
mcnp_debug$(OBJF) : mcnp_params$(OBJF)
mcnp_global$(OBJF) : ephcom$(OBJF) fixcom$(OBJF) pblcom$(OBJF) tscom$(OBJF)
varcom$(OBJF) \
@@ -176,37 +200,41 @@
mctalw$(OBJF) : mcnp_global$(OBJF) ral_mod$(OBJF) ra2_mod$(OBJF) mcnp_debug$(OBJF)
messages$(OBJF) : dmmp$(OBJF) mcnp_debug$(OBJF)
mgacol$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
-
mgcoln$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
+
mgcoln$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF) dxtran_mod$(OBJF)
mgcolp$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
-
mgimps$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
-
mgxspt$(OBJF) : mcnp_global$(OBJF) dynamic_arrays$(OBJF) mcnp_debug$(OBJF)
+
mgimps$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF) erprnt$(OBJF)
+
mgxspt$(OBJF) : mcnp_global$(OBJF) dynamic_arrays$(OBJF) mcnp_debug$(OBJF) \
+
erprnt$(OBJF)
midpnt$(OBJF) : mcnp_global$(OBJF) mcnp_input$(OBJF) mcnp_debug$(OBJF)
movlat$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
msgcon$(OBJF) : mcnp_global$(OBJF) dmmp$(OBJF) messages$(OBJF) ral_mod$(OBJF) \
-
racom$(OBJF) fmesh_mod$(OBJF) mcnp_debug$(OBJF)
+
racom$(OBJF) fmesh_mod$(OBJF) mcnp_debug$(OBJF) qttyin$(OBJF) \
+
erprnt$(OBJF)
msgtsk$(OBJF) : mcnp_global$(OBJF) dmmp$(OBJF) messages$(OBJF) dynamic_arrays$(OBJF) \
smmp$(OBJF) ral_mod$(OBJF) racom$(OBJF) fmesh_mod$(OBJF) mcnp_debug$(OBJF)
namchg$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
-
namrsd$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
+
namrsd$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF) erprnt$(OBJF)
newcd1$(OBJF) : mcnp_global$(OBJF) dynamic_arrays$(OBJF) mcnp_input$(OBJF) \
-
ra2_mod$(OBJF) fmesh_mod$(OBJF) mcnp_debug$(OBJF)
+
ra2_mod$(OBJF) fmesh_mod$(OBJF) mcnp_debug$(OBJF) qttyin$(OBJF) \
+
erprnt$(OBJF)
newcel$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
-
newcrd$(OBJF) : mcnp_global$(OBJF) mcnp_input$(OBJF) fmesh_mod$(OBJF) mcnp_debug$(OBJF)
+
newcrd$(OBJF) : mcnp_global$(OBJF) mcnp_input$(OBJF) fmesh_mod$(OBJF) mcnp_debug$(OBJF)
\
+
qttyin$(OBJF) erprnt$(OBJF)
nextit$(OBJF) : mcnp_global$(OBJF) mcnp_input$(OBJF) ral_mod$(OBJF) ra2_mod$(OBJF) \

```

```

- fmesh_mod$(OBJF) mcnp_debug$(OBJF)
-norma$(OBJF) : mcnp_global$(OBJF) mcnp_input$(OBJF) mcnp_debug$(OBJF)
-normh$(OBJF) : mcnp_global$(OBJF) mcnp_input$(OBJF) mcnp_debug$(OBJF)
+ fmesh_mod$(OBJF) mcnp_debug$(OBJF) erprnt$(OBJF)
+norma$(OBJF) : mcnp_global$(OBJF) mcnp_input$(OBJF) mcnp_debug$(OBJF) erprnt$(OBJF)
+normh$(OBJF) : mcnp_global$(OBJF) mcnp_input$(OBJF) mcnp_debug$(OBJF) erprnt$(OBJF)
nsf$(OBJF) : mcnp_global$(OBJF) mcnp_input$(OBJF) mcnp_debug$(OBJF)
-nsourc$(OBJF) : mcnp_global$(OBJF) mcnp_input$(OBJF) mcnp_debug$(OBJF)
+nsourc$(OBJF) : mcnp_global$(OBJF) mcnp_input$(OBJF) mcnp_debug$(OBJF) erprnt$(OBJF)
nxttitl$(OBJF) : mcnp_global$(OBJF) dynamic_arrays$(OBJF) mcnp_input$(OBJF) \
ra2_mod$(OBJF) fmesh_mod$(OBJF) mcnp_debug$(OBJF)
nxtsym$(OBJF) : mcnp_debug$(OBJF)
oldcd1$(OBJF) : mcnp_global$(OBJF) dynamic_arrays$(OBJF) mcnp_input$(OBJF) \
fmesh_mod$(OBJF) mcnp_debug$(OBJF)
oldcrd$(OBJF) : mcnp_global$(OBJF) mcnp_input$(OBJF) ral_mod$(OBJF) \
- fmesh_mod$(OBJF) mcnp_debug$(OBJF)
+ fmesh_mod$(OBJF) mcnp_debug$(OBJF) erprnt$(OBJF)
output$(OBJF) : mcnp_global$(OBJF) mcplot_module$(OBJF) critl_mod$(OBJF) \
- ral_mod$(OBJF) mcnp_debug$(OBJF)
+ ral_mod$(OBJF) mcnp_debug$(OBJF) qttyin$(OBJF)
pareto$(OBJF) : mcnp_params$(OBJF) mcnp_debug$(OBJF)
pass1$(OBJF) : mcnp_global$(OBJF) dynamic_arrays$(OBJF) mcnp_input$(OBJF)
mcnp_debug$(OBJF)
pathmz$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
@@ -232,17 +260,19 @@
pnctot$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
polhed$(OBJF) : mcnp_global$(OBJF) mcnp_input$(OBJF) mcnp_debug$(OBJF)
prhpdf$(OBJF) : mcnp_global$(OBJF) mcnp_input$(OBJF) mcnp_debug$(OBJF)
-prinv$(OBJF) : mcnp_global$(OBJF) mcnp_input$(OBJF) mcnp_debug$(OBJF)
+prinv$(OBJF) : mcnp_global$(OBJF) mcnp_input$(OBJF) mcnp_debug$(OBJF) \
+ erprnt$(OBJF)
+ prlost$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
+ prsdf$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
+ prsdst$(OBJF) : mcnp_global$(OBJF) mcnp_input$(OBJF) mcnp_debug$(OBJF)
+ prssrj$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
+ prstat$(OBJF) : mcnp_global$(OBJF) ra2_mod$(OBJF) mcnp_debug$(OBJF)
-prtfc$(OBJF) : mcnp_global$(OBJF) ra2_mod$(OBJF) mcnp_debug$(OBJF)
-psurf$(OBJF) : mcnp_global$(OBJF) mcnp_input$(OBJF) mcnp_debug$(OBJF)
-ptfc$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
+prtfc$(OBJF) : mcnp_global$(OBJF) ra2_mod$(OBJF) mcnp_debug$(OBJF) erprnt$(OBJF)
+psurf$(OBJF) : mcnp_global$(OBJF) mcnp_input$(OBJF) mcnp_debug$(OBJF) \
+ erprnt$(OBJF)
+ptfc$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF) erprnt$(OBJF)
+ptost$(OBJF) : mcnp_global$(OBJF) mcnp_plot$(OBJF) mcnp_debug$(OBJF)
+ptrak$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
+ptrak$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF) erprnt$(OBJF)
+pttyin$(OBJF) : mcnp_global$(OBJF) dmmp$(OBJF) mcnp_debug$(OBJF)
+putlbl$(OBJF) : mcnp_global$(OBJF) mcnp_plot$(OBJF) mcnp_debug$(OBJF)
+putnq$(OBJF) : mcnp_global$(OBJF) mcnp_input$(OBJF) mcnp_debug$(OBJF)
@@ -253,15 +283,17 @@
quart$(OBJF) : mcnp_params$(OBJF) mcnp_debug$(OBJF)
ral_mod$(OBJF) : mcnp_global$(OBJF) dynamic_arrays$(OBJF) messages$(OBJF) \
crit2_mod$(OBJF) ra2_mod$(OBJF) racom$(OBJF) mcnp_debug$(OBJF)
-ra2_mod$(OBJF) : mcnp_global$(OBJF) mcnp_input$(OBJF) racom$(OBJF) mcnp_debug$(OBJF)
+ra2_mod$(OBJF) : mcnp_global$(OBJF) mcnp_input$(OBJF) racom$(OBJF) mcnp_debug$(OBJF) \
+ erprnt$(OBJF)
+ racom$(OBJF) : mcnp_params$(OBJF) dmmp$(OBJF)
-rdprob$(OBJF) : mcnp_global$(OBJF) mcnp_input$(OBJF) mcnp_debug$(OBJF)
+rdprob$(OBJF) : mcnp_global$(OBJF) mcnp_input$(OBJF) mcnp_debug$(OBJF) \
+ erprnt$(OBJF)
+reflec$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
+refpbc$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
-regula$(OBJF) : mcnp_global$(OBJF) mcnp_plot$(OBJF) mcnp_debug$(OBJF)
-rhoden$(OBJF) : mcnp_global$(OBJF) mcnp_input$(OBJF) mcnp_debug$(OBJF)
+regula$(OBJF) : mcnp_global$(OBJF) mcnp_plot$(OBJF) mcnp_debug$(OBJF) erprnt$(OBJF)
+rhoden$(OBJF) : mcnp_global$(OBJF) mcnp_input$(OBJF) mcnp_debug$(OBJF) erprnt$(OBJF)
+rmc_mod$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
-ronge$(OBJF) : mcnp_global$(OBJF) mcnp_landau$(OBJF) mcnp_debug$(OBJF)
+ronge$(OBJF) : mcnp_global$(OBJF) mcnp_landau$(OBJF) mcnp_debug$(OBJF) erprnt$(OBJF)
rotas$(OBJF) : mcnp_random$(OBJF) mcnp_params$(OBJF) mcnp_debug$(OBJF)
rslmaz$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)

```

```

runtpq$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
@@ -277,8 +309,9 @@
setdas$(OBJF) : mcnp_global$(OBJF) messages$(OBJF) dynamic_arrays$(OBJF) \
mcnp_input$(OBJF) mcnp_plot$(OBJF) \
ra2_mod$(OBJF) fmesh_mod$(OBJF) mcnp_debug$(OBJF)
-sfiles$(OBJF) : mcnp_global$(OBJF) mcnp_input$(OBJF) mcnp_debug$(OBJF)
-shade$(OBJF) : mcnp_global$(OBJF) mcnp_plot$(OBJF) gkssim$(OBJF) mcnp_debug$(OBJF)
+sfiles$(OBJF) : mcnp_global$(OBJF) mcnp_input$(OBJF) mcnp_debug$(OBJF) erprnt$(OBJF)
+shade$(OBJF) : mcnp_global$(OBJF) mcnp_plot$(OBJF) gkssim$(OBJF) mcnp_debug$(OBJF) \
+
simint$(OBJF) : mcnp_params$(OBJF) mcnp_debug$(OBJF)
simplx$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
sing$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
@@ -289,25 +322,26 @@
sourck$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
spec$(OBJF) : mcnp_global$(OBJF) mcnp_input$(OBJF) mcnp_params$(OBJF)
mcnp_debug$(OBJF)
spol$(OBJF) : mcnp_params$(OBJF) mcnp_debug$(OBJF)
-sprob$(OBJF) : mcnp_global$(OBJF) mcnp_input$(OBJF) mcnp_debug$(OBJF)
+sprob$(OBJF) : mcnp_global$(OBJF) mcnp_input$(OBJF) mcnp_debug$(OBJF) erprnt$(OBJF)
sqqint$(OBJF) : mcnp_global$(OBJF) mcnp_input$(OBJF) mcnp_debug$(OBJF)
srcdx$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
-srsrcrf$(OBJF) : mcnp_global$(OBJF) mcnp_input$(OBJF) mcnp_debug$(OBJF)
+read$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
+srsrcrf$(OBJF) : mcnp_global$(OBJF) mcnp_input$(OBJF) mcnp_debug$(OBJF) erprnt$(OBJF)
+read$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF) qttyin$(OBJF) erprnt$(OBJF)
+ssmsrc$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
+startp$(OBJF) : mcnp_global$(OBJF) rmc_mod$(OBJF) mcnp_debug$(OBJF)
+startp$(OBJF) : mcnp_global$(OBJF) rmc_mod$(OBJF) mcnp_debug$(OBJF) dxtran_mod$(OBJF)
+sttop$(OBJF) : mcnp_global$(OBJF) mcnp_plot$(OBJF) mcnp_debug$(OBJF)
-stuff$(OBJF) : mcnp_global$(OBJF) mcnp_input$(OBJF) mcnp_debug$(OBJF) fmesh_mod$(OBJF)
+stuff$(OBJF) : mcnp_global$(OBJF) mcnp_input$(OBJF) mcnp_debug$(OBJF) fmesh_mod$(OBJF)
\
+
+ qttyin$(OBJF) erprnt$(OBJF)
sufwrt$(OBJF) : mcnp_global$(OBJF) smmp$(OBJF) ra2_mod$(OBJF) mcnp_debug$(OBJF)
summary$(OBJF) : mcnp_global$(OBJF) crit1_mod$(OBJF) ra2_mod$(OBJF) \
-
fmesh_mod$(OBJF) mcnp_debug$(OBJF)
+
fmesh_mod$(OBJF) mcnp_debug$(OBJF) erprnt$(OBJF) dxtran_mod$(OBJF)
+
surfac$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
sursrc$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
-tallmg$(OBJF) : mcnp_global$(OBJF) smmp$(OBJF) mcnp_debug$(OBJF)
-talloc$(OBJF) : mcnp_global$(OBJF) mcnp_input$(OBJF) mcnp_debug$(OBJF)
+tallmg$(OBJF) : mcnp_global$(OBJF) smmp$(OBJF) mcnp_debug$(OBJF) erprnt$(OBJF)
+talloc$(OBJF) : mcnp_global$(OBJF) mcnp_input$(OBJF) mcnp_debug$(OBJF) erprnt$(OBJF)
tally$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
tallyd$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
-tallyh$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
+tallyh$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF) qttyin$(OBJF)
tallyp$(OBJF) : mcnp_global$(OBJF) ra2_mod$(OBJF) mcnp_debug$(OBJF)
tallyq$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
tallyx$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
@@ -322,16 +356,16 @@
torus$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
tpefil$(OBJF) : mcnp_global$(OBJF) dynamic_arrays$(OBJF) ra1_mod$(OBJF) \
ra2_mod$(OBJF) mcnp_debug$(OBJF)
-track$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
+track$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF) qttyin$(OBJF)
transm$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
-trfmat$(OBJF) : mcnp_global$(OBJF) mcnp_input$(OBJF) mcnp_debug$(OBJF)
-trfsrf$(OBJF) : mcnp_global$(OBJF) mcnp_input$(OBJF) mcnp_debug$(OBJF)
+trfmat$(OBJF) : mcnp_global$(OBJF) mcnp_input$(OBJF) mcnp_debug$(OBJF) erprnt$(OBJF)
+trfsrf$(OBJF) : mcnp_global$(OBJF) mcnp_input$(OBJF) mcnp_debug$(OBJF) erprnt$(OBJF)
trnspt$(OBJF) : mcnp_global$(OBJF) smmp$(OBJF) ra2_mod$(OBJF) mcnp_debug$(OBJF)
tskcom$(OBJF) : fixcom$(OBJF) varcom$(OBJF) mcnp_params$(OBJF)
-ttbr$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
+ttbr$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF) erprnt$(OBJF) dxtran_mod$(OBJF)
ttyint$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
-ufiles$(OBJF) : mcnp_global$(OBJF) mcnp_input$(OBJF) mcnp_debug$(OBJF)
-unimaz$(OBJF) : mcnp_global$(OBJF) dynamic_arrays$(OBJF) mcnp_debug$(OBJF)
+ufiles$(OBJF) : mcnp_global$(OBJF) mcnp_input$(OBJF) mcnp_debug$(OBJF) erprnt$(OBJF)
+unimaz$(OBJF) : mcnp_global$(OBJF) dynamic_arrays$(OBJF) mcnp_debug$(OBJF) erprnt$(OBJF)

```

```

unique$(OBJF) : mcnp_debug$(OBJF)
uplev$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
uplpos$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
@@ -339,8 +373,9 @@
utask$(OBJF) : mcnp_global$(OBJF) smmp$(OBJF) ral_mod$(OBJF) mcnp_debug$(OBJF)
varcom$(OBJF) : dmmp$(OBJF) mcnp_params$(OBJF) racom$(OBJF)
viewz$(OBJF) : mcnp_global$(OBJF) mcnp_plot$(OBJF) mcnp_debug$(OBJF)
-voidcd$(OBJF) : mcnp_global$(OBJF) mcnp_input$(OBJF) mcnp_debug$(OBJF)
-volume$(OBJF) : mcnp_global$(OBJF) mcnp_input$(OBJF) mcnp_debug$(OBJF)
+voidcd$(OBJF) : mcnp_global$(OBJF) mcnp_input$(OBJF) mcnp_debug$(OBJF) erprnt$(OBJF)
+volume$(OBJF) : mcnp_global$(OBJF) mcnp_input$(OBJF) mcnp_debug$(OBJF) qttyin$(OBJF) \
+
+ erprnt$(OBJF)
vtask$(OBJF) : mcnp_global$(OBJF) smmp$(OBJF) ral_mod$(OBJF) \
fmesh_mod$(OBJF) mcnp_debug$(OBJF)
wgtul$(OBJF) : mcnp_global$(OBJF) mcnp_input$(OBJF) mcnp_debug$(OBJF)
@@ -348,12 +383,12 @@
wtcalc$(OBJF) : mcnp_global$(OBJF) mcnp_input$(OBJF) mcnp_debug$(OBJF)
wtmult$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
wtwndo$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
-wwfile$(OBJF) : mcnp_global$(OBJF) rmc_mod$(OBJF) mcnp_debug$(OBJF)
+wwfile$(OBJF) : mcnp_global$(OBJF) rmc_mod$(OBJF) mcnp_debug$(OBJF) erprnt$(OBJF)
wwval$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
xact$(OBJF) : mcnp_global$(OBJF) crit1_mod$(OBJF) mcnp_debug$(OBJF)
xsec$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
-xsgen$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
-ypbssp$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF)
+xsgen$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF) qttyin$(OBJF) erprnt$(OBJF)
+ypbssp$(OBJF) : mcnp_global$(OBJF) mcnp_debug$(OBJF) dxtran_mod$(OBJF)
zaid$(OBJF) : mcnp_debug$(OBJF)
#
# DOTCOMM objects
diff -Naurd MCNP5/Source/src/dopplerp.F90 MCNP5_new/Source/src/dopplerp.F90
--- MCNP5/Source/src/dopplerp.F90 2003-04-30 20:10:38.000000000 -0600
+++ MCNP5_new/Source/src/dopplerp.F90 2004-07-22 15:14:41.000000000 -0600
@@ -25,14 +25,11 @@
use mcnp_random, only : rang

implicit real(dknd) (a-h,o-z)

-
- real(dknd), parameter :: ascl = 1.956934142 !1/rest mass electron
- real(dknd), parameter :: asc2 = 137.03605 !fine struct. const.
!-----

! For amu near unity
if (amu > 0.999) then
- esc = ene/(1+ene*ascl*(1-amu))
+ esc = ene/(one+ene/gpt(3)*(one-amu))
return
endif

@@ -68,28 +65,55 @@
esgmax = ene-be
if( esgmax<=zero ) cycle

-
! Sample electron momentum pz from Compton profile cdf...
+
! Calculate PZMAX
+ za = (be-ene*esgmax*(one-amu)/gpt(3))
+ zb = (two*ene*esgmax*(one-amu)+be**2)**0.5
+ pzmax = -fscon*za/zb
+
+
! Find corresponding cdf for PZMAX
+
! Index location of Compton Profile data
+ lp = jxs(10,iex)+nint(xss(jxs(9,iex)+ishell-1))-1 !beginning of CP data for
+
+ !a given shell
+
+ it = nint(xss(lp)) !it = interpolation parameter
+ ne = nint(xss(lp+1)) !ne = number of momentum entries
+ jlp = lp+2 !index of pz(1)
+ jup = lp+ne+1 !index of pz(ne)
+ jlc = lp+2*ne+2 !index of CDF(1)
+ juc = lp+3*ne+1 !index of CDF(ne)
+

```

```

+      ! binary search of momentum values, pz
+      do
+        if( jup-jlp<=1 ) exit
+        jmp = (jup+jlp)/2
+        if( pzmax<xss(jmp) ) then
+          jup = jmp
+        else
+          jlp = jmp
+        endif
+      enddo
+
+      cdfmax = xss(jlp+2*ne)      !Maximum value of CDF based on pzmax
+
+      ! Sample electron momentum pz from Compton profile cdf
+      ! Limits sampling of pzrn to pzrn <= pzmax
+      rn = rang()*cdfmax      !Normalization to maximum value of CDF
+      if( rn > cdfmax) cycle
+
+      ! binary search of Compton profile cdf
-      rn = rang()
-      lp = jxs(10,iex)+nint(xss(jxs(9,iex)+ishell-1))-1
-      it = nint(xss(lp))      !it = interpolation parameter
-      ne = nint(xss(lp+1))    !ne = number of momentum entries
-      jl = lp+2+2*ne          !index of CDF(1)
-      ju = lp+1+3*ne         !index of CDF(ne)
-      do
-        if( ju-jl<=1 ) exit
-        jm = (ju+jl)/2
-        if( rn<xss(jm) ) then
-          ju = jm
+        if( juc-jlc<=1 ) exit
+        jmc = (juc+jlc)/2
+        if( rn<xss(jmc) ) then
+          juc = jmc
+        else
-          jl = jm
+          jlc = jmc
+        endif
-      enddo
-      cdf1 = xss(jl)
-      pdf1 = xss(jl-ne)      !(lp+1+ne) + (jl-(lp+1+2ne))
-      p1 = xss(jl-2*ne)     !(lp+1) + (jl-(lp+1+2ne))
-      pdf2 = xss(jl+1-ne)
-      p2 = xss(jl+1-2*ne)
+      cdf1 = xss(jlc)
+      pdf1 = xss(jlc-ne)    !(lp+1+ne) + (jlc-(lp+1+2ne))
+      p1 = xss(jlc-2*ne)   !(lp+1) + (jlc-(lp+1+2ne))
+      pdf2 = xss(jlc+1-ne)
+      p2 = xss(jlc+1-2*ne)

      ! linear interpolation scheme
      if( p1 == p2 ) then
@@ -98,30 +122,26 @@
        pzrn = p1 + (rn - cdf1) / pdf1
      else
        bb = (pdf2 - pdf1) / (p2 - p1)
-      pzrn = p1 + (sqrt(max(zero,pdf1**2+2*bb*(rn-cdf1)))-pdf1)/bb
+      pzrn = p1 + (sqrt(max(zero,pdf1**2+two*bb*(rn-cdf1)))-pdf1)/bb
      endif

-      ! Calculate PZMAX; Reject if sampled PZRN is out of range
-      za = (be-ene*esgmax*(1-amu)*asc1)
-      zb = (2*ene*esgmax*(1-amu)+be**2)**0.5
-      pzmax = -asc2*za/zb
      if( pzrn<zero .or. pzmax<zero ) then
-      esc = ene/(1.+ene*asc1*(1.-amu))
+      esc = ene/(one+ene/gpt(3)*(one-amu))
+      exit
      endif
      if( pzrn > pzmax ) cycle

```

```

! Calculate ESC from sampled pzrn
- xa = (pzrn/asc2)**2-1.-((ene*(1.-amu)*asc1)**2)-2.*ene*(1.-amu)*asc1
- xb = 2*ene+2*(ene**2)*(1.-amu)*asc1-2.*(pzrn/asc2)**2*ene*amu
- xc = ((pzrn*ene/asc2)**2)-ene**2
- xrad = xb**2-4.*xa*xc
+ xa = (pzrn/fscon)**2-one-((ene*(one-amu)/gpt(3))**2)-two*ene*(one-amu)/gpt(3)
+ xb = two*ene+two*(ene**2)*(one-amu)/gpt(3)-two*(pzrn/fscon)**2*ene*amu
+ xc = ((pzrn*ene/fscon)**2)-ene**2
+ xrad = xb**2-four*xa*xc
+ if( xrad<zero ) cycle
+ rn = rang()
- if( rn<0.5 ) then
-   esc = .5*(-xb+sqrt(xrad))/xa
+ if( rn<half ) then
+   esc = half*(-xb+sqrt(xrad))/xa
+   else
-   esc = .5*(-xb-sqrt(xrad))/xa
+   esc = half*(-xb-sqrt(xrad))/xa
+ end if
+ if( esc>0 .and. esc <= esgmax ) exit
enddo
diff -Naurd MCNP5/Source/src/dotrcl.F90 MCNP5_new/Source/src/dotrcl.F90
--- MCNP5/Source/src/dotrcl.F90      2003-04-30 20:10:40.000000000 -0600
+++ MCNP5_new/Source/src/dotrcl.F90  2004-07-22 15:14:41.000000000 -0600
@@ -7,6 +7,7 @@
+ use mcnp_global
+ use mcnp_debug
+ use mcnp_input
+ use erprnt_mod

implicit real(dknd) (a-h,o-z)

diff -Naurd MCNP5/Source/src/dxdiag.F90 MCNP5_new/Source/src/dxdiag.F90
--- MCNP5/Source/src/dxdiag.F90      2003-04-30 20:10:40.000000000 -0600
+++ MCNP5_new/Source/src/dxdiag.F90  2004-07-22 15:14:41.000000000 -0600
@@ -13,7 +13,7 @@
+ if( ndx(ip)==0 ) cycle DO_140

+ write(iuo,10) hnp(ip)(1:len_trim(hnp(ip)))/'s',nps
-10 format( "ldxtran diagnostics -- ",a9,7x, "nps =",i9,51x,"print table 150")
+10 format( "ldxtran diagnostics -- ",a9,7x, "nps =",i12,48x,"print table 150")

! print a table for each dxtran sphere.
DO 130: do n=1,ndx(ip)
@@ -38,7 +38,7 @@
+ if( ddx(ip,1,n)<0. ) t4=-talb(j,2)*ddx(ip,1,n)
+ write(iuo,50)t4,int(dxd(ip,j,n)),t1,fpi*dxd(ip,j+9,n),t2
+ end do
- if( ddx(ip,1,n)<0. ) write(iuo,50) huge,int(dxd(ip,9,n)),1.,fpi*dxd(ip,18,n),1.
+ if( ddx(ip,1,n)<0. ) write(iuo,50)
+ huge_float,int(dxd(ip,9,n)),1.,fpi*dxd(ip,18,n),1.
+ 50 format(1pe19.4,i15,0pf20.5,1pe20.5,0pf15.5)
+ if( ddx(ip,1,n)>=0. ) write(iuo,60) int(dxd(ip,9,n)),1.,fpi*dxd(ip,18,n),1.
+ 60 format( " 1st 200 histories",i15,0pf20.5,1pe20.5,0pf15.5)
@@ -46,7 +46,7 @@
+ if( dxd(ip,20,n)/=0. ) t = dxd(ip,21,n)/(dxd(ip,20,n)*fpi)
+ write(iuo,70) dxd(ip,20,n)*fpi,dxd(ip,21,n),t,int(dxd(ip,23,n))
+ 70 format(/ " average weight per history =",1pe12.5,7x,"largest weight =",e12.5/&
+ & " largest/average =",e12.5,18x, "nps of largest =",i9)
+ & " largest/average =",e12.5,18x, "nps of largest =",i12)
+ write(iuo,80)
+ 80 format(2/," contributions by cell",2/,8x, "cell",4x, "misses",&
+ & 6x, "hits",4x, "weight per history",4x, "weight per hit"/)
diff -Naurd MCNP5/Source/src/dxtran.F90 MCNP5_new/Source/src/dxtran.F90
--- MCNP5/Source/src/dxtran.F90      2003-04-30 20:10:40.000000000 -0600
+++ MCNP5_new/Source/src/dxtran.F90  1969-12-31 17:00:00.000000000 -0700
@@ -1,299 +0,0 @@
-!+ $Id$
-! Copyright LANL/UC/DOE - see file COPYRIGHT_INFO
-
-subroutine dxtran

```

```

- ! create particles on the dxtran spheres.
- use mcnp_global
- use mcnp_debug
- implicit real(dknd) (a-h,o-z)
-
- ! return if kcode problem is not settled. initialize.
- if( kc8>0 ) return
- tw = wgt
- if( ipsc==10 ) tw = tw*cbwf
- te = erg
-
- ! adjust the weight according to the cell probability.
- if( dxcp(0,ipt,icl)==0. ) go to 110
- if( dxcp(0,ipt,icl)<1. ) then
-   if( rang(>)>dxcp(0,ipt,icl) ) go to 110
-   tw = tw/dxcp(0,ipt,icl)
- endif
-
- ! pre-processing for special cases.
- select case( ipsc )
-
-   case( 4 )
-     ! >>>> ipsc=4 -- neutron from collision with moving target.
-     tw = cmult*tw
-     if( ntyn<0 ) then
-       f = awn(iex)/ycn
-       tpd(7) = f*ssr
-       tpd(1) = tpd(7)
-       if( ntyn/=-99 ) tpd(1) = (1.+awn(iex))*sqrt(ergace/eg0)
-       tpd(2) = eg0/(1.+awn(iex))**2
-       tpd(4) = uold(1)+f*vtr(1)
-       tpd(5) = uold(2)+f*vtr(2)
-       tpd(6) = uold(3)+f*vtr(3)
-     else
-       g = sqrt(2.*ttn/awn(iex))
-       tpd(7) = g*ssr
-       tpd(1) = sqrt(2.*ergace)
-       tpd(2) = .5d+0
-       tpd(4) = g*vtr(1)
-       tpd(5) = g*vtr(2)
-       tpd(6) = g*vtr(3)
-     endif
-     tpd(3) = tpd(4)**2+tpd(5)**2+tpd(6)**2
-     if( tpd(1)**2<tpd(3) ) then
-       tw = tw*2.
-       if( rang(>)>.5d+0 ) tpd(3) = -tpd(3)
-     endif
-     go to 130
-
-   case( 5, 14:16, 104 )
-     ! >>>> ipsc=5 -- neutron from collision with stationary target and
-     ! ipsc=14 -- neutron from kalbach-87 (law 44) collision and
-     ! ipsc=15 -- neutron from law 67 (endf/b-vi law 7) collision and
-     ! ipsc=16 -- neutron from law 61 (tabulated energy / angle) and
-     ! ipsc=104 -- particle from isotropic multigroup collision.
-     tw = cmult*tw
-     go to 130
-
-   case( 103 )
-     ! >>>> ipsc=103 -- photon from double fluorescence.
-     if( rang(>)>.5d+0 ) te = xss(jxs(4,iex)+3*nxs(4,iex)+1)
-     tw = 2.*tw
-     if( te>elc(2) ) go to 130
-     go to 110
-
-   case( 105 )
-     ! >>>> ipsc=105 -- photon from pair production.
-     tw = 2.*tw
-     go to 130
-
- case( 3, 6:13, 17:18, 101:102, 106 )

```

```

-      go to 130
-
-      case default
-        call expirx(1,'dxtran','illegal value for ipsc.')
-        return
-
-      end select
-
-110 continue
- ! increment nziytc for particles that failed.
- l = icl+mx*(ndx(1)*(ipt-1)-1)
- do ix = 1,ndx(ipt)
-   if( idx/=ix ) then
-     nziytc(1,ix,ipt) = nziytc(1,ix,ipt)+1
-     dxc(kdxc+3,l+mx*ix) = dxc(kdxc+3,l+mx*ix)+1.
-   endif
- enddo
- return
-
-130 continue
- ! do all of the spheres for the current kind of particle.
- call savpar(0,2)
- nb = npb
- DO_370: do ix = 1,ndx(ipt)
-   if( idx==ix ) cycle DO_370
-
-   ld = icl9(npb)+mx*(ix-1+(ipt-1)*ndx(1))
-   dxc(kdxc+3,ld) = dxc(kdxc+3,ld)+1.
-   wgt = tw
-   if( dxcp(ix,ipt,icl)==0. ) go to 280
-   if( dxcp(ix,ipt,icl)/=1. ) then
-     if( rang()>dxcp(ix,ipt,icl) ) go to 280
-     wgt = wgt/dxcp(ix,ipt,icl)
-   endif
-   idx = ix
-
-   ! calculate the distance to the center of the sphere.
-   if( lev==0 ) then
-     f = dxx(ipt,1,ix)-xxx
-     g = dxx(ipt,2,ix)-yyy
-     h = dxx(ipt,3,ix)-zzz
-   else
-     f = dxx(ipt,1,ix)-udt(1,0)
-     g = dxx(ipt,2,ix)-udt(2,0)
-     h = dxx(ipt,3,ix)-udt(3,0)
-   endif
-   ds = f**2+g**2+h**2
-   rd = 1./sqrt(ds)
-
-   ! sample the direction to the point on the dxtran sphere.
-   pd = 1.
-   erg = te
-   psc = .5d+0
-   if( ipsc/=11 ) then
-     if( dxx(ipt,5,ix)<=1.d-5*ds ) then
-       d4 = dxx(ipt,4,ix)
-       d5 = dxx(ipt,5,ix)
-       if( d4<=1.d-10*ds ) d4 = d5
-       if( rang()*(4.*d4+d5)>=d5-d4 ) then
-         cf = (ds-rang()*.5d+0*d4)/ds
-         pd = .1d+0*(4.*d4+d5)/ds
-       else
-         cf = (ds-.5d+0*(d5-rang()*(d5-d4)))/ds
-         pd = .5d+0*(4.*d4+d5)/ds
-       endif
-     else
-       ci = sqrt(ds-dxx(ipt,4,ix))*rd
-       co = sqrt(ds-dxx(ipt,5,ix))*rd
-       pd = 5.-4.*ci-co
-       if( rang()*pd>=ci-co ) then
-         cf = (ci+rang()*(1.-ci))

```



```

-         pd = .2d+0*pd
-         else
-           cf = (co+rang()*(ci-co))
-         endif
-       endif
-       tpp(1) = f*rd
-       tpp(2) = g*rd
-       tpp(3) = h*rd
-       call rotas(cf,tpp,uvw,0,irt)
-       if( lev/=0 ) call dddlev
-
-       ! calculate the scattering probability and energy.
-       if( ipsc<=100 ) then
-         call calcpsc
-         if( kdb/=0 ) go to 380
-         if( psc==0. ) go to 290
-         if( erg<elc(ipt) ) go to 310
-         if( ipt/=2 ) vel = slite*sqrt(erg*(erg+2.*gpt(ipt)))/(erg+gpt(ipt))
-       endif
-     endif
-
-     ! calculate the transmission to the new location.
-     if( lev==0 ) then
-       q = f*uuu+g*vvv+h*www
-     else
-       q = f*udt(4,0)+g*udt(5,0)+h*udt(6,0)
-     endif
-     if( q<0. ) go to 290
-     dl = dx(ipt,5,ix)-ds+q**2
-     if( dl<0. ) go to 290
-     dd = q-sqrt(dl)
-     dd = dd-dd*ld-10
-     if( dd>=vel*(tco(ipt)-tme) ) go to 300
-     s = 0.
-     if( ddx(ipt,1,ix)<0. ) then
-       s = -ddx(ipt,1,ix)/(wgt*psc*pd)
-     elseif( ddx(ipt,1,ix)>0. .and. npstc>200 ) then
-       s = ddx(ipt,1,ix)*dxd(ipt,24,ix)/(wgt*psc*pd)
-     endif
-     call transm(dd,s,iz)
-     if( iz/=0 ) go to 295
-
-     ! set up and bank the new particle.
-     jsu = 0
-     wgt = wgt*psc*pd*exp(-amfp)
-     if( iets(ipt)>0 ) then
-       call ergimp(0)
-     endif
-     do i = 1,mipt
-       elc(i) = elp(i,icl)
-       fiml(i) = fim(i,icl)
-       do l = 0,lev-1
-         elc(i) = max( elc(i), elp(i,int(udt(7,l))) )
-         fiml(i) = fiml(i)*fim(i,int(udt(7,l)))
-       enddo
-     enddo
-     sf = wtfasv
-     if( dbcn(20)/=0. ) sf = 1.
-     if( wgt*fiml(1)*sf<=fiml9(1,1)*dxw(ipt,2) ) then
-       if( wgt*fiml(1)*sf<fiml9(1,1)*dxw(ipt,1)*rang() ) go to 320
-       wgt = fiml9(1,1)*dxw(ipt,1)/(fiml(1)*sf)
-     endif
-     if( erg<elc(ipt) ) go to 310
-     npa = 1
-     iex = iex9(npb)
-     paxtc(1,8,ipt) = paxtc(1,8,ipt)+1.
-     paxtc(2,8,ipt) = paxtc(2,8,ipt)+wgt
-     paxtc(3,8,ipt) = paxtc(3,8,ipt)+wgt*erg
-     pwb(kpwb+ipt,10,icl) = pwb(kpwb+ipt,10,icl)+wgt
-     call bankit(1)
-

```

```

- ! accumulate data for dxtran diagnostics.
- dxd(kdxd+ipt,20,ix) = dxd(kdxd+ipt,20,ix)+wgt
- j = 0
- if( ddx(ipt,1,ix)<0. ) then
-   if( wgt>=-ddx(ipt,1,ix)*ddx(ipt,2,ix) ) j = 1
-   do i = 1,8
-     if( wgt<=-talb(i,2)*ddx(ipt,1,ix) ) exit
-   enddo
- else
-   i = 9
-   if( npstc>200 ) then
-     if( wgt>=ddx(ipt,2,ix)*dxd(ipt,24,ix) ) j = 1
-     i = 1
-     if( wgt>ddx(ipt,1,ix)*dxd(ipt,24,ix) ) then
-       do i = 2,7
-         if( wgt<=talb(i,1)*dxd(ipt,24,ix) ) exit
-       enddo
-     endif
-   endif
- endif
- dxd(kdxd+ipt,i,ix) = dxd(kdxd+ipt,i,ix)+1.
- dxd(kdxd+ipt,i+9,ix) = dxd(kdxd+ipt,i+9,ix)+wgt
- if( wgt>dxd(kdxd+ipt,21,ix) ) dxd(kdxd+ipt,23,ix) = npstc
- dxd(kdxd+ipt,21,ix) = max(dxd(kdxd+ipt,21,ix),wgt)
- dxc(kdxc+1,ld) = dxc(kdxc+1,ld)+1.
- dxc(kdxc+2,ld) = dxc(kdxc+2,ld)+wgt
-
- ! print a line for especially heavy created particles.
- if( j==0 ) go to 330
-
- !$OMP CRITICAL (PRINT_OUTPUT)
- if( dxd(ipt,22,ix)<100. ) then
-   dxd(ipt,22,ix) = dxd(ipt,22,ix)+1.
-   if( mct>=-1 ) then
-     write(iuo,260) hnp(ipt),idx,wgt,wgt9(npb),psc,amfp,&
-       & dd,erg,ncl(icl9(npb)),npstc,ncp
-260   format( / " idx",4x, " dx wgt",4x, " col wgt",5x, " psc",7x, " amfp",8x,&
-     & " dd",9x, " erg",5x, " cell",8x, " nps ncp",13x,al,&
-     & /i3,lp,6ell.4,i6,i11,i5)
-   endif
- endif
- !$OMP END CRITICAL (PRINT_OUTPUT)
-
- go to 330
-
- ! increment nziytc for particles that failed.
-280 continue
- nziytc(1,ix,ipt) = nziytc(1,ix,ipt)+1
- go to 330
-290 continue
- nziytc(2,ix,ipt) = nziytc(2,ix,ipt)+1
- go to 330
-295 continue
- if( kdb/=0 ) go to 380
- nziytc(iz,ix,ipt) = nziytc(iz,ix,ipt)+1
- if( iz/=5 ) go to 330
- j = nziy(5,ix,ipt)+nziytc(5,ix,ipt)-1
- call errprn(1,j,2,zero+ix,zero+ncl(icl),'dxt','cel',&
-   & 'contribution to dxtran sphere prevented by zero importance.')
- go to 330
-300 continue
- nziytc(6,ix,ipt) = nziytc(6,ix,ipt)+1
- go to 330
-310 continue
- nziytc(7,ix,ipt) = nziytc(7,ix,ipt)+1
- go to 330
-320 continue
- nziytc(8,ix,ipt) = nziytc(8,ix,ipt)+1
-
-330 continue
- ! restore the particle description.

```

```

-   call getpar(nb,2)
-   enddo DO_370
-   npb = nb-1
-   return
-
-380 continue
- ! return with kdb=5 or 6 if the particle gets lost.
-   kdb = kdb+4
-   npb = nb-1
-   return
-end subroutine dxtran
diff -Naurd MCNP5/Source/src/dxtran_mod.F90 MCNP5_new/Source/src/dxtran_mod.F90
--- MCNP5/Source/src/dxtran_mod.F90 1969-12-31 17:00:00.000000000 -0700
+++ MCNP5_new/Source/src/dxtran_mod.F90 2004-07-22 15:14:41.000000000 -0600
@@ -0,0 +1,483 @@
+!+ $Id: dxtran_mod.F90,v 1.1 2004/04/07 16:19:47 jgoorley Exp $
+! Copyright LANL/UC/DOE - see file COPYRIGHT_INFO
+
+module dxtran_mod
+ !-----
+ ! This module contains:
+ ! (1) dxtran - perform dxtran calculations & tallies
+ ! (2) dxdiag - print dxtran diagnostics, called from summary
+ ! (3) inside_dxtran_sphere - returns the number of the dxtran
+ ! sphere containing particle, 0 if not inside sphere
+ ! (4) dist_dxtran_sphere - returns distance to nearest dxtran
+ ! sphere
+ !-----
+ use mcnp_global
+ use mcnp_debug
+ !save
+
+ ! varcom:
+ ! integer :: nziy( 8, mxdx, mipt ) != DXTRANs lost to zero importance
+ ! real(dknd):: dxcp( 0:mxdx*min(1,nxn), mipt, mxa ) != DXTRAN cell probabilities
+ ! real(dknd):: dxc( 3, mxa*nxn*mt ) != DXTRAN contributions by cell
+ ! real(dknd):: dxd( mipt, 24, mxdx*(mt+1) ) != DXTRAN diagnostics
+ ! fixcom:
+ ! real(dknd):: ddx( mipt, 2, mxdx ) != controls for DXTRAN diagnostics
+ ! real(dknd):: dxx( mipt, 5, mxdx ) != DXTRAN sphere parameters
+ ! real(dknd):: dxw( mipt, 3 ) != DXTRAN weight cutoffs
+ ! integer :: ndx(mipt) != Number of neutron & photon DXTRAN spheres
+ ! integer :: nxn != Number of DXTRAN spheres in problem
+ ! tskcom:
+ ! integer :: nziytc( 8, mxdx, mipt ) != Task copy of nziy
+ !common /dxtran_com/ nziytc
+ !xxOMP THREADPRIVATE( /dxtran_com/ )
+
+CONTAINS
+
+ !-----
+subroutine dxtran
+ ! create particles on the dxtran spheres - called during histories
+ implicit none
+ real(dknd) :: ci, co, cf, d4, d5, dd, dl, ds
+ real(dknd) :: f, g, h, pd, q, rd, rg, s, sf, te, tw
+ integer :: i, ix, iz, j, l, ld, nb
+
+ ! return if kcode problem is not settled. initialize.
+ if( kc8>0 ) return
+ tw = wgt
+ if( ipsc==10 ) tw = tw*cbwf
+ te = erg
+
+ ! adjust the weight according to the cell probability.
+ if( dxcp(0,ipt,icl)==zero ) go to 110
+ if( dxcp(0,ipt,icl)<one ) then
+ if( rang()>dxcp(0,ipt,icl) ) go to 110
+ tw = tw/dxcp(0,ipt,icl)
+ endif

```

```

+
+ ! pre-processing for special cases.
+ select case( ipsc )
+
+ case( 4 )
+ ! >>>> ipsc=4 -- neutron from collision with moving target.
+ tw = cmult*tw
+ if( ntyn<0 ) then
+   f = awn(iex)/ycn
+   tpd(7) = f*ssr
+   tpd(1) = tpd(7)
+   if( ntyn/=-99 ) tpd(1) = (one+awn(iex))*sqrt(ergace/eg0)
+   tpd(2) = eg0/(one+awn(iex))**2
+   tpd(4:6) = uold(1:3)+f*vtr(1:3)
+ else
+   g = sqrt(two*ttn/awn(iex))
+   tpd(7) = g*ssr
+   tpd(1) = sqrt(two*ergace)
+   tpd(2) = half
+   tpd(4:6) = g*vtr(1:3)
+ endif
+ tpd(3) = tpd(4)**2+tpd(5)**2+tpd(6)**2
+ if( tpd(1)**2<tpd(3) ) then
+   tw = tw*two
+   if( rang(>)>half ) tpd(3) = -tpd(3)
+ endif
+ go to 130
+
+ case( 5, 14:16, 104 )
+ ! >>>> ipsc=5 -- neutron from collision with stationary target and
+ ! ipsc=14 -- neutron from kalbach-87 (law 44) collision and
+ ! ipsc=15 -- neutron from law 67 (endf/b-vi law 7) collision and
+ ! ipsc=16 -- neutron from law 61 (tabulated energy / angle) and
+ ! ipsc=104 -- particle from isotropic multigroup collision.
+ tw = cmult*tw
+ go to 130
+
+ case( 103 )
+ ! >>>> ipsc=103 -- photon from double fluorescence.
+ if( rang(>)>half ) te = xss(jxs(4,iex)+3*nxs(4,iex)+1)
+ tw = two*tw
+ if( te>elc(2) ) go to 130
+ go to 110
+
+ case( 105 )
+ ! >>>> ipsc=105 -- photon from pair production.
+ tw = two*tw
+ go to 130
+
+ case( 3, 6:13, 17:18, 101:102, 106 )
+ go to 130
+
+ case default
+ call expirx(1,'dxtran','illegal value for ipsc.')
+ return
+
+ end select
+
+110 continue
+ ! increment nziytc for particles that failed.
+ l = icl+mxa*(ndx(1)*(ipt-1)-1)
+ do ix = 1,ndx(ipt)
+   if( idx/=ix ) then
+     nziytc(1,ix,ipt) = nziytc(1,ix,ipt)+1
+     dxc(kdxc+3,l+mxa*ix) = dxc(kdxc+3,l+mxa*ix)+one
+   endif
+ enddo
+ return
+
+130 continue
+ ! do all of the spheres for the current kind of particle.

```

```

+ call savpar(0,2)
+ nb = npb
+ DO_370: do ix = 1,ndx(ipt)
+   if( idx==ix ) cycle DO_370
+
+   ld = icl9(npb)+mxa*(ix-1+(ipt-1)*ndx(1))
+   dxc(kdxc+3,ld) = dxc(kdxc+3,ld)+one
+   wgt = tw
+   if( dxcp(ix,ipt,icl)==zero ) go to 280
+   if( dxcp(ix,ipt,icl)/=one ) then
+     if( rang(>dxcp(ix,ipt,icl) ) go to 280
+     wgt = wgt/dxcp(ix,ipt,icl)
+   endif
+   idx = ix
+
+   ! calculate the distance to the center of the sphere.
+   if( lev==0 ) then
+     f = dxx(ipt,1,ix)-xxx
+     g = dxx(ipt,2,ix)-yyy
+     h = dxx(ipt,3,ix)-zzz
+   else
+     f = dxx(ipt,1,ix)-udt(1,0)
+     g = dxx(ipt,2,ix)-udt(2,0)
+     h = dxx(ipt,3,ix)-udt(3,0)
+   endif
+   ds = f**2+g**2+h**2
+   rd = one/sqrt(ds)
+
+   ! sample the direction to the point on the dxtran sphere.
+   pd = one
+   erg = te
+   psc = half
+   if( ipsc/=11 ) then
+     if( dxx(ipt,5,ix)<=1.e-5_dknd*ds ) then
+       d4 = dxx(ipt,4,ix)
+       d5 = dxx(ipt,5,ix)
+       if( d4<=1.e-10_dknd*ds ) d4 = d5
+       if( rang()* (four*d4+d5)>=d5-d4 ) then
+         cf = (ds-rang()*half*d4)/ds
+         pd = tenth*(four*d4+d5)/ds
+       else
+         cf = (ds-half*(d5-rang()* (d5-d4)))/ds
+         pd = half*(four*d4+d5)/ds
+       endif
+     else
+       ci = sqrt(ds-dxx(ipt,4,ix))*rd
+       co = sqrt(ds-dxx(ipt,5,ix))*rd
+       pd = five-four*ci-co
+       if( rang()*pd>=ci-co ) then
+         cf = (ci+rang()* (one-ci))
+         pd = .2_dknd*pd
+       else
+         cf = (co+rang()* (ci-co))
+       endif
+     endif
+   endif
+   tpp(1) = f*rd
+   tpp(2) = g*rd
+   tpp(3) = h*rd
+   call rotas(cf,tpp,uvw,0,irt)
+   if( lev/=0 ) call dddlev
+
+   ! calculate the scattering probability and energy.
+   if( ipsc<=100 ) then
+     call calcps
+     if( kdb/=0 ) go to 380
+     if( psc==zero ) go to 290
+     if( erg<elc(ipt) ) go to 310
+     if( gpt(ipt)/=zero ) then
+       vel = slite*sqrt(erg*(erg+two*gpt(ipt)))/(erg+gpt(ipt))
+     else
+       vel = slite

```

```

+         endif
+     endif
+ endif
+
+ ! calculate the transmission to the new location.
+ if( lev==0 ) then
+     q = f*uuu+g*vvv+h*www
+ else
+     q = f*udt(4,0)+g*udt(5,0)+h*udt(6,0)
+ endif
+ if( q<zero ) go to 290
+ dl = dxx(ipt,5,ix)-ds+q**2
+ if( dl<zero ) go to 290
+ dd = q-sqrt(dl)
+ dd = dd-dd*1.0e-10_dknd
+ if( dd>=vel*(tco(ipt)-tme) ) go to 300
+ s = zero
+ if( ddx(ipt,1,ix)<zero ) then
+     s = -ddx(ipt,1,ix)/(wgt*psc*pd)
+ elseif( ddx(ipt,1,ix)>zero .and. npstc>200_i8knd ) then
+     s = ddx(ipt,1,ix)*dxd(ipt,24,ix)/(wgt*psc*pd)
+ endif
+ call transm(dd,s,iz)
+ if( iz/=0 ) go to 295
+
+ ! set up and bank the new particle.
+ jsu = 0
+ wgt = wgt*psc*pd*exp(-amfp)
+ if( iets(ipt)>0 ) then
+     call ergimp(0)
+ endif
+ do i = 1,mipt
+     elc(i) = elp(i,icl)
+     fiml(i) = fim(i,icl)
+     do l = 0,lev-1
+         elc(i) = max( elc(i), elp(i,int(udt(7,l))) )
+         fiml(i) = fiml(i)*fim(i,int(udt(7,l)))
+     enddo
+ enddo
+ sf = wtfasv
+ if( wgt*fiml(1)*sf<=fiml9(1,1)*dxw(ipt,2) ) then
+     if( wgt*fiml(1)*sf<fiml9(1,1)*dxw(ipt,1)*rang() ) go to 320
+     wgt = fiml9(1,1)*dxw(ipt,1)/(fiml(1)*sf)
+ endif
+ if( erg<elc(ipt) ) go to 310
+ npa = 1
+ iex = iex9(npb)
+ paxtc(1,8,ipt) = paxtc(1,8,ipt)+1.
+ paxtc(2,8,ipt) = paxtc(2,8,ipt)+wgt
+ paxtc(3,8,ipt) = paxtc(3,8,ipt)+wgt*erg
+ pwb(kpwb+ipt,10,icl) = pwb(kpwb+ipt,10,icl)+wgt
+ call bankit(1)
+
+ ! accumulate data for dxtran diagnostics.
+ dxd(kxd+ipt,20,ix) = dxd(kxd+ipt,20,ix)+wgt
+ j = 0
+ if( ddx(ipt,1,ix)<zero ) then
+     if( wgt>=-ddx(ipt,1,ix)*ddx(ipt,2,ix) ) j = 1
+     do i = 1,8
+         if( wgt<=-talb(i,2)*ddx(ipt,1,ix) ) exit
+     enddo
+ else
+     i = 9
+     if( npstc>200_i8knd ) then
+         if( wgt>=ddx(ipt,2,ix)*dxd(ipt,24,ix) ) j = 1
+         i = 1
+         if( wgt>ddx(ipt,1,ix)*dxd(ipt,24,ix) ) then
+             do i = 2,7
+                 if( wgt<=talb(i,1)*dxd(ipt,24,ix) ) exit
+             enddo
+         endif
+     endif
+ endif

```

```

+     endif
+   endif
+   dxd(kdxd+ipt,i,ix) = dxd(kdxd+ipt,i,ix)+one
+   dxd(kdxd+ipt,i+9,ix) = dxd(kdxd+ipt,i+9,ix)+wgt
+   if( wgt>dxd(kdxd+ipt,21,ix) ) dxd(kdxd+ipt,23,ix) = npstc
+   dxd(kdxd+ipt,21,ix) = max(dxd(kdxc+1,ld),wgt)
+   dxc(kdxc+1,ld) = dxc(kdxc+1,ld)+one
+   dxc(kdxc+2,ld) = dxc(kdxc+2,ld)+wgt
+
+   ! print a line for especially heavy created particles.
+   if( j==0 ) go to 330
+
+   !$OMP CRITICAL (PRINT_OUTPUT)
+   if( dxd(ipt,22,ix)<hundred ) then
+     dxd(ipt,22,ix) = dxd(ipt,22,ix)+one
+     if( mct>=-1 ) then
+       write(iuo,260) hnp(ipt),idx,wgt,wgt9(npb),psc,amfp,&
+         & dd,erg,ncl(icl9(npb)),npstc,ncp
+260     format(/ " idx",4x, "dx wgt",4x, "col wgt",5x, "psc",7x, "amfp",8x,&
+       & "dd",9x, "erg",5x, "cell",8x, " nps ncp",13x,a1,&
+       & /i3,6es11.4,i6,i12,i5)
+     endif
+   endif
+   !$OMP END CRITICAL (PRINT_OUTPUT)
+
+   go to 330
+
+   ! increment nziytc for particles that failed.
+280 continue
+   nziytc(1,ix,ipt) = nziytc(1,ix,ipt)+1
+   go to 330
+290 continue
+   nziytc(2,ix,ipt) = nziytc(2,ix,ipt)+1
+   go to 330
+295 continue
+   if( kdb/=0 ) go to 380
+   nziytc(iz,ix,ipt) = nziytc(iz,ix,ipt)+1
+   if( iz/=5 ) go to 330
+   j = nziy(5,ix,ipt)+nziytc(5,ix,ipt)-1
+   call errprn(1,j,2,real(ix,dknd),real(ncl(icl),dknd),'dxt','cel',&
+     & 'contribution to dxtran sphere prevented by zero importance.')
+   go to 330
+300 continue
+   nziytc(6,ix,ipt) = nziytc(6,ix,ipt)+1
+   go to 330
+310 continue
+   nziytc(7,ix,ipt) = nziytc(7,ix,ipt)+1
+   go to 330
+320 continue
+   nziytc(8,ix,ipt) = nziytc(8,ix,ipt)+1
+
+330 continue
+   ! restore the particle description.
+   call getpar(nb,2)
+   enddo DO_370
+   npb = nb-1
+   return
+
+380 continue
+   ! return with kdb=5 or 6 if the particle gets lost.
+   kdb = kdb+4
+   npb = nb-1
+   return
+end subroutine dxtran
+
+!-----
+
+subroutine dxdiag
+ ! print dxtran diagnostics - called by main thread in master
+ implicit none
+ real(dknd) :: t, t1, t2, t3, t4

```

```

+ integer    :: i, ip, j, l, m, n
+
+ ! print separate tables for neutron and photon spheres.
+ DO_140: do ip=1,mipt
+   if( ndx(ip)==0 ) cycle DO_140
+
+   write(iuo,10) hnp(ip)(1:len_trim(hnp(ip)))// 's',nps
+10  format( "ldxtran diagnostics -- ",a9,7x, "nps =",i12,48x,"print table 150")
+
+   ! print a table for each dxtran sphere.
+   DO_130: do n=1,ndx(ip)
+     if( ddx(ip,1,n)<zero ) then
+       write(iuo,20) n, (dxx(ip,i,n),i=1,3), '      maximum weight'
+     else
+       write(iuo,20) n, (dxx(ip,i,n),i=1,3), 'times average weight'
+20   format(2/, " dxtran sphere no.",i2, " located at x,y,z =",3es12.5/&
+     & 45x, "cumulative",8x, "weight",11x, "cumulative"/&
+     & 45x, "fraction of",7x, "transmitted",6x, "fraction of"/&
+     & 2x,a20,5x, "transmissions",5x, "transmissions",5x,&
+     & "per history",6x, "total weight"/)
+   endif
+   t1 = zero
+   t2 = zero
+   t3 = sum( dxd(ip,1:9,n) )
+   do j=1,8
+     if( t3/=zero ) t1=t1+dxd(ip,j,n)/t3
+     if( dxd(ip,20,n)/=zero ) t2=t2+dxd(ip,j+9,n)/dxd(ip,20,n)
+     if( ddx(ip,1,n)>=zero ) then
+       if( j==1 ) then
+         t4 = ddx(ip,1,n)
+       else
+         t4 = talb(j,1)
+       endif
+     else
+       t4 = -talb(j,2)*ddx(ip,1,n)
+     endif
+     write(iuo,50) t4,int(dxd(ip,j,n)),t1,fpi*dxd(ip,j+9,n),t2
+   end do
+   if( ddx(ip,1,n)<zero ) then
+     write(iuo,50) huge_float,int(dxd(ip,9,n)),one,fpi*dxd(ip,18,n),one
+50   format(es19.4,i15,f20.5,es20.5,f15.5)
+   endif
+   if( ddx(ip,1,n)>=zero ) then
+     write(iuo,60) int(dxd(ip,9,n)),one,fpi*dxd(ip,18,n),one
+60   format( " 1st 200 histories",i15,f20.5,es20.5,f15.5)
+   endif
+   t = one
+   if( dxd(ip,20,n)/=zero ) t = dxd(ip,21,n)/(dxd(ip,20,n)*fpi)
+   write(iuo,70) dxd(ip,20,n)*fpi,dxd(ip,21,n),t,int(dxd(ip,23,n))
+70  format(/ " average weight per history =",es12.5,7x,"largest weight =",es12.5/&
+     & " largest/average =",es12.5,18x, "nps of largest =",i12)
+   write(iuo,80)
+80  format(2/," contributions by cell",2/,8x, "cell",4x, "misses",&
+     & 6x, "hits",4x, "weight per history",4x, "weight per hit"/)
+   j = 0
+   m = 0
+   t = zero
+   l = mxa*((ip-1)*ndx(1)+n-1)
+   do i=1,msa
+     if( dxc(3,l+i)==zero ) cycle
+     j = j+dxc(3,l+i)
+     m = m+dxc(1,l+i)
+     t = t+dxc(2,l+i)
+     write(iuo,90) i,ncl(i),int(dxc(3,l+i)-dxc(1,l+i)),&
+     & int(dxc(1,l+i)),dxc(2,l+i)*fpi,dxc(2,l+i)/max(dxc(1,l+i),one)
+90   format(2i6,2i10,es18.5,es20.5)
+   end do
+   if( m/=0 ) then
+     write(iuo,110) j-m,m,t*fpi,t/m
+110  format(7x, "total",2i10,es18.5,es20.5)
+   endif

```



```

+       write(iuo,120) (nziy(i,n,ip),i=1,8)
+120  format(2/," misses"/ "   russian roulette on dxc",i19/&
+       & "   psc=0.",i36/ "   russian roulette in transmission",i10/&
+       & "   underflow in transmission",i17/&
+       & "   hit a zero-importance cell",i16/ "   time cutoff",i31/&
+       & "   energy cutoff",i29/ "   weight cutoff",i29)
+     end do DO_130
+   end do DO_140
+   return
+end subroutine dxdiag
+
+!-----
+
+function inside_dxtran_sphere()
+ ! see if particle is inside a dxtran sphere.
+ ! if so, return the sphere number, otherwise return 0
+ implicit none
+ integer :: inside_dxtran_sphere
+ integer :: j
+
+ inside_dxtran_sphere = 0
+ if( lev==0 ) then
+   do j=1,ndx(ipt)
+     if( sum((xyz(1:3)-dxx(ipt,1:3,j))**2) < dxx(ipt,5,j) ) then
+       inside_dxtran_sphere = j
+       exit
+     endif
+   enddo
+ else
+   do j=1,ndx(ipt)
+     if( sum((udt(1:3,0)-dxx(ipt,1:3,j))**2) < dxx(ipt,5,j) ) then
+       inside_dxtran_sphere = j
+       exit
+     endif
+   enddo
+ endif
+ return
+end function inside_dxtran_sphere
+
+!-----
+
+function dist_dxtran_sphere()
+ ! Calculate the distance to the nearest dxtran sphere, dxl.
+ implicit none
+ real(dknd) :: dist_dxtran_sphere
+ real(dknd) :: sr(3), sd(3), q, c
+ integer :: i
+
+ dist_dxtran_sphere = huge_float
+
+ do i = 1,ndx(ipt)
+   if( idx/=i ) then
+     if( lev==0 ) then
+       sr = dxx(ipt,1:3,i) - xyz
+       sd = uvw
+     else
+       sr = dxx(ipt,1:3,i) - udt(1:3,0)
+       sd = udt(4:6,0)
+     endif
+     q = sum( sr*sd )
+     c = min(max(zero,q),dist_dxtran_sphere)
+     if( sum( (sr-sd*c)**2 ) < dxx(ipt,5,i) ) then
+       dist_dxtran_sphere = min( dist_dxtran_sphere, &
+         & q-sqrt(max(zero,q**2+dxx(ipt,5,i)-sum(sr**2))) )
+     endif
+   endif
+ enddo
+ return
+end function dist_dxtran_sphere
+
+!-----

```

```

+end module dxtran_mod
diff -Naurd MCNP5/Source/src/electr.F90 MCNP5_new/Source/src/electr.F90
--- MCNP5/Source/src/electr.F90      2003-04-30 20:10:42.000000000 -0600
+++ MCNP5_new/Source/src/electr.F90  2004-07-22 15:14:41.000000000 -0600
@@ -5,6 +5,7 @@
! run one electron track.

use mcnp_global
+ use dxtran_mod
use mcnp_debug
use fmesh_mod, only: mesh_score, nmesh

@@ -47,12 +48,12 @@
! calculate the distances to time cutoff and energy substep.
dtc = vel*(tco(3)-tme)
n1 = ngp
- pmf = huge
+ pmf = huge_float
if( mkc/=0 ) pmf=drs(nq+nee*(mkc-1))/rho(icl)

! calculate the distance to the cell boundary, dls.
if( mbd(icl)==0 .and. jsu==0 ) then
- dls = huge
+ dls = huge_float
rr = rr-pmf
if( rr>0. ) go to 70
rr = dbmin()-pmf
@@ -98,7 +99,7 @@
pac(kpac+3,5,icl) = pac(kpac+3,5,icl)+wgt*dt*erg
pac(kpac+3,6,icl) = pac(kpac+3,6,icl)+wgt*d*erg
pac(kpac+3,7,icl) = pac(kpac+3,7,icl)+d
- if( pmf/=huge ) then
+ if( pmf/=huge_float ) then
pac(kpac+3,8,icl) = pac(kpac+3,8,icl)+wgt*d*pmf
endif
pac(kpac+3,9,icl) = pac(kpac+3,9,icl)+wgt*dt
@@ -241,11 +242,7 @@
jsu = 0
npa = 1
ncp = 0
- idx = 0
- do ii=1,ndx(2)
- if( (xxx-dxx(2,1,ii))**2+(yyy-dxx(2,2,ii))**2+
& (zzz-dxx(2,3,ii))**2 < dxx(2,5,ii) ) idx=ii
- end do
+ idx = inside_dxtran_sphere()
ipsc = 102
vel = slite
call isos(uvw,lev)
diff -Naurd MCNP5/Source/src/ephcom.F90 MCNP5_new/Source/src/ephcom.F90
--- MCNP5/Source/src/ephcom.F90      2003-04-30 20:10:44.000000000 -0600
+++ MCNP5_new/Source/src/ephcom.F90  2004-07-22 15:14:41.000000000 -0600
@@ -19,38 +19,27 @@
public
save

- ! Ephcom lengths and equivalences
+ !-----
--
+ ! (1) parameters for the length of the 3 portions of /ephcm/
+
integer, parameter :: nephcm =& != Length of real part of /EPHCM/.
& 12*(1) + 1*(4) + 1*(11)

integer, parameter :: lephcm =& != Length of integer part of /EPHCM/.
- & 49*(1) + 2*(2) + 1*(3) + 1*(novr) + 1*(nptr)
+ & 46*(1) + 2*(2) + 1*(3) + 1*(novr)

- real(dknd) :: gephcm(nephcm) != Equivalence to real part of /EPHCM/.
- integer :: jephcm(lephcm) != Equivalence to integer part of /EPHCM/.
- equivalence (cp1,gephcm), (ics,jephcm)

```

```

+ integer, parameter :: l8ephcm = &  != Length of integer*8 part of /EPHCM/.
+   & 3*1 + 1*(nptr)

- ! reals.
- common /ephcm/ &
-   & cp1, cp3, ctme, fpi, &
-   & freq, ssb, tdc, tlc, trm, &
-   & wnvp, xhom, xnum, yhom, zephcm
+ !-----
--
+ ! (2) declarations for 3 arrays equivalenced to /ephcm/

- ! integers.
- common /ephcm/ &
-   & ics, idmp, ifile, iln, iln1, &
-   & inform, iovr, inpd, iptr, iptra, &
-   & irup, itask, iterm, itfxs, itotnu, &
-   & iuou, jchar, jfcn, jgf, jgxa, &
-   & jgxo, jovr, jtasks, jtfc, jvp, &
-   & kbp, kdbnps, kmplot, komout, konrun, &
-   & kprod, krflg, krtm, ksr, ktfile, &
-   & lchnk, lfat1, lock1, lspeed, ltasks, &
-   & mazf, mcolor, mdc, mmkdb, mnk, &
-   & mpc, mrm, nde, nkrp, nomore, &
-   & nrc, nst, ntasks, mephcm, lock1, &
-   & mynum
+ real(dknd) :: gephcm(nephcm) != Equivalence to real part of /EPHCM/.
+ integer(i8knd) :: i8ephcm(l8ephcm) != Equivalence to integer*8 part of /EPHCM/.
+ integer :: jephcm(lephcm) != Equivalence to integer part of /EPHCM/.

+ !-----
--
+ ! (3) declarations for /ephcm/ REALS
real(dknd) :: cp1           != Computer time used after beginning MCRUN.
real(dknd) :: cp3           != Computer time of multiprocessing subtasks.
real(dknd) :: ctme          != User requested ctm endtime.
@@ -66,6 +55,14 @@
real(dknd) :: yhom          != Vertical coordinate of home position.
real(dknd) :: zephcm       != Marker after floating-point part of /EPHCM/.

+ !-----
--
+ ! (4) declarations for /ephcm/ INTEGER*8
+ integer(i8knd) :: kdbnps   != NPS of bad-trouble history in multitasking.
+ integer(i8knd) :: inpd     != TFC rendezvous frequency (5th PRDMP entry).
+ integer(i8knd) :: nde     != Value of execute-message item DEBUG n.
+ integer(i8knd) :: iptra(nptr) != Pointer to PTR() for each PTRAC keyword.
+ !-----
--
+ ! (5) declarations for /ephcm/ INTEGERS
integer :: ics              != Flag for error on current input card.
integer :: idmp            != Number of the dump to start a continue run from.
integer :: ifile           != I/O unit of current plot input file.
@@ -73,9 +70,7 @@
integer :: iln1            != Saved count of lines of input data.
integer :: inform          != Flag for output to plot user.
integer :: iovr            != Index of the current code section.
- integer :: inpd          != TFC rendezvous frequency (5th PRDMP entry).
integer :: iptr            != PTRAC option flag.
- integer :: iptra(nptr)   != Pointer to PTR() for each PTRAC keyword.
integer :: irup            != Flag set by user with ctrl-c interrupt.
integer :: itask           != Number of active tasks.
integer :: iterm           != Type of plotting display.
@@ -92,7 +87,6 @@
integer :: jtfc            != Flag to indicate TFC update is due.
integer :: jvp             != Flag for square viewport.
integer :: kbp             != Interrupt flag for multitasking mode.
- integer :: kdbnps        != NPS of bad-trouble history in multitasking.
integer :: kmplot          != Indicator of < ctrl-e > MCPLLOT interrupt.
integer :: komout          != Indicator that COMOUT has been created.
integer :: konrun          != Continue-run flag.

```

```

@@ -113,7 +107,6 @@
integer :: mnk           != Flag to indicate maximum printing is wanted.
integer :: mpc           != Flag indicating that printing is due to be done.
integer :: mrm           != Flag indicating that plotting is due to be done.
- integer :: nde         != Value of execute-message item DEBUG n.
integer :: nkrp         != Latch for warning in CALCPS.
integer :: nomore       != Flag for exhausted surface-source file.
integer :: nrc          != Count of restarts in the run.
@@ -124,21 +117,37 @@

logical :: lockl       ! = Logical lock variable.

-contains

- subroutine eph_cast(mh,mx,ie)
- ! Description:
- ! DMMP bcast of ephcom data.
- ! Arguments:
- integer,intent(in)    :: mh ! action flag, 0 -> sender.
- integer,intent(in)    :: mx ! message chunk size (max).
- integer,intent(inout) :: ie ! return status.
+ !-----
--
+ ! (6) declaration for /ephcm/ (real, integer*8, integer)

- call dm_bcast(mh,gephcm,nephcm,mx,ie)
- call dm_bcast(mh,jephcm,lephcm,mx,ie)
+ common /ephcm/ &
+ & cp1, cp3, ctme, fpi, &
+ & freq, ssb, tdc, tlc, trm, &
+ & wnvp, xhom, xnum, yhom, zephcm

- return
- end subroutine eph_cast
+ common /ephcm/ &
+ & kdbnps, inpd, nde, iptra
+
+
+ common /ephcm/ &
+ & ics, idmp, ifile, iln, iln1, &
+ & inform, iovr, iptr, &
+ & irup, itask, iterm, itfxs, itotnu, &
+ & iuou, jchar, jfcn, jgf, jgxa, &
+ & jgxo, jovr, jtasks, jtfc, jvp, &
+ & kbp, kmplot, komout, konrun, &
+ & kprod, krflg, krtm, ksr, ktfile, &
+ & lchnk, lfatl, locki, lspeed, ltasks, &
+ & mazf, mcolor, mdc, mmkdb, mnk, &
+ & mpc, mrm, nkrp, nomore, &
+ & nrc, nst, ntasks, mephcm, lockl, &
+ & mynum

+ equivalence (cp1, gephcm)
+ equivalence (kdbnps, i8ephcm)
+ equivalence (ics, jephcm)
+
+ !-----
end module ephcom
!-
diff -Naurd MCNP5/Source/src/eqpbbn.F90 MCNP5_new/Source/src/eqpbbn.F90
--- MCNP5/Source/src/eqpbbn.F90 2003-04-30 20:10:44.000000000 -0600
+++ MCNP5_new/Source/src/eqpbbn.F90 2004-07-22 15:14:41.000000000 -0600
@@ -13,6 +13,7 @@
use mcnp_global
use mcnp_debug
use mcnp_input
+ use erprnt_mod

implicit real(dknd) (a-h,o-z)
external spec
diff -Naurd MCNP5/Source/src/ergimp.F90 MCNP5_new/Source/src/ergimp.F90

```

```

--- MCNP5/Source/src/ergimp.F90      2003-04-30 20:10:46.000000000 -0600
+++ MCNP5_new/Source/src/ergimp.F90  2004-07-22 15:14:41.000000000 -0600
@@ -19,7 +19,7 @@
    sf = wtfasv
    wtfasv = 1.
    e0 = eg0
-   if( i0==0 ) e0=huge
+   if( i0==0 ) e0=huge_float
    ! find esplt/tsplt importance ratio bins for increasing values.
    tf = erg
    do ib=1,2
diff -Naurd MCNP5/Source/src/erprnt.F90 MCNP5_new/Source/src/erprnt.F90
--- MCNP5/Source/src/erprnt.F90      2003-04-30 20:10:46.000000000 -0600
+++ MCNP5_new/Source/src/erprnt.F90  2004-07-22 15:14:41.000000000 -0600
@@ -1,89 +1,360 @@
-!+ $Id$
+!+ $Id: erprnt.F90,v 1.3 2004/05/19 21:09:38 fbrown Exp $
    ! Copyright LANL/UC/DOE - see file COPYRIGHT_INFO

-subroutine erprnt(im,jf,nk,k1,k2,k3,k4,js,hf)
+module erprnt_mod
    ! Description:
    ! Print messages about errors in the problem specifications.
    ! Notice:
    ! Terminal messages on some systems are limited to 70 characters.
    ! So fatal errors should have only 55 characters, warnings 59.
+   ! Four versions are supplied: erprnt, erprnt_i8_k1, erprnt_i8_k2, and
+   ! erprnt_i8_k1k2. The specializations allow passing of i8knd integers.

-   ! Modules used:
-   use mcnp_global
-   use mcnp_debug
-   implicit none
+   contains

-   ! Argument declarations:
-   integer :: im,jf,nk,k1,k2,k3,k4,js
-   ! im=1 print message only. im=2 klin also, to terminal.
-   ! jf=1 fatal error. jf=2 warning only. jf=3=comment only
-   ! nk = how many of the parameters k1 thru k4 are to be printed.
-   ! js > 0 set ics = -1; js < 0 print to jtty only.
-   character(len=*) :: hf ! partial printing format.
+   subroutine erprnt(im,jf,nk,k1,k2,k3,k4,js,hf)
+   ! erprnt subroutine when all variables are the same type of integers.
+   ! Note that on some platforms they will all be I4, on other
+   ! platforms (usually compiled with -I8R8) all arguments will be I8.

-   ! Local declarations:
-   integer :: kk(4), j
-   character(len=100) :: hp
-   character(len=20),dimension(3) :: hs = &
-   & (/ '(" fatal error. ",', '&
-   & '(" warning. ",', '&
-   & '(" comment. ",', '/')
+   ! Modules used:
+   use mcnp_global
+   use mcnp_debug

+   implicit none

-   ! Move the parameters to be printed into the printing block.
-   kk = (/k1,k2,k3,k4/)
+   ! Argument declarations:
+   integer :: im,jf,nk,k1,k2,k3,k4,js
+   ! im=1 print message only. im=2 klin also, to terminal.
+   ! jf=1 fatal error. jf=2 warning only. jf=3 comment only.
+   ! nk = how many of the parameters k1 thru k4 are to be printed.
+   ! js > 0 set ics = -1; js < 0 print to jtty only.
+   character(len=*) :: hf ! partial printing format.

-   ! Assemble the format from the leaders and the partial format, hf.

```

```

- j = jf
- if( jf<1 .or. jf>3 ) j = 1
- hp = hs(j) // hf // ')'
+ ! Local declarations:
+ integer :: kk(4)
+ integer :: j
+ character(len=100) :: hp
+ character(len=20),dimension(3) :: hs = &
+ & (/ (' fatal error. ', ', &
+ & (' warning. ', ', &
+ & (' comment. ', ' /)

- ! Print the error message to the output file.
- if( js>=0 ) then
-   if( im==1 ) write(iuo,'(" ")')
-   if( iln1<0 .and. im==2 ) write(iuo,'(1x,a69)') klin(1:69)
-   if( nk==0 ) then
-     write(iuo,hp)
+
+ ! Move the parameters to be printed into the printing block.
+ kk = (/k1,k2,k3,k4/)
+
+ ! Assemble the format from the leaders and the partial format, hf.
+ j = jf
+ if( jf<1 .or. jf>3 ) j = 1
+ hp = hs(j) // hf // ')'
+
+ ! Print the error message to the output file.
+ if( js>=0 ) then
+   if( im==1 ) write(iuo,'(" ")')
+   if( iln1<0 .and. im==2 ) write(iuo,'(1x,a69)') klin(1:69)
+   if( nk==0 ) then
+     write(iuo,hp)
+   else
+     write(iuo,hp) kk(1:min(4,nk))
+   endif
+ endif
+
+ ! Also print, if required, to the terminal.
+ ! In production mode, messages are not sent to the terminal.
+ if( (kprod==0 .and. nwer+nfer<20) .or. (nfer==0 .and. jf==1) ) then
+   if( iovr==1 .and. im/=2 .and. iln1/=0 ) write(jtty,'(" ")')
+   if( im/=2 ) iln1 = 0
+   if( iln/=iln1 .and. im==2 ) write(jtty,'(1x,a69)') klin(1:69)
+   if( im==2 ) iln1 = iln
+   if( nk==0 ) then
+     write(jtty,hp)
+   else
+     write(jtty,hp) kk(1:min(4,nk))
+   endif
+ endif
+
+ ! Limit the number of error messages to the controller to 20.
+ if( kprod==0 .and. nfer+nwer==20 ) write(jtty,20) outp
+20 format(" additional error messages on file ",a8)
+
+ ! Increment count of fatal errors or warnings.
+ if( jf==3 ) then
+   ! don't count the "comments"
+   continue
+ elseif( jf==2 ) then
+   ! Warning only.
+   if( npp>=0 ) nwer = nwer+1
+ else
-   write(iuo,hp) kk(1:min(4,nk))
+   ! Fatal condition.
+   nfer = nfer+1
+   if( mct>=0 ) then
+     ink(1:mink) = 1
+     mnk = 1

```

```

+     endif
+   endif
- endif
+   if( js>0 )   ics = -1

- ! Also print, if required, to the terminal.
- ! In production mode, messages are not sent to the terminal.
- if( (kprod==0 .and. nwer+nfer<20) .or. (nfer==0 .and. jf==1) ) then
-   if( iovr==1 .and. im/=2 .and. iln1/=0 ) write(jtty,'(" ")')
-   if( im/=2 )   iln1 = 0
-   if( iln/=iln1 .and. im==2 ) write(jtty,'(1x,a69)')   klin(1:69)
-   if( im==2 )   iln1 = iln
-   if( nk==0 ) then
-     write(jtty,hp)
+   return
+ end subroutine erprnt
+
+ subroutine erprnt_i8_k1(im,jf,nk,k1,k2,k3,k4,js,hf)
+   ! erprnt subroutine for explicit 8 byte integer argument k1.
+
+   ! Modules used:
+   use mcnp_global
+   use mcnp_debug
+
+   implicit none
+
+   ! Argument declarations:
+   integer      :: im,jf,nk,k2,k3,k4,js
+   integer(i8knd) :: k1
+   ! im=1 print message only.   im=2 klin also, to terminal.
+   ! jf=1 fatal error.         jf=2 warning only.   jf=3 comment only.
+   ! nk = how many of the parameters k1 thru k4 are to be printed.
+   ! js > 0 set ics = -1;   js < 0 print to jtty only.
+   character(len=*)  :: hf ! partial printing format.
+
+   ! Local declarations:
+   integer(i8knd) :: kk(4)
+   integer      :: j
+   character(len=100) :: hp
+   character(len=20),dimension(3) :: hs = &
+     & (/ '(" fatal error. ", ', &
+     & '(" warning. ",      ', &
+     & '(" comment. ",      ' /)
+
+   ! Move the parameters to be printed into the printing block.
+   kk = (/k1,int(k2,i8knd),int(k3,i8knd),int(k4,i8knd)/)
+
+   ! Assemble the format from the leaders and the partial format, hf.
+   j = jf
+   if( jf<1 .or. jf>3 ) j = 1
+   hp = hs(j) // hf // ' '
+
+   ! Print the error message to the output file.
+   if( js>=0 ) then
+     if( im==1 ) write(iuo,'(" ")')
+     if( iln1<0 .and. im==2 ) write(iuo,'(1x,a69)')   klin(1:69)
+     if( nk==0 ) then
+       write(iuo,hp)
+     else
+       write(iuo,hp)   kk(1:min(4,nk))
+     endif
+   endif
+
+   ! Also print, if required, to the terminal.
+   ! In production mode, messages are not sent to the terminal.
+   if( (kprod==0 .and. nwer+nfer<20) .or. (nfer==0 .and. jf==1) ) then
+     if( iovr==1 .and. im/=2 .and. iln1/=0 ) write(jtty,'(" ")')
+     if( im/=2 )   iln1 = 0
+     if( iln/=iln1 .and. im==2 ) write(jtty,'(1x,a69)')   klin(1:69)
+     if( im==2 )   iln1 = iln

```

```

+     if( nk==0 ) then
+       write(jtty,hp)
+     else
+       write(jtty,hp)  kk(1:min(4,nk))
+     endif
+   endif
+
+
+   ! Limit the number of error messages to the controller to 20.
+   if( kprod==0 .and. nfer+nwer==20 ) write(jtty,20) outp
+20 format(" additional error messages on file ",a8)
+
+   ! Increment count of fatal errors or warnings.
+   if(   jf==3 ) then
+     ! don't count the "comments"
+     continue
+   elseif( jf==2 ) then
+     ! Warning only.
+     if( npp>=0 ) nwer = nwer+1
+   else
-     write(jtty,hp)  kk(1:min(4,nk))
+     ! Fatal condition.
+     nfer = nfer+1
+     if( mct>=0 ) then
+       ink(1:mink) = 1
+       mnk = 1
+     endif
-   endif
+   if( js>0 ) ics = -1
+
+   return
+ end subroutine erprnt_i8_k1
-
- ! Limit the number of error messages to the controller to 20.
- if( kprod==0 .and. nfer+nwer==20 ) write(jtty,20) outp
-20 format(" additional error messages on file ",a8)
+ subroutine erprnt_i8_k2(im,jf,nk,k1,k2,k3,k4,js,hf)
+   ! erprnt subroutine for explicit 8 byte integer argument k2.
-
- ! Increment count of fatal errors or warnings.
- if(   jf==3 ) then
-   ! don't count the "comments"
-   continue
- elseif( jf==2 ) then
-   ! Warning only.
-   if( npp>=0 ) nwer = nwer+1
- else
-   ! Fatal condition.
-   nfer = nfer+1
-   if( mct>=0 ) then
-     ink(1:mink) = 1
-     mnk = 1
+   ! Modules used:
+   use mcnp_global
+   use mcnp_debug
+
+   implicit none
+
+   ! Argument declarations:
+   integer      :: im,jf,nk,k1,k3,k4,js
+   integer(i8knd) :: k2
+   ! im=1 print message only.   im=2 klin also, to terminal.
+   ! jf=1 fatal error.         jf=2 warning only.   jf=3 comment only.
+   ! nk = how many of the parameters k1 thru k4 are to be printed.
+   ! js > 0 set ics = -1;  js < 0 print to jtty only.
+   character(len=*)  :: hf ! partial printing format.
+
+   ! Local declarations:
+   integer(i8knd) :: kk(4)
+   integer      :: j

```



```

+ character(len=100) :: hp
+ character(len=20),dimension(3) :: hs = &
+   & (/ '(" fatal error. ", ' , &
+     & '(" warning. ", ' , &
+     & '(" comment. ", ' /)
+
+
+   ! Move the parameters to be printed into the printing block.
+   kk = (/int(k1,i8knd),k2,int(k3,i8knd),int(k4,i8knd)/)
+
+   ! Assemble the format from the leaders and the partial format, hf.
+   j = jf
+   if( jf<1 .or. jf>3 ) j = 1
+   hp = hs(j) // hf // ' '
+
+   ! Print the error message to the output file.
+   if( js>=0 ) then
+     if( im==1 ) write(iuo,'(" ")')
+     if( iln1<0 .and. im==2 ) write(iuo,'(1x,a69)') klin(1:69)
+     if( nk==0 ) then
+       write(iuo,hp)
+     else
+       write(iuo,hp) kk(1:min(4,nk))
+     endif
+   endif
- endif
- if( js>0 ) ics = -1

- return
-end subroutine erprnt
+   ! Also print, if required, to the terminal.
+   ! In production mode, messages are not sent to the terminal.
+   if( (kprod==0 .and. nwer+nfer<20) .or. (nfer==0 .and. jf==1) ) then
+     if( iover==1 .and. im/=2 .and. iln1/=0 ) write(jtty,'(" ")')
+     if( im/=2 ) iln1 = 0
+     if( iln/=iln1 .and. im==2 ) write(jtty,'(1x,a69)') klin(1:69)
+     if( im==2 ) iln1 = iln
+     if( nk==0 ) then
+       write(jtty,hp)
+     else
+       write(jtty,hp) kk(1:min(4,nk))
+     endif
+   endif
+
+   ! Limit the number of error messages to the controller to 20.
+   if( kprod==0 .and. nfer+nwer==20 ) write(jtty,20) outp
+20 format(" additional error messages on file ",a8)
+
+   ! Increment count of fatal errors or warnings.
+   if( jf==3 ) then
+     ! don't count the "comments"
+     continue
+   elseif( jf==2 ) then
+     ! Warning only.
+     if( npp>=0 ) nwer = nwer+1
+   else
+     ! Fatal condition.
+     nfer = nfer+1
+     if( mct>=0 ) then
+       ink(1:mink) = 1
+       mnk = 1
+     endif
+   endif
+   if( js>0 ) ics = -1
+
+   return
+ end subroutine erprnt_i8_k2
+
+ subroutine erprnt_i8_k1k2(im,jf,nk,k1,k2,k3,k4,js,hf)
+   ! erprnt subroutine for explicit 8 byte integer arguments k1 and k2.

```

```

+
+ ! Modules used:
+ use mcnp_global
+ use mcnp_debug
+
+ implicit none
+
+ ! Argument declarations:
+ integer      :: im,jf,nk,k3,k4,js
+ integer(i8knd) :: k1,k2
+ ! im=1 print message only.   im=2 klin also, to terminal.
+ ! jf=1 fatal error.         jf=2 warning only.   jf=3 comment only.
+ ! nk = how many of the parameters k1 thru k4 are to be printed.
+ ! js > 0 set ics = -1;  js < 0 print to jtty only.
+ character(len=*)  :: hf ! partial printing format.
+
+ ! Local declarations:
+ integer(i8knd) :: kk(4)
+ integer      :: j
+ character(len=100) :: hp
+ character(len=20),dimension(3) :: hs = &
+   & (/ ' (" fatal error.  ", ' ', &
+   &   ' (" warning.  ",      ' ', &
+   &   ' (" comment.  ",      ' ' /)
+
+
+ ! Move the parameters to be printed into the printing block.
+ kk = (/k1,k2,int(k3,i8knd),int(k4,i8knd)/)
+
+ ! Assemble the format from the leaders and the partial format, hf.
+ j = jf
+ if( jf<1 .or. jf>3 ) j = 1
+ hp = hs(j) // hf // ' )'
+
+ ! Print the error message to the output file.
+ if( js>=0 ) then
+   if( im==1 ) write(iuo,' ( " ")')
+   if( iln1<0 .and. im==2 ) write(iuo,'(1x,a69)') klin(1:69)
+   if( nk==0 ) then
+     write(iuo,hp)
+   else
+     write(iuo,hp)  kk(1:min(4,nk))
+   endif
+ endif
+
+ ! Also print, if required, to the terminal.
+ ! In production mode, messages are not sent to the terminal.
+ if( (kprod==0 .and. nwer+nfer<20) .or. (nfer==0 .and. jf==1) ) then
+   if( iovr==1 .and. im/=2 .and. iln1/=0 ) write(jtty,' ( " ")')
+   if( im/=2 ) iln1 = 0
+   if( iln1/=iln1 .and. im==2 ) write(jtty,'(1x,a69)') klin(1:69)
+   if( im==2 ) iln1 = iln
+   if( nk==0 ) then
+     write(jtty,hp)
+   else
+     write(jtty,hp)  kk(1:min(4,nk))
+   endif
+ endif
+
+ ! Limit the number of error messages to the controller to 20.
+ if( kprod==0 .and. nfer+nwer==20 ) write(jtty,20) outp
+20 format(" additional error messages on file ",a8)
+
+ ! Increment count of fatal errors or warnings.
+ if( jf==3 ) then
+   ! don't count the "comments"
+   continue
+ elseif( jf==2 ) then
+   ! Warning only.
+   if( npp>=0 ) nwer = nwer+1

```

```

+   else
+     ! Fatal condition.
+     nfer = nfer+1
+     if( mct>=0 ) then
+       ink(1:mink) = 1
+       mnk = 1
+     endif
+   endif
+   if( js>0 ) ics = -1
+
+   return
+ end subroutine erprnt_i8_k1k2
+
+end module erprnt_mod
diff -Naurd MCNP5/Source/src/errprn.F90 MCNP5_new/Source/src/errprn.F90
--- MCNP5/Source/src/errprn.F90      2003-04-30 20:10:48.000000000 -0600
+++ MCNP5_new/Source/src/errprn.F90  2004-07-22 15:14:41.000000000 -0600
@@ -21,14 +21,14 @@
    real(dknd),      intent(in)      :: v1, v2
    character(len=*), intent(in)      :: h1, h2, hf
    integer(i8knd)  :: i8_count
-   character       :: ha*16, hb*26, hc*37, hd*60
+   character       :: ha*18, hb*26, hc*37, hd*60

    ! Print warning if this is the first time encountered.
    if( n1<=0 ) then

        !$OMP CRITICAL (PRINT_OUTPUT)
        hd = hf
-       write(ha, '(' nps =",i10)') npstc
+       write(ha, '(' nps =",i12)') npstc
        !*** Note: next line differs from versions prior to 5
        call RN_query( count=i8_count )
        write(hb, '('nrn =",i20,lx)') i8_count
@@ -46,22 +46,24 @@
        case default
            hc = ' '
        end select
-       write(iuo, '(' warning. ",a60/a16,5x,a26,a37)') hd,ha,hb,hc
+       write(iuo, '(' warning. ",a60/a18,5x,a26,a37)') hd,ha,hb,hc
        if( ntasks<=1 .and. ltasks<=1 )&
-         & write(jtty, '(' warning. ",a60/a16,5x,a37)') hd,ha,hc
+         & write(jtty, '(' warning. ",a60/a18,5x,a37)') hd,ha,hc
        !$OMP END CRITICAL (PRINT_OUTPUT)

        if( npp>=0 ) then
-         !$OMP ATOMIC
+         !$OMP CRITICAL      (UPDATE_VARCOM)
            nwer = nwer+1
+         !$OMP END CRITICAL  (UPDATE_VARCOM)
        endif

    endif

    ! Increment counts and unlock multitasking as required.
    if( n1>=0 ) then
-     !$OMP ATOMIC
+     !$OMP CRITICAL      (UPDATE_VARCOM)
        n1 = n1+1
+     !$OMP END CRITICAL  (UPDATE_VARCOM)
    endif

    return
diff -Naurd MCNP5/Source/src/etsplt.F90 MCNP5_new/Source/src/etsplt.F90
--- MCNP5/Source/src/etsplt.F90      2003-04-30 20:10:48.000000000 -0600
+++ MCNP5_new/Source/src/etsplt.F90  2004-07-22 15:14:41.000000000 -0600
@@ -6,6 +6,7 @@
    ! print esplt and tsplt importance tables if requested (ink(80)).
    use mcnp_global
    use mcnp_debug
+   use erprnt_mod

```

```

integer :: js(2)          = (/ 0, 0 /)
integer :: ke(2,mipt) = reshape( (/ (0,i=1,2*mipt) /), (/2,mipt/) )
diff -Naurd MCNP5/Source/src/exemes.F90 MCNP5_new/Source/src/exemes.F90
--- MCNP5/Source/src/exemes.F90      2003-04-30 20:10:50.000000000 -0600
+++ MCNP5_new/Source/src/exemes.F90  2004-07-22 15:14:41.000000000 -0600
@@ -9,6 +9,7 @@
use mcnp_global
use dmmp, only: dm_nhost
use mcnp_debug
+ use erprnt_mod

implicit real(dknd) (a-h,o-z)

@@ -28,6 +29,7 @@
! Do the execute line message and the inp message block.
DO_250: do ls = 1,2

+
call set_filenames
hm(:) = ' '

diff -Naurd MCNP5/Source/src/expire.F90 MCNP5_new/Source/src/expire.F90
--- MCNP5/Source/src/expire.F90      2003-04-30 20:10:52.000000000 -0600
+++ MCNP5_new/Source/src/expire.F90  2004-07-22 15:14:41.000000000 -0600
@@ -41,11 +41,11 @@
if( mm/=0 ) then
kd = 1
if( kdbnps==0 ) then
- write( hd(2),'(a,i10)' ) ' source particle no. ',nps
+ write( hd(2),'(a,i12)' ) ' source particle no. ',nps
call RN_query( first=i8_first, nps=int(nps,i8knd) )
write( hd(3),'(a,i20)' ) ' starting random number = ',i8_first
else
- write( hd(2),'(a,i10)' ) ' source particle no. ',kdbnps
+ write( hd(2),'(a,i12)' ) ' source particle no. ',kdbnps
hd(3) = ' '
endif
endif

@@ -60,9 +60,9 @@
! If required, back up to history beginning.
nst = nst+512
if( iovr==4 .and. (ntasks>1.or.ltasks>1) ) return
- if( mm/=0 .and. nps>=50 ) then
+ if( mm/=0 .and. nps>=50_i8knd ) then
call backup
- nps = nps-1
+ nps = nps-1_i8knd
call RN_init_particle( int(nps,i8knd) )
call vtask
call output
diff -Naurd MCNP5/Source/src/expung.F90 MCNP5_new/Source/src/expung.F90
--- MCNP5/Source/src/expung.F90      2003-04-30 20:10:52.000000000 -0600
+++ MCNP5_new/Source/src/expung.F90  2004-07-22 15:14:41.000000000 -0600
@@ -8,6 +8,7 @@

use mcnp_global
use mcnp_debug
+ use erprnt_mod

implicit real(dknd) (a-h,o-z)

diff -Naurd MCNP5/Source/src/ffetch.F90 MCNP5_new/Source/src/ffetch.F90
--- MCNP5/Source/src/ffetch.F90      2003-04-30 20:10:54.000000000 -0600
+++ MCNP5_new/Source/src/ffetch.F90  2004-07-22 15:14:41.000000000 -0600
@@ -3,14 +3,13 @@

subroutine ffetch(hf,hr)
! Description:
- ! Fetch file hf from CFS by the route hr.
+ ! Formerly - Fetch file hf from CFS by the route hr.

```

```

+ ! Presently - warn user that the xsdir xs library file is not present.
  use mcnp_global, only : jtty
  use mcnp_debug
  character(len=*) :: hf
  character(len=*) :: hr
  !
- write(jtty,10)hr,hf
-10 format("CFS node:",a," ",a)
- call expire(0,'ffetch','CFS fetching no longer possible')
+ call expire(0,'ffetch','cannot find xs library file specified in xsdir')
  return
end subroutine ffetch
diff -Naurd MCNP5/Source/src/FILE.list MCNP5_new/Source/src/FILE.list
--- MCNP5/Source/src/FILE.list      2003-04-30 20:09:58.000000000 -0600
+++ MCNP5_new/Source/src/FILE.list  2004-07-22 15:14:40.000000000 -0600
@@ -14,7 +14,7 @@
  covar.F90      cprinp.F90      crit1_mod.F90      crit2_mod.F90 \
  crspro.F90     crtcze.F90      dbmin.F90          dddet.F90      \
  ddddiag.F90    dddlev.F90      den1.F90           den2.F90      dmmp.F90        dosef.F90      \
-dotrcl.F90     dunlev.F90      dxdiag.F90         dxtran.F90     dynamic_arrays.F90 \
+dotrcl.F90     dunlev.F90      dxtran_mod.F90     dynamic_arrays.F90 \
  echkcl.F90     electr.F90      emaker.F90         ephcom.F90     eqpbbn.F90      erf2.F90      \
  ergimp.F90     erprnt.F90      errprn.F90         escat.F90      esloss.F90      eventp.F90    \
  exemes.F90     exmg.F90        expire.F90         expirx.F90     expung.F90      extran.F90    \
@@ -25,7 +25,7 @@
  inpert.F90     inter.F90       intsec.F90         ipbc.F90       isheet.F90      \
  isos.F90       isourc.F90      issrc.F90          itally.F90     italpr.F90      \
  items.F90      iwtwnd.F90      ixmdir.F90         jbin.F90       jdecod.F90      \
-jsourc.F90     kdarg.F90       kdata.F90          keypro.F90     klein.F90        knock.F90      \
+jsourc.F90     kdarg.F90       kdata.F90          klein.F90       knock.F90       \
  kxray.F90      latcon.F90      levcel.F90         \
  levchk.F90     lgeval.F90      likebt.F90         \
  lx5_mod.F90    main.F90        mapmaz.F90         matmpy.F90     mbody.F90       \
@@ -74,7 +74,7 @@
#####
# Files not needed, depending on CONFIG options #
#####
-UNWANTED_F_SRC :=      cgsdci.F90      keypro.F90
+UNWANTED_F_SRC :=      cgsdci.F90
UNWANTED_C_SRC :=

  ifeq (,$(findstring plot,$(CONFIG)))
diff -Naurd MCNP5/Source/src/fixcom.F90 MCNP5_new/Source/src/fixcom.F90
--- MCNP5/Source/src/fixcom.F90     2003-04-30 20:10:56.000000000 -0600
+++ MCNP5_new/Source/src/fixcom.F90 2004-07-22 15:14:41.000000000 -0600
@@ -18,25 +18,32 @@
! Fixcom tag:
  character(len=64), parameter, private :: fx_tag = "fixcom 07/11/2001"

- ! Fixcom length parameters.:
- integer, parameter :: nfixcm =& != Size of floating-point part of /FIXCM/.
+ !-----
--
+ ! (1) parameters for the length of the 3 portions of /fxcom/
+
+ integer, parameter :: nfixcm =& != Size of floating-point part of /FIXCM/.
+ & 10*(1) + 1*(9) + 2*(26) + 1*(51) + 1*(maxi) + 5*(mipt) + 1*(mbng) &
+ & + 2*(mtop) + 1*(nsp) + 1*(3*maxv) + (2*mipt*42) + 1*(mipt*3) &
+ & + 1*(mipt*8) + 1*(2*mxdt) + 1*(mipt+1) + 1*(mipt*5*mxdx) &
+ & + 1*(mipt*2*mxdx)
+
+ integer, parameter :: l8fixcm = 6      != Size of integer*8 part of /fxcom/.
+
+ integer, parameter :: lfixcm =& != Size of integer part of /FIXCM/.
- & 167*(1) + 3*(3) + 1*(2*6) + 1*(2*mxdt) &
+ & 165*(1) + 3*(3) + 1*(2*6) + 1*(2*mxdt) &
+ & + 4*(maxv) + 1*(mink) + 9*(mipt) + 3*(mipt+1) + 1*(mxdt) &
+ & + 3*(mxss) + 1*(nmkey) + mipt + 2*mipt + 1
- integer, parameter :: l8fixcm = 3      != Size of integer*8 part of /FIXCM/.

- ! Common block equivalences:

```

```

+ !-----
--
+ ! (2) declarations for 3 arrays equivalenced to parts of /fxcom/
+
real(dknd)      :: gfixcm(nfixcm) != Equivalence to real part of /FIXCM/.
- integer       :: jfixcm(lfixcm) != Equivalence to integer part of /FIXCM/.
integer(i8knd) :: i8fixcm(l8fixcm) != Equivalence to integer*8 part of /FIXCM/.
- equivalence (bbrem,gfixcm), (ibad,jfixcm), (RN_seed_input,i8fixcm)
+ integer       :: jfixcm(lfixcm) != Equivalence to integer part of /FIXCM/.

- ! Fixcom reals:
+ !-----
--
+ ! (3) declarations for /fxcom/ REALS
+
real(dknd) :: &
& bbrem(mtop),      & != Bremsstrahlung energy bias factors.
& bnum,             & != Bremsstrahlung bias number.
@@ -76,8 +83,23 @@
& xunru              != Highest energy of any unresolved
                    != resonance probability table.

- ! Fixcom integers:
+ !-----
--
+ ! (4) declarations for /fxcom/ INTEGER*8
+
integer(i8knd) :: &
+ & niss,            & != Number of histories in input surface source.
+ & npl,             & != Number of histories in surface source write run.
+ & nrss,           & != Number of tracks on input surface source file.
+ & RN_seed_input,  & != user input, starting RN seed
+ & RN_stride_input, & != user input, RN stride
+ & RN_hist_input   & != user input, start RN sequence with this history
+
+ !-----
--
+ ! (5) declarations for /fxcom/ INTEGERS
+
integer :: &
+ & flag_speed_tally_used, & != Flag to indicate if lattice speed tally modifications
used.
+
+ ! 1 = used, -1 = not used
& ibad,          & != Flag for simple bremsstrahlung distribution.
& icw,           & != Reference cell for generated weight windows.
& ndefv(maxv),   & != Flags for presence of variable names on SDEF.
@@ -170,7 +192,6 @@
& nilr(mxss),    & != Number of cells on SSR card.
& nilw,          & != Number of cells on SSW card.
& nips,          & != Source particle type.
- & niss,         & != Number of histories in input surface source.
& njsr(mxss),    & != Number of surfaces in JASR.
& njss,          & != Number of surfaces in JSS.
& njsx(mxss),    & != Number of surfaces in ISS.
@@ -185,7 +206,6 @@
& nocoh,         & != Flag to inhibit coherent photon scattering.
& nodop,         & != Flag to inhibit Doppler photon scattering.
& nord,          & != Number of source variables to be sampled.
- & npl,          & != Number of histories in surface source write run.
& npikmt,        & != Number of PIKMT entries.
& npn,           & != Length of adjustable dimension of PAN.
& ipert,         & != Number of PERT card keywords, dimension of RPTB.
@@ -196,7 +216,6 @@
& nmzu,          & != Length of MAZU array.
& npert,         & != Number of perturbations.
& nrzd,          & != Number of values in a surface-source record.
- & nrss,         & != Number of tracks on input surface source file.
& nsph,          & != Flag for spherical output surface source.
& nsr,           & != Source type.
& nsrc,          & != Number of entries on SRC card.
@@ -236,27 +255,27 @@

```

```

    & iptra2,kfl1, indt1, ndup1(3),    naw1, lrt1, nmfm1, mseb1, kt11, &
    & ides1

- ! Offset l<var>s with parallel k<var>s in common /itskpt/.
- integer :: lpac = 0           != Offset for PAC array.
- integer :: lpan = 0          != Offset for PAN array.
- integer :: lpwb = 0          != Offset for PWB array.
-
- ! Random number generator input parameters
- integer      :: RN_gen_input
- ! fixcom integer*8
- integer(i8knd) :: RN_seed_input
- integer(i8knd) :: RN_stride_input
- integer(i8knd) :: RN_hist_input
+ integer :: RN_gen_input      != user input, index of RN generator parameter set
+
+ !-----
--
+ ! (6) declaration for /fxcom/ (real, interger*8, integer)

! Fixed common -- constant after the problem is initiated.
+ ! Real
common /fxcom/ &
  & bbrem, bnum, calph, coincd,ddg, ddx, dnb, dxw, dxx, ecf, &
  & efac, emcf, emx, enum, etspl, fnw, hsb, rim, rkt, rka, &
  & rnok, srv, tco, thgf, wc1, wc2, wwg, wwp, wwm, wwma, &
  & xunrl, xunru
- !
- ! Fixcom integers.
+
+ ! Integer*8
+ common /fxcom/ &
+   & niss, npl, nrss, RN_seed_input, RN_stride_input, RN_hist_input
+
+ ! Integer
common /fxcom/ &
+   & flag_speed_tally_used, &
  & ibad, icw, idefv, ides, idrc, iets, ifft, igm, ikz, img, &
  & imt, imesh, indt, ink, ioid, iphot, iplt, ipty, isb, ism, &
  & ispn, issw, istern,istrg, its30, iunr, ivdd, ivdis, ivord, iwwg, &
@@ -265,9 +284,9 @@
  & mcal, mct, mgegbt,mgm, mgww, mix, mjss, mlaj, mlja, mrkp, &
  & mrl, msd, msrk, mtasks,mww, mxa, mxafs, mxe, mxj, mxj, &
  & mxt, mxtr, mxxs, ndet, ndnd, ndtt, ndx, nee, nets, ngww, &
- & nhb, nilr, nilw, nips, niss, njsr, njss, njsx, nkxs, nlat, &
- & nlev, nlja, nmat, nmxf, nnpos, nocoh, nodop, nord, npl, npikmt, &
- & npn, ipert, mnnm, mxfp, nmaz, nmip, nmzu, npert, nrcd, nrss, &
+ & nhb, nilr, nilw, nips, njsr, njss, njsx, nkxs, nlat, &
+ & nlev, nlja, nmat, nmxf, nnpos, nocoh, nodop, nord, npikmt, &
+ & npn, ipert, mnnm, mxfp, nmaz, nmip, nmzu, npert, nrcd, &
  & nsph, nsr, nsrc, nsrck, nstp, ntal, ntop, numb, nvec, nwang, &
  & nwgeoa,nwgeom,nwgm, nwgma, nwnng, nww, nwwm, nwwma, nxxn

@@ -283,178 +302,22 @@

common /fxcom/ &
  & RN_gen_input
- common /fxcom/ &
-   & RN_seed_input, RN_stride_input, RN_hist_input
+
+ EQUIVALENCE (bbrem, gfixcm)
+ EQUIVALENCE (niss, i8fixcm)
+ EQUIVALENCE (flag_speed_tally_used, jfixcm)

! Length of and Equivalence array to match /itskpt/.
integer,parameter :: ltskpt = 47

-contains
-
- ! -----
- subroutine fx_init

```

```

-   ! Description:
-   ! Initialize fixcom variables.
-   gfixcm = 0.0d+0
-   jfixcm = 0
-   i8fixcm = 0
-   return
- end subroutine fx_init
-
- ! -----
-
- subroutine fx_write(iu,ierr)
- ! Description:
- ! Write fixcom data to pre-positioned file.
-
- ! Argument declarations:
- integer, intent(in)  :: iu      ! file unit number.
- integer, intent(out) :: ierr    ! status.
-
- ! Local declarations:
- logical              :: lopen
- character(len=11)   :: hformat
-
- ! File must be opened and unformatted.
- inquire(UNIT = iu, OPENED = lopen, FORM = hformat)
-
- if( lopen .and. hformat == "UNFORMATTED") then
-   ierr = 0
-
-   ! Write tag.
-   write(iu) fx_tag
-
-   ! Write reals.
-   write(iu) &
-     & bbrem,bnum,calph,coincd,ddg,ddx,dnb,dxw,dxx,ecf,efac,emcf,&
-     & emx,enum,etspl,fnw,hsb,rim,rkt,rka,rnok,&
-     & srv,tco,thgf,wcl,wc2,wwg,wwp,wwm,wwma,xunrl,xunru
-
-   ! Write integers in separate blocks.
-   ! Generic integers.
-   write(iu) &
-     & ibad,icw,idefv,ides,idrc,iets,iff,igm,ikz,img,imt,imesh,indt,ink,ioid,&
-     & iphot,iplt,ipty,isb,ism,ispn,issw,istern,istrg,its30,iunr,ivdd,ivdis,&
-     & ivord,iwwg,jgm,jtlx,junf,kf8,kfl,kfq,kjaq,knods,knrm,kpt,ktls,&
-     & kufil,lfcdg,lfcdj,locdt,lvc dg,lvc dj,lxs,mai,mbnk,mcal,mct,mgegbt,mgm,&
-     & mgww,mix,mjss,maj,mlja,mrkp,mrl,msd,msrk,mtasks,mww,mxa,mxafs,mxe,&
-     & mxj,mxt,mxtr,mxxs,ndet,ndnd,nddt,ndx,nee,nets,ngww,nhb,nilr,nilw,&
-     & nips,niss,njsr,njss,njsx,nkxs,nlat,nlev,nlja,nmat,nmxf,nnpes,nocoh,nodop,&
-     & nord,np1,npikmt,npn,ipert,mnmm,mxfr,nmaz,nmip,nmzu,npert,nrcd,nrss,&
-     & nsph,nsr,nsrc,nsrck,nstp,ntal,ntop,numb,nvec,nwang,nwgeoa,&
-     & nwgeom,nwgm,nwgma,nwng,nww,nwmm,nwwma,nxnx
-
-   ! Variables used for dynamic allocation.
-   write(iu) &
-     & neel,nmat1,istrgl,mixl,mxel,ipltl,mxal,igml, &
-     & npertl,mnmml,nxnx1,msd1,mbbm1,mgww1,mcall,npnl,kptl, &
-     & ipertl,nscl,mxxsl,ltdl,mxtl,mxtrl,nlatl,nvecl,nwgm1,nwwml, &
-     & nwgm1,nwml,mlja1,mxj1,ntall,mww1,njsxl,litl,njsrl,nilrl, &
-     & njswl,niwrl,msscl,mjssl,nilw1,junf1,mkcpl,mlaf1,mxafs1, &
-     & nmzul,miptsl,maj1,ndnd1,icw1,msrk1,nwmm1,nmaz1,njssl, &
-     & npikmt1,iptra1,iptra2,kfl1,indt1,ndupl,nawl,lrt1,nmfml, &
-     & msebl,ktl1,ides1
-
-   ! Offset l<var>s with parallel k<var>s in common /itskpt/.
-   write(iu) lpac, lpan, lpwb
-
-   ! random number generator parameters
-   write(iu) RN_gen_input, RN_seed_input, RN_stride_input, RN_hist_input
- else
-   ! either not open or not unformatted.
-   ierr = -1
-   ! return an error.
- endif
-
- endif
-
- end subroutine

```



```

-   return
- end subroutine fx_write
-
- ! -----
-
- subroutine fx_read(iu,ierr)
-   ! Description:
-   ! Read fixcom data from pre-positioned file.
-   ! Position verified by module tag.
-
-   ! Argument declarations:
-   integer, intent(in) :: iu      ! file unit number.
-   integer, intent(out) :: ierr   ! status.
-
-   ! Local declarations:
-   logical      :: lopen
-   character(len=11) :: hformat
-   character(len=64) :: tag
-
-   ! File must be opened and unformatted.
-   inquire(UNIT = iu, OPENED = lopen, FORM = hformat)
-
-   if ( .not. lopen .or. hformat/"UNFORMATTED" ) then
-     ierr = -1 ! return error
-
-   else
-     ! Read tag and verify it against module tag parameter.
-     read(iu) tag
-     if( tag/=fx_tag ) then
-       ierr = -2 ! return error
-
-     else
-       ierr = 0
-       ! Read reals.
-       read(iu) &
-         & bbrem, bnum, calph, coincd, ddg, ddx, dnb, dxw, dxx, ecf, efac, emcf, &
-         & emx, enum, etspl, fnw, hsb, rim, rkt, rka, rnok, &
-         & srv, tco, thgf, wcl, wc2, wwg, wwp, wwm, wwma, xunrl, xunru
-
-       ! Read integers in separate blocks.
-       ! Generic integers.
-       read(iu) &
-         & ibad, icw, idefv, ides, idrc, iets, ifft, igm, ikz, img, imt, imesh, indt, ink, ioid, &
-         & iphot, iptl, ipty, isb, ism, ispn, issw, istern, istrg, its30, iunr, ivdd, ivdis, &
-         & ivord, iwwg, jgm, jtlx, junf, kf8, kfl, kfq, kjaq, knods, knrm, kpt, ktls, &
-         & kufil, lfcgd, lfcdj, locdt, lvcdg, lvcdj, lxs, mai, mbnk, mcal, mct, mgegbt, mgm, &
-         & mgww, mix, mjss, mlaj, mlja, mrkp, mrl, msd, msrk, mtasks, mww, mxa, mxafs, mxe, &
-         & mxj, mxj, mxt, mxtr, mxxs, ndet, ndnd, nddt, ndx, nee, nets, ngww, nhb, nilr, nilw, &
-         & nips, niss, njsr, njss, njsx, nkxs, nlat, nlev, nlja, nmat, nmxf, nnpos, nocoh, nodop, &
-         & nord, npl, npikmt, npn, ipert, mnm, mxfp, nmaz, nmip, nmzu, npert, nrcd, nrss, &
-         & nsph, nsr, nsrc, nsrck, nstp, ntal, ntop, numb, nvec, nwang, nwgeoa, &
-         & nwgeom, nwgm, nwgma, nwnng, nww, nwwm, nwwma, nxxn
-
-       ! Variables used for dynamic allocation.
-       read(iu) &
-         & neel, nmat1, istrgl, mixl, mxel, iptl, mxal, igml, &
-         & npertl, mnnml, nxxn1, msdl, mbbml, mgww1, mcall, npnl, kptl, &
-         & ipertl, nsc1, mxxs1, ltdl, mxtl, mxtrl, nlatl, nvec1, nwgml, nwwml, &
-         & nwgml, nwmal, mljal, mxj1, ntall, mww1, njsx1, lit1, njsr1, nilr1, &
-         & njsw1, niwrl, msscl, mjss1, nilw1, junf1, mkcpl, mlaf1, mxafs1, &
-         & nmzul, mipts1, mlaj1, ndnd1, icw1, msrkl, nwwmal, nmaz1, njss1, &
-         & npikmt1, iptra1, iptra2, kfll, indtl, ndupl, naw1, lrt1, nmfml, &
-         & msebl, ktll, ides1
-
-       ! Offset l<var>s with parallel k<var>s in common /itskpt/.
-       read(iu) lpac, lpan, lpwb
-
-       ! random number generator parameters
-       read(iu) RN_gen_input, RN_seed_input, RN_stride_input, RN_hist_input
-     endif
-
-   endif
-
- end subroutine fx_read

```

```

+ !-----
--
+ ! (7) declaration & initialization of lpac,lpan,lpwb variables
+ ! Offset l<var>s with parallel k<var>s in common /itskpt/.

-   endif
-   return
- end subroutine fx_read
+ integer :: lpac = 0           != Offset for PAC array.
+ integer :: lpan = 0          != Offset for PAN array.
+ integer :: lpwb = 0          != Offset for PWB array.

! -----
-
- subroutine fx_cast(mh,mx,ie)
- ! Description:
- ! DMMP bcast of fixcom data.
- ! Arguments:
- integer,intent(in)      :: mh ! action flag, 0 -> sender.
- integer,intent(in)      :: mx ! message chunk size (max).
- integer,intent(inout)   :: ie ! return status.
-
- call dm_bcast(mh,gfixcm, nfixcm, mx,ie)
- call dm_bcast(mh,jfixcm, lfixcm, mx,ie)
- call dm_bcast(mh,i8fixcm,l8fixcm,mx,ie)
-
- return
- end subroutine fx_cast
-
end module fixcom
!-
diff -Naurd MCNP5/Source/src/flaug.F90 MCNP5_new/Source/src/flaug.F90
--- MCNP5/Source/src/flaug.F90      2003-04-30 20:10:58.000000000 -0600
+++ MCNP5_new/Source/src/flaug.F90  2004-07-22 15:14:41.000000000 -0600
@@ -14,6 +14,7 @@
!       and variance reduction; =2 for colidp; =3 for kxray.

use mcnp_global
+ use dxtran_mod
use mcnp_debug

implicit real(dknd) (a-h,o-z)
@@ -171,10 +172,7 @@
paxtc(2,15,2) = paxtc(2,15,2)+wgt
paxtc(3,15,2) = paxtc(3,15,2)+wgt*erg
pwb(kpwb+2,16,icl) = pwb(kpwb+2,16,icl)+wgt
- do i=1,ndx(2)
-   if( (xxx-dxx(2,1,i))**2+(yyy-dxx(2,2,i))**2+&
-     & (zzz-dxx(2,3,i))**2 < dxx(2,5,i) ) idx=i
- end do
+ idx = inside_dxtran_sphere()
if( ndet(2)/=0 ) then
  call tallyd
endif
diff -Naurd MCNP5/Source/src/fmesh_mod.F90 MCNP5_new/Source/src/fmesh_mod.F90
--- MCNP5/Source/src/fmesh_mod.F90  2003-11-05 17:23:12.000000000 -0700
+++ MCNP5_new/Source/src/fmesh_mod.F90  2004-07-22 15:14:41.000000000 -0600
@@ -8,6 +8,7 @@

use mcnp_debug
use mcnp_params, only: dknd
+ use erprnt_mod
implicit none
public
save
@@ -70,14 +71,10 @@
& ndfb,      & ! Number of dose function bins.
& ifm_card,  & ! Flag for mesh tally FM card.
& nreact,    & ! Number of reactions on the FM card.
- & nireact,  & ! size of ireact array.
- & mat,      & ! Material number for FM reactions.

```

```

+      & nireact, & ! size of react array.
+      & mat, & ! Material index number for FM reactions.
+      & outf ! Output format:
+              ! 0=column, 1=ij, 2=ik, 3=jk, 4=column-full.
-
-      integer, POINTER :: &
-      & ireact(:) ! Reaction numbers for the FM card.
-
-      real(dknd) :: &
+      & fact, & ! Multiplication factor.
+      & fmult, & ! FM card multiplier.
@@ -87,6 +84,7 @@
+      & org(3) ! Origin of mesh.

+      real(dknd), POINTER :: &
+      & react(:), & ! Reaction/attenuator values from the FM card.
+      & xrbn(:), & ! Bin values for x/r coord.
+      & yzbn(:), & ! Bin values for y/z coord.
+      & ztbn(:), & ! Bin values for z/theta coord.
@@ -147,7 +145,7 @@
! Write the allocatable arrays of derived type fm
do i = 1, nmesh
  if( fm(i)%nireact>0 ) then
-    write(iu) fm(i)%ireact
+    write(iu) fm(i)%react
  endif
  write(iu) fm(i)%xrbn, fm(i)%yzbn, fm(i)%ztbn, fm(i)%enbin
enddo
@@ -191,13 +189,22 @@

! allocate the derived types
if ( .not. allocated (fmtal) ) then
- allocate (fmtal(nmesh),stat = is)
- if(is/=0) call erprnt(1,1,0,0,0,0,0,1, ' mesh tally memory allocation failure"')
+ allocate (fmtal(nmesh),stat = is)
+ if(is/=0) call erprnt(1,1,0,0,0,0,0,1, ' mesh tally memory allocation failure"')
+ do i=1, nmesh
+   nullify (fmtal(i)%tally)
+ enddo
endif

if( .not. allocated (fm) ) then
- allocate (fm(nmesh),stat = is)
- if(is/=0) call erprnt(1,1,0,0,0,0,0,1, ' mesh tally memory allocation failure"')
+ allocate (fm(nmesh),stat = is)
+ if(is/=0) call erprnt(1,1,0,0,0,0,0,1, ' mesh tally memory allocation failure"')
+
+ ! nullify pointer arrays
+ do i=1, nmesh
+   nullify( fm(i)%react, fm(i)%xrbn, fm(i)%yzbn, fm(i)%ztbn, fm(i)%enbin, &
+   & fm(i)%de, fm(i)%df, fm(i)%fmarry, fm(i)%fmerr)
+ enddo
endif

! Next read in the scalar and non-allocatable arrays of derived type fm
@@ -211,27 +218,27 @@
! Allocate and read the allocatable arrays of derived type fm
do i = 1, nmesh
  if( fm(i)%nireact>0 ) then
-    is_assoc = associated(fm(i)%ireact)
+    is_assoc = associated(fm(i)%react)
    if( .not. is_assoc ) then
-    allocate (fm(i)%ireact(fm(i)%nireact),stat = is)
-    if(is/=0) call erprnt(1,1,0,0,0,0,0,1, ' mesh tally memory allocation failure"')
-    endif
+    allocate (fm(i)%react(fm(i)%nireact),stat = is)
+    if(is/=0) call erprnt(1,1,0,0,0,0,0,1, ' mesh tally memory allocation
failure"')
+    endif
+  endif
endif

```

```

is_assoc = associated(fm(i)%xrbn)
if (.not. is_assoc ) then
- allocate (fm(i)%xrbn(fm(i)%nxrb),stat = is)
- if(is/=0) call erprnt(1,1,0,0,0,0,0,1,' "mesh tally memory allocation failure"')
- allocate (fm(i)%yzbin(fm(i)%nyzb),stat = is)
- if(is/=0) call erprnt(1,1,0,0,0,0,0,1,' "mesh tally memory allocation failure"')
- allocate (fm(i)%ztbin(fm(i)%nztb),stat = is)
- if(is/=0) call erprnt(1,1,0,0,0,0,0,1,' "mesh tally memory allocation failure"')
- allocate (fm(i)%enbin(fm(i)%nenb),stat = is)
- if(is/=0) call erprnt(1,1,0,0,0,0,0,1,' "mesh tally memory allocation failure"')
+ allocate (fm(i)%xrbn(fm(i)%nxrb),stat = is)
+ if(is/=0) call erprnt(1,1,0,0,0,0,0,1,' "mesh tally memory allocation
failure"')
+ allocate (fm(i)%yzbin(fm(i)%nyzb),stat = is)
+ if(is/=0) call erprnt(1,1,0,0,0,0,0,1,' "mesh tally memory allocation
failure"')
+ allocate (fm(i)%ztbin(fm(i)%nztb),stat = is)
+ if(is/=0) call erprnt(1,1,0,0,0,0,0,1,' "mesh tally memory allocation
failure"')
+ allocate (fm(i)%enbin(fm(i)%nenb),stat = is)
+ if(is/=0) call erprnt(1,1,0,0,0,0,0,1,' "mesh tally memory allocation
failure"')
endif

if( fm(i)%nireact>0 ) then
- read (iu) fm(i)%ireact
+ read (iu) fm(i)%react
endif
read (iu) fm(i)%xrbn, fm(i)%yzbin, fm(i)%ztbin, fm(i)%enbin
enddo
@@ -240,14 +247,14 @@
do i = 1,nmesh
if( fm(i)%intrapol>0 ) then
is_assoc = associated(fm(i)%de)
if (.not. is_assoc ) then
- allocate (fm(i)%de(fm(i)%ndfb),stat = is)
- if(is/=0) call erprnt(1,1,0,0,0,0,0,1,' "mesh tally memory allocation failure"')
- allocate (fm(i)%df(fm(i)%ndfb),stat = is)
- if(is/=0) call erprnt(1,1,0,0,0,0,0,1,' "mesh tally memory allocation failure"')
+ if (.not. is_assoc ) then
+ allocate (fm(i)%de(fm(i)%ndfb),stat = is)
+ if(is/=0) call erprnt(1,1,0,0,0,0,0,1,' "mesh tally memory allocation
failure"')
+ allocate (fm(i)%df(fm(i)%ndfb),stat = is)
+ if(is/=0) call erprnt(1,1,0,0,0,0,0,1,' "mesh tally memory allocation
failure"')
+ endif
read(iu) fm(i)%de, fm(i)%df
endif
endif
enddo

@@ -259,21 +266,21 @@
ie = fm(i)%nenb-1
is_assoc = associated(fm(i)%fmarry)
if (.not. is_assoc ) then
- allocate (fm(i)%fmarry(ix, iy, iz, ie, ntasks+1),stat = is)
- if(is/=0) call erprnt(1,1,0,0,0,0,0,1,' "mesh tally memory allocation failure"')
- allocate (fm(i)%fmerr(ix, iy, iz, ie, ntasks+1),stat = is)
- if(is/=0) call erprnt(1,1,0,0,0,0,0,1,' "mesh tally memory allocation failure"')
- allocate (fntal(i)%tally(ix, iy, iz, ie, ntasks+1),stat = is)
- if(is/=0) call erprnt(1,1,0,0,0,0,0,1,' "mesh tally memory allocation failure"')
+ allocate (fm(i)%fmarry(ix, iy, iz, ie, ntasks+1),stat = is)
+ if(is/=0) call erprnt(1,1,0,0,0,0,0,1,' "mesh tally memory allocation
failure"')
+ allocate (fm(i)%fmerr(ix, iy, iz, ie, ntasks+1),stat = is)
+ if(is/=0) call erprnt(1,1,0,0,0,0,0,1,' "mesh tally memory allocation
failure"')
+ allocate (fntal(i)%tally(ix, iy, iz, ie, ntasks+1),stat = is)

```

```

+         if(is/=0) call erprnt(1,1,0,0,0,0,1,' "mesh tally memory allocation
failure"')
        endif

-         read(iu)  fm(i)%fmarray(:,:,,:,1), &
-         &        fm(i)%fmerr( :,:,,:,1)
+         read(iu)  fm(i)%fmarray(:,:,,:,1), &
+         &        fm(i)%fmerr(:,:,,:,1)
        do j=2,ntasks+1
            fm(i)%fmarray(:,:,,:,j) = 0
            fm(i)%fmerr(:,:,,:,j) = 0
        enddo
-         fmtal(i)%tally = 0
+         fmtal(i)%tally = 0
        enddo

        ! Allocate scratch arrays
@@ -285,13 +292,13 @@
        i_size_bins=i_size_bins*0.2/ntasks + 1

        if( .not. allocated (i_bins) ) then
-         allocate (i_bins(5,i_size_bins,ntasks),stat = is)
-         if(is/=0) call erprnt(1,1,0,0,0,0,1,' "mesh tally memory allocation failure"')
+         allocate (i_bins(5,i_size_bins,ntasks),stat = is)
+         if(is/=0) call erprnt(1,1,0,0,0,0,1,' "mesh tally memory allocation failure"')
        endif

        if( .not. allocated (num_bins) ) then
-         allocate (num_bins(ntasks),stat = is)
-         if(is/=0) call erprnt(1,1,0,0,0,0,1,' "mesh tally memory allocation failure"')
+         allocate (num_bins(ntasks),stat = is)
+         if(is/=0) call erprnt(1,1,0,0,0,0,1,' "mesh tally memory allocation failure"')
        endif
        num_bins=0
        i_bins=0
@@ -304,11 +311,12 @@
subroutine ifmesh_print
    ! Subroutine to write initial information about the mesh tallies to OUTF

-    use mcnp_global, only:ink
+    use mcnp_global, only:ink,nmt
    use mcnp_params, only:iuo

-    integer          :: i,j          ! Loop variables
-    character(6)     :: intpol_mode  ! Dose response function interpolation mod
+    integer          :: i,ii,iw,j,k  ! Loop variables & misc integers
+    character(6)     :: intpol_mode  ! Dose response function interpolation mod
+    character(13)    :: ht(18)       ! FM card reaction list/attenuation set

    do i = 1,nmesh

@@ -331,13 +339,47 @@
        endif

        ! print the energy-dependent-multiplier bins.
-         if( fm(i)%nreact/=0 .or. fm(i)%fmult/=1. ) then
-         if( fm(i)%nreact/=0 ) then
+         if ( fm(i)%ifm_card /= 0 .or. fm(i)%fmult /= 1 ) then
+         if ( fm(i)%nreact==0 .and. fm(i)%ifm_card > -1 ) then
            write(iuo, &
                & '(/ " all scores are multiplied by",es13.5)') fm(i)%fmult*fm(i)%fact
-         else
-         write(iuo,'(/ " multiplier bins"/ " att",2x, "constant",4x, "material",&
-         & 3x, "reactions or material-rho*x pairs"')
+         else
+         if ( fm(i)%ifm_card == -1 ) then
+         write(iuo,'(/ " multiplier bins"/ 6x, "constant"')
+         write(iuo,'(lpe16.5,4x, "tracks"') fm(i)%fmult
+         else if ( fm(i)%ifm_card == -2 ) then
+         write(iuo,'(/ " multiplier bins"/ 6x, "constant"')
+         write(iuo,'(lpe16.5,4x, "1/velocity"') fm(i)%fmult

```

```

+         else
+         if ( fm(i)%mat /= -1 ) then          ! FM card contains a reaction list
+         write(iuo,'(/ " multiplier bins"/ 6x, "constant",4x, "material",&
+         & 3x, "reactions"'))
+         do iw=1,fm(i)%nreact
+         ii = mod(iw-1,14)+1
+         k = fm(i)%react(iw)
+         ht(ii) = '          :'
+         if ( k /= 1000003 ) write(ht(ii) (1:6),'(i6)') k
+         if ( ii < 14 .and. iw < fm(i)%nreact ) cycle
+         if ( iw <= 14 ) then
+         if ( fm(i)%mat /= 0 ) then
+         write(iuo,'(3x,1pe13.5,i7,5x,14a6)') &
+         & fm(i)%fmult,nmt(fm(i)%mat),(ht(k),k=1,ii)
+         else
+         write(iuo,'(3x,1pe13.5," default",3x,14a6)') &
+         & fm(i)%fmult,(ht(k),k=1,ii)
+         endif
+         endif
+         if ( iw > 14 ) write(iuo,'(28x,14a6)') (ht(k),k=1,ii)
+         enddo
+         else
+         ! FM card contains an attenuator set
+         write(iuo,'(/ " multiplier bins"/ 6x, "constant",15x, &
+         & "material-rho*x pairs"'))
+         write (iuo,340) fm(i)%fmult,(nmt(int(fm(i)%react(j))),fm(i)%react(j+1),
+         &
+         & j=1,fm(i)%nreact,2)
+340      format(1pe16.5,i17,e12.4,4(i6,e12.4)/ &
+         & (i33,e12.4,i6,e12.4,i6,e12.4,i6,e12.4,i6,e12.4,i6,e12.4))
+         endif
+         endif
+         endif
+         endif
+         endif
@@ -435,6 +477,13 @@
      nmesh = 0      !reset nmesh to zero for 2nd read of INP file

+ ! nullify pointer arrays
+ do i=1,nmesh
+   nullify( fm(i)%react, fm(i)%xrbn, fm(i)%yzbin, fm(i)%ztbin, fm(i)%enbin, &
+   & fm(i)%de, fm(i)%df, fm(i)%fmarry, fm(i)%fmerr )
+   nullify( fmtal(i)%tally )
+ enddo
+
+   endif
+   return
end subroutine fmesh_allocate
@@ -447,7 +496,7 @@
! fm(kk)%ifm_card = FM card flag
! fm(kk)%mat = index of the material
! fm(kk)%nreact= number of mt reactions (negative if elastic or total)
- ! fm(kk)%ireact(1,2,...) = mt reaction numbers
+ ! fm(kk)%react(1,2,...) = mt reaction numbers or attenuation factors

use mcnp_global

@@ -466,7 +515,7 @@
if( fm(kk)%mat<0. ) go to 220
h = 0.
mk = fm(kk)%mat
- if( mk==0 ) go to 200
+ if( mk==0 ) mk = mat(icl)
if( fm(kk)%ipt==2 ) go to 140

! neutron multipliers
@@ -533,7 +582,7 @@
f = 0.
g = 1.
do n = 1,mod(int(abs(fm(kk)%nreact)),1000000)
- mt = fm(kk)%ireact(n)

```

```

+         mt = fm(kk)%react(n)
+         if( mt==1000003 ) then
+             f = f+g
+             g = 1.
@@ -554,11 +603,11 @@
+         f = 0.
+         g = 1.
+         do n = 1,mod(int(fm(kk)%nreact),10000000)
-             if( fm(kk)%ireact(n)==1000003 ) then
+             if( fm(kk)%react(n)==1000003 ) then
+                 f = f+g
+                 g = 1.
-             else
+                 j = -fm(kk)%ireact(n)
+                 j = -fm(kk)%react(n)
+                 if( mcal==0 ) then
+                     xs = rtc(krtc+j,iex)
+                     if( j>1 ) xs = xs-rtc(krtc+j-1,iex)
@@ -592,7 +641,7 @@
+         h = 0.
+         ttn = 253e-10
+         do n = 1,int(fm(kk)%nreact),2
-             mk = fm(kk)%ireact(n)
+             mk = fm(kk)%react(n)
+             if( mk==0 ) cycle
+             if( mcal==0 ) then
+                 if( ipt==1 ) jf = 1
@@ -605,7 +654,7 @@
+             totm = totm+getxs(1)*fme(m)
+             enddo
+             endif
-             h = h+ fm(kk)%ireact(n+1)*totm
+             h = h+ fm(kk)%react(n+1)*totm
+             enddo
+             if( h>80. ) t = 0.
+             if( h<=80. ) t = t*exp(-h)
@@ -660,7 +709,7 @@
+
+             call msg_put (fm(i)%nireact)
+             if( fm(i)%nireact>0 ) then
-                 call msg_put (fm(i)%ireact,1,fm(i)%nireact)
+                 call msg_put (fm(i)%react,1,fm(i)%nireact)
+             endif
+
+             call msg_put (fm(i)%axs, 1, 3)
@@ -704,6 +753,13 @@
+             allocate (fmtal(nmesh),stat = is)
+             if(is/=0) call erprnt(1,1,0,0,0,0,0,1,' "mesh tally memory allocation failure"')
+
+             ! nullify pointer arrays
+             do i=1,nmesh
+                 nullify( fm(i)%react, fm(i)%xrbins, fm(i)%yzbins, fm(i)%ztbins, fm(i)%enbins, &
+                     & fm(i)%de, fm(i)%df, fm(i)%fmarry, fm(i)%fmerr )
+                 nullify( fmtal(i)%tally )
+             enddo
+
+             Loop1: do i = 1,nmesh
+                 call msg_get (fm(i)%id)
+                 call msg_get (fm(i)%ipt)
@@ -723,11 +779,11 @@
+                 call msg_get (fm(i)%fact)
+                 call msg_get (fm(i)%fmult)
+
-                 call msg_get(fm(i)%nireact) ! get size of ireact array
+                 call msg_get(fm(i)%nireact) ! get size of react array
+                 if( fm(i)%nireact>0 ) then
-                     allocate (fm(i)%ireact(fm(i)%nireact),stat = is)
+                     allocate (fm(i)%react(fm(i)%nireact),stat = is)
+                     if(is/=0) call erprnt(1,1,0,0,0,0,0,1,' "mesh tally memory allocation
failure"')
-                     call msg_get (fm(i)%ireact,1,fm(i)%nireact)

```

```

+         call msg_get (fm(i)%react,1,fm(i)%nreact)
endif

        call msg_get (fm(i)%axs, 1, 3)
@@ -919,7 +975,7 @@
        ! Called from hstory

        use mcnp_params, only:dknd
-       use mcnp_global, only:trf,huge,rho,icl,ktask,kc8
+       use mcnp_global, only:trf,huge_float,rho,icl,ktask,kc8

        integer , intent(in) :: ipt
        real(dknd), intent(in) :: x,y,z,u,v,w,erg,wgt,d
@@ -932,7 +988,7 @@
        real(dknd) :: dstnce_to_travel ! Distance remaining for the particle to travel
        real(dknd) :: dstnce_to_bin ! Distance to the next mesh bin boundary

-       real(dknd), parameter :: tiny = 1/huge
+       real(dknd), parameter :: tiny = 1/huge_float
        integer :: i,j,k,il,iu,im,ien,ixr,iyz,izt,kt,kt1

        ! return if kcode problem is not settled
@@ -1004,7 +1060,7 @@
        else if( r(1)-fm(i)%xrbin(fm(i)%nxrb)>=1d-10 ) then
            cycle Loop1
        else
-           dr(1) = huge
+           dr(1) = huge_float
        endif
        else if( dircos(1)<-tiny ) then
            if( r(1)-fm(i)%xrbin(fm(i)%nxrb)>1d-10 ) then
@@ -1014,10 +1070,10 @@
                else if( r(1)-fm(i)%xrbin(1)<= -1d-10 ) then
                    cycle Loop1
                else
-                   dr(1) = huge
+                   dr(1) = huge_float
                endif
            else
-                dr(1) = huge
+                dr(1) = huge_float
            endif
        endif

        if( dircos(2)>tiny ) then
@@ -1028,7 +1084,7 @@
            else if( r(2)-fm(i)%yzbin(fm(i)%nyzb)>=1d-10 ) then
                cycle Loop1
            else
-                dr(2) = huge
+                dr(2) = huge_float
            endif
            else if( dircos(2)<-tiny ) then
                if( r(2)-fm(i)%yzbin(fm(i)%nyzb)>1d-10 ) then
@@ -1038,10 +1094,10 @@
                    else if( r(2)-fm(i)%yzbin(1)<= -1d-10 ) then
                        cycle Loop1
                    else
-                       dr(2) = huge
+                       dr(2) = huge_float
                    endif
                else
-                    dr(2) = huge
+                    dr(2) = huge_float
                endif
            endif

            if( dircos(3)>tiny ) then
@@ -1052,7 +1108,7 @@
                else if( r(3)-fm(i)%ztbin(fm(i)%nztb)>=1d-10 ) then
                    cycle Loop1
                else
-                   dr(3) = huge

```



```

+           dr(3) = huge_float
+           endif
+           else if( dircos(3)<-tiny ) then
+             if( r(3)-fm(i)%ztbin(fm(i)%nztb)>1d-10 ) then
@@ -1062,10 +1118,10 @@
+               else if( r(3)-fm(i)%ztbin(1)<= -1d-10 ) then
+                 cycle Loop1
+               else
-                 dr(3) = huge
+                 dr(3) = huge_float
+               endif
-             else
+             dr(3) = huge
+           endif
+         dr(3) = huge_float
+       endif
+     dstnce_to_bin = min(dr(1),dr(2),dr(3))
@@ -1115,27 +1171,18 @@
+
+   ! find distance to next cell
+   Loop3: do while (dstnce_to_travel>1d-9*d)
-     dr(1) = huge
+     dr(1) = huge_float
+     if( dircos(1)>0.) dr(1) = (fm(i)%xrbin(ixr+1)-r(1))/dircos(1)
+     if( dircos(1)<0.) dr(1) = (fm(i)%xrbin(ixr)-r(1))/dircos(1)
-     dr(2) = huge
+     dr(2) = huge_float
+     if( dircos(2)>0.) dr(2) = (fm(i)%yzbin(iyz+1)-r(2))/dircos(2)
+     if( dircos(2)<0.) dr(2) = (fm(i)%yzbin(iyz)-r(2))/dircos(2)
-     dr(3) = huge
+     dr(3) = huge_float
+     if( dircos(3)>0.) dr(3) = (fm(i)%ztbin(izt+1)-r(3))/dircos(3)
+     if( dircos(3)<0.) dr(3) = (fm(i)%ztbin(izt)-r(3))/dircos(3)
+     dstnce_to_bin = min(dr(1),dr(2),dr(3),dstnce_to_travel)
+     if( dstnce_to_bin>1d-15*d ) then
-
-       t = 1.*fm(i)%fmult
-       if( fm(i)%fmult<0) t = -t*rho(icl)
-       if( fm(i)%ifm_card/=0 ) then
-         call wtmult_fmsh(t,i)
-       endif
-
-       ! Score the track length
-       dt = dstnce_to_bin
-
-       ! Enter values in scratch arrays
+       if( i_size_bins>num_bins(kt1) ) then
+         num_bins(kt1)=num_bins(kt1)+1
@@ -1146,23 +1193,21 @@
+         i_bins(5,num_bins(kt1),kt1)=ien
+       endif
-
-       ! No dose response function
-
-       if( fm(i)%intrpol==0 ) then
-         if( fm(i)%icx==0 ) then
-           score=dt*wtg*t
-         else if ( fm(i)%icx==1 ) then
-           score=dt*wtg*erg*t
-         endif
+       ! Score the track length
+
+       ! Dose response function
+       t = 1._dknd
+       if( fm(i)%ifm_card/=0 ) then
+         call wtmult_fmsh(t,i)
+       endif
+       t = t*fm(i)%fmult
+       if( fm(i)%fmult < 0 ) t = -t*rho(icl)
-
-       else if( fm(i)%intrpol==1 ) then

```

```

-         if( fm(i)%icx==0 ) then
-             score=dt*wgt*t*dosef_fmesh(erg,i)
-         else if( fm(i)%icx==1 ) then
-             score=dt*wgt*t*erg*dosef_fmesh(erg,i)
-         endif
+         if ( fm(i)%ifm_card == -1 ) then ! Special tally multiplier -- # of tracks
+             score = t
+         else
+             score = dstnce_to_bin*wgt*t
+             if ( fm(i)%icx == 1 ) score = score*erg
+             if ( fm(i)%intrapol /= 0 ) score = score*dosef_fmesh(erg,i)
+         endif

        fmtal(i)%tally(ixr,iyz,izt,ien,kt)=
fmtal(i)%tally(ixr,iyz,izt,ien,kt)+score
@@ -1203,12 +1248,12 @@
    ! Algorithm based on cylindrical weight-window mesh

    use mcnp_params, only:dknd,one,pie
-    use mcnp_global, only:trf,huge,rho,icl,ktask
+    use mcnp_global, only:trf,huge_float,rho,icl,ktask

    integer , intent(in) :: i
    real(dknd), intent(in) :: x,y,z,u,v,w,erg,wgt,d

-    real(dknd), parameter :: tiny = 1/huge
+    real(dknd), parameter :: tiny = 1/huge_float

    real(dknd) :: dstnce_to_travel ! Distance remaining for the particle to travel
    real(dknd) :: dstnce_to_bin ! Distance to the next mesh bin boundary
@@ -1297,7 +1342,7 @@
        rv = r(1)*dircos(1)+r(2)*dircos(2)
        ! if rv >= 0, particle is moving away from the mesh
        if( r(1)>fm(i)%xrbin(fm(i)%nxrb).and.rv>=0 ) return
-        dr(1) = huge
+        dr(1) = huge_float
        if( dcos/=0.) then
            rs = r(1)**2+r(2)**2
            a = rv/dcos
@@ -1311,7 +1356,7 @@
        endif
    endif
    if( dr(1)<=-1d-10 ) then
-        dr(1) = huge
+        dr(1) = huge_float
    else if( dr(1)<=1d-10 ) then
        dr(1) = 1d-10
    endif
@@ -1324,7 +1369,7 @@
    else if ( cylr(2)-fm(i)%yzbin(fm(i)%nyzb)>=1d-10 ) then
        return
    else
-        dr(2) = huge
+        dr(2) = huge_float
    endif
    else if( dircos(3)<-tiny ) then
        if( cylr(2)-fm(i)%yzbin(fm(i)%nyzb)>1d-10 ) then
@@ -1334,10 +1379,10 @@
        else if( cylr(2)-fm(i)%yzbin(1)<= -1d-10 ) then
            return
        else
-            dr(2) = huge
+            dr(2) = huge_float
        endif
    else
-        dr(2) = huge
+        dr(2) = huge_float
    endif

    dstnce_to_bin = min(dr(1),dr(2))
@@ -1390,7 +1435,7 @@

```

```

! find distance to next mesh cell
do while (dstnce_to_travel>1d-15*d)
  rv = r(1)*dircos(1)+r(2)*dircos(2)
-   dr(1) = huge
+   dr(1) = huge_float
  if( dcos/=0. ) then
    rs = r(1)**2+r(2)**2
    a = rv/dcos
@@ -1412,7 +1457,7 @@
  endif
endif

-   dr(2) = huge
+   dr(2) = huge_float
  if( dircos(3)>0. ) then
    dr(2) = (fm(i)%yzbin(iyz+1)-r(3))/dircos(3)
    nextbin(2) = 1
@@ -1422,7 +1467,7 @@
  endif
  ! theta
  ! if single bin, point is always in it
-   dr(3) = huge
+   dr(3) = huge_float
  if( fm(i)%nztb/=2 ) then
    rp = -dircos(1)*r(2)+dircos(2)*r(1)
    if( rp<0. ) then
@@ -1433,7 +1478,7 @@
      if( vn<0 ) then
        dr(3) = (st*r(1)-ct*r(2))/vn
        nextbin(3) = -1
-      if( dr(3)<-1d-9 ) dr(3)=huge !allow for round-off errors
+      if( dr(3)<-1d-9 ) dr(3)=huge_float !allow for round-off errors
    endif
  else
    t = fm(i)%ztbin(izt+1)
@@ -1443,21 +1488,13 @@
    if( vn>0 ) then
      dr(3) = (st*r(1)-ct*r(2))/vn
      nextbin(3) = 1
-      if( dr(3)<-1d-9 ) dr(3)=huge !allow for round-off errors
+      if( dr(3)<-1d-9 ) dr(3)=huge_float !allow for round-off errors
    endif
  endif
endif

dstnce_to_bin = min(dr(1),dr(2),dr(3),dstnce_to_travel)
if( dstnce_to_bin>1d-10*d ) then
-   t = 1.*fm(i)%fmult
-   if( fm(i)%fmult<0 ) t = -t*rho(icl)
-   if( fm(i)%ifm_card/=0 ) then
-     call wtmult_fmsh(t,i)
-   endif
-
-   ! Score the track length
-   dt = dstnce_to_bin

  ! Enter values in scratch arrays
  if( i_size_bins>num_bins(kt1) ) then
@@ -1469,23 +1506,20 @@
    i_bins(5,num_bins(kt1),kt1)=ien
  endif

-   ! No dose response function
-
-   if( fm(i)%intrapol==0 ) then
-     if( fm(i)%icx==0 ) then
-       score=dt*wgt*t
-     else if ( fm(i)%icx==1 ) then
-       score=dt*wgt*erg*t
-     endif
-

```

```

-      ! Dose response function
+      ! Score the track length
+      t = 1._dknd
+      if( fm(i)%ifm_card /= 0 ) then
+          call wtmult_fmsh(t,i)
+      endif
+      t = t*fm(i)%fmult
+      if( fm(i)%fmult <0 ) t = -t*rho(icl)

-      else if(fm(i)%intrpol==1) then
-          if(fm(i)%icx==0) then
-              score=dt*wgt*t*dosef_fmsh(erg,i)
-          else if(fm(i)%icx==1) then
-              score=dt*wgt*t*erg*dosef_fmsh(erg,i)
-          endif
+      if ( fm(i)%ifm_card == -1 ) then ! Special tally multiplier -- # of tracks
+          score = t
+      else
+          score = dstnce_to_bin*wgt*t
+          if ( fm(i)%icx == 1 ) score = score*erg
+          if ( fm(i)%intrpol /= 0 ) score = score*dosef_fmsh(erg,i)
+      endif

      fmtal(i)%tally(ixr,iyz,izt,ien,kt)= fmtal(i)%tally(ixr,iyz,izt,ien,kt)+score
@@ -1723,18 +1757,43 @@
      use mcnp_global,      only: emx,mct,fpi
      implicit real(dknd) (a-h,o-z)
      integer i,j,jj,k,kk,l
+     integer      :: maxbin = 1
+     integer      :: n_reclength = 1
      real(dknd), ALLOCATABLE :: rel_err(:, :)
      real(dknd) sp_norm

      ! Get the source particle normalization.
      sp_norm = 1./fpi

+     ! Determine maximum record length
+     do i=1,nmesh
+         maxbin=max (fm(i)%nxrb, fm(i)%nyzb, fm(i)%nztb, maxbin)
+         select case (fm(i)%outf)
+             !
+             ! column format
+             !
+             case (0,4)
+                 n_reclength = max (105,35+10*maxbin,n_reclength)
+                 !
+                 ! ij, ik format
+                 !
+             case (1,2)
+                 n_reclength = max (105,17+12*fm(i)%nxrb,35+10*maxbin,n_reclength)
+                 !
+                 ! jk format
+                 !
+             case (3)
+                 n_reclength = max (105,17+12*fm(i)%nyzb,35+10*maxbin,n_reclength)
+             end select
+         enddo
+
+     ! open the meshtal file
+
+     if( lmtout ) then
-         rewind(iumt)
+         open(iumt,status='unknown',file=meshtal,form='formatted',recl=n_reclength)
+     else
+         call unique (meshtal,jtty)
-         open(iumt,status='new',file=meshtal,form='formatted',recl=262144)
+         open(iumt,status='new',file=meshtal,form='formatted',recl=n_reclength)
+         lmtout = .true.
+     endif
+     if(mct >=0) write(iumt,'(a6, " version ",a5, " ld=",a8,2x, "probid = ",a19 )') &
@@ -1771,7 +1830,7 @@

```

```

        write (iumt,"(4x,'Y direction:',10000f10.2)") (fm(j)%yzbin(k),k=1,fm(j)%nyzb)
        write (iumt,"(4x,'Z direction:',10000f10.2)") (fm(j)%ztbin(k),k=1,fm(j)%nztb)
    else if( fm(j)%icrd==2 ) then
-       write(iumt,'(x," Cylinder origin at ",3es10.2," axis in ",3es10.3,   &
+       write(iumt,'(1x," Cylinder origin at ",3es10.2," axis in ",3es10.3,   &
        & " direction")') fm(j)%org,fm(j)%axs
        write (iumt,"(4x,'R direction:',10000f10.2)") (fm(j)%xrbin(k),k=1,fm(j)%nxrb)
        write (iumt,"(4x,'Z direction:',10000f10.2)") (fm(j)%yzbin(k),k=1,fm(j)%nyzb)
@@ -2103,28 +2162,42 @@

        ! First set up the dose response functions

-       ! Check to see if the number of energy values equal the number of
-       ! response function values
-       if( ndeitm(i)/=ndfitm(i) ) then
-       call erprnt(1,1,1,meshid(i),0,0,0,0,&
-       & ' "number of values on de and df of mesh",i4, " not equal."')
-       endif
        ! If meshid = 0, enter the default response function for
        ! those mesh tallies that do not have response functions assigned
        if( meshid(i)==0 ) then
+
+       ! Compensate for incorrect number of items on de,df card if 'lin' is specified
+       indx_de = 0
+       indx_df = 0
+       if ( intrpol(i) > 2 ) indx_de = 1
+       if ( mod(intrpol(i),2) == 0 ) indx_df = 1
+
+       ! Check to see if the number of energy values equal the number of
+       ! response function values
+       if( ndeitm(i)-indx_de /= ndfitm(i)-indx_df ) then
+       call erprnt(1,1,1,meshid(i),0,0,0,0,&
+       & ' "number of values on de and df of mesh",i4, " not equal."')
+       endif
        do j = 1,nmesh
            if( fm(j)%ndfb==0 ) then !ndfb = 0 for all meshes w/out dose functions
                fm(j)%intrpol = intrpol(i)
-               fm(j)%ndfb = ndfitm(i)
+               fm(j)%ndfb = ndfitm(i)-indx_df
                allocate (fm(j)%de(fm(j)%ndfb))
                allocate (fm(j)%df(fm(j)%ndfb))
                do k = 1, fm(j)%ndfb
-                   fm(j)%de(k) = detmp(i,k)
-                   fm(j)%df(k) = dftmp(i,k)
+                   fm(j)%de(k) = detmp(i,k+indx_de)
+                   fm(j)%df(k) = dftmp(i,k+indx_df)
                enddo
            endif
        enddo
        else ! find the mesh for this response function and fill in the values
+
+       ! Check to see if the number of energy values equal the number of
+       ! response function values
+       if( ndeitm(i) /= ndfitm(i) ) then
+       call erprnt(1,1,1,meshid(i),0,0,0,0,&
+       & ' "number of values on de and df of mesh",i4, " not equal."')
+       endif
        do j = 1,nmesh
            if( fm(j)%id==meshid(i) ) then
                if( fm(j)%ndfb==0 ) then
@@ -2165,19 +2238,18 @@

        ! find the mesh for this FM card and fill in the values
        nfm_do: do i = 1,nfm
-       iflg = 0 ! zero mesh tally id flag
-       nmesh_do: do j = 1,nmesh
+       nmesh_do: do j = 1,nmesh
            if( fm(j)%id==meshfm(i) ) then
-               iflg = 1.
+               kl = fm(j)%id
            ! count bins

```

```

k = 1
- do while (fmtmp(k,i)/=0)
+ do while (fmtmp(k,i) /= 0 .or. fmtmp(k+1,i) /= 0)
  k = k+1
enddo
n = k-1
fm(j)%nireact = n+10
- allocate(fm(j)%ireact(fm(j)%nireact))
- fm(j)%ireact = 0
+ allocate(fm(j)%react(fm(j)%nireact))
+ fm(j)%react = 0

if( fm(j)%ipt==3 .and. n>1 ) call erprnt(1,1,0,0,0,0,0,0,&
& ' "fm for electron mesh tally has more than just a constant."'')
@@ -2212,7 +2284,7 @@
  fm(j)%fmult = fmtmp(k+1,i)
  ni = ni+1
  if( ni>1 ) call erprnt(1,1,1,meshfm(i),0,0,0,0,&
- & ' "mesh tally ",i4," only one mulitplier set per mesh tally"'')
+ & ' "mesh tally ",i4," only one mulitplier set per mesh tally"'')
  420 continue
  if( m+m1+max(0,k2)>2 .or. m<0 .or. k==n .and. (m/=0) ) go to 580
enddo Loop_420
@@ -2253,12 +2325,16 @@
  if( fmtmp(k+2,i)==1000002 ) go to 490
  ii = -1
  if( fmtmp(k+1,i)<0 ) go to 480
- do ii = 1,nmat
-   if( nmt(ii)==fmtmp(k+1,i)) exit
- enddo
+ if( fmtmp(k+1,i) == 0 ) then
+   ii = 0
+ else
+   do ii = 1,nmat
+     if( nmt(ii)==fmtmp(k+1,i)) exit
+   enddo
+ endif
  480 continue
  fm(j)%mat = ii
- call erprnt(1,2,2,ii,fm(j)%id,0,0,0, &
+ if (fm(j)%mat > 0 ) call erprnt(1,2,2,nmt(ii),fm(j)%id,0,0,0, &
& ' " FM card uses material ",i4," cross sections over all of mesh tally ",i4')
  kq = 1
  ll = ld+1
@@ -2271,23 +2347,23 @@
  cycle Loop_560
  500 continue
  if( k<k1+3 ) cycle Loop_560
- if( ii>0 ) go to 540
+ if( ii>=0 ) go to 540
  if( ii== -2 ) go to 530
  do jj = 1,nmat
    if( nmt(jj)==fmtmp(k,i) ) go to 520
  enddo
  520 continue
  fm(j)%ireact(ld) = jj
+ fm(j)%react(ld-2) = jj
  fm(j)%nreact = fm(j)%nreact+2.
  ii = -2
  go to 550
  530 continue
- fm(j)%ireact(ld) = fmtmp(k,i)
+ fm(j)%react(ld-2) = fmtmp(k,i)
  ii = -3
  go to 550
  540 continue
- fm(j)%ireact(ld-2) = fmtmp(k,i)
- jj = fm(j)%ireact(ld-2)
+ fm(j)%react(ld-2) = fmtmp(k,i)
+ jj = fm(j)%react(ld-2)
+ if( fm(j)%ipt==1 .and. jj<=-6 ) itfxs = 1

```

```

                if( fm(j)%ipt==1 .and. jj<-8 .or. &
                  & fm(j)%ipt==2 .and. jj<-6 ) call erprnt(1,1,2,j,kl,0,0,0,&
@@ -2302,7 +2378,7 @@
                go to 590
580                continue
                call erprnt(1,1,1,kl,0,0,0,0,&
-                  & ' "fm card of tally",i4, " has wrong format."' )
+                  & ' "fm card of mesh tally",i4, " has wrong format."' )

590                continue
                exit nmesh_do
@@ -2367,16 +2443,16 @@
!-----
----

subroutine fmesh_vtask(ktask)
-
+
! Subroutine to merge the mesh tally values into the 1st array bin.
! This needs to be done even if run as a sequential code
! called from vtask
-
+
integer, intent(in) :: ktask
integer :: i,kt
-
+
kt = ktask+2
- do i = 1,nmesh
+ do i=1,nmesh
    fm(i)%fmarray(:, :, :, 1) = fm(i)%fmarray(:, :, :, 1)+fm(i)%fmarray(:, :, :, kt)
    fm(i)%fmerr(:, :, :, 1) = fm(i)%fmerr(:, :, :, 1)+fm(i)%fmerr(:, :, :, kt)
    fm(i)%fmarray(:, :, :, kt) = 0
@@ -2418,3 +2494,4 @@
!-----
----

end module fmesh_mod
+
diff -Naurd MCNP5/Source/src/getexm.F90 MCNP5_new/Source/src/getexm.F90
--- MCNP5/Source/src/getexm.F90      2003-04-30 20:11:00.000000000 -0600
+++ MCNP5_new/Source/src/getexm.F90  2004-07-22 15:14:41.000000000 -0600
@@ -26,7 +26,6 @@
character(len=80) :: hm
integer :: eol

-#ifndef PCDOS
integer*4 ia
hm = ' '
j = 0
@@ -45,16 +44,10 @@
end do
hm(:) = hm(1:eol)

-#endif
-
#ifdef HPUX
$hp9000_800 system off
#endif /*def.hpux*/

-#ifndef PCDOS
- call getcl(hm)
-#endif /*def.pcdos*/
-

return
end subroutine getexm
diff -Naurd MCNP5/Source/src/getxst.F90 MCNP5_new/Source/src/getxst.F90
--- MCNP5/Source/src/getxst.F90      2003-04-30 20:11:02.000000000 -0600
+++ MCNP5_new/Source/src/getxst.F90  2004-07-22 15:14:41.000000000 -0600
@@ -11,6 +11,7 @@

```

```

    use mcnp_global
    use mcnp_debug
    use dynamic_arrays
+   use erprnt_mod

    implicit real(dknd) (a-h,o-z)

@@ -24,7 +25,7 @@

    ! Expand xss array to accomodate the largest table,
    !     or exs array to hold all tables
-   et = huge
+   et = huge_float
    em = 0.
    ih = 0
    th = 0.
@@ -93,20 +94,12 @@
    inquire( file=ha, exist=file_exists )
    if( .not.file_exists ) then
        if( len_trim(hdpath)>0 ) then
-#ifdef PCDOS
-    ha = hdpath(1:len_trim(hdpath))//'\ '//hf
-#else
    ha = hdpath(1:len_trim(hdpath))//'\ '//hf
-#endif
        endif
    inquire( file=ha, exist=file_exists )
    if( .not.file_exists ) then
        if( len_trim(hdpth)>0 ) then
-#ifdef PCDOS
-    ha = hdpth(1:len_trim(hdpth))//'\ '//hf
-#else
    ha = hdpth(1:len_trim(hdpth))//'\ '//hf
-#endif
        endif
    inquire( file=ha, exist=file_exists )
    if( .not.file_exists ) then
@@ -379,12 +372,12 @@

    ! Print the total storage used and the expunge limits.
    write(iuo,'(/ " total",i12)') lxs
-   if( emx(1)<huge ) then
+   if( emx(1)<huge_float ) then
        write(iuo,430) emx(1)
    430 format(/ " any neutrons with energy greater than emax =",1pe12.5,&
        & " from the source or from a collision will be resampled.")
        endif
-   if( (emx(1)<huge .or. ecf(1)/=0.) .and. mcal==0 ) then
+   if( (emx(1)<huge_float .or. ecf(1)/=0.) .and. mcal==0 ) then
        write(iuo,440) ecf(1),emx(1)
    440 format(/ " neutron cross sections outside the range from",&
        & 1pe11.4, " to",e11.4, " mev are expunged.")
@@ -403,7 +396,7 @@
    call erprnt(1,3,1,ih,0,0,0,0,&
        & 'i4, " cross sections modified by free gas thermal treatment."')
    endif
-   if( kpt(2)/=0 .and. et/=huge ) emx(2) = exp(et)
+   if( kpt(2)/=0 .and. et/=huge_float ) emx(2) = exp(et)
    if( kpt(3)/=0 .or. (kpt(2)/=0 .and. ides==0) ) emx(2) = min(emx(2),emx(3))
    if( abs(emx(2)-emx(3))<.00001*emx(3) ) emx(2) = emx(3)
    if( emx(2)<emx(3) ) then
diff -Naurd MCNP5/Source/src/ginst.F90 MCNP5_new/Source/src/ginst.F90
--- MCNP5/Source/src/ginst.F90      2003-04-30 20:11:04.000000000 -0600
+++ MCNP5_new/Source/src/ginst.F90  2004-07-22 15:14:41.000000000 -0600
@@ -1,7 +1,7 @@
-!+ $Id: ginst.F90,v 1.3 2002/12/03 19:21:47 ljcox Exp $
+!+ $Id: ginst.F90,v 1.2 2004/04/06 16:01:09 jgoorley Exp $
    ! Copyright LANL/UC/DOE - see file COPYRIGHT_INFO

-#ifdef GKSSIM
+#if defined(PLOT) || defined(MCPLOT)

```



```

subroutine ginst(nw,nd,ll,h1,ip,x1,x2,y1,y2,lb,ld,hd)
  ! perform gks function 'initialise string'.
  ! nw = workstation identifier
@@ -27,4 +27,4 @@
  #endif /*def.xlib*/
  return
end subroutine ginst
-#endif /*def.gkssim*/
+#endif
diff -Naurd MCNP5/Source/src/gkssim.F90 MCNP5_new/Source/src/gkssim.F90
--- MCNP5/Source/src/gkssim.F90      2003-04-30 20:11:04.000000000 -0600
+++ MCNP5_new/Source/src/gkssim.F90  2004-07-22 15:14:41.000000000 -0600
@@ -3,14 +3,11 @@

module gkssim
  ! Description:
- ! Low level graphics routines. Access QuickWin, Winteracter or Xlib.
+ ! Low level graphics routines using Xlib.
  ! Postscript is also written if requested.
  ! The original genesis of these routines seems to have been written to
  ! be used on systems without GKS graphics.

- ! Note: In LAHEY mode, this module depends on gxsub:gxon. But gxsub also
- !       depends on gkssim. A quandry.
-
  ! Modules used:
  use mcnp_plot
  use mcnp_debug
@@ -22,7 +19,7 @@
  &      gsplci, gstxci, gqcf

  contains
-#ifndef GKSSIM
+#if defined(PLOT) || defined(MCPLLOT)

  !-----

@@ -82,53 +79,6 @@

  subroutine gacwk(nw)
    ! perform gks function 'activate workstation'.
-#ifndef QWIN
-  use dflib
-
-  character h*20
-  logical*4 st
-  type (qwinfo) wi,wf
-  type (windowconfig) wc
-
-  if( nw/=1 ) go to 10
-
-  ! move the execute window to the bottom of the frame.
-  ! this assumes a font size of 8x16 (wf has units of pixels).
-  k = getwsizqq(qwin$framewindow,qwin$sizecurr,wf)
-  wi.type = qwin$set
-  wi.x = 0
-  wi.y = max(0,int(wf.h/16.))-32)
-  wi.h = 30
-  wi.w = 80
-  k = setwsizqq(0,wi)
-
-  ! open the plot window and set its size (height=3/4 of width).
-  ! may not get this exact shape - use viewport to rectify.
-  open(99,file='user')
-  k = setactiveqq(99)
-  wc.numypixels = max(480,min(int(wf.h*0.8),int(wf.w*3./4.)))
-  wc.numxpixels = int(4./3.*wc.numypixels)
-  wc.numtextcols = -1
-  wc.numtextrows = -1
-  wc.numcolors = -1
-  wc.fontsize = -1

```

```

-   wc.title="MCNP Plot Window"C
-   st = setwindowconfig(wc)
-   IF(.not.st ) st = setwindowconfig(wc)
-   st = getwindowconfig(wc)
-
-   ! set font width based on 32 characters in 1/4 of window.
-   ! if font not found, use a 5x10 font.
-   k = initializefonts()
-   write(h,'(a,i1)')'bfw',min(8,int(wc.numxpixels/4./32.))
-   k = setfont(h)
-   IF(k < 0)k=setfont('bw5')
-
-   ! once window is maximized, force it to stay that way.
-   wi.type = qwin$max
-   k = setwsizqq(99,wi)
-10 continue
-#endif /*def.qwin*/

#ifdef XLIB
    if( nw==1 ) call xgacwk()
@@ -150,10 +100,6 @@
    if( nw==1 ) call xgdawk()
#endif /*def.xlib*/

-#ifdef QWIN
-   if( nw==1 ) close(99)
-#endif /*def.qwin*/
-
-   jta(nw) = 0

    return
@@ -164,15 +110,6 @@
    subroutine gclrwk(nw,k)
        ! perform gks function 'clear workstation'.

-#ifdef QWIN
-   use dflib
-
-   if( nw==1 ) then
-       j = setactiveqq(99)
-       call clearscreen($gclearscreen)
-   endif
-#endif /*def.qwin*/
-
#ifdef XLIB
    if( nw==1) call xgclrw()
#endif /*def.xlib*/
@@ -184,11 +121,6 @@

    subroutine guwk(nw,k)
        ! perform gks function 'update workstation'.
-#ifdef QWIN
-   use dflib
-
-   if( nw==1 .and. k==0 ) j = focusqq(99)
-#endif /*def.qwin*/

#ifdef XLIB
    if( nw==1 .and. k==0 ) call xguwk()
@@ -203,14 +135,7 @@

    subroutine gpl(n,x,y)
        ! perform gks function 'polyline'.
-#ifdef LAHEY
-   use WINTERACTER
-#endif /*def.lahey*/
-#ifdef QWIN
-   use dflib
-
-   type (wxycoord) xy
-#endif /*def.qwin*/

```

```

+
  real :: cr(4,3),x(n),y(n),xw(20),yw(20)
  data cr/.006,.004,.006,.004,4*.003,.009,3*.003/

@@ -242,20 +167,6 @@
  call xgpl(x(i-1),y(i-1),x(i),y(i))
  enddo
  #endif /*def.xlib*/
-#ifndef QWIN
-  call moveto_w(dble(x(1)),dble(y(1)),xy)
-  do i = 2,n
-    k = lineto_w(dble(x(i)),dble(y(i)))
-  enddo
-#endif /*def.qwin*/
-#ifndef LAHEY
-  call IGrMoveto(11.*(x(1)-xlf)/(xrt-xlf)*.75/chite(4),&
-    & 8.5*(y(1)-ybt)/(ytp-ybt))
-  do i = 2,n
-    call IGrLineTo(11.*(x(i)-xlf)/(xrt-xlf)*.75/chite(4),&
-    & 8.5*(y(i)-ybt)/(ytp-ybt))
-  enddo
-#endif /*def.lahey*/
  return

  ! draw interrupted line.
@@ -292,20 +203,6 @@
  call xgpl(xw(i-1),yw(i-1),xw(i),yw(i))
  enddo
  #endif /*def.xlib*/
-#ifndef QWIN
-  call moveto_w(dble(xw(1)),dble(yw(1)),xy)
-  do i = 2,m
-    k = lineto_w(dble(xw(i)),dble(yw(i)))
-  enddo
-#endif /*def.qwin*/
-#ifndef LAHEY
-  call IGrMoveTo(11.*(xw(1)-xlf)/(xrt-xlf)*.75/chite(4),&
-    & 8.5*(yw(1)-ybt)/(ytp-ybt))
-  do i = 2,m
-    call IGrLineTo(11.*(xw(i)-xlf)/(xrt-xlf)*.75/chite(4),&
-    & 8.5*(yw(i)-ybt)/(ytp-ybt))
-  enddo
-#endif /*def.lahey*/
  50 continue
  xw(1) = xw(m)
  yw(1) = yw(m)
@@ -327,13 +224,6 @@
  subroutine gtx(x,y,h)
    ! perform gks function 'text'.

-#ifndef LAHEY
-  use WINTERACTER
-#endif /*def.lahey*/
-#ifndef QWIN
-  use dflib
-  type (wxycoord) xy
-#endif /*def.qwin*/
  character(len=*) :: h
  real :: x,y
  character(len=120) :: hn
@@ -377,28 +267,6 @@
  #ifdef XLIB
  call xgtx(h,n,x,y)
  #endif /*def.xlib*/
-#ifndef QWIN
-
-  ! top left of character string is the origin.
-  ! font size is not set to chite(5) in gschup, but this works.
-  x1 = x
-  y1 = y
-  if( abs(chup(1))>abs(chup(2))) x1 = x1-2.*chite(5)

```

```

-   IF(abs(chup(1))<=abs(chup(2)))  y1 = y1+chite(5)
-   call moveto_w(dble(x1),dble(y1),xy)
-   call outgtext(h(1:n))
-#endif /*def.qwin*/
-#ifdef LAHEY
-   m = 1
-   if( abs(chup(1))>abs(chup(2)))  m = n
-   ic = nint((x-xlf)/(xrt-xlf)*.75/chite(4)*10000)
-   if( abs(chup(1))>abs(chup(2)))  ic = max(0,ic-1)
-   il = max(0,nint(((ytp-y)/(ytp-ybt))-m+1)*10000))
-   do i = 1,m
-       call WindowOutString(ic,il,h(i:i+n-m))
-       il = il+1
-   enddo
-#endif /*def.lahey*/
-   return
-   end subroutine gtx

@@ -439,9 +307,6 @@

-   subroutine gschup(x,y)
-       ! perform gks function 'set character up vector'.
-#ifdef QWIN
-   use dflib
-#endif /*def.qwin*/

-   chup(1) = x
-   chup(2) = y
@@ -451,15 +316,6 @@
-   call xgschu(x,y)
-#endif /*def.xlib*/

-#ifdef QWIN
-   ! tenths of degrees for counterclockwise rotation.
-   if( x==0. .and. y>0.)  k = 0
-   if( x==0. .and. y<0.)  k = 1800
-   if( x<0. .and. y==0.)  k = 900
-   if( x>0. .and. y==0.)  k = -900
-   if( x/=0. .and. y/=0.) k = nint(1800./3.14159265*atan2(x,y) -900)
-   call setgtextrotation(k)
-#endif /*def.qwin*/
-   return
-   end subroutine gschup

@@ -467,9 +323,6 @@

-   subroutine gswn(nt, xm, xx, ym, yx)
-       ! perform gks function 'set window'.
-#ifdef QWIN
-   use dflib
-#endif /*def.qwin*/

-   integer :: nt
-   real :: xm,xx,ym,yx
@@ -486,10 +339,6 @@
-   call xgswn(xm,xx,ym,yx)
-#endif /*def.xlib*/

-#ifdef QWIN
-   k = setwindow(.true.,dble(xm),dble(ym),dble(xx),dble(yx))
-#endif /*def.qwin*/
-
-   return
-   end subroutine gswn

@@ -497,24 +346,13 @@

-   subroutine gsvp(nt, xm, xx, ym, yx)
-       ! perform gks function 'set viewport'.
-#ifdef QWIN
-   use dflib

```

```

-   logical*4 st
-   type (windowconfig) wc
-#endif /*def.qwin*/
-   integer :: nt
-   real    :: xm,xx,ym,yx

-   chite(3) = xx-xm
-   chite(4) = yx-ym

-#ifndef QWIN
-   st = getwindowconfig(wc)
-   call setviewport(int2(xm),int2(ym),min(int2(wc.numxpixels), &
-     & int2(wc.numypixels/yx)),int2(wc.numypixels))
-#endif /*def.qwin*/
-
-   return
- end subroutine gsvp

@@ -550,9 +388,6 @@
!-----

-   subroutine grqlc(nw,j,is,i,x,y)
-#ifndef LAHEY
-   use WINTERACTER
-#endif /*def.lahey*/
-   ! perform gks function 'request locator'.

-   integer :: nw,j,is,i
@@ -564,47 +399,6 @@
-   call xgrqlc(j,x,y)
-#endif /*def.xlib*/

-#ifndef LAHEY
-   type (win_message) ::mesg
-   logical click
-   do i = 1,10
-     call WMessageEnable(i,0)
-   enddo
-   call WindowOutString(100,9500,'Click for Cursor Location')
-   call WindowOutString(100,9700,'Click on Title Bar to Redraw')
-   call WindowOutString(100,9900,'Drag on Title Bar to Move Window')
-   call WMessageEnable(MouseButtonDown,1)
-   call WMessageEnable(Expose,1)
-   click = .false.
-   do while (.not.click)
-     call WmessagePeek(itype,mesg)
-     select case(itype)
-     case(Expose)
-       call gxon(1)
-       call tekdv
-       call WindowOutString(100,9500,'Click for Cursor Location')
-       call WindowOutString(100,9700,'Click on Title Bar to Redraw')
-       call WindowOutString(100,9900,'Drag on Title Bar to Move Window')
-     case(mousebutton)
-       click = .true.
-     end select
-   enddo
-   call WMessageEnable(MouseButtonDown,0)
-   call WMessageEnable(Expose,0)
-   call gxon(1)
-   call tekdv
-   call WindowClearArea(0,9700,2000,9990)
-   x = mesg%gx * (xrt-xlf)/11.0/0.75*chite(4) + xlf
-   y = mesg%gy * (ytp-ybt)/8.5 + ybt
-   ! draw cross hairs.
-   do i = -1,1,2
-     call IGrColourN(40)
-     call IGrMoveTo(mesg%gx,mesg%gy)
-     call IGrLineTo(mesg%gx+i*0.1,mesg%gy)
-     call IGrMoveTo(mesg%gx,mesg%gy)

```

```

-      call IGrLineTo(mesg%gx,mesg%gy+i*0.1)
-      enddo
-#endif /*def.lahey*/
      return
    end subroutine grqlc

@@ -613,13 +407,6 @@
      subroutine gfa(n,x,y)
        ! perform gks function 'fill area'.

-#ifdef LAHEY
-      use WINTERACTER
-#endif /*def.lahey*/
-#ifdef QWIN
-      use dflib
-#endif /*def.qwin*/
-
        integer :: n
        real    :: x(n),y(n)
        integer :: nx(10),ny(10)
@@ -642,20 +429,6 @@
        call xgfa(x(1),y(1),x(3),y(3))
      #endif /*def.xlib*/

-#ifdef QWIN
-      k = rectangle_w($gfillinterior,dbble(x(1)),dbble(y(1)),&
-        & dbble(x(3)),dbble(y(3)))
-#endif /*def.qwin*/
-
-#ifdef LAHEY
-      do i = 1,n
-        xn(i) = 11.*(x(i)-xlf)/(xrt-xlf)*.75/chite(4)
-        yn(i) = 8.5*(y(i)-ybt)/(ytp-ybt)
-      enddo
-      call IGrFillPattern(4,2,3)
-      call IGrPolygonComplex(xn,yn,n)
-#endif /*def.lahey*/
-
      return
    end subroutine gfa

@@ -663,14 +436,6 @@

      subroutine gsfaci(ic,md)
        ! perform gks function 'set fill area color index'.
-      !* need to check on allowed color numbering schemes for LAHEY
-
-#ifdef LAHEY
-      use WINTERACTER
-#endif /*def.lahey*/
-#ifdef QWIN
-      use dflib
-#endif /*def.qwin*/

        integer :: ic ! color index.
        integer :: md ! mode: 0 = use colors; 1 = use shades.
@@ -689,7 +454,6 @@
        case default ! use contrasted shades

          c = colors(ic)
-
        end select

@@ -703,16 +467,6 @@
        call xgsplc(c%rgb)
      #endif /*def.xlib*/

-#ifdef QWIN
-      ! Set QuickWin graphics foreground RGB color.
-      ik = c%rgb(1) + 256*c%rgb(2) + 256**2*c%rgb(3)

```

```

-   k = setcolorrrgb(ik)
-#endif /*def.qwin*/
-
-#ifdef LAHEY
-   call IGrColourN(16*(ic-1))
-#endif /*def.lahey*/
-
-   return
-   end subroutine gsfaci
@@ -720,12 +474,6 @@

-   subroutine gsplci(ic,md)
-   ! perform gks function 'set polyline color index'.
-#ifdef LAHEY
-   use WINTERACTER
-#endif /*def.lahey*/
-#ifdef QWIN
-   use dflib
-#endif /*def.qwin*/

-   integer :: ic ! index of color to set.
-   integer :: md ! mode: 0 = use colors; 1 = use shades
@@ -756,16 +504,6 @@
-   call xgsplc(c%rgb)
-#endif /*def.xlib*/

-#ifdef QWIN
-   ! Set QuickWin graphics foreground RGB color.
-   ik = c%rgb(1) + 256*c%rgb(2) + 256**2*c%rgb(3)
-   k = setcolorrrgb(ik)
-#endif /*def.qwin*/
-
-#ifdef LAHEY
-   call IGrColourN(16*(ic-1))
-#endif /*def.lahey*/
-
-   return
-   end subroutine gsplci
@@ -774,13 +512,6 @@
-   subroutine gstxci(ic,md)
-   ! perform gks function 'set text color index'.

-#ifdef QWIN
-   use dflib
-#endif /*def.qwin*/
-#ifdef LAHEY
-   use WINTERACTER
-   type (win_font) :: MCNPfont
-#endif /*def.lahey*/
-   integer :: ic ! Index of color to set.
-   integer :: md ! mode: 0 = use colors; 1 = use shades.
-   type(color) :: c
@@ -807,21 +538,6 @@
-   call xgsplc(c%rgb)
-#endif /*def.xlib*/

-#ifdef QWIN
-   ! Set QuickWin graphics foreground RGB color.
-   ik = c%rgb(1) + 256*c%rgb(2) + 256**2*c%rgb(3)
-   k = setcolorrrgb(ik)
-#endif /*def.qwin*/
-
-#ifdef LAHEY
-   MCNPfont%ifontnum = 0
-   MCNPfont%ifcol = (ic-1)/2
-   MCNPfont%ibcol = -1
-   MCNPfont%iwidth = 100
-   MCNPfont%iheight = 200
-   MCNPfont%ibold = 1

```

```

-   call WindowFont(MCNPfont)
-#endif /*def.lahey*/
    return
    end subroutine gstxci

@@ -830,18 +546,6 @@
    subroutine gqcf(ic,ni)
        ! perform gks function 'inquire color facilities'.

-#ifdef QWIN
-   use dflib
-   type (windowconfig) wc
-#endif /*def.qwin*/
-#ifdef LAHEY
-   use WINTERACTER
-   type (win_style) :: MCNPwin
-   type (win_font) :: MCNPfont
-   real(dknd) :: ra(7)
-   integer :: ia(9)
-   character hl*40
-#endif /*def.lahey*/
    integer :: ic ! color flag.
    integer :: ni ! number of colors.

@@ -853,35 +557,6 @@
    if( ic/=0) ni = ncolor
    #endif /*def.xlib*/

-#ifdef QWIN
-   k = getwindowconfig(wc)
-   ni = min(ncolor,wc.numcolors)
-   if( ni>2) ic = 1
-#endif /*def.qwin*/
-
-#ifdef LAHEY
-   call WInitialise(' ')
-   MCNPwin%flags = MinButton + MaxButton
-   MCNPwin%x = 0
-   MCNPwin%y = 0
-   MCNPwin%width = 0
-   MCNPwin%height = 0
-   MCNPwin%menuid = 0
-   MCNPwin%title = "MCNP Plot Window"
-   call WindowOpen(MCNPwin)
-   call IGrArea(0.0,0.0,1.0,1.0)
-   call IGrUnits(0.0,0.0,11.0,8.5)
-   ni = min(ncolor,InfoGrScreen(30))
-   MCNPfont%ifontnum = 4
-   MCNPfont%iwidth = 100
-   MCNPfont%iheight = 200
-   MCNPfont%ibold = 1
-   call WindowFont(MCNPfont)
-   nctext = 10000/WInfoFont(9)
-   nltext = 10000/WInfoFont(10)
-   call WindowClose
-   if( ni>2 ) ic = 1
-#endif /*def.lahey*/
    return
    end subroutine gqcf

@@ -956,5 +631,5 @@
    return
    end subroutine gqcf

-#endif /*def.gkssim*/
+#endif /*def PLOT or MCPLLOT */
    end module gkssim
diff -Naurd MCNP5/Source/src/gmgww.F90 MCNP5_new/Source/src/gmgww.F90
--- MCNP5/Source/src/gmgww.F90      2003-04-30 20:11:04.000000000 -0600
+++ MCNP5_new/Source/src/gmgww.F90  2004-07-22 15:14:41.000000000 -0600
@@ -69,7 +69,7 @@

```



```

        if( rim/=0. ) r=log10(rim)
        do jg=1,jgm(ip)
            tm = 0.
-           ts = huge
+           ts = huge_float
            do ia=1,msa
                if( fim(ip,ia)==0. ) cycle
                t = scr(msa*(jg-1)+ia)
diff  -Naurd MCNP5/Source/src/gxsub.F90 MCNP5_new/Source/src/gxsub.F90
--- MCNP5/Source/src/gxsub.F90      2003-04-30 20:11:04.000000000 -0600
+++ MCNP5_new/Source/src/gxsub.F90  2004-07-22 15:14:41.000000000 -0600
@@ -61,10 +61,6 @@

        ! Modules used:
        use mcnp_plot
-#ifdef LAHEY
-    use WINTERACTER
-    type (win_style) :: MCNPwin
-#endif
        integer :: nw
        integer :: kn(2),ic,ni,i,jt,ie,nc
        character(len=12) :: hf
@@ -98,11 +94,6 @@
            if( ic/=0 .and. ni>2 ) then
                mcolor = sign(min(ni,ncolor),mcolor)
                do i = 1,ncolor+7
-#if defined(LAHEY) || defined(QWIN)
-                if( i<=ncolor ) kcolor(i) = i
-                if( i<=7 ) kcolor(ncolor+i) = i
-                if( ni<ncolor+7 ) cycle
-#endif
                kcolor(i) = abs(kci(i))
                colors(i)%rgb(1) = nint(255*colors(i)%r)
                colors(i)%rgb(2) = nint(255*colors(i)%g)
@@ -124,21 +115,6 @@
        call gsvp(1,0.,1.,0.,.75+jvp*.25)
        wnvp(3) = 1.
        wnvp(4) = .75+jvp*.25
-#ifdef LAHEY
-    if( nw==1 ) then
-        call WInitialise(' ')
-        MCNPwin%flags = MinButton + MaxButton
-        MCNPwin%x = 0
-        MCNPwin%y = 0
-        MCNPwin%width = 0
-        MCNPwin%height = 0
-        MCNPwin%menuid = 0
-        MCNPwin%title = "MCNP Plot Window"
-        call WindowOpen(MCNPwin)
-        call IGrArea(0.0,0.0,1.0,1.0)
-        call IGrUnits(0.0,0.0,11.0,8.5)
-    endif
-#endif
        return
    end subroutine gxon

@@ -162,34 +138,12 @@
        ! Description:
        ! Return home, update the display, and be ready for fortran i/o.

-    ! Modules used
-#ifdef LAHEY
-    use WINTERACTER
-#endif
-
        real :: s,t
-#ifdef LAHEY
-    integer :: ia(9)
-    real :: ra(7), t1, t2
-    character(len=40) :: hl
-#endif

```

```

        if( jgxa(1)==0 ) return
        call gschh(.01*real(wnvp(2)))

-#ifndef LAHEY
        call gtx(s,t, '.')
-
-#else
-   !* seems to be a 4 sec pause for LAHEY only.
-   call secnd(t1)
-   if( ifile/=itty ) then
-       do
-           call secnd(t2)
-           if( t2-t1>=4.d0 ) exit
-       enddo
-   endif
-#endif
        call guwk(1,0)
        return
    end subroutine gxhome
@@ -455,3 +409,4 @@
    end subroutine gxaxis
#endif
end module gxsub
+
diff -Naurd MCNP5/Source/src/hpsort.F90 MCNP5_new/Source/src/hpsort.F90
--- MCNP5/Source/src/hpsort.F90      2003-04-30 20:11:06.000000000 -0600
+++ MCNP5_new/Source/src/hpsort.F90  2004-07-22 15:14:41.000000000 -0600
@@ -1,84 +1,181 @@
-!+ $Id: hpsort.F90,v 1.4 2002/12/03 19:22:02 ljcox Exp $
+!+ $Id: hpsort.F90,v 1.2 2004/04/01 23:48:02 jgoorley Exp $
+ ! Copyright LANL/UC/DOE - see file COPYRIGHT_INFO

-subroutine hpsort(it, kn, ks, np, ns)
- ! sort (heapsort) the np extreme tallies into ascending order.
- ! it is the tally number, kn and ks are offsets in the nhsd and
- ! shsd arrays, np is the number of extreme tallies in the shsd
- ! array, and ns is the number of big,small tallies in array stt.
- use mcnp_global
- use mcnp_debug
+module hpsort_mod

- implicit real(dknd) (a-h,o-z)
+ interface hpsort
+ ! ==> specific routines used for generic subroutine:
+ module procedure hpsort_i4, hpsort_i8
+ end interface

- real(dknd) :: ar(2*ntp)
-
- ! fill array ar with the history tally points to be sorted.
- do j=1,ns
-   ar(j) = stt(kstt+j,it)
- end do
- do j=1,np
-   ar(ns+j) = shsd(ks+j,it)
- end do
- nh = ns+np
- ir = nh
- l = ir/2+1
-
- ! perform the sort using the heapsort (nlogn) algorithm.
-40 continue
- if( l<=1 ) go to 90
- l = l-1
- a = ar(l)
-50 continue
- ii = l
- j = l+1
- if( j>ir ) then
-   ar(ii) = a

```

```

-   go to 40
-   elseif( j==ir ) then
-     go to 70
-   else
-     go to 60
-   endif
-60 continue
-   if( ar(j)<ar(j+1) ) j=j+1
-70 continue
-   if( a>=ar(j) ) go to 80
-   ar(ii) = ar(j)
-   ii = j
-   j = j+j
-   if( j>ir ) then
-     ar(ii) = a
-     go to 40
-   elseif( j==ir ) then
-     go to 70
-   else
-     go to 60
-   endif
-80 continue
-   j = ir+1
-   if( j>ir ) then
-     ar(ii) = a
-     go to 40
-   elseif( j==ir ) then
-     go to 70
-   else
-     go to 60
-   endif
-90 continue
-   a = ar(ir)
-   ar(ir) = ar(1)
-   ir = ir-1
-   if( ir/=1 ) go to 50
-   ar(1) = a
-
-   ! fill shsd(kshs+nsp+6,it) with the ntp largest,smallest values.
-   nt = min(ntp,nh)
-   do j=1,nt
-     shsd(ks+j,it) = ar(nh-nt+j)
-   enddo
-   nhsd(kn+1,it) = nt
-   nhsd(kn+2,it) = 0
-   if( nt==ntp ) shsd(ks+ntp+1,it)=shsd(ks+1,it)
-   return
-end subroutine hpsort
+ contains
+
+   subroutine hpsort_i4(it,kn,ks,np,ns)
+     ! sort (heapsort) the np extreme tallies into ascending order.
+     ! it is the tally number, kn and ks are offsets in the nhsd and
+     ! shsd arrays, np is the number of extreme tallies in the shsd
+     ! array, and ns is the number of big,small tallies in array stt.
+     use mcnp_global
+     use mcnp_debug
+
+     implicit real(dknd) (a-h,o-z)
+
+     integer          :: it,kn,ks
+     integer(i4knd)  :: np,ns
+     real(dknd)      :: ar(2*ntp)
+
+     ! fill array ar with the history tally points to be sorted.
+     do j=1,ns
+       ar(j) = stt(kstt+j,it)
+     end do
+     do j=1,np
+       ar(ns+j) = shsd(ks+j,it)
+     end do

```

```

+   nh = ns+np
+   ir = nh
+   l = ir/2+1
+
+   ! perform the sort using the heapsort (nlogn) algorithm.
+40  continue
+   if( l<=1 ) go to 90
+   l = l-1
+   a = ar(l)
+50  continue
+   ii = l
+   j = l+1
+   if( j>ir ) then
+     ar(ii) = a
+     go to 40
+   elseif( j==ir ) then
+     go to 70
+   else
+     go to 60
+   endif
+60  continue
+   if( ar(j)<ar(j+1) ) j=j+1
+70  continue
+   if( a>=ar(j) ) go to 80
+   ar(ii) = ar(j)
+   ii = j
+   j = j+j
+   if( j>ir ) then
+     ar(ii) = a
+     go to 40
+   elseif( j==ir ) then
+     go to 70
+   else
+     go to 60
+   endif
+80  continue
+   j = ir+1
+   if( j>ir ) then
+     ar(ii) = a
+     go to 40
+   elseif( j==ir ) then
+     go to 70
+   else
+     go to 60
+   endif
+90  continue
+   a = ar(ir)
+   ar(ir) = ar(l)
+   ir = ir-1
+   if( ir/=1 ) go to 50
+   ar(l) = a
+
+   ! fill shsd(kshs+nsp+6,it) with the ntp largest,smallest values.
+   nt = min(ntp,nh)
+   do j=1,nt
+     shsd(ks+j,it) = ar(nh-nt+j)
+   enddo
+   nhsd(kn+1,it) = int(nt,i8knd)
+   nhsd(kn+2,it) = 0_i8knd
+   if( nt==ntp ) shsd(ks+ntp+1,it)=shsd(ks+1,it)
+   return
+ end subroutine hpsort_i4
+
+ subroutine hpsort_i8(it,kn,ks,np,ns)
+ ! sort (heapsort) the np extreme tallies into ascending order.
+ ! it is the tally number, kn and ks are offsets in the nhsd and
+ ! shsd arrays, np is the number of extreme tallies in the shsd
+ ! array, and ns is the number of big,small tallies in array stt.
+ use mcnp_global
+ use mcnp_debug
+

```

```

+   implicit real(dknd) (a-h,o-z)
+
+   integer          :: it, kn, ks
+   integer(i8knd)  :: np, ns
+   real(dknd)      :: ar(2*ntp)
+
+   ! fill array ar with the history tally points to be sorted.
+   do j=1,ns
+     ar(j) = stt(kstt+j,it)
+   end do
+   do j=1,np
+     ar(ns+j) = shsd(ks+j,it)
+   end do
+   nh = ns+np
+   ir = nh
+   l = ir/2+1
+
+   ! perform the sort using the heapsort (nlogn) algorithm.
+40  continue
+   if( l<=1 ) go to 90
+   l = l-1
+   a = ar(l)
+50  continue
+   ii = l
+   j = l+1
+   if( j>ir ) then
+     ar(ii) = a
+     go to 40
+   elseif( j==ir ) then
+     go to 70
+   else
+     go to 60
+   endif
+60  continue
+   if( ar(j)<ar(j+1) ) j=j+1
+70  continue
+   if( a>=ar(j) ) go to 80
+   ar(ii) = ar(j)
+   ii = j
+   j = j+j
+   if( j>ir ) then
+     ar(ii) = a
+     go to 40
+   elseif( j==ir ) then
+     go to 70
+   else
+     go to 60
+   endif
+80  continue
+   j = ir+1
+   if( j>ir ) then
+     ar(ii) = a
+     go to 40
+   elseif( j==ir ) then
+     go to 70
+   else
+     go to 60
+   endif
+90  continue
+   a = ar(ir)
+   ar(ir) = ar(1)
+   ir = ir-1
+   if( ir/=1 ) go to 50
+   ar(1) = a
+
+   ! fill shsd(kshs+nsp+6,it) with the ntp largest,smallest values.
+   nt = min(ntp,nh)
+   do j=1,nt
+     shsd(ks+j,it) = ar(nh-nt+j)
+   enddo
+   nhsd(kn+1,it) = int(nt,i8knd)

```

```

+   nhsd(kn+2,it) = 0_i8knd
+   if( nt==ntp ) shsd(ks+ntp+1,it)=shsd(ks+1,it)
+   return
+ end subroutine hpsort_i8
+
+end module hpsort_mod
diff -Naurd MCNP5/Source/src/hstory.F90 MCNP5_new/Source/src/hstory.F90
--- MCNP5/Source/src/hstory.F90      2003-04-30 20:11:06.000000000 -0600
+++ MCNP5_new/Source/src/hstory.F90  2004-07-22 15:14:41.000000000 -0600
@@ -8,6 +8,7 @@
! Modules:
  use smmp, only: sm_lon, sm_loff
  use mcnp_global
+ use dxtran_mod
  use mcnp_debug
  use rmc_mod
  use ral_mod
@@ -20,9 +21,9 @@

! Debug features: Set up event log. Print debug line.
krflg = 0
- if( npstc>=dbcn(3) .and. npstc<=dbcn(4) ) krflg = 1
+ if( npstc>=int(dbcn(3),i8knd) .and. npstc<=int(dbcn(4),i8knd) ) krflg = 1
if( dbcn(2)/=0. ) then
-   if( mod(npstc,int(dbcn(2)))==0 ) then
+   if( mod(npstc,int(dbcn(2),i8knd))==0 ) then
      call RN_query( first = i8_first, nps = int(nps,i8knd) )
      if( ltasks>1 .or. ntasks>1 .or. mct<0 ) then
        write(iuo,10) npstc, i8_first
@@ -82,26 +83,7 @@
if( kdb/=0 ) go to 390

! Calculate the distance to the nearest dxtran sphere, dxl.
- dxl = huge
- do i = 1,ndx(ipt)
-   if( idx/=i ) then
-     if( lev==0 ) then
-       sr = (/ xxx, yyy, zzz /)
-       sd = (/ uuu, vvv, www /)
-     else
-       sr = udt(1:3,0)
-       sd = udt(4:6,0)
-     endif
-     f = dxx(ipt,1,i)-sr(1)
-     g = dxx(ipt,2,i)-sr(2)
-     h = dxx(ipt,3,i)-sr(3)
-     q = f*sd(1)+g*sd(2)+h*sd(3)
-     c = min(max(zero,q),dxl)
-     if( (f-sd(1)*c)**2+(g-sd(2)*c)**2+(h-sd(3)*c)**2<dxx(ipt,5,i) ) then
-       dxl = min(dxl,q-sqrt(max(zero,q**2+dxx(ipt,5,i)-f**2-g**2-h**2)))
-     endif
-   endif
- enddo
+ dxl = dist_dxtran_sphere()

! Calculate the distance to time cutoff, dtc.
dtc = vel*(tco(ipt)-tme)
@@ -112,7 +94,7 @@
totm = 0.
pfp = 0.
stp = 0.
- deb = huge
+ deb = huge_float
if( mk/=0 ) then
  if( ipt==1 ) then
    call acetot(0,mk)
@@ -132,9 +114,10 @@

! Calculate the mean free path, gs, and its reciprocal, qpl.
gs = 0.
- pmf = huge

```

```

- dw = huge
+ pmf = huge_float
+ dw = huge_float
  qpl = (totm+pfp)*rh
+
  if( ipt==1 ) qpl = qpl + abs(ra_qpl())
  ple = qpl
  if( ple/=0. ) then
@@ -157,7 +140,7 @@
    call forcol
    if( kdb/=0 ) go to 390
    if( nter/=0 ) go to 260
-   dw = huge
+   dw = huge_float
  endif
  endif
  endif
@@ -262,6 +245,7 @@
  udt(1:3,1) = udt(1:3,1)+udt(4:6,1)*d
  enddo

+
! Special treatment for multigroup electrons.
if( stp/=0. ) then
  t1 = d*stp
@@ -487,7 +471,7 @@
  rh = rho(icl)
  mk = mat(icl)
  totm = 0.
-  deb = huge
+  deb = huge_float
  if( mk/=0 ) then
    if( ipt==1 ) then
      call acetot(0,mk)
@@ -495,8 +479,8 @@
      call photot(mk)
    endif
  endif
-  pmf = huge
-  dw = huge
+  pmf = huge_float
+  dw = huge_float
  qpl = totm*rh
  if( ipt==1 ) qpl = qpl + abs(ra_qpl())
  ple = qpl
diff -Naurd MCNP5/Source/src/igeom.F90 MCNP5_new/Source/src/igeom.F90
--- MCNP5/Source/src/igeom.F90 2003-04-30 20:11:06.000000000 -0600
+++ MCNP5_new/Source/src/igeom.F90 2004-07-22 15:14:41.000000000 -0600
@@ -6,6 +6,7 @@
  use mcnp_global
  use mcnp_debug
  use mcnp_input
+ use erprnt_mod

  implicit real(dknd) (a-h,o-z)

diff -Naurd MCNP5/Source/src/imcn.F90 MCNP5_new/Source/src/imcn.F90
--- MCNP5/Source/src/imcn.F90 2003-04-30 20:11:08.000000000 -0600
+++ MCNP5_new/Source/src/imcn.F90 2004-07-22 15:14:41.000000000 -0600
@@ -14,6 +14,10 @@
  use fmesh_mod, only: nmesh, fmesh_initialize

  implicit real(dknd) (a-h,o-z)
+
+ integer :: i, ip, it, iu, j, k, la, m, mt, n, ne, nl, nn
+ integer(i8knd) :: n_i8knd
+
  character(len=8) :: hs
  real(dknd), parameter :: eb(16) = &
    & (/ 20.d0, 15.d0, 10.d0, 9.d0, 8.d0, 7.d0, 6.d0, 5.d0, &
@@ -141,26 +145,26 @@

```

```

! Initialize general common not yet done.
- ddg( 1:2, 1:mxdt ) = huge
- ddx( 1:mipt, 1:2, 1:mxdx ) = huge
+ ddg( 1:2, 1:mxdt ) = huge_float
+ ddx( 1:mipt, 1:2, 1:mxdx ) = huge_float
dbcn(10) = dftint
dmp      = dfdmp
dnb      = -1.
ecf(2)   = .001d0
efac     = sqrt(sqrt(sqrt(.5+zero)))
emcf( 2:mipt) = 100.
- emx(1)  = huge
- emx(2)  = huge
+ emx(1)  = huge_float
+ emx(2)  = huge_float
ikz      = 30
kct      = -1
ivdd     = (/ (i,i = 1,maxv) /)
lost(1)  = 10
lost(2)  = 10
- npd     = 1000
+ npd     = 1000_i8knd
ntc      = 50
ntc1     = 50
rkk      = 1.
- tco( 1:mipt ) = .001d0*huge
+ tco( 1:mipt ) = .001d0*huge_float
bnum     = 1.
xnum     = 1.
rnok     = 1.
@@ -168,10 +172,10 @@
wcl(1)   = -.50d0
wc2(1)   = -.25d0
if( kpt(2)/=0 ) then
-   wcl(2) = huge
-   wc2(2) = huge
+   wcl(2) = huge_float
+   wc2(2) = huge_float
endif
- wgts(1) = huge
+ wgts(1) = huge_float
if( wwp(1,4)>0. ) wcl(1) = 0.
if( wwp(1,4)>0. ) wc2(1) = 0.
if( wwp(2,4)>0. ) wcl(2) = 0.
@@ -181,7 +185,7 @@
! Initialize dynamically allocated common.
jasw = 0
do j = 1,mipt
-   if( ndx(j)/=0 ) dxcp( :, j, : ) = huge
+   if( ndx(j)/=0 ) dxcp( :, j, : ) = huge_float
   if( ngww(j)/=0 ) ewwg( ngww(j)+mgww(j) ) = 100.
enddo
if( kpt(1)*kpt(2)/=0 ) gwt(:) = -1.
@@ -196,11 +200,11 @@
lxd( 2, 1:nmat1 ) = ichar('')+256*(ichar('')+256*ichar('p'))
lxd( 3, 1:nmat1 ) = ichar('')+256*(ichar('')+256*ichar('e'))
lxd( 4, 1:nmat1 ) = ichar('')+256*(ichar('')+256*ichar('u'))
- pnt( 1:nmat1 ) = huge
+ pnt( 1:nmat1 ) = huge_float
trf(5, 0) = 1.
trf(9, 0) = 1.
trf(13,0) = 1.
- trf(5:13, 1: ) = huge
+ trf(5:13, 1: ) = huge_float
tmp(:) = 253.d-10

@@ -453,7 +457,7 @@
endif

```



```

allocate( gbnk( 1:mbnk*mtasks ) )
- allocate( ibnk( 1:(nbmx*(lpblcm+2*abs(iunr))+1)*mtasks ) )
+ allocate( ibnk( 0:(nbmx*(lpblcm+2*abs(iunr))+1)*mtasks ) )
allocate( tal( 1:(nmxf*mx+ktls)*mt ) )
gbnk = 0.0
ibnk = 0
@@ -482,9 +486,9 @@
wcs2(1) = max( wc2(1), -wc2(1)*swtm )
if( kf8==3 ) wcl(2) = 0.
do i = 2,mipt
- if( wcl(i)==huge .and. kpt(1)/=0 ) wcl(i) = wcl(1)
- if( wcl(i)==huge .and. kpt(1)==0 ) wcl(i) = -.5d0
- if( wc2(i)==huge ) wc2(i) = .5*wcl(i)
+ if( wcl(i)==huge_float .and. kpt(1)/=0 ) wcl(i) = wcl(1)
+ if( wcl(i)==huge_float .and. kpt(1)==0 ) wcl(i) = -.5d0
+ if( wc2(i)==huge_float ) wc2(i) = .5*wcl(i)
wcs1(i) = max(wcl(i),-wcl(i)*swtm)
wcs2(i) = max(wc2(i),-wc2(i)*swtm)
enddo
@@ -557,9 +561,9 @@
& new_count_max_nps = int(nrn(3), i8knd )

if( nde/=0 ) dbcn(2) = nde
- if( nsr==6 .and. nrrs>=nrss .and. npp>=0 ) &
+ if( nsr==6 .and. nrrs>=nrss .and. npp>=0_i8knd ) &
& call expire(0,'imcn', 'no more tracks on '//rssa//' file.')
- if( (nfer==0 .or. lfat1/=0) .and. jovr(4)/=0 .and. npp>=0 ) then
+ if( (nfer==0 .or. lfat1/=0) .and. jovr(4)/=0 .and. npp>=0_i8knd ) then
call tpefil(6)
endif

@@ -567,14 +571,14 @@
! Set npc(nn) to zero if tfc nps entry was not scheduled.
nn = 0
do i = 1,20
- if( npc(i)/=0) nn = i
+ if( npc(i)/=0_i8knd) nn = i
enddo
if( nn/=1 ) then
- n = npd
- if( nn==20 ) n = npd/2
- if( npc(nn)/=npc(nn-1)+n ) npc(nn) = 0
+ n_i8knd = npd
+ if( nn==20 ) n_i8knd = npd/2
+ if( npc(nn)/=npc(nn-1)+n_i8knd ) npc(nn) = 0_i8knd
else
- if( npc(1)/=npd ) npc(1) = 0
+ if( npc(1)/=npd ) npc(1) = 0_i8knd
endif
endif

diff -Naurd MCNP5/Source/src/inpert.F90 MCNP5_new/Source/src/inpert.F90
--- MCNP5/Source/src/inpert.F90 2003-04-30 20:11:08.000000000 -0600
+++ MCNP5_new/Source/src/inpert.F90 2004-07-22 15:14:41.000000000 -0600
@@ -8,6 +8,7 @@
use mcnp_global
use mcnp_debug
use mcnp_input
+ use erprnt_mod

implicit real(dknd) (a-h,o-z)

diff -Naurd MCNP5/Source/src/ipbc.F90 MCNP5_new/Source/src/ipbc.F90
--- MCNP5/Source/src/ipbc.F90 2003-04-30 20:11:10.000000000 -0600
+++ MCNP5_new/Source/src/ipbc.F90 2004-07-22 15:14:41.000000000 -0600
@@ -7,6 +7,7 @@
use mcnp_global
use mcnp_debug
use mcnp_input
+ use erprnt_mod

```

```

implicit real(dknd) (a-h,o-z)

! set up trf and ksu array pointers.
@@ -60,8 +61,8 @@
if( jd==1 ) go to 360

! check reciprocity.
- db = huge
- dt = -huge
+ db = huge_float
+ dt = -huge_float
do j1 = 1,mxj
  if( kst(j1)>4 .or. ksu(j1)==-3 ) cycle
  if( ksu(j1)>0 ) then
@@ -110,14 +111,14 @@
! tpp(i+3) in perimeter direction trf(7+i,k).
n = 1
do m = mx,mxtr
- trf(3,m) = huge
+ trf(3,m) = huge_float
t = dot_product(trf(5:7,m),trf(8:10,k))
if( abs(t)>=1.e-6 ) then
  trf(3,m) = (trf(4,m)-dot_product(trf(5:7,m),tpp(4:6)))/t
endif
if( trf(3,m)<trf(3,n) ) n = m
enddo
- if( trf(3,n)==huge ) then
+ if( trf(3,n)==huge_float ) then
  call erprnt(1,1,0,0,0,0,0,0,&
    & ' "not all periodic boundaries specified."')
endif
@@ -126,14 +127,14 @@
! gpblcm(i) is the center of each facet.
! check inward/outward jsu surface normal, gpblcm(3+i).
! set trf(2,k) = +1/-1 for jsu normal in/out of cell.
- d2 = huge
+ d2 = huge_float
do
  d1 = trf(3,n)
- trf(3,n) = huge
+ trf(3,n) = huge_float
do m = mx,mxtr
  if( trf(3,m)<trf(3,n) ) n = m
enddo
- if( trf(3,n)==huge ) exit
+ if( trf(3,n)==huge_float ) exit

dx = .5*(d1+trf(3,n))
do i = 1,3
@@ -176,7 +177,7 @@
if( fim(1,i1)==0. .and. fim(1,i2)/=0. ) iz = -1.
if( iz==0 ) cycle

- if( d2==huge ) d2 = d1
+ if( d2==huge_float ) d2 = d1
d3 = trf(3,n)
trf(2,k) = iz
jz = max(-iz*i1,iz*i2)
@@ -188,7 +189,7 @@
& ' "zero-importance cell",i5, " cannot have fill."')
endif
enddo
- if( d2==huge ) then
+ if( d2==huge_float ) then
  call erprnt(1,1,1,nsf(jsu),0,0,0,0,&
    & ' "periodic surface",i5, " must bound zero-importance cell."')
endif
diff -Naurd MCNP5/Source/src/isourc.F90 MCNP5_new/Source/src/isourc.F90
--- MCNP5/Source/src/isourc.F90 2003-04-30 20:11:12.000000000 -0600
+++ MCNP5_new/Source/src/isourc.F90 2004-07-22 15:14:41.000000000 -0600
@@ -9,15 +9,13 @@

```

```

        use mcnp_debug
        use mcnp_input
        use critl_mod
+   use qttyin_mod, only:qTTYin

        implicit real(dknd) (a-h,o-z)
        character(len=80) :: hq
        character(len=9)  :: hf
        character(len=8)  :: hp(miPT)

-#ifdef PCDOs
-   if(lockl) call pTTYin
-#endif /*def.pcdos*/
        if( irup/=0 ) then
            call qTTYin(0,' "isourc source processing."')
        endif
diff -NaurD MCNP5/Source/src/issrc.F90 MCNP5_new/Source/src/issrc.F90
--- MCNP5/Source/src/issrc.F90      2003-04-30 20:11:12.000000000 -0600
+++ MCNP5_new/Source/src/issrc.F90  2004-07-22 15:14:41.000000000 -0600
@@ -7,11 +7,13 @@
        use mcnp_global
        use mcnp_debug
        use mcnp_input
+   use erprnt_mod

        implicit real(dknd) (a-h,o-z)
        character(len=80) :: hq
        character(len=9)  :: hf
        character(len=8)  :: hp(miPT)
+   integer(i8knd)      :: n_i8knd

        ! replace problem names of surfaces by program names.
        nx = 1
@@ -82,9 +84,9 @@

        ! write summary totals.
        write(iuo,80) np1,nrss,niss
-80 format( " the original number of histories was",i10,&
-   & " the total number of tracks recorded was",i10,&
-   & " from",i10, " independent histories.")
+80 format( " the original number of histories was",i12,&
+   & " the total number of tracks recorded was",i12,&
+   & " from",i12, " independent histories.")

        ! print surface information.
        if( ink(10)/=0 .and. njsw/=0 ) write(iuo,90)
@@ -132,19 +134,19 @@
        ! read information for the first track into the ssb array.
        read(iusr,end=320) (ssb(i),i=1,nrcd)
        nqss = dbcn(8)
-   do n=1,nqss-1
+   do n_i8knd=1,nqss-1_i8knd
            a = ssb(1)
            do
                read(iusr,end=320) (ssb(i),i=1,nrcd)
-               nrrs = nrrs+1
+               nrrs = nrrs+1_i8knd
            if( ssb(1)/=a ) exit
            enddo
        end do

        ! set up defaulted arrays.
        snit = 1.
-   if( npp>0 .and. npp/=np1 ) snit=npp/(np1+zero)
-   npp = 0
+   if( npp>0_i8knd .and. npp/=np1 ) snit=real(npp,dknd)/real(np1,dknd)
+   npp = 0_i8knd
        if( jasr(1,1)==0 ) then
            do j=1,njsr(1)+nilr(1)
                jasr(2,j) = 0
diff -NaurD MCNP5/Source/src/italy.F90 MCNP5_new/Source/src/italy.F90

```

```

--- MCNP5/Source/src/italy.F90      2003-04-30 20:11:12.000000000 -0600
+++ MCNP5_new/Source/src/italy.F90  2004-07-22 15:14:41.000000000 -0600
@@ -16,6 +16,7 @@
    use mcnp_debug
    use mcnp_input
    use fmesh_mod,  only:  nmesh
+   use erprnt_mod

    implicit real(dknd) (a-h,o-z)
    character(len=1) :: h
@@ -58,7 +59,7 @@

    ! set ddm(1,ital)=-huge for tallies that are all negative.
    do i = 0,npert
-     ddm(1,ital+i*ntal) = -huge
+     ddm(1,ital+i*ntal) = -huge_float
    enddo

    ! set up the default bin counts.
@@ -693,7 +694,7 @@
    tds(ld+16) = rtp(j+8)
    if( tds(ld+15)==0. .and. jptal(8,ital)>3 ) then
        if( jptal(8,ital)==4 ) then
-         tds(ld+15) = huge
+         tds(ld+15) = huge_float
        else
            call erprnt(1,1,1,kl,0,0,0,0,"cylindrical grid radius is zero for
tally",i4')
        endif
@@ -1191,13 +1192,13 @@

    ! process c, e, and t data:  cosine, energy, and time bins
    700 continue
-   tc = -huge
+   tc = -huge_float
    do i = 1,mipt
        if( ktp(i,ital)/=0 ) tc = max(tc,tco(i))
    enddo
    DO_820: do iw = 1,3
        n6 = 0
-       tn = huge
+       tn = huge_float
        if( iw==2 .and. ktp(1,ntal)/=0 .and. img==0 ) tn = emx(1)
        if( iw==3 .and. iy/=5 ) tn = tc
        if( iy==5 .and. iw==1 ) cycle DO_820
@@ -1233,7 +1234,7 @@
    n = i
    750 continue
    if( iw==2 .and. np/=3 ) then
-     b = -huge
+     b = -huge_float
    do i = 1,mipt
        if( ktp(i,ital)/=0 ) b = max(b,ecf(i))
    enddo
@@ -1368,13 +1369,13 @@
    if( ipnt(2,21,0)>=2 ) d2 = rtp(ipnt(1,21,0)+1)
    do ip = 1,mipt
        do i = 1,mxdx
-         if( ddx(ip,1,i)==huge ) ddx(ip,1,i) = d1
-         if( ddx(ip,2,i)==huge ) ddx(ip,2,i) = d2
+         if( ddx(ip,1,i)==huge_float ) ddx(ip,1,i) = d1
+         if( ddx(ip,2,i)==huge_float ) ddx(ip,2,i) = d2
        enddo
    enddo
    do i = 1,ndtt
-     if( ddg(1,i)==huge ) ddg(1,i) = d1
-     if( ddg(2,i)==huge ) ddg(2,i) = d2
+     if( ddg(1,i)==huge_float ) ddg(1,i) = d1
+     if( ddg(2,i)==huge_float ) ddg(2,i) = d2
    enddo

```

```

! set up the tally locators.
diff -Naurd MCNP5/Source/src/italpr.F90 MCNP5_new/Source/src/italpr.F90
--- MCNP5/Source/src/italpr.F90      2003-04-30 20:11:14.000000000 -0600
+++ MCNP5_new/Source/src/italpr.F90  2004-07-22 15:14:41.000000000 -0600
@@ -328,7 +328,7 @@
    l = iptal(iw+5,1,ital)
    hf = ' -i'
    if( iw==1 ) write(hf,'(lpe13.5)') -1.
-   a = huge
+   a = huge_float
    do i=1,mipt
        if( ktp(i,ital)/=0 ) a=min(a,ecf(i))
    end do
diff -Naurd MCNP5/Source/src/items.F90 MCNP5_new/Source/src/items.F90
--- MCNP5/Source/src/items.F90      2003-04-30 20:11:14.000000000 -0600
+++ MCNP5_new/Source/src/items.F90  2004-07-22 15:14:41.000000000 -0600
@@ -6,19 +6,22 @@
    use mcnp_global
    use mcnp_debug
    use mcnp_input
+   use erprnt_mod, only: erprnt

    implicit real(dknd) (a-h,o-z)

    character(len=25) :: hh
    character(len=16) :: hs
-
+   integer(i8knd)    :: i8, i1
+   integer           :: ii
+
! special treatment for pure text data cards.
if( ich=='fc' .or. ich=='sc' .or. ich=='mplot' ) then
    if( mm==1 ) call nxttitl
    if( mm==2 ) call nexttit
    return
endif
-
+
! read the next item and determine its type.
! ki: 0=character 1=real 2=integer
irc = max(1,irc)
@@ -31,28 +34,50 @@
    if( irc==1 ) return
    ki = kdata(klin(it:iu))
    ii = 0
-   ri = 0.
-   if( ki/=0 ) then
+   i8 = 0_i8knd
+   ri = zero
+   if( ki/=0 ) then ! Numeric item.
        hh = ' '
        hh(25-iu+it:25) = klin(it:iu)
-       if( iu-it > 8 ) ki = 1
-       if( ki==2 ) then
-           read(hh,'(i25)') ii
-           ri = ii
+
+       ! Integers that are too long must be read as reals.
+       if ( ki == 2 ) then
+           if ( klin(it:it) == '+' .or. klin(it:it) == '-' ) then
+               if ( (iu-it) > 19 ) ki = 1
+           else
+               if ( (iu-it) > 18 ) ki = 1
+           endif
+       endif
+
+       if( ki==2 ) then ! Item read is integer
+           read(hh,'(i25)') i8
+           if (abs(i8) <= int(huge(ii),i8knd)) then
+               ii = int(i8) ! ii may be I4 or I8 depending on platform
+           else

```

```

+         ii = -huge(ii)          ! overflow on I4
+     endif
+     ri = real(i8,dknd)
+ else
+     read(hh,'(e25.0)') ri
-     if( abs(ri) <= 2147483647. ) ii=nint(ri)
-     if( ri==0. ) ki=2
-     if( ii/=0 ) then
-         if( abs(ri-anint(ri)) <= 5e-14*abs(ri) ) then
-             ri = ii
+         if( abs(ri) <= real(i8limit,dknd) ) i8=nint(ri,i8knd)
+         if( abs(ri) <= real(huge(ii),dknd) ) then
+             ii=int(ri)          ! ii may be I4 or I8 depending on platform
+         else
+             ii = 0              ! overflow on I4, leave as 0 and not -huge(ii)
+         endif
+         if( ri==zero ) ki=2
+         if( i8/=0_i8knd ) then
+             if( abs(ri-anint(ri)) <= 5e-14_dknd*abs(ri) ) then
+                 ri = i8
+                 ki = 2
+             endif
+         endif
+     endif
+ endif
-
+     if( i8 > int(i4limit,i8knd) ) int_large_input = 1
+
+     ! store nii interpolated values before the current item.
+     ! interpolation scheme does not apply to I8
+     if( nii>0 ) then
+         if( ki==0 ) go to 150
+         dl = (ri-ritm)/(nii+1)
@@ -69,7 +94,7 @@
+         end do
+         go to 130
+     endif
-
+
+     ! look for a special r, i, m, or j item.
+     if( ki/=0 ) go to 130
+     ks = index('rimj',klin(iu:iu))
@@ -87,32 +112,32 @@
+     select case( ks )
+     case(1) ! >>>> r: repeat previous item n times.
-         if( nwc==0 .or. nii/=0 ) go to 150
+         do i=1,n
+         do i=1,n
+             if( mm==1 ) call nxttit1
+             if( mm==2 ) call nexttit
+             if( ics<0 ) return
+         end do
+         cycle
-
+
+     case(2) ! >>>> i: set up to store n interpolated values next time.
+         if( nwc==0 .or. nii/=0 .or. kitm==0 ) go to 150
+         hs = klin(it:iu)
+         nii = n
+         cycle
-
+
+     case(3) ! >>>> m: store an item h times the value of the previous item.
+         if( nwc==0 .or. nii/=0 .or. kitm==0 .or. iu==it ) go to 150
+         ritm = h*ritm
+         iitm = n*iitm
+         go to 140
-
+
+     case(4) ! >>>> j: skip n storage spaces.
+         if( krq(4,ica)==0 ) go to 150

```

```

        nwc = nwc+n
        nii = -1
        cycle
    end select
-
+
    ! set up the current item and store it.
    130 continue
        kitm = ki
@@ -120,13 +145,14 @@
        nitm = iu-it+1
        ritm = ri
        iitm = ii
+   i8itm = i8
        nii = 0
    140 continue
        if( mm==1 ) call nxitl
        if( mm==2 ) call nextit
        if( ics<0 ) return
    enddo
-
+
    150 continue
        ics = -1
        if( mm==1 ) return
diff -Naurd MCNP5/Source/src/iwtwnd.F90 MCNP5_new/Source/src/iwtwnd.F90
--- MCNP5/Source/src/iwtwnd.F90      2003-04-30 20:11:14.000000000 -0600
+++ MCNP5_new/Source/src/iwtwnd.F90  2004-07-22 15:14:41.000000000 -0600
@@ -6,6 +6,7 @@
    use mcnp_global
    use mcnp_debug
    use mcnp_input
+   use erprnt_mod

    implicit real(dknd) (a-h,o-z)

@@ -46,7 +47,7 @@
    ! check input importances and weight-windows.
    a = 0.
    b = 0.
-   c = huge
+   c = huge_float
    do i=1, mxa
        a = max(a, fim(ip,i))
        if( fim(ip,i)/=0. ) c=min(c, fim(ip,i))
diff -Naurd MCNP5/Source/src/ixsdir.F90 MCNP5_new/Source/src/ixsdir.F90
--- MCNP5/Source/src/ixsdir.F90      2003-04-30 20:11:16.000000000 -0600
+++ MCNP5_new/Source/src/ixsdir.F90  2004-07-22 15:14:41.000000000 -0600
@@ -9,6 +9,8 @@
    use mcnp_global
    use mcnp_debug
    use mcnp_input
+   use qttyin_mod, only: qttyin
+   use erprnt_mod, only: erprnt

    implicit real(dknd) (a-h,o-z)
    character(len=1)  :: ha
@@ -81,18 +83,10 @@
    hl = xsdir
    inquire( file=hl, exist=file_exists )
    if( .not.file_exists ) then
-#ifndef PCDOS
-   if( len_trim(hdpath) > 0 ) hl=hdpath(1:len_trim(hdpath))//'\ '//xsdir
-#else
    if( len_trim(hdpath) > 0 ) hl=hdpath(1:len_trim(hdpath))//'\ '//xsdir
-#endif
        inquire( file=hl, exist=file_exists )
        if( .not.file_exists ) then
-#ifndef PCDOS
-   if( len_trim(hdpth) > 0 ) hl=hdpth(1:len_trim(hdpth))//'\ '//xsdir
-#else

```

```

        if(len_trim(hdpth) > 0 ) hl=hdpth(1:len_trim(hdpth))//'/ '//xmdir
-#endif
        inquire( file=hl, exist=file_exists )
        if( .not.file_exists ) then
            write(jtty,'( " searched directories:"/a80/a80)')hdpth,hdpth
@@ -197,9 +191,6 @@
        240 continue
            hz = hl(1:10)
            ha = hz(10:10)
-#ifndef PCDOS
- if( lockl) call ptttyin
-#endif /*def.pcdos*/
        if( irup/=0 ) call qtttyin(0,"reading xmdir '//hz//'")

        ! look for a match with the directory file entry.
diff -Naurd MCNP5/Source/src/jdecod.F90 MCNP5_new/Source/src/jdecod.F90
--- MCNP5/Source/src/jdecod.F90      2003-04-30 20:11:16.000000000 -0600
+++ MCNP5_new/Source/src/jdecod.F90  2004-07-22 15:14:41.000000000 -0600
@@ -14,6 +14,7 @@
        use mcnp_plot
        use gxsub
        use mcplot_module
+ use qtttyin_mod, only: qtttyin

        implicit real(dknd) (a-h,o-z)

diff -Naurd MCNP5/Source/src/jsourc.F90 MCNP5_new/Source/src/jsourc.F90
--- MCNP5/Source/src/jsourc.F90      2003-04-30 20:11:18.000000000 -0600
+++ MCNP5_new/Source/src/jsourc.F90  2004-07-22 15:14:41.000000000 -0600
@@ -9,6 +9,7 @@
        use mcnp_global
        use mcnp_debug
        use mcnp_input
+ use erprnt_mod

        implicit real(dknd) (a-h,o-z)
        character ht*12
diff -Naurd MCNP5/Source/src/keypro.F90 MCNP5_new/Source/src/keypro.F90
--- MCNP5/Source/src/keypro.F90      2003-04-30 20:11:20.000000000 -0600
+++ MCNP5_new/Source/src/keypro.F90  1969-12-31 17:00:00.000000000 -0700
@@ -1,44 +0,0 @@
-!+ $Id: keypro.F90,v 1.3 2002/12/03 19:23:42 ljc Ex $
-! Copyright LANL/UC/DOE - see file COPYRIGHT_INFO
-
-#ifndef QWIN
-function keypro(nc,mp,lp)
- use mcnp_debug
- integer*4 keypro
- ! allow processing of keyboard input for interrupts.
- !DEC$ ATTRIBUTES STDCALL, ALIAS: '_keypro@12' :: keypro
- use dfwin
- use dflib
- keypro=0
- !
- ! check mp for character code 67 (letter c).
- ! check if cntl key was depressed (16th bit nonzero).
- ! only send signal when key is released (lp 32nd bit nonzero).
- if(nc >= 0.and.mp == 67.and.getkeystate(vk_control) < 0)then
- if(lp < 0)i=raiseqq(sig$int)
- keypro=1
- end if
- return
-end function keypro
-function initialsettings()
- logical*4 initialsettings
- ! initialize the frame window and set its parameters.
- ! this function is called before main execution.
- use dfwin
- use dflib
- external keypro
- !DEC$ ATTRIBUTES STDCALL, ALIAS: '_keypro@12' :: keypro

```



```

- type (qwinfo) wi
- k=setexitqq(qwin$exitpersist)
- !
- ! enable keyboard interrupts on the main execute thread.
- k=setwindowshookex(wh_keyboard,loc(keypro),0,&
- & getcurrentthreadid())
- !
- ! set the frame window to its maximum size.
- k=getwsizqq(qwin$framewindow,qwin$sizemax,wi)
- k=setwsizqq(qwin$framewindow,wi)
- initialsettings=.true.
- return
-end function initialsettings
-#endif /*def.qwin*/
diff -Naurd MCNP5/Source/src/main.F90 MCNP5_new/Source/src/main.F90
--- MCNP5/Source/src/main.F90 2003-04-30 20:11:26.000000000 -0600
+++ MCNP5_new/Source/src/main.F90 2004-07-22 15:14:41.000000000 -0600
@@ -45,10 +45,6 @@
! Modules used:
use lx5_mod
use dmmp, only: dm_enrl, dm_term, dm_bcast, dm_ntasks
-#ifdef QWIN
- use dflib,only: setactiveqq, getwindowconfig, setwindowconfig, &
- & windowconfig, setexitqq, qwin$exitpersist
-#endif
use mcnp_global
use mcnp_debug
use gxsub, only : gxquit
@@ -62,12 +58,11 @@

character(len=18) :: hn = '
character(len=80) :: hp
-#ifdef QWIN
- logical*4 st
- type (windowconfig) wc
-#endif
! -----

+ ! Nullify pointer in mcnp_global
+ call mcnp_global_nullify
+
! Initialize cpu clock.
call secnd(tq)

@@ -84,14 +79,6 @@
! set up terminal & graphics
itty = 5
jtty = 6
-#ifdef QWIN
- ! Change the execute window title (unit 0).
- k = setactiveqq(0)
- st = getwindowconfig(wc)
- wc.title="MCNP Execute Window"C
- st = setwindowconfig(wc)
- k = setexitqq(qwin$exitpersist)
-#endif

! Check for conversion of source code to upper case.
! One "A" must be upper case.
@@ -106,28 +93,35 @@

! Initialize module data.
gfixcm(1:nfixcm) = 0. ! call fix_init
+ i8fixcm(1:l8fixcm) = 0_i8knd
jfixcm(1:lfixcm) = 0
- i8fixcm(1:l8fixcm) = 0
-
- gvarcm(1:nvarcm) = 0. ! call var_init
- avarcm(1:l3) = 0.
- jvarcm(1:lvarcm) = 0
+

```

```

+ gvarcm(1:nvarcm) = 0.      ! call var_init
+ i8varcm(1:i8varcm) = 0_i8knd
+ avarcm(1:13) = 0.
+ jvarcm(1:lvarcm) = 0

- gephcm(1:nephcm) = 0.      ! call eph_init
- jephcm(1:lephcm) = 0
+ gephcm(1:nephcm) = 0.      ! call eph_init
+ i8ephcm(1:i8ephcm) = 0_i8knd
+ jephcm(1:lephcm) = 0
  lockl = .false.

- gtskcm(1:ntskcm) = 0.      ! call tsk_init
- jtskcm(1:ltskcm) = 0
- ktskpt(1:ltskpt) = 0
+ gtskcm(1:ntskcm) = 0.      ! call tsk_init
+ i8tskcm(1:i8tskcm) = 0_i8knd
+ jtskcm(1:ltskcm) = 0
+ ktskpt(1:ltskpt) = 0

  gpblcm(1:npblcm) = 0.      ! call pbl_init
  jpblcm(1:lpblcm) = 0
  gpb9cm(1:mpb,1:npblcm) = 0.
  jpb9cm(1:mpb,1:lpblcm) = 0

+ ! Initialize specific variables in fixcom to correct default.
+ flag_speed_tally_used=-1
+
+
+   iterm = 3
-#ifndef GKSSIM
+#if !defined(PLOT) && !defined(MCPLOT)
  #ifdef AIX
    iterm = 1
  #endif
@@ -172,6 +166,7 @@
  ntasks = max(1,ntasks)      ! threads
  ktask = 0                   ! threads

+
+ ! Set up default values for unspecified file names.
  do i = 1,ndef
    if( isub(i)==' ' .and. iname/' ' .and. i<=10 ) then
diff  -Naurd MCNP5/Source/src/mapmaz.F90 MCNP5_new/Source/src/mapmaz.F90
--- MCNP5/Source/src/mapmaz.F90      2003-04-30 20:11:26.000000000 -0600
+++ MCNP5_new/Source/src/mapmaz.F90  2004-07-22 15:14:41.000000000 -0600
@@ -8,6 +8,9 @@

    use mcnp_global
    use mcnp_debug
+   use qttyin_mod, only: qttyin
+   use erprnt_mod, only: erprnt
+
+
  implicit real(dknd) (a-h,o-z)

@@ -91,9 +94,6 @@
  130 continue
    if( ie(lv)<ne(lv) ) go to 70
    kp = (100*mz)/nmaz
-#ifdef PCDOS
-  if( lockl ) call ptttyin
-#endif /*def.pcdos*/
    if( irup/=0 ) call qttyin(kp, ' "print table 128.",i7, "%"')
    lv = lv-1
    if( lv>=0 ) go to 130
diff  -Naurd MCNP5/Source/src/mbody.F90 MCNP5_new/Source/src/mbody.F90
--- MCNP5/Source/src/mbody.F90      2003-04-30 20:11:26.000000000 -0600
+++ MCNP5_new/Source/src/mbody.F90   2004-07-22 15:14:42.000000000 -0600
@@ -8,6 +8,7 @@
    use mcnp_global

```

```

    use mcnp_debug
    use mcnp_input
+   use erprnt_mod

    implicit real(dknd) (a-h,o-z)

diff -Naurd MCNP5/Source/src/mbodyo.F90 MCNP5_new/Source/src/mbodyo.F90
--- MCNP5/Source/src/mbodyo.F90      2003-04-30 20:11:28.000000000 -0600
+++ MCNP5_new/Source/src/mbodyo.F90   2004-07-22 15:14:42.000000000 -0600
@@ -8,6 +8,7 @@

    use mcnp_debug
    use mcnp_params, only: dknd
+   use erprnt_mod
    implicit real(dknd) (a-h,o-z)

    real(dknd) :: sc(33)
diff -Naurd MCNP5/Source/src/mbodyr.F90 MCNP5_new/Source/src/mbodyr.F90
--- MCNP5/Source/src/mbodyr.F90      2003-04-30 20:11:28.000000000 -0600
+++ MCNP5_new/Source/src/mbodyr.F90   2004-07-22 15:14:42.000000000 -0600
@@ -6,6 +6,7 @@

    use mcnp_debug
    use mcnp_params, only: dknd
+   use erprnt_mod
    implicit real(dknd) (a-h,o-z)

    real(dknd) :: sc(33)
diff -Naurd MCNP5/Source/src/mbodys.F90 MCNP5_new/Source/src/mbodys.F90
--- MCNP5/Source/src/mbodys.F90      2003-04-30 20:11:30.000000000 -0600
+++ MCNP5_new/Source/src/mbodys.F90   2004-07-22 15:14:42.000000000 -0600
@@ -7,6 +7,7 @@

    use mcnp_debug
    use mcnp_params, only: dknd
+   use erprnt_mod
    implicit real(dknd) (a-h,o-z)

    real(dknd) :: sc(33)
diff -Naurd MCNP5/Source/src/mc.c MCNP5_new/Source/src/mc.c
--- MCNP5/Source/src/mc.c      2003-04-30 20:11:30.000000000 -0600
+++ MCNP5_new/Source/src/mc.c  2004-07-22 15:14:42.000000000 -0600
@@ -8,7 +8,7 @@
#include <time.h>
#include <sys/stat.h>
#else
-#if defined(DEC) || defined(PCDOS)
+#if defined(DEC)
#include <stdlib.h>
#endif
@@ -105,28 +105,6 @@
#define XGQCF __stdcall XGQCF
#define XLNWID __stdcall XLNWID
#endif
-#ifndef PCDOS
-/* Lower case with appended underscore */
-#define XGOPWK xgopwk_
-#define XGCLWK xgclwk_
-#define XGACWK xgacwk_
-#define XGDawk xgdawk_
-#define XGCLRW xgclrw_
-#define XGUWK xguwk_
-#define XGPL xgpl_
-#define XGTX xgtx_
-#define XGSCHH xgschh_
-#define XGSCHU xgschu_
-#define XGSWN xgswn_
-#define XGSWK xgswk_
-#define XGRQLC xgrqlc_
-#define XGINST xginst_

```

```

-#define XGRQST xgrqst_
-#define XGFA xgfa_
-#define XGSPLC xgsplc_
-#define XGQCF xgqcf_
-#define XLNWID xlnwid_
-#endif
-#endif
/* Define character type from Fortran if not previously defined */
#ifdef CDEF
diff -Naurd MCNP5/Source/src/mcnp_data.F90 MCNP5_new/Source/src/mcnp_data.F90
--- MCNP5/Source/src/mcnp_data.F90 2003-04-30 20:11:30.000000000 -0600
+++ MCNP5_new/Source/src/mcnp_data.F90 2004-07-22 15:14:42.000000000 -0600
@@ -148,21 +148,21 @@
& 'kz ', 'sq ', 'gq ', 'tx ', 'ty ', 'tz ', 'x ', 'y ', 'z ', 'box', &
& 'rpp', 'sph', 'rcc', 'rec', 'ell', 'trc', 'wed', 'arb', 'rhp' /)

- character(len=58) :: rfq(15) = & != Partial formats for termination messages.
- & (/ " seconds before job time limit." ' , &
- & ' "when particle histories were done." ' , &
- & ' "because particles got lost." ' , &
- & ' "by tty interrupt." ' , &
- & ' "when it had used minutes of computer time." ' , &
- & ' "by sense switch 1." ' , &
- & ' "when kcode cycles were done." ' , &
- & ' "when events were written to the ptrac file." ' , &
- & ' "because of bad trouble." ' , &
- & ' "at end of surface-source input file." ' , &
- & ' "because of fatal errors." ' , &
- & ' ' , &
- & ' ' , &
- & ' ' , &
- & ' ' /)
+ character(len=60) :: rfq(15) = & != Partial formats for termination messages.
+ & (/ " seconds before job time limit." ' , &
+ & ' "when particle histories were done." ' , &
+ & ' "because particles got lost." ' , &
+ & ' "by tty interrupt." ' , &
+ & ' "when it had used minutes of computer time." ' , &
+ & ' "by sense switch 1." ' , &
+ & ' "when kcode cycles were done." ' , &
+ & ' "when events were written to the ptrac file." ' , &
+ & ' "because of bad trouble." ' , &
+ & ' "at end of surface-source input file." ' , &
+ & ' "because of fatal errors." ' , &
+ & ' ' , &
+ & ' ' , &
+ & ' ' , &
+ & ' ' /)

end module mcnp_data
diff -Naurd MCNP5/Source/src/mcnp_global.F90 MCNP5_new/Source/src/mcnp_global.F90
--- MCNP5/Source/src/mcnp_global.F90 2003-04-30 20:11:32.000000000 -0600
+++ MCNP5_new/Source/src/mcnp_global.F90 2004-07-22 15:14:42.000000000 -0600
@@ -164,6 +164,24 @@
& mazu(:), & != Universe/lattice map pointers. See App. E.
& mfl(:, :) != Fill data for each cell.

+ ! Declaration of flags to check speed tally requirements
+ integer :: &
+ & flag_speed_tally_ok = 0 , & != Overall flag to enable lattice speed tally
modifications
+ ! for lattices (modifications to tally.F90)
+ ! 1 = criteria to use lattice speed tally has been
fulfilled.
+ ! 0 = default (not tested yet or no lat=1 keyword
in geometry)
+ ! -1 = lat present, but criteria to use lattice
speed tally has NOT been fulfilled.
+ & flag_speed_tally_force = 0 != Overall flag to force use of lattice speed tally
modifications
+ ! for lattices (modifications to tally.F90)

```

```

+                                     ! 1 = forced use of lattice speed tally 0 =
default (neither)
+                                     ! -1 = forced use of regular tally routine (i.e.
slow)
+ integer, ALLOCATABLE :: &
+   & flag_speed_tally_fm(:,:), & ! Flag to check if each f4 has corresponding fm card
present. 0=no 1=yes
+                                     ! the fm card should be present to enable the
lattice speed tally modifications
+   & flag_speed_tally_de(:,:), & ! Flag to check if each f4 has corresponding de df
cards present. 0=no 1=yes
+                                     ! the de df cards should be present to enable the
lattice speed tally modifications
+                                     ! Both of these variables place icn (the user-
defined tally number) in the 2nd dimension.
+
! "VDAC" -- variable dynamically allocated common
real(dknd), ALLOCATABLE :: &
& ara(:), & != Areas of the surfaces in the problem.
@@ -176,10 +194,11 @@
integer, ALLOCATABLE :: &
& jfq(:,:), & != Order for printing tally results.
& lfcl(:), & != Cells where fission is treated like capture.
- & npsw(:), & != For each surface source surface, the last history in
- != which a track crossed it.
& nsl(:,:), & != Summary information for surface source file.
& ntbb(:,:), & != Counts of scores beyond the last bin.
+ integer(i8knd), ALLOCATABLE :: &
+ & npsw(:) != For each surface source surface, the last history in
+ != which a track crossed it.

! Task "VDAC" (have l<var> and k<var> references).
real(dknd), ALLOCATABLE :: &
@@ -206,15 +225,16 @@
& wns(:,:), & != Actual frequencies of source sampling.
& wwfa(:) != Weight window generator entering weight array.
integer, ALLOCATABLE :: &
- & isef(:,:), & != Source position tries and rejections.
& laj(:), & != Cells on the other sides of the surfaces in LJA.
& lcaj(:), & != For each surface in LJA, a pointer into the list of
!= other-side cells in LAJ.
& lse(:), & != Cells where source particles have appeared.
& maze(:), & != Universe/lattice map values. See App. E.
- & nbal(:), & != Number of histories processed by each task.
& ndpf(:,:), & != Accounts of detector scores that failed.
- & ndr(:), & != List of discrete-reaction rejections.
+ & ndr(:) != List of discrete-reaction rejections.
+ integer(i8knd), ALLOCATABLE :: &
+ & isef(:,:), & != Source position tries and rejections.
+ & nbal(:), & != Number of histories processed by each task.
& nhsd(:,:), & != Number in history score distribution which counts
!= nonzero scores for statistical analysis.

@@ -309,4 +329,29 @@
& lsg(:), & != Kind of line to plot for each segment of curve.
& ncs(:) != Number of curves where surface meets plot plane.

+ CONTAINS
+
+ subroutine mcnp_global_nullify
+
+ ! This routine ensures that the pointers declared above have
+ ! a defined association status.
+ implicit none
+
+ nullify( ncl )
+ nullify( nsfm )
+ nullify( kxs )
+ nullify( laf )
+ nullify( jun )
+ nullify( mat )

```

```

+   nullify( mazp )
+   nullify( mazu )
+   nullify( mfl )
+   nullify( xss )
+   nullify( exs )
+   nullify( zst )
+
+   return
+
+ end subroutine mcnp_global_nullify
+
end module mcnp_global
diff -Naurd MCNP5/Source/src/mcnp_input.F90 MCNP5_new/Source/src/mcnp_input.F90
--- MCNP5/Source/src/mcnp_input.F90 2003-11-05 17:23:12.000000000 -0700
+++ MCNP5_new/Source/src/mcnp_input.F90 2004-07-22 15:14:42.000000000 -0600
@@ -8,7 +8,7 @@
integer,private :: i ! Local loop variable.

! Module Parameters:
- integer,parameter :: nkcd = 101 ! = Number of different types of input cards.
+ integer,parameter :: nkcd = 102 ! = Number of different types of input cards.
integer,parameter :: nta1mx = 1000 ! = Maximum number of tallies.
integer,parameter :: mopts = 7 ! = Number of M card options (gas, estep, etc.).

@@ -84,6 +84,8 @@
integer :: nwc ! = Count of items on current input card.
integer :: nxsc = 0 ! = Number of XSn cards.

+ integer(i8knd) :: i8itm ! = 8 Byte Integer form of current item from
input card.
+
character(len=5 ) :: cnm(nkcd)
character(len=80) :: hitm
character(len=80) :: hlin
@@ -234,5 +236,5 @@
data cnm(99), (krq(i,99),i=1,7) / 'rand ',0,0, 0,0, 0, 12,0 /
data cnm(100), (krq(i,100),i=1,7) / 'irmc ',1,0, 0,1, 2, 50,0 /
data cnm(101), (krq(i,101),i=1,7) / 'rrmc ',1,0, 0,1,-1, 50,0 /
-
+ data cnm(102), (krq(i,102),i=1,7) / 'spdt1',0,0, 0,0, 0, 1,0 /
end module mcnp_input
diff -Naurd MCNP5/Source/src/mcnp_params.F90 MCNP5_new/Source/src/mcnp_params.F90
--- MCNP5/Source/src/mcnp_params.F90 2003-11-05 17:23:12.000000000 -0700
+++ MCNP5_new/Source/src/mcnp_params.F90 2004-07-22 15:14:42.000000000 -0600
@@ -55,7 +55,7 @@
& mcnp_opt_multt = mcnp_opt_omp, &
& mcnp_opt_parallel = mcnp_opt_multp .or. mcnp_opt_multt

- real(dknd),parameter :: huge = 1.0d+36 ! = A very large number.
+ real(dknd),parameter :: huge_float = 1.0d+36 ! = A very large number.

! array dimensions.
integer,parameter :: lmrkp = 651 ! = Minimum number of kcode cycles to plot
(mrkp).
@@ -137,11 +137,43 @@
& euler = .577215664901532861d+0, & ! = Euler constant used in electron
transport.
& fscon = 137.0393d+0, & ! = Inverse fine-structure constant.
& hsl1 = 1.0d-30, & ! = History score lower bin bound.
- & one = 1.0d+0, & ! = Floating-point constant 1. for arguments.
& pie = 3.1415926535898d+0, & ! = pi.
& planck = 4.135732d-13, & ! = Planck constant.
- & slite = 299.7925d+0, & ! = Speed of light.
- & third = one/3.0d+0, & ! = Floating-point constant 1/3.
- & zero = 0.0d+0 ! = Floating-point constant 0. for arguments.
+ & slite = 299.7925d+0 ! = Speed of light.
+ ! Frequently used real numbers:
+ real(dknd),parameter :: &
+ & one = 1.0_dknd, &
+ & two = 2.0_dknd, &
+ & three = 3.0_dknd, &

```

```

+ & four      = 4.0_dknd,      &
+ & five      = 5.0_dknd,      &
+ & six       = 6.0_dknd,      &
+ & seven     = 7.0_dknd,      &
+ & eight     = 8.0_dknd,      &
+ & nine      = 9.0_dknd,      &
+ & ten       = 10.0_dknd,     &
+ & twenty    = 20.0_dknd,     &
+ & thirty    = 30.0_dknd,     &
+ & forty     = 40.0_dknd,     &
+ & fifty     = 50.0_dknd,     &
+ & sixty     = 60.0_dknd,     &
+ & seventy   = 70.0_dknd,     &
+ & eighty   = 80.0_dknd,     &
+ & ninety   = 90.0_dknd,     &
+ & hundred  = 100.0_dknd,    &
+ & one_eighty = 180.0_dknd,   &
+ & three_sixty = 360.0_dknd,  &
+ & thousand  = 1000.0_dknd,   &
+ & third     = one/three,     &
+ & half      = 0.5_dknd,      &
+ & tenth     = 0.1_dknd,      &
+ & hundredth = 0.01_dknd,     &
+ & thousandth = 0.001_dknd,  &
+ & zero      = 0.0_dknd
+
+ integer(i8knd), parameter :: i8limit = huge(1_i8knd)    != Max integer*8 ~1E20
+ integer,          parameter :: i4limit = huge(1_i4knd)    != Max integer*4

end module mcnp_params
+
+
diff -Naurd MCNP5/Source/src/mcplot_module.F90 MCNP5_new/Source/src/mcplot_module.F90
--- MCNP5/Source/src/mcplot_module.F90      2003-11-05 17:23:12.000000000 -0700
+++ MCNP5_new/Source/src/mcplot_module.F90  2004-07-22 15:14:42.000000000 -0600
@@ -244,9 +244,6 @@
     ! Make plots of tally data in response to input from the user.

     ! Modules:
-#ifdef LAHEY
-    use WINTERACTER
-#endif
    use dynamic_arrays

    hovr = 'mcplot'
@@ -305,9 +302,6 @@
        read(ifile,'(a80)',iostat=istat) klin
        if( istat==0 ) then
            continue
-#ifdef LAHEY
-    call IGrAreaClear()
-#endif
        else
            klin = ' '
            if( ifile/=itty ) then
@@ -1003,8 +997,8 @@
                if( kxsplt/=0 ) then
                    call abvals( abl(1:), 1 )
                    call exord(2)
-                    xyzmn(3) = huge
-                    xyzmx(3) = -huge
+                    xyzmn(3) = huge_float
+                    xyzmx(3) = -huge_float
                    call exord(1)
                    ym = xyzmn(3)
                    yx = xyzmx(3)
@@ -1234,8 +1228,8 @@
                enddo
            elseif( i>=36 .and. i<40 ) then
                ! Make criticality frequency plot.
-                ablo(1) = huge

```

```

-      abhi(1) = -huge
+      ablo(1) = huge_float
+      abhi(1) = -huge_float
      ki = i-35
      if( i==39) ki = 20
      do j = k0,kcz
@@ -1307,9 +1301,9 @@
      ! Check log plot ordinate array for non-positive values.
      200 continue
      if( abs(lax-3)/=1) go to 260
-      ap = huge
-      am = huge
-      ax = -huge
+      ap = huge_float
+      am = huge_float
+      ax = -huge_float
      do i = 1,npt(1)
        am = min(am,ord(i))
        if( ord(i)>0.) ap = min(ap,ord(i))
@@ -1349,8 +1343,8 @@
      ! Determine axis limits.
      if( jlim(1)==0) call gxlims(ablo(1),abhi(1),xyzmn(1),xyzmx(1),n,max(0,lax-2))
      if( jlim(2)/=0) go to 300
-      a = huge
-      b = -huge
+      a = huge_float
+      b = -huge_float
      do i = 1,npt(1)
        a = min(a,.95*ord(i))
        b = max(b,1.05*ord(i))
@@ -1399,8 +1393,8 @@
      if( washme ) ab2(0) = ablo(2)

      if( inform/=0) return
-      xyzmn(3) = huge
-      xyzmx(3) = -huge
+      xyzmn(3) = huge_float
+      xyzmx(3) = -huge_float
      call exord(1)
      if( xyzmx(3)>xyzmn(3)) go to 380
      write(jtty,370)
@@ -1499,7 +1493,6 @@
      call gslwsc(1.)
      call gsln(1)
      if( mcolor>2 ) call gsplci( kcolor(ncolor+1),0)
-
      ! Add error bars if required.
      if( noerbr==0 .and. (itfc<=1 .or. itfc>=41 .and. itfc<=43 .or. &
        & itfc>=46 .and. itfc<=47 .or. itfc==52 .or. itfc==54 .or. &
@@ -2122,7 +2115,7 @@
      ablo(iv) = 0.
      if( ifree(iv)==7 .and. ktfile==1 ) then
        ! Energy bins from RUNTPE.
-      ablo(iv) = huge
+      ablo(iv) = huge_float
      j = jptal(3,mtal)
      do i = 1,mipt
        if( mod(j,2)/=0 ) ablo(iv) = min(ablo(iv),ecf(i))
@@ -2290,9 +2283,9 @@

      ! Find next minimum energy of given isotopes.
      ! Eo=-huge for photons.
-      eo = -huge
+      eo = -huge_float
      do
-      en = huge
+      en = huge_float
      do j = 1,kxsplt
        if( kxspen(j)<=0 .or. kxspxs(j)<=0 ) cycle
        if( kxspnx(mxel+j)>kxspnx(j) ) cycle
@@ -2302,7 +2295,7 @@

```



```

        k = j
        en = e
    enddo
-   if( en==huge ) exit
+   if( en==huge_float ) exit
    kxspnx(mxel+k) = kxspnx(mxel+k)+1
    if( en<=eo ) cycle
    eo = en
@@ -2338,15 +2331,15 @@

    i = 0
    if( ktfile==1 ) then
-   t = max(1,nps)
+   t = max(1_i8knd,nps)
    if( nsr==71 .and. kcz>=ikz ) t = nsrck*(kcz-ikz)
    call ra_kcheck(kcheck)
    call ra_lcheck(lsav,ldif)
    if( kcheck>0 .and. kcz>=lsav ) t = nsrck*(kcz-lsav)
    if( kc8<0 ) t = t+nsrck-wt0*nsa
    if( knrm/=0 .or. (kcheck>0 .and. kcz<lsav) ) t = pax(1,1,1)
-   if( nsr==6 .and. nrrs>=nrss ) t = max(1,np1)
-   if( nsr==6 .and. nrrs<nrss ) t = max(1,npsr)
+   if( nsr==6 .and. nrrs>=nrss ) t = max(1_i8knd,np1)
+   if( nsr==6 .and. nrrs<nrss ) t = max(1_i8knd,npsr)
    fp = 1./max(t,one)
    endif
    j = jptal(5,mtal)
@@ -2609,11 +2602,6 @@
    ! Return 1 for any termination command, otherwise 0.
    ! Return ln=1 for end of line, otherwise ln=0.

-   ! Modules:
-#ifdef LAHEY
-   use WINTERACTER
-#endif
-
    character(len=80) :: ha
    character(len=8)  :: hm
@@ -3033,7 +3021,6 @@
    lax = 3
    if( itfc==6 ) lax = 4
    endif
-
    return

    case( 33 )
@@ -3290,12 +3277,7 @@
    write(jtty,'( " bad argument of ",a8, " command: ",a8)')hm,ha

    9020 continue
-#ifdef LAHEY
-   if( koplot/=0 ) call WindowClose
-   write(jtty,'( " the rest of the command line is ignored.")')
-#else
    write(jtty,'( " the rest of the command line is ignored.")')
-#endif
    ln = 1

    9030 continue
@@ -4154,7 +4136,7 @@
    fn = (ord(j)-ord(j-1))*f1+(ord(j+1)-ord(j))*f2
    fd = (ab1(j)-ab1(j-1))*f1+(ab1(j+1)-ab1(j))*f2
    t(j-i+1) = 1.
-   if( fn/=0. ) t(j-i+1) = huge*1e-10
+   if( fn/=0. ) t(j-i+1) = huge_float*1e-10
    if( fd/=0. ) t(j-i+1) = fn/fd
    enddo
    if( i==1 ) then
diff -Naurd MCNP5/Source/src/mctalw.F90 MCNP5_new/Source/src/mctalw.F90
--- MCNP5/Source/src/mctalw.F90      2003-04-30 20:11:38.000000000 -0600

```

```

+++ MCNP5_new/Source/src/mctalw.F90 2004-07-22 15:14:42.000000000 -0600
@@ -22,23 +22,23 @@
    call unique(hm,jtty)
    open(iut,file=hm,status='new')
    write(ht,'(f16.0)')rnr
-   if( mct<0 ) write(iut,'(35x,i5,i11,a15)')knod,nps,ht(1:15)
-   if( mct>=0 ) write(iut,'(2a8,a19,i5,i11,a15)')kod,ver,probid,knod,nps,ht(1:15)
+   if( mct<0 ) write(iut,'(35x,i5,i12,a15)')knod,nps,ht(1:15)
+   if( mct>=0 ) write(iut,'(2a8,a19,i5,i12,a15)')kod,ver,probid,knod,nps,ht(1:15)
    write(iut,'(1x,a79)') aid
    if( npert==0 ) write(iut,'( "ntal",i6)')ntal
    if( npert/=0 ) write(iut,'( "ntal",i6, " npert",i6)')ntal,npert
    write(iut,'(16i5)') (jptal(1,i),i=1,ntal)

    ! calculate the tally normalization factor.
-   t = max(1,nps)
+   t = max(1_i8knd,nps)
    if( nsr==71 .and. kcz>=ikz) t = nsrck*(kcz-ikz)
    call ra_kcheck( kcheck )
    call ra_lcheck( lsav, ldif )
    if( kcheck>0 .and. kcz>=lsav) t = nsrck*(kcz-lsav)
    if( kc8<0) t = t+nsrck-wt0*nsa
    if( knrm/=0 .or. (kcheck>0 .and. kcz<lsav) ) t = pax(1,1,1)
-   if( nsr==6 .and. nrrs>=nrss) t = max(1,np1)
-   if( nsr==6 .and. nrrs<nrss) t = max(1,npsr)
+   if( nsr==6 .and. nrrs>=nrss) t = max(1_i8knd,np1)
+   if( nsr==6 .and. nrrs<nrss) t = max(1_i8knd,npsr)
    fp = 1./max(t,one)

    ! determine if surfaces have macrobody facets.
diff -Naurd MCNP5/Source/src/messages.F90 MCNP5_new/Source/src/messages.F90
--- MCNP5/Source/src/messages.F90 2003-11-05 17:23:12.000000000 -0700
+++ MCNP5_new/Source/src/messages.F90 2004-07-22 15:14:42.000000000 -0600
@@ -24,13 +24,11 @@
    ! msgZ_put(array, nitem) for zero-based arrays
    ! (nstart is first element of the array if lower bound is not 1.)
    ! msg_get and msgZ_get have same arguemnts as msg_put and msgZ_put
-
+ use mcnp_params, only: i4knd, i8knd, rknd, dknd, iuo, zero
+ use mcnp_iofiles, only: jtty
implicit none

- integer, parameter, PRIVATE :: iknd = selected_int_kind( 9)
- integer, parameter, PRIVATE :: i8knd = selected_int_kind(18)
- integer, parameter, PRIVATE :: rknd = selected_real_kind(6,37)
- integer, parameter, PRIVATE :: dknd = selected_real_kind(15,307)
+ private i4knd, i8knd, rknd, dknd, iuo, jtty

interface msg_get
    ! ==> specific routines used for generic subroutine:
@@ -38,7 +36,7 @@
    module procedure msg_get_i1, msg_get_i2, msg_get_i3, msg_get_i4
    module procedure msg_get_d1, msg_get_d2, msg_get_d3, msg_get_d4
    module procedure msg_get_d5
-   module procedure msg_get_i80,msg_get_i81
+   module procedure msg_get_i80,msg_get_i81,msg_get_i82
end interface

interface msg_put
@@ -47,7 +45,7 @@
    module procedure msg_put_i1, msg_put_i2, msg_put_i3, msg_put_i4
    module procedure msg_put_d1, msg_put_d2, msg_put_d3, msg_put_d4
    module procedure msg_put_d5
-   module procedure msg_put_i80,msg_put_i81
+   module procedure msg_put_i80,msg_put_i81,msg_put_i82
end interface

! msgZ_get and msgZ_put to handle arrays with first lbound /=1.
@@ -55,11 +53,13 @@
    interface msgZ_get
        module procedure msgZ_get_d1, msgZ_get_d3

```

```

        module procedure msgZ_get_i1, msgZ_get_i2
+       module procedure msgZ_get_i81, msgZ_get_i82
end interface

interface msgZ_put
    module procedure msgZ_put_d1, msgZ_put_d3
    module procedure msgZ_put_i1, msgZ_put_i2
+   module procedure msgZ_put_i81, msgZ_put_i82
end interface

contains
@@ -186,7 +186,7 @@
    use dmmp
    implicit none
    !
-   integer(iknd), intent(out) :: val
+   integer(i4knd), intent(out) :: val
    integer :: rc
    !
    call dm_get(val,1,rc)
@@ -198,7 +198,7 @@
    use dmmp
    implicit none
    !
-   integer(iknd), intent(inout) :: ptr(:)
+   integer(i4knd), intent(inout) :: ptr(:)
    integer, intent(in) :: nstart,n
    integer :: rc
    !
@@ -211,7 +211,7 @@
    use dmmp
    implicit none
    !
-   integer, intent(inout) :: ptr(:,:)
+   integer(i4knd), intent(inout) :: ptr(:,:)
    integer, intent(in) :: nstart,n
    integer :: rc
    #if defined(AIX) || defined(LAHEYLF95) || defined (ABSOFIT) || defined(PGF90) || defined
(INTEL)
@@ -301,6 +301,29 @@
    if( rc/=0 ) call expire( 0, 'msg_get_i81', 'dm_get errors -' )
    return
end subroutine msg_get_i81
+   !-----
+   subroutine msg_get_i82(ptr,nstart,n)
+   use dmmp
+   implicit none
+   !
+   integer(i8knd), intent(inout) :: ptr(:,:)
+   integer, intent(in) :: nstart,n
+   integer :: rc
+   #if defined(AIX) || defined(LAHEYLF95) || defined (ABSOFIT) || defined(PGF90) || defined
(INTEL)
+   integer, dimension(size(ptr)) :: tmp
+   if( n<size(ptr) ) then !preserve remainder of array
+   tmp = reshape(ptr,shape(tmp))
+   else !whole array to be overwritten
+   tmp = 0
+   endif
+   call dm_get(tmp(nstart:nstart+n-1),n,rc)
+   ptr = reshape(tmp,shape(ptr))
+   #else
+   call dm_get(ptr(nstart:,1),n,rc)
+   #endif
+   return
+   if( rc/=0 ) call expire( 0, 'msg_get_i82', 'dm_get errors -' )
+   end subroutine msg_get_i82
+   !-----
    subroutine msg_get_c(val)
    use dmmp
@@ -414,7 +437,7 @@

```

```

        use dmmp
        implicit none
        !
-       integer(iknd), intent(in)  :: val
+       integer(i4knd), intent(in) :: val
        integer :: rc
        !
        call dm_put(val,1,rc)
@@ -426,7 +449,7 @@
        use dmmp
        implicit none
        !
-       integer(iknd), intent(in) :: ptr(:)
+       integer(i4knd), intent(in) :: ptr(:)
        integer,          intent(in) :: nstart,n
        integer :: rc
        call dm_put(ptr(nstart:),n,rc)
@@ -438,7 +461,7 @@
        use dmmp
        implicit none
        !
-       integer,          intent(in)          :: ptr(:,:)
+       integer(i4knd),  intent(in)          :: ptr(:,:)
        integer,          intent(in)          :: nstart,n
        integer           :: rc
        #if defined(AIX) || defined(LAHEYLF95) || defined (ABSOFIT) || defined(PGF90) || defined
(INTEL)
@@ -511,6 +534,24 @@
        if( rc/=0 ) call expire( 0, 'msg_put_i81', 'dm_put errors - ' )
        return
    end subroutine msg_put_i81
+   !-----
+   subroutine msg_put_i82(ptr,nstart,n)
+   use dmmp
+   implicit none
+   !
+   integer(i8knd),  intent(in)          :: ptr(:,:)
+   integer,          intent(in)          :: nstart,n
+   integer           :: rc
+   #if defined(AIX) || defined(LAHEYLF95) || defined (ABSOFIT) || defined(PGF90) || defined
(INTEL)
+   integer,dimension(size(ptr)) :: tmp
+   tmp = reshape(ptr,shape(tmp))
+   call dm_put(tmp(nstart:nstart+n-1),n,rc)
+   #else
+   call dm_put(ptr(nstart:,1),n,rc)
+   #endif
+   if( rc/=0 ) call expire( 0, 'msg_put_i82', 'dm_put errors - ' )
+   return
+   end subroutine msg_put_i82
+   !-----
    subroutine msg_put_c(val)
        use dmmp
@@ -568,9 +609,9 @@
        use dmmp
        implicit none
        !
-       integer,          intent(inout)     :: ptr(:)
-       integer,          intent(in)        :: n
-       integer           :: rc
+       integer(i4knd),  intent(inout)     :: ptr(:)
+       integer,          intent(in)        :: n
+       integer           :: rc
        !
        call dm_get(ptr(:),n,rc)
        if( rc/=0 ) call expire( 0, 'msgZ_get_i1', 'dm_get errors -' )
@@ -581,9 +622,9 @@
        use dmmp
        implicit none
        !
-       integer, intent(inout)  :: ptr(:,:)

```

```

-   integer,   intent(in)   :: n
-   integer                                :: rc
+   integer(i4knd), intent(inout) :: ptr(:, :)
+   integer,   intent(in)   :: n
+   integer                                :: rc
#if defined(AIX) || defined(LAHEYLF95) || defined (ABSOFIT) || defined(PGF90) || defined
(INTEL)
    integer, dimension(size(ptr)) :: tmp
    if( n<size(ptr) ) then          !preserve remainder of array
@@ -599,6 +640,42 @@
        if( rc/=0 ) call expire( 0, 'msgZ_get_i2', 'dm_get errors -' )
        return
    end subroutine msgZ_get_i2
+   !-----
+   subroutine msgZ_get_i81(ptr,n)
+   use dmmp
+   implicit none
+   !
+   integer(i8knd), intent(inout) :: ptr(:)
+   integer,intent(in)           :: n
+   integer                       :: rc
+   !
+   call dm_get(ptr(:),n,rc)
+   if( rc/=0 ) call expire( 0, 'msgZ_get_i81', 'dm_get errors -' )
+   return
+ end subroutine msgZ_get_i81
+   !-----
+   subroutine msgZ_get_i82(ptr,n)
+   use dmmp
+   implicit none
+   !
+   integer(i8knd), intent(inout) :: ptr(:, :)
+   integer,intent(in)           :: n
+   integer                       :: rc
+#if defined(AIX) || defined(LAHEYLF95) || defined (ABSOFIT) || defined(PGF90) || defined
(INTEL)
+   integer(i8knd), dimension(size(ptr)) :: tmp
+   if( n<size(ptr) ) then          !preserve remainder of array
+       tmp = reshape(ptr,shape(tmp))
+   else
+       tmp = 0                      !whole array to be overwritten
+   endif
+   call dm_get(tmp(:),n,rc)
+   ptr = reshape(tmp,shape(ptr))
+#else
+   call dm_get(ptr(:,1),n,rc)
+#endif
+   if( rc/=0 ) call expire( 0, 'msgZ_get_i82', 'dm_get errors -' )
+   return
+ end subroutine msgZ_get_i82

!=====
    subroutine msgZ_put_d1(ptr,n)
@@ -635,9 +712,9 @@
    use dmmp
    implicit none
    !
-   integer,   intent(in)           :: ptr(:)
-   integer,   intent(in)           :: n
-   integer                                :: rc
+   integer(i4knd), intent(in)       :: ptr(:)
+   integer,   intent(in)           :: n
+   integer                                :: rc
    call dm_put(ptr(:),n,rc)
    if( rc/=0 ) call expire( 0, 'msgZ_put_i1', 'dm_put errors -' )
    return
@@ -648,9 +725,9 @@
    use dmmp
    implicit none
    !
-   integer, intent(in)              :: ptr(:, :)

```

```

-   integer,    intent(in)      :: n
-   integer                                :: rc
+   integer(i4knd), intent(in)   :: ptr(:, :)
+   integer,    intent(in)      :: n
+   integer                                :: rc
#if defined(AIX) || defined(LAHEYLF95) || defined(ABSOFIT) || defined(PGF90) || defined
(INTEL)
    integer,dimension(size(ptr)) :: tmp
    tmp = reshape(ptr,shape(tmp))
@@ -661,6 +738,35 @@
    if( rc/=0 ) call expire( 0, 'msgZ_put_i2', 'dm_put errors - ' )
    return
end subroutine msgZ_put_i2
-
+ ! -----
+ subroutine msgZ_put_i81(ptr,n)
+   use dmmp
+   implicit none
+   !
+   integer(i8knd), intent(in)   :: ptr(:)
+   integer, intent(in)          :: n
+   integer                      :: rc
+   call dm_put(ptr(:),n,rc)
+   if( rc/=0 ) call expire( 0, 'msgZ_put_i81', 'dm_put errors - ' )
+   return
+ end subroutine msgZ_put_i81
+ !-----
+ subroutine msgZ_put_i82(ptr,n)
+   use dmmp
+   implicit none
+   !
+   integer(i8knd), intent(in)   :: ptr(:, :)
+   integer, intent(in)          :: n
+   integer                      :: rc
+#if defined(AIX) || defined(LAHEYLF95) || defined(ABSOFIT) || defined(PGF90) || defined
(INTEL)
+   integer(i8knd),dimension(size(ptr)) :: tmp
+   tmp = reshape(ptr,shape(tmp))
+   call dm_put(tmp(:),n,rc)
+#else
+   call dm_put(ptr(:,1),n,rc)
+#endif
+   if( rc/=0 ) call expire( 0, 'msgZ_put_i82', 'dm_put errors - ' )
+   return
+ end subroutine msgZ_put_i82

end module messages
diff -Naurd MCNP5/Source/src/mgcoln.F90 MCNP5_new/Source/src/mgcoln.F90
--- MCNP5/Source/src/mgcoln.F90      2003-04-30 20:11:40.000000000 -0600
+++ MCNP5_new/Source/src/mgcoln.F90  2004-07-22 15:14:42.000000000 -0600
@@ -4,6 +4,7 @@
subroutine mgcoln
! calculate a neutron multigroup forward collision.
use mcnp_global
+ use dxtran_mod
use mcnp_debug

implicit real(dknd) (a-h,o-z)
@@ -29,10 +30,7 @@
l = jxs(1,iex)-1+nint(xss(jxs(13,iex)+1))+(jg-1)*jgm(2)
ipt = 2
ncp = 0
- idx = 0
- do i=1,ndx(2)
-   if( (xxx-dxx(2,1,i))**2+(yyy-dxx(2,2,i))**2+(zzz-dxx(2,3,i))**2 < dxx(2,5,i) )
idx=i
- end do
+ idx = inside_dxtran_sphere()
vel = slite
st = totm
do i=1,n

```

```

diff -Naurd MCNP5/Source/src/mgimps.F90 MCNP5_new/Source/src/mgimps.F90
--- MCNP5/Source/src/mgimps.F90      2003-04-30 20:11:40.000000000 -0600
+++ MCNP5_new/Source/src/mgimps.F90  2004-07-22 15:14:42.000000000 -0600
@@ -5,6 +5,7 @@
! check multigroup tables and calculate multigroup arrays.
use mcnp_global
use mcnp_debug
+ use erprnt_mod

implicit real(dknd) (a-h,o-z)

@@ -112,7 +113,7 @@
if( iplt==1 ) then
do ip = 1,mipt
do jg = 1,jgm(ip)
- t = huge
+ t = huge_float
do ia = 1,mxa
if( fim(ip,ia)/=0. .and. &
& gmg(ia+mxa*(jg-1+mgm(ip)))>0. ) t = min(t,gmg(ia+mxa*(jg-1+mgm(ip))))
diff -Naurd MCNP5/Source/src/mgxspt.F90 MCNP5_new/Source/src/mgxspt.F90
--- MCNP5/Source/src/mgxspt.F90      2003-04-30 20:11:42.000000000 -0600
+++ MCNP5_new/Source/src/mgxspt.F90  2004-07-22 15:14:42.000000000 -0600
@@ -9,6 +9,7 @@
use mcnp_global
use mcnp_debug
use dynamic_arrays
+ use erprnt_mod
implicit real(dknd) (a-h,o-z)

character hn*9,ht*10
diff -Naurd MCNP5/Source/src/msgcon.F90 MCNP5_new/Source/src/msgcon.F90
--- MCNP5/Source/src/msgcon.F90      2003-04-30 20:11:42.000000000 -0600
+++ MCNP5_new/Source/src/msgcon.F90  2004-07-22 15:14:42.000000000 -0600
@@ -14,6 +14,8 @@
use mcnp_debug
use messages
use fmesh_mod, only:fmesh_msgput,fmesh_msgcon
+ use qttyin_mod, only: qttyin
+ use erprnt_mod, only: erprnt, erprnt_i8_k1

implicit real(dknd) (a-h,o-z)

@@ -22,13 +24,16 @@
integer :: mn
save np, ns, mn, nc
real(dknd) :: rg(11)
- integer,allocatable :: nc(:, :)
+ integer(i8knd),allocatable :: nc(:, :)
character(len=130) :: hf
character(len=69) :: hm
character(len=19) :: hd
character(len=6) :: hs
+
+ integer(i8knd) :: np(2,6) = reshape( (/ (0,i=1,12) /), (/ 2,6 /) )
+ integer(i8knd) :: ni8knd
+ integer(i8knd) :: n_i8
integer :: lf = 5
- integer :: np(2,6) = reshape( (/ (0,i=1,12) /), (/ 2,6 /) )

if( .not.mcnp_opt_multp ) then
! Just return, if not using MPI or PVM message-passing
@@ -86,18 +91,18 @@
mn= ltasks
endif
allocate (nc(0:mn,1:4))
- nc=0
+ nc=0_i8knd

! Initialize all possible rendezvous points.
nbal(1:ltasks+1) = 0

```

```

    if( nsr/=71 ) then
-   if( prn>0. ) np(1,1) = int(prn)
-   if( dmp>0. ) np(1,2) = int(dmp)
-   if( krtm/=0 .and. freq>0. ) np(1,3) = int(freq)
+   if( prn>0. ) np(1,1) = int(prn,i8knd)
+   if( dmp>0. ) np(1,2) = int(dmp,i8knd)
+   if( krtm/=0 .and. freq>0. ) np(1,3) = int(freq,i8knd)
endif
- np(1,5) = 200
+ np(1,5) = 200_i8knd
  np(1,6) = npp
- if( nsr==6 ) np(1,6) = nps+nint(min(one,1.1*snit)*(niss-nqss))
+ if( nsr==6 ) np(1,6) = nps+nint(min(one,1.1*snit)*(niss-nqss),i8knd)
  if( nsr==71 ) np(1,6) = nps+nsa
  np(2,1:6) = np(1,1:6)

@@ -106,20 +111,20 @@
! - if prdmp(5)=0 1/10th of job unless ddg(1,*)>0;
! - if prdmp(5)>0 set to prdmp(5).
ns = 0
- if( inpd<0 .or. (konrun/=0 .and. inpd==0) ) go to 80
+ if( inpd<0_i8knd .or. (konrun/=0 .and. inpd==0_i8knd) ) go to 80
  if( any( ddg(1,1:ndtt)>0 ) ) go to 70
  do i = 1,mipt
    if( any( ddx(i,1,1:ndx(i))>0 ) ) go to 70
  enddo
- if( inpd>0 ) go to 80
- n = max(0,npp-nps)
- if( nsr==6 ) n = nint(min(one,snit)*(niss-nqss))
- if( nsr==71 ) n = nsrck*(kct-kcy)
- if( npp==0 .and. nsr/=6 .and. nsr/=71 ) ns = 1
- npd = 1000*max(1,nint(one*n/10000.))
+ if( inpd>0_i8knd ) go to 80
+ n_i8 = max(0_i8knd,npp-nps)
+ if( nsr==6 ) n_i8 = nint(min(one,snit)*(niss-nqss))
+ if( nsr==71 ) n_i8 = nsrck*(kct-kcy)
+ if( npp==0_i8knd .and. nsr/=6 .and. nsr/=71 ) ns = 1
+ npd = 1000_i8knd*max(1_i8knd,nint(one*n_i8/10000._dknd,i8knd))
70 continue
- if( inpd>0 ) call erprnt(1,2,1,npd,0,0,0,0,&
-   & ' "detector roulette data updated every",i10, " particles."' )
+ if( inpd>0_i8knd ) call erprnt_i8_k1(1,2,1,npd,0,0,0,0,&
+   & ' "detector roulette data updated every",i12, " particles."' )
80 continue

! Send work-exists flag.
@@ -130,13 +135,18 @@
write(jtty,*) "master sending static commons..."
call dm_sndi
call msg_put( gfixcm, 1, nfixcm )
- call msg_put( jfixcm, 1, lfixcm )
call msg_put( i8fixcm, 1, l8fixcm )
+ call msg_put( jfixcm, 1, lfixcm )
+
call msg_put( gvarcm, 1, nvarcm )
+ call msg_put( i8varcm, 1, l8varcm )
call msg_put( jvarcm, 1, lvarcm )
+
call msg_put( rdum, 1, n_rdum )
call msg_put( idum, 1, n_idum )
+
call msg_put( gepHCM, 1, nepHCM )
+ call msg_put( i8epHCM, 1, l8epHCM )
call msg_put( jepHCM, 1, lepHCM )
call dm_send(-1,4,i)

@@ -162,6 +172,7 @@
call dm_sndi
mr = (lchnk+nrcd-1)/nrcd
call msg_put( ssb, 1, nrcd)
+ ! QUESTION should n be i8

```



```

do n = 2,nrss-nrrs
  read(iusr,end = 600) (ssb(i),i = 1,nrcd)
  call msg_put( ssb, 1, nrcd)
@@ -185,22 +196,22 @@

! Find the next rendezvous point.
if( nst/=0 ) return
- if( ns>0 ) npd = 1000*max(1,nint(ctme*60.*nps/max(one,cts)/10000.))
+ if( ns>0 ) npd =
1000_i8knd*max(1_i8knd,nint(ctme*60.*nps/max(one,cts)/10000._dknd,i8knd))
  if( ntal>0 ) np(1,4) = npd
  if( ns>0 .and. ntal==0 ) np(2,6) = nps+npd
  if( nsr==71 ) np(2,6) = nps+nsa
- n = max( 100000, np(1,4), np(1,6)-nps )
+ n_i8 = max( 100000_i8knd, np(1,4), np(1,6)-nps )
do i = 1,6
- if( i<=4 .and. np(1,i)>0 .and. nps>=np(2,i) ) then
-   np(2,i) = np(2,i)+np(1,i)*((nps-np(2,i))/np(1,i)+1)
+ if( i<=4 .and. np(1,i)>0_i8knd .and. nps>=np(2,i) ) then
+   np(2,i) = np(2,i)+np(1,i)*((nps-np(2,i))/np(1,i)+1_i8knd)
  endif
- if( nps<np(2,i) ) n = min(n,np(2,i)-nps)
+ if( nps<np(2,i) ) n_i8 = min(n_i8,np(2,i)-nps)
enddo

! Determine the number of microtasks.
- if( n<mf*ltasks .or. jtasks<0 ) then
+ if( n_i8<int(mf*ltasks,i8knd) .or. jtasks<0 ) then
  nm = ltasks
- elseif( n<lf*ltasks ) then
+ elseif( n_i8<int(lf*ltasks,i8knd) ) then
  nm = min(mf*ltasks,mn)
else
  nm = min(lf*ltasks,mn)
@@ -208,16 +219,16 @@

! Set nps ranges for each microtask.
do i = 1,nm
- nc(i,1) = nps+int(float(n*i)/nm)
- nc(i,2) = 0
- nc(i,3) = 0
+ nc(i,1) = nps+int(real(n_i8*int(i,i8knd),dknd)/nm,i8knd)
+ nc(i,2) = 0_i8knd
+ nc(i,3) = 0_i8knd
enddo
nc(0,1) = nps
- nc(nm,1) = nps+n
+ nc(nm,1) = nps+n_i8
call getidt(hd)
- write(jtty,(' master set rendezvous nps =",i10,5x,a19)') nps+n, hd
+ write(jtty,(' master set rendezvous nps =",i12,3x,a19)') nps+n_i8, hd
if( mct>=0 )&
- & write(iuo,(' master set rendezvous nps =",i10,5x,a19)') nps+n, hd
+ & write(iuo,(' master set rendezvous nps =",i12,3x,a19)') nps+n_i8, hd

! Send nps ranges for all microtasks.
@@ -236,6 +247,7 @@
call msg_put( ddn, 1, 24*ndnd)
call msg_put( dxd, 1, mipt*24*mxdx)
call msg_put( gvarcm, 1, nvarcm)
+ call msg_put( i8varcm,1, l8varcm)
call msg_put( jvarcm, 1, lvarcm)
call msg_put( nbal, 1, size(nbal))
call msg_put( rdum, 1, n_rdum )
@@ -260,7 +272,7 @@
! Clear the interrupt and check for an available host.
200 continue
if( irup/=0 ) then
- call qttyin( max(1,nc(nk,1)), ' "dmmp microtask assignment, nps =",i9' )
+ call qttyin( max(1_i8knd,nc(nk,1)), ' "dmmp microtask assignment, nps =",i12' )

```

```

endif

! Fault tolerance for PVM only.
@@ -363,6 +375,7 @@
  call dm_rcv(-2,4,i)
  call dm_rcvi(i,nh)
  call msg_get( gtskcm, 1, nvarsw)
+  call msg_get( i8tskcm, 1, l8varsw)
  call msg_get( jtskcm, 1, lvarsw)
  call msg_get( ktskpt, 1, ltskpt-1)

@@ -385,13 +398,13 @@
  call fmesh_msgcon

! Receive output variables not updated in vtask.
-  call msg_get( n )
-  if( n/=0 ) then
+  call msg_get( ni8knd )
+  if( ni8knd/=0 ) then
    call msg_get( m )
    call msg_get( hs )
    call msg_get( hm )
-  if( kdbnps==0 ) then
-  kdbnps = n
+  if( kdbnps==0_i8knd ) then
+  kdbnps = ni8knd
  mmkdb = m
  hsub = hs
  hmes = hm
@@ -435,10 +448,10 @@
      nkrp = nkrp+n-m5
      call msg_get( n )
      jtlx = jtlx+n-m6
-  call msg_get( n )
-  nqsw = nqsw+n
-  call msg_get( n )
-  nrsw = nrsw+n
+  call msg_get( ni8knd )
+  nqsw = nqsw+ni8knd
+  call msg_get( ni8knd )
+  nrsw = nrsw+ni8knd
  do k = 1,njss+nilw
    do j = 1,2+4*mipt
      call msg_get( n )
@@ -461,12 +474,12 @@
  enddo
  do j = 1,ndnd
    call msg_get( a )
-  ddn(22,j) = ddn(22,j)+dble(nint(a))
+  ddn(22,j) = ddn(22,j)+real(nint(a),dknd)
  enddo
  do k = 1,mxdx*min(1,nxnx)
    do j = 1,mipt
      call msg_get( a )
-  dxd(j,22,k) = dxd(j,22,k)+dble(nint(a))
+  dxd(j,22,k) = dxd(j,22,k)+real(nint(a),dknd)
  enddo
  enddo

@@ -504,7 +517,7 @@
  enddo DO_360

! Step through the microtasks in order - to preserve tracking.
-  nc(0,2) = 0
+  nc(0,2) = 0_i8knd
  DO_430: do mt = 1,nm
    nh = nc(mt,2)
    nc(nh,3) = nc(nh,3)+1
@@ -572,16 +585,16 @@
  nn = nm
  nx = 1

```

```

do nt = 1,ltasks
-   nn = min(nn,nc(nt,3))
-   nx = max(nx,nc(nt,3))
+   nn = min(int(nn,i8knd),nc(nt,3))
+   nx = max(int(nx,i8knd),nc(nt,3))
enddo
-   lf = nint((float(nx)/float(max(1,nn)))**3)
+   lf = nint((real(nx)/real(max(1,nn)))**3)
   lf = min(lf,30)
   lf = max(lf,mf)
endif

! Undo nst=4 and reset appropriately.
-   if( (nps<npp .or. npp==0) .and. mod(nst/4,2)/=0 ) nst = nst-4
+   if( (nps<npp .or. npp==0_i8knd) .and. mod(nst/4,2)/=0 ) nst = nst-4
! check for max time used
   if( ctme/=0.0 .and. cts>=ctme*60. ) nst = nst + 32
   if( krtm/=0 .and. nst/=0 ) mrm = 1
diff -Naurd MCNP5/Source/src/msgtsk.F90 MCNP5_new/Source/src/msgtsk.F90
--- MCNP5/Source/src/msgtsk.F90      2003-11-05 17:23:12.000000000 -0700
+++ MCNP5_new/Source/src/msgtsk.F90  2004-07-22 15:14:42.000000000 -0600
@@ -20,8 +20,8 @@

integer          :: mn
real(dknd)       :: rg(11)
- integer,allocatable :: nc(:, :)
- integer(i8knd)     :: i8a, i8b, i8c, i8d
+ integer(i8knd),allocatable :: nc(:, :)
+ integer(i8knd)       :: i8a, i8b, i8c, i8d, i8i
character(len=130) :: hf
logical          :: file_open
#ifdef AIX
@@ -46,13 +46,18 @@
call dm_rcv(-1,4,i)
call secnd(t1)
call msg_get( gfixcm, 1, nfixcm )
- call msg_get( jfixcm, 1, lfixcm )
call msg_get( i8fixcm, 1, l8fixcm )
+ call msg_get( jfixcm, 1, lfixcm )
+
call msg_get( gvarcm, 1, nvarcm )
+ call msg_get( i8varcm, 1, l8varcm )
call msg_get( jvarcm, 1, lvarcm )
+
call msg_get( rdum, 1, n_rdum )
call msg_get( idum, 1, n_idum )
+
call msg_get( gepbcm, 1, nepbcm )
+ call msg_get( i8epbcm, 1, l8epbcm )
call msg_get( jepbcm, 1, lepbcm )

if(jtasks > 0) then
@@ -96,7 +101,7 @@
mt = 1
endif
allocate( gbnk( 1:mbnk*mtasks ) )
- allocate( ibnk( 1:(nbmx*(lpblcm+2*abs(iunr))+1)*mtasks ) )
+ allocate( ibnk( 0:(nbmx*(lpblcm+2*abs(iunr))+1)*mtasks ) )
allocate( tal( 1:(nmxf*mxkf+ktls)*mt ) )
gbnk = 0.0
ibnk = 0
@@ -169,6 +174,7 @@
call msg_get( ddn, 1, 24*ndnd)
call msg_get( dxd, 1, mipt*24*mxdx)
call msg_get( gvarcm, 1, nvarcm )
+ call msg_get( i8varcm, 1, l8varcm )
call msg_get( jvarcm, 1, lvarcm )
call msg_get( nbal, 1, size(nbal))
call msg_get( rdum, 1, n_rdum )
@@ -203,9 +209,10 @@
endif

```

```

! Clear the swept part of varcom.
- gvarcm(1:nvarsw) = 0.
- jvarcm(1:lvarsw) = 0
- wgts(1) = huge
+ gvarcm(1:nvarsw) = 0.
+ i8varcm(1:i8varsw) = 0_i8knd
+ jvarcm(1:lvarsw) = 0
+ wgts(1) = huge_float

call RN_init_problem( new_standard_gen = RN_gen_input,      &
&
& new_seed = RN_seed_input,      &
@@ -234,8 +241,8 @@
    if( mt==nm ) kbp = 0
endif
! Skip over starters from previous chunks.
- do i = nps+1,nc(mt-1,1)
- nps = nps+1
+ do i8i = nps+1_i8knd,nc(mt-1,1)
+ nps = nps+1_i8knd
call RN_init_particle( int(nps,i8knd) )
if( nsr==6 ) then
call sursrc(1)
@@ -323,6 +330,7 @@
! Send task common data stored in varcom.
call dm_sndi
call msg_put( gvarcm, 1, nvarsw)
+ call msg_put( i8varcm, 1, i8varsw)
call msg_put( jvarcm, 1, lvarsw)
call msg_put( ktskpt, 1, ltskpt-1)
call dm_send(0,4,i)
diff -Naurd MCNP5/Source/src/namrsd.F90 MCNP5_new/Source/src/namrsd.F90
--- MCNP5/Source/src/namrsd.F90      2003-04-30 20:11:44.000000000 -0600
+++ MCNP5_new/Source/src/namrsd.F90  2004-07-22 15:14:42.000000000 -0600
@@ -15,6 +15,7 @@
! Modules used:
use mcnp_global
use mcnp_debug
+ use erprnt_mod
implicit real(dknd) (a-h,o-z)
character(len=*) :: hh
character(len=120) :: hs
diff -Naurd MCNP5/Source/src/newcd1.F90 MCNP5_new/Source/src/newcd1.F90
--- MCNP5/Source/src/newcd1.F90      2003-04-30 20:11:46.000000000 -0600
+++ MCNP5_new/Source/src/newcd1.F90  2004-07-22 15:14:42.000000000 -0600
@@ -10,6 +10,8 @@
use mcnp_debug
use mcnp_input
use dynamic_arrays
+ use qttyin_mod, only: qttyin
+ use erprnt_mod, only: erprnt

implicit real(dknd) (a-h,o-z)

@@ -76,9 +78,6 @@
return
100 continue
ndup(min(ica,3)) = ndup(min(ica,3))+1
-#ifndef PCDOS
- if(lockl) call ptttyin
-#endif /*def.pcdos*/
if(irup /= 0) call qttyin(0,"reading input cards. '//ich//'")

! Do the processing necessary for the particular card type.
@@ -124,8 +123,9 @@

if((ich == 'de'.or.ich == 'df').and.icn/=0) return
if (ich == 'fm') return !The 'fm' card is also used by the mesh tallies
-
+
if( ich=='dd' .and. (icn==1 .or. icn==2) ) return

```

```

+
+   i = icn+1000*nqw
+   do itat_tmp=0,ntal
+     ital = ital_tmp
@@ -209,6 +209,17 @@
+   case (96) !====> third spare card type                                zc
+     continue

+   case (102) !====> force use of lattice speed tally modifications  spdtl
+   call nxtsym(hlin, ' ',1,istart,ifinish,1)          ! Find card name
+   call nxtsym(hlin, ' ',ifinish+1,istart,ifinish,1) ! Find keyword
+   if ( ifinish == 0 ) call erprnt(2,1,0,0,0,0,0,0,&
+     & "spdtl card must have exactly one keyword, either force or off.")
+   if ( hlin(istart:ifinish) /= 'force' .and. hlin(istart:ifinish) /= 'off' ) &
+     & call erprnt(2,1,0,0,0,0,0,0,"spdtl card must have exactly one keyword, either
force or off.")
+   if ( hlin(istart:ifinish) == 'force' ) flag_speed_tally_force = 1
+   if ( hlin(istart:ifinish) == 'off' ) flag_speed_tally_force = -1
+   continue
+
+   case default !====> default - do nothing
+     continue

diff -Naurd MCNP5/Source/src/newcrd.F90 MCNP5_new/Source/src/newcrd.F90
--- MCNP5/Source/src/newcrd.F90      2003-04-30 20:11:46.000000000 -0600
+++ MCNP5_new/Source/src/newcrd.F90  2004-07-22 15:14:42.000000000 -0600
@@ -8,6 +8,8 @@
+   use mcnp_debug
+   use mcnp_input
+   use fmesh_mod
+   use qttyin_mod, only: qttyin
+   use erprnt_mod, only: erprnt

+   implicit real(dknd) (a-h,o-z)
+   character(len=8) :: ht
@@ -87,9 +89,6 @@
+   call erprnt(2,1,0,0,0,0,0,1,"'//ich//' is not a legal data symbol.")
+   return
+   80 continue
-#ifdef PCDOS
-  if(lockl)call ptttyin
-#endif
+   if( irup/=0 ) call qttyin(0,"reading input cards.      '//ich)
+   if( krq(2,ica)/=0 .and. nqw==0 ) then
+     call erprnt(2,1,0,0,0,0,0,1, "particle-type designator is missing.")
@@ -189,6 +188,9 @@
+     & "dxtran cell probabilities without '//hnp(i)//' dxtran spheres.")
+   endif
+   end do
+   if ( flag_speed_tally_ok == 1 ) flag_speed_tally_ok= -1
+   if ( flag_speed_tally_force == 1 ) call erprnt(2,3,0,0,0,0,0,0,&
+     & "lattice speed tally conflicts with dxc card.")
+   go to 9010

+   case( 17 )
@@ -259,7 +261,45 @@
+     return
+   endif
+   350 continue
+   !
+
+   ! Checks for lattice speed tally criteria
+   ! Print warning about conflict if spdtl force card is used
+   iy = mod(icn,10)
+   if ((ich=='ft' .or. ich=='cf' .or. ich=='sf' .or. ich=='t' .or. &
+     & ich=='e' .or. ich=='tm' .or. ich=='cm' .or. ich=='em' .or. &
+     & ich=='sf' .or. ich=='c' .or. ich=='fs') .and. iy/=5 ) then
+     if ( flag_speed_tally_ok == 1 ) flag_speed_tally_ok = -1
+     if ( flag_speed_tally_force == 1 ) call erprnt(2,3,1,icn,0,0,0,0,&
+       & "lattice speed tally conflicts with '//ich(1:3)//' card for tally",i4,"")
+   endif

```

```

+
+   if ( ich == 'f' ) then
+     ! Set flags for fm and de,df cards.
+     flag_speed_tally_fm(ital,2)=icn
+     flag_speed_tally_de(ital,2)=icn
+     ! Exclude all tallies except F4 for lattice speed tally
+     if ( iy==1 .or. iy==2 .or. iy==3 .or. &
+       & iy==6 .or. iy==7 .or. iy==8) then
+       if ( flag_speed_tally_ok == 1 ) flag_speed_tally_ok = -1
+       if ( flag_speed_tally_force == 1 ) call erprnt(2,3,1,icn,0,0,0,0,&
+         & '"lattice speed tally conflicts with tally",i4, ". "')
+     endif
+     if ( iy==4 ) then
+       ! exclude *F4 tallies for lattice speed tally
+       if ( icx /= 0 ) then
+         if ( flag_speed_tally_ok == 1 ) flag_speed_tally_ok = -1
+         if ( flag_speed_tally_force == 1 ) call erprnt(2,3,1,icn,0,0,0,0,&
+           & '"lattice speed tally conflicts with *f4 tally",i4, ". "')
+       endif
+       ! check for [] on f4 tally line for lattice speed tally
+       i = 0
+       i = index(klin,[''])
+       if ( i <= 3 .and. flag_speed_tally_ok == 1 ) flag_speed_tally_ok = -1
+       if ( i <= 3 .and. flag_speed_tally_force == 1 ) &
+         & call erprnt(2,3,1,icn,0,0,0,0,&
+           & '"lattice speed tally needs lattice index range [] for tally",i4, ". "')
+     endif
+   endif
+   !
+   if( ich=='fq' ) then
+     do i=1,8
+       jfq(i,ital) = i
+@@ -355,6 +395,7 @@
+       ! >>>> tally multiplier
+       ! m3c = 0 tally multiplier card
+       ! = 1 mesh tally multiplier card
+
+     m3c=1
+     ital=0
+     do ital_tmp=1,ntal
+@@ -363,7 +404,7 @@
+       exit
+     endif
+   enddo
+
+
+
+
+   if(m3c==1) then
+     nfm=nfm+1
+     meshfm(nfm)=icn
+@@ -376,6 +417,8 @@
+     ipnt(1,krq(3,ica),ital) = ipl+1
+   endif
+
+   ! Set flag for spdtl that de df cards for tally ital exist
+   if (m3c == 0) flag_speed_tally_fm(ital,1)=icn
+
+   case( 35,36)
+     ! >>>> response functions
+@@ -406,8 +449,20 @@
+     ipnt(1,krq(3,ica),ital) = ipl+1
+   endif
+
+   ! Set flag for spdtl that de df cards for tally ital exist
+   if( ital==0 ) then
+     flag_speed_tally_de(ital,1)=1000 ! flag for fm0 cards
+   else
+     flag_speed_tally_de(ital,1)=icn
+   endif
+
+   case( 47 )
+     ! >>>> dxtran parameters
+
+

```

```

+   if ( flag_speed_tally_ok == 1 ) flag_speed_tally_ok= -1
+   if ( flag_speed_tally_force == 1 ) call erprnt(2,3,0,0,0,0,0,0,&
+     & '"lattice speed tally conflicts with dxt card."')
+
+   if( nqp(3)/=0 ) then
+     call erprnt(2,1,0,0,0,0,0,1,&
+       & ' "dxtran is not available for electrons."' )
@@ -467,9 +522,19 @@
+     call erprnt(2,1,0,0,0,0,0,0,&
+       & ' "ksrc and sdef cards are incompatible."' )
+   endif
+
+ case( 71 )
+ ! >>>> weight-window generator parameters                               wwg
+ if ( flag_speed_tally_ok == 1 ) flag_speed_tally_ok = -1
+ if ( flag_speed_tally_force == 1 ) call erprnt(2,3,0,0,0,0,0,0,&
+   & '"lattice speed tally conflicts with wwg card."')
+
+ case( 72 )
+ ! >>>> energy bins for weight-window generator                               wwge
+ if ( flag_speed_tally_ok == 1 ) flag_speed_tally_ok = -1
+ if ( flag_speed_tally_force == 1 ) call erprnt(2,3,0,0,0,0,0,0,&
+   & '"lattice speed tally conflicts with wwge card."')
+
+ if( iwwg==0 ) then
+   call erprnt(2,1,0,0,0,0,0,0,&
+     & '""//ich//'card without any wwg card."' )
@@ -537,6 +602,9 @@
+   call erprnt(2,2,0,0,0,0,0,0,&
+     & ' "this perturbation is not consistent with the problem mode."' )
+   endif
+ if ( flag_speed_tally_ok == 1 ) flag_speed_tally_ok = -1
+ if ( flag_speed_tally_force == 1 ) call erprnt(2,3,0,0,0,0,0,0,&
+   & '"lattice speed tally conflicts with pert card."')
+
+ case( 86 )
+ ! >>>> superimposed weight window generator mesh                               mesh
diff -Naurd MCNP5/Source/src/nexttit.F90 MCNP5_new/Source/src/nexttit.F90
--- MCNP5/Source/src/nexttit.F90      2003-04-30 20:11:48.000000000 -0600
+++ MCNP5_new/Source/src/nexttit.F90   2004-07-22 15:14:42.000000000 -0600
@@ -8,6 +8,7 @@
+ use mcnp_debug
+ use mcnp_input
+ use fmesh_mod
+ use erprnt_mod

implicit real(dknd) (a-h,o-z)
character(len=75) :: ht
@@ -475,7 +476,7 @@
+ ! >>>> tally multiplier                                                     fm
+ ! m3c = 0  tally multiplier card
+ !       = 1  mesh tally multiplier card
-   ks = index('():#<[,u=',hitm(1:1))
+   ks = index('():#<[,u=',hitm(1:1))
+   if( m3c==1 ) then
+     if( kitm/=0 ) then
+       fmtmp(nwc,nfm) = ritm
@@ -489,6 +490,14 @@
+       if( ks/=0 ) rtp(ipl+nwc) = 1000000+ks
+     endif
+   endif
+ ! Disable lattice speed tally if more than one entry on fm card.
+ if( mod(icn,10) == 4 .and. m3c == 0 ) then
+   if( nwc > 1 .and. flag_speed_tally_ok == 1 ) flag_speed_tally_ok = -1
+   if( nwc > 1 .and. flag_speed_tally_force == 1 ) call erprnt(2,3,1,icn,0, &
+     & 0,0,0, &
+     & '"lattice speed tally conflicts with multiple entries on fm",i4," card."')
+   endif
+
+ case( 35,36 )

```

```

! >>>> response function
@@ -513,8 +522,10 @@
    else
        intrpol(ndf) = intrpol(ndf)+ 1
    endif
+   nwc = nwc-1
    endif
    if( m2c==0 .or. icn==0 ) then
+   if ( m2c == 1 ) nwc = nwc+1
        rtp(ipl+nwc) = -1.
    endif
    else if(hitm=='log')then
@@ -540,7 +551,7 @@
        return
    endif
    do k = 1,mipt
-   if( ddx(k,i,j)==huge ) ddx(k,i,j) = ritm
+   if( ddx(k,i,j)==huge_float ) ddx(k,i,j) = ritm
    enddo
    endif
    if( kitm/=0 ) then
@@ -757,16 +768,16 @@
    if( nwc==5 .and. ritm==0.) swtm = -1.
    if( nqp(1)/=0 .and. nwc==1 .and. ritm/=0. ) then
        do i = 2,mipt
-   if( tco(i)==.001d0*huge) tco(i) = tco(1)
+   if( tco(i)==.001d0*huge_float) tco(i) = tco(1)
        enddo
    endif

    case( 60 )
! >>>> source particle cutoff number
-   if( nwc==1 ) npp = iitm
-   if( nwc==2 .and. (konrun==0 .or. iitm/=0) ) npsmg = iitm
-   if( konrun/=0 .and. nwc==2 .and. iitm>nps )&
-   & call erprnt(2,2,1,npsmg-nps,0,0,0,0,&
+   if( nwc==1 ) npp = i8itm
+   if( nwc==2 .and. (konrun==0 .or. i8itm/=0_i8knd) ) npsmg = i8itm
+   if( konrun/=0 .and. nwc==2 .and. i8itm>nps )&
+   & call erprnt_i8_kl(2,2,1,npsmg-nps,0,0,0,0,&
+   & ' "adding ",i5, " more source contributions to image."')

    case( 61 )
@@ -787,8 +798,8 @@
        if( nwc==2 ) dmp = ritm
        if( nwc==3 ) mct = iitm
        if( nwc==4 ) ndmp = iitm
-   if( nwc==5 .and. iitm>0 ) npd = iitm
-   if( nwc==5 .and. mcnp_opt_multp ) inpd = iitm
+   if( nwc==5 .and. i8itm>0_i8knd ) npd = i8itm
+   if( nwc==5 .and. mcnp_opt_multp ) inpd = i8itm

    case( 65 )
! >>>> termination and print control for lost particles
@@ -973,7 +984,7 @@
    case( 3 )
        if( nwc==m2c+2 ) then
            ktr(m1c) = trf(2,mxtr)
-   trf(2,mxtr) = huge
+   trf(2,mxtr) = huge_float
            mxtr = mxtr-1
        else
            call trfmat(mxtr)
@@ -1050,7 +1061,7 @@
        if( nwc==m2c+2 ) then
            if( m3c==0) mfl(3,m1c) = trf(2,mxtr)
            if( m3c/=0) laf(3+m1af+3,m3c) = trf(2,mxtr)
-   trf(2,mxtr) = huge
+   trf(2,mxtr) = huge_float
            mxtr = mxtr-1
        else

```



```

        call trfmat(mxtr)
@@ -1118,6 +1129,8 @@
        ptr(iptra(mlc)) = m3c
        if( kitm==1) ptr(m2c) = ritm
        if( kitm==2) ptr(m2c) = iitm
+       if( kitm==2 .and. hptr(mlc)=='nps' ) ptr(m2c) = ritm
+       if( kitm==2 .and. hptr(mlc)=='max' ) ptr(m2c) = ritm
        endif
        else
        if(index(',','hitm(1:1))/=0) return
@@ -1448,6 +1461,13 @@
        ! >>>> real quantities for Recursive Monte Carlo
        rrmc(nwc) = ritm
                                rrmc

+ case( 102 )
+ ! >>>> force lattice speed tally modifications (override appropriate) spdtl
+ if ( flag_speed_tally_ok == 0 ) &
+ & call erprnt(2,2,0,0,0,0,0,0,"spdtl card present, but no lattice. spdtl
ignored."')
+ flag_speed_tally_used = -1
+ continue
+
        end select
        return
    end subroutine nextit
diff -Naurd MCNP5/Source/src/norma.F90 MCNP5_new/Source/src/norma.F90
--- MCNP5/Source/src/norma.F90      2003-04-30 20:11:48.000000000 -0600
+++ MCNP5_new/Source/src/norma.F90  2004-07-22 15:14:42.000000000 -0600
@@ -6,6 +6,7 @@
    use mcnp_global
    use mcnp_debug
    use mcnp_input
+ use erprnt_mod

    implicit real(dknd) (a-h,o-z)

diff -Naurd MCNP5/Source/src/normh.F90 MCNP5_new/Source/src/normh.F90
--- MCNP5/Source/src/normh.F90     2003-04-30 20:11:48.000000000 -0600
+++ MCNP5_new/Source/src/normh.F90  2004-07-22 15:14:42.000000000 -0600
@@ -10,6 +10,7 @@
    use mcnp_global
    use mcnp_debug
    use mcnp_input
+ use erprnt_mod

    implicit real(dknd) (a-h,o-z)

        ! Trim the distribution if it is an energy distribution.
diff -Naurd MCNP5/Source/src/nsourc.F90 MCNP5_new/Source/src/nsourc.F90
--- MCNP5/Source/src/nsourc.F90    2003-04-30 20:11:50.000000000 -0600
+++ MCNP5_new/Source/src/nsourc.F90 2004-07-22 15:14:42.000000000 -0600
@@ -24,6 +24,7 @@
    use mcnp_global
    use mcnp_debug
    use mcnp_input
+ use erprnt_mod

    implicit double precision (a-h,o-z)
    character(len=80) :: hh
diff -Naurd MCNP5/Source/src/nxtit1.F90 MCNP5_new/Source/src/nxtit1.F90
--- MCNP5/Source/src/nxtit1.F90    2003-04-30 20:11:50.000000000 -0600
+++ MCNP5_new/Source/src/nxtit1.F90 2004-07-22 15:14:42.000000000 -0600
@@ -471,6 +471,8 @@
    case( 77 )
        ! >>>> lattice type
        if( iitm/=0 ) nlat = nlat+1
                                lat
+       ! Enable lattice speed tally modifications for hexahedra lattices
+       if( iitm==1 ) flag_speed_tally_ok = 1

    case( 78 )
        ! >>>> cell-filling universes, with transformations
                                fill
diff -Naurd MCNP5/Source/src/oldcd1.F90 MCNP5_new/Source/src/oldcd1.F90

```

```

--- MCNP5/Source/src/oldcd1.F90      2003-04-30 20:11:52.000000000 -0600
+++ MCNP5_new/Source/src/oldcd1.F90  2004-07-22 15:14:42.000000000 -0600
@@ -14,7 +14,7 @@
! space needed for input coefficients for each surface type.
integer :: ns(39) = &
& (/ 4, 1, 1, 1, 1, 4, 2, 2, 2, 3, 3, 3, 1, 1, 1, 5, 5, 5, 3, 3, &
- & 3,10,10, 7, 7, 7, 0, 0, 0,24,15, 4,18,18,10,18,20,24,32 /)
+ & 3,10,10, 7, 7, 7, 0, 0, 0,24,24, 4,18,18,10,18,20,24,32 /)

select case( ica )

diff -Naurd MCNP5/Source/src/oldcrd.F90 MCNP5_new/Source/src/oldcrd.F90
--- MCNP5/Source/src/oldcrd.F90      2003-04-30 20:11:52.000000000 -0600
+++ MCNP5_new/Source/src/oldcrd.F90  2004-07-22 15:14:42.000000000 -0600
@@ -8,8 +8,10 @@
use mcnp_debug
use mcnp_input
use fmesh_mod
+ use erprnt_mod

implicit real(dknd) (a-h,o-z)
+ integer(i8knd) :: k8

! correct number of input coefficients for each surface type.
integer :: ns(39) = &
@@ -195,7 +197,6 @@
! >>>> cell volumes for tallies                                vol
if( novol==0 .or. nwc/=0 ) go to 500
return

-
case( 8 )
! >>>> surface areas for tallies                                area
if( nwc/=mxj ) call erprnt(2,2,2,nwc,mxj,0,0,0,&
@@ -439,7 +440,7 @@
! >>>> various cell data          vol,pwt,ext,fcl,wnw,pd,dxc,tmp,u,lat
if( nwc/=mxa ) call erprnt(2,2,2,nwc,mxa,0,0,0,&
& 'i5, " entries not equal to number of cells =",i5, ".")
- return
+ return

case( 72 )
! >>>> energy bins for weight-window generator                wwge
@@ -553,9 +554,9 @@
cycle DO_700
660 continue
if( n>1 ) go to 650
- k = nint(ptr(j+1))
- if(hptr(i) == 'max'.and.k < 0)iptr=-iptr
- iptra(i) = abs(k)
+ k8 = nint(ptr(j+1),i8knd)
+ if(hptr(i) == 'max'.and. k8 < 0)iptr=-iptr
+ iptra(i) = abs(k8)
cycle DO_700
670 continue
if( n>2 ) go to 650
@@ -840,6 +841,7 @@
end select
return

+
! a common complaint
9010 continue
call erprnt(2,1,0,0,0,0,0,0,' "entries are not monotonically increasing."')
diff -Naurd MCNP5/Source/src/output.F90 MCNP5_new/Source/src/output.F90
--- MCNP5/Source/src/output.F90      2003-04-30 20:11:52.000000000 -0600
+++ MCNP5_new/Source/src/output.F90  2004-07-22 15:14:42.000000000 -0600
@@ -10,6 +10,7 @@
use mcnp_debug
use mcplot_module
use crit1_mod
+ use qttyin_mod, only:qTTYin

```

```

use ra2_mod

implicit real(dknd) (a-h,o-z)
@@ -22,12 +23,12 @@

! Keyboard interrupt.
if( lockl ) call pttin
- if( irup/=0 ) call qttyin(nps,' "output rendezvous, nps =",i9')
+ if( irup/=0 ) call qttyin(nps,' "output rendezvous, nps =",i12')

- if( ntal/=0 .and. npp>=0 ) then
+ if( ntal/=0 .and. npp>=0_i8knd ) then
! Update detector and dxtran russian roulette criteria.
- if( nps==200 .or. jtfc/=0 ) then
+ if( nps==200_i8knd .or. jtfc/=0 ) then
ddn(24,1:ndnd) = ddn(20,1:ndnd)/nps
dxd(1:mipt,24,1:mxdx) = dxd(1:mipt,20,1:mxdx)/nps
endif
@@ -91,14 +92,14 @@
endif

! Write restart (runtp) if required.
- if( mdc+nst/=0 .and. npp>=0 ) then
+ if( mdc+nst/=0 .and. npp>=0_i8knd ) then
call tpefil(4)
tdc = cpl
if( issw/=0 .and. nst/=0 ) call wrwssa
endif

! Write mctal file if required.
- if( mct/=0 .and. (nst/=0 .or. npp<0) ) then
+ if( mct/=0 .and. (nst/=0 .or. npp<0_i8knd) ) then
hf = mctal
call mctalw(hf)
mctal = hf
diff -Naurd MCNP5/Source/src/pconst.F90 MCNP5_new/Source/src/pconst.F90
--- MCNP5/Source/src/pconst.F90 2003-04-30 20:11:56.000000000 -0600
+++ MCNP5_new/Source/src/pconst.F90 2004-07-22 15:14:42.000000000 -0600
@@ -17,7 +17,7 @@
! Write physical constants table.
write(iuo,'( "lphysical constants",85x, "print table 98",2/)' )
write(iuo,'(3x, "name",20x, "value",5x, "description"/)' )
- write(iuo,'(3x, "huge",1ple25.13,5x, "infinity"/)' )huge
+ write(iuo,'(3x, "huge",1ple25.13,5x, "infinity"/)' )huge_float
write(iuo,'(4x, "pie",1ple25.13,5x, "pi"/)' )pie
write(iuo,'(2x, "euler",1ple25.13,5x, "euler constant"/)' )euler
write(iuo,'(1x, "avogad",1ple25.13,5x,&
@@ -66,21 +66,9 @@
#ifdef MCPLOT
write(iuo,'(5x, "mcplot" )' )
#endif /*def.mcplot*/
-#ifdef GKSSIM
- write(iuo,'(5x, "gkssim" )' )
-#endif /*def.gkssim*/
#ifdef XLIB
write(iuo,'(5x, "xlib" )' )
#endif /*def.xlib*/
-#ifdef PCDOS
- write(iuo,'(5x, "pcdos" )' )
-#endif /*def.pcdos*/
-#ifdef LAHEY
- write(iuo,'(5x, "lahey" )' )
-#endif /*def.lahey*/
-#ifdef QWIN
- write(iuo,'( "qwin" )' )
-#endif /*def.qwin*/
#ifdef LINUX
write(iuo,'(5x, "linux" )' )
#endif /*def.linux*/
diff -Naurd MCNP5/Source/src/plotg.F90 MCNP5_new/Source/src/plotg.F90

```

```

--- MCNP5/Source/src/plotg.F90      2003-04-30 20:12:00.000000000 -0600
+++ MCNP5_new/Source/src/plotg.F90  2004-07-22 15:14:42.000000000 -0600
@@ -165,15 +165,9 @@
    if( jvp==0) sl = xhom
    if( jvp==0) tl = yhom
  #endif
-#ifdef LAHEY
-  call WindowOutString(100,5000,hl)
-#else
  call gtx(sl,tl,hl)
-#endif
  if( mcolor>2) call gstxci(kcolor(ncolor+1),0)
-#ifndef LAHEY
  call gxhome(real(xhom),real(yhom))
-#endif
  go to 60
endif

diff -Naurd MCNP5/Source/src/pltdat.F90 MCNP5_new/Source/src/pltdat.F90
--- MCNP5/Source/src/pltdat.F90      2003-04-30 20:12:00.000000000 -0600
+++ MCNP5_new/Source/src/pltdat.F90  2004-07-22 15:14:42.000000000 -0600
@@ -133,9 +133,9 @@
    if( nv<=3 ) return
    f = 0.
    if( nv==4 ) then
-     f = 1./max(nps,1)
-     if( nsr==6 .and. nrrs>=nrss ) f = 1./max(np1,1)
-     if( nsr==6 .and. nrrs<nrss ) f = 1./max(npsr,1)
+     f = 1./max(nps,1_i8knd)
+     if( nsr==6 .and. nrrs>=nrss ) f = 1./max(np1,1_i8knd)
+     if( nsr==6 .and. nrrs<nrss ) f = 1./max(npsr,1_i8knd)
    endif
    if( nv==5 .and. pac(ip,9,iap)/=0. ) f = 1./pac(ip,9,iap)
    if( nv==6 .and. pac(ip,10,iap)/=0. ) f = 1./pac(ip,10,iap)
diff -Naurd MCNP5/Source/src/pltmsh.F90 MCNP5_new/Source/src/pltmsh.F90
--- MCNP5/Source/src/pltmsh.F90      2003-04-30 20:12:02.000000000 -0600
+++ MCNP5_new/Source/src/pltmsh.F90  2004-07-22 15:14:42.000000000 -0600
@@ -248,7 +248,7 @@
    elseif(kk==3 ) then
      if( km(1)==1 ) cycle DO_620
      if( ih==0 ) cycle DO_610
-     cc(1,3) = sin(wr)
+     cc(1,3) = -sin(wr)
      cc(3,1) = cc(1,3)
      cc(1,4) = cos(wr)
      cc(4,1) = cc(1,4)
diff -Naurd MCNP5/Source/src/prhpdf.F90 MCNP5_new/Source/src/prhpdf.F90
--- MCNP5/Source/src/prhpdf.F90      2003-04-30 20:12:06.000000000 -0600
+++ MCNP5_new/Source/src/prhpdf.F90  2004-07-22 15:14:42.000000000 -0600
@@ -16,6 +16,7 @@
    real(dknd) :: pd(59), pl(59), sb(60), sp(59)
    integer    :: np(59)
+   integer(i8knd) :: ns,ni
    character(len=100) :: da = &
      & '-----10-----20-----30-----40-----50&
      & -----60-----70-----80-----90-----100'
@@ -27,7 +28,7 @@
    character(len=7)   :: he
    character(len=8)   :: ha, hf(2)
    character(len=9)   :: hb
-
+
! set the upper(nu) and lower(nl) grid bin limits for score prd.
it = ital+iper*ntal
nu = nhsd(nsp+4,it)-1
@@ -35,145 +36,145 @@
if( nu-nl<=0 ) then
  write(iuo,10)hsb(nl),hsb(nl+1)
  10 format( " print table 161 cannot be done for this tally",&
-     & " because all tallies were between",lpe12.5, " and",e12.5,&

```

```

+      & " because all tallies were between",es12.5, " and",es12.5,&
+      & " which is one tally bin.")
+      return
+    endif
-
+
+    ! set flag no for tallies above hsb(nsp-1) and/or below hsb(1).
+    no = 0
-   if( nhsd(1,it)>0 ) no=1
-   if( nhsd(nsp,it)>0 ) no=no+2
+   if( nhsd(1,it)>0_i8knd ) no=1
+   if( nhsd(nsp,it)>0_i8knd ) no=no+2
+   kp = 59
+   if( no>0 ) kp=58
-
+
+    ! calculate information arrays for the distribution tables.
+    ! nc is the number of bins to collapse to keep table on one page.
+    nc = (nu-nl)/kp+1
-   pg = -huge
-   ps = huge
+   pg = -huge_float
+   ps = huge_float
+   sb(1) = hsb(nl)
-
+
+    ! loop over all of the tally distribution information.
+    k = 0
-   do i=nl,nu,nc
+   do i=nl,nu,nc
+     k = k+1
+     np(k) = 0
-     pd(k) = 0.
-     pl(k) = 0.
-     sp(k) = 0.
-
+     pd(k) = zero
+     pl(k) = zero
+     sp(k) = zero
+
+     ! collapse statistical tally information if necessary.
-     do j=1,nc
+     do j=1,nc
+       if( i+j-1>nu ) exit
+       np(k) = np(k)+nhsd(i+j,it)
+       sp(k) = sp(k)+shsd(i+j,it)
-     end do
-
+     end do
+
+     ! calculate number density in tally bin pd and take the log10.
+     if( np(k)/=0 ) then
+       pd(k) = np(k)*fpi/(hsb(i+j-1)-hsb(i))
-       if( pd(k)>0. ) pl(k)=log10(pd(k))
+       if( pd(k)>zero ) pl(k)=log10(pd(k))
+       ps = min(ps,pl(k))
+       pg = max(pg,pl(k))
+     endif
+     sb(k+1) = hsb(i+j-1)
-   end do
-
+   end do
+
+   ! set up constants to give from 1 to 100 characters on a line.
-   d = 100./(1.01*(pg-ps))
-   pt = 1.01*ps-.01*pg
-
+   d = hundred/(1.01_dknd*(pg-ps))
+   pt = 1.01_dknd*ps-hundredth*pg
+
+   ! create a character line with a 'd' approximately every decade.

```

```

j = 1
ld = nint(d)
ls = ld
- do i=2,100
+ do i=2,100
    dl(i) = '-'
    ll(i) = ' '
-   if( mod(i,ld)/=0 ) cycle
+   if( mod(i,ld)/=0 ) cycle
    dl(i) = 'd'
    if( ls>6 .or. mod(j,3)==0 ) ll(i)='|'
    j = j+1
    ld = nint(j*d)
- end do
-
+ end do
+
! set some character and other variables for later use.
- t5 = min(10.+zero,tfc(5,nn,it))
- if( t5<=1. .and. t5/=0. ) t5=10.
+ t5 = min(ten,tfc(5,nn,it))
+ if( t5<=one .and. t5/=zero ) t5=ten
t6 = tfc(6,nn,it)
tb = shsd(nspt,it)
- if( t5==0. .or. t5==10. ) tb=hsb(nsp-1)
+ if( t5==zero .or. t5==ten ) tb=hsb(nsp-1)
hb = ',s=slope)'
if( tb==hsb(nsp-1) ) hb=' '
he = ' '
- if( hsb(nsp)<0. ) he='[f(-x)]'
+ if( hsb(nsp)<zero ) he='[f(-x)]'
j1 = jptal(1,ital)
-
+
! print the history tally probability density function plot.
sm = hsb(nsp)*shsd(nsp+2,it)/nhsd(nsp+2,it)
write(iuo,80) j1,he,sm,nps,t5,(dl(j),j=1,100)
80 format(/ "lunnormed tally density for tally",i4,1x,a7,4x, "nonzero",&
- & " tally mean(m) =",1pe10.3,3x, "nps =",i10,4x, "print table 161",&
+ & " tally mean(m) =",es10.3,3x, "nps =",i12,2x, "print table 161",&
& 2/," abscissa",13x, " ordinate",2x, " log plot of tally",&
& " probability density function in tally fluctuation chart bin",&
- & "(d=decade,slope=",0pf4.1, ")/"&
+ & "(d=decade,slope=",f4.1, ")/"&
& " tally number num den log den:",100a1)
-
+
! loop over k table lines and check for mean(m) line.
ny = 0
DO_160: do i=1,k
    n = 0
-   if( np(i)>0. ) n=nint((pl(i)-pt)*d)
+   if( np(i)>0 ) n=nint((pl(i)-pt)*d)
    ch = '*'
    if( sm>sb(i) .and. sm<=sb(i+1) ) ch='m'
-
+
! delete the e from two floating point numbers for tight print.
- write(hb,'(1pe9.2)') sb(i+1)
+ write(hb,'(es9.2)') sb(i+1)
hf(1) = hb(1:5)//hb(7:9)
- write(hb,'(1pe9.2)') pd(i)
+ write(hb,'(es9.2)') pd(i)
hf(2) = hb(1:5)//hb(7:9)
-
+
! create a line for the print plot for the ith line.
- do j=1,100
+ do j=1,100
    l2(j) = ll(j)
- end do

```

```

-   do j=1,n
+   end do
+   do j=1,n
      if( l2(j)/='|' ) l2(j)=ch
-   end do
-
+   end do
+
      ! set location of s for printed pareto tail plot at average sb.
-   ! log point for a pareto is t5*log10(1.+t6*(avg sb)/(t5-1.))
+   ! log point for a pareto is t5*log10(one+t6*(avg sb)/(t5-one))
      ! location nz=ny-d*(log10(sb(i+1)>tb)-log10(first sb(i+1)>tb)).
      if( tb<sb(i+1) ) then
        if( ny==0 ) then
          ny = min(n+10,100)
          if( l2(ny)=='|' ) ny=ny-1
          l2(ny) = 's'
-         ty = ny+d*t5*log10(t6*(1.+t6*(0.7*sb(i)+0.3*sb(i+1))/(t5-1.)))
+         ty = ny+d*t5*log10(t6*(one+t6*(0.7_dknd*sb(i)+0.3_dknd*sb(i+1))/(t5-one)))
        else
-         nz = nint(ty-d*t5*log10(t6*(1.+t6*(0.7*sb(i)+0.3*sb(i+1))/(t5-1.))))
+         nz = nint(ty-d*t5*log10(t6*(one+t6*(0.7_dknd*sb(i)+0.3_dknd*sb(i+1))/(t5-one))))
          if( nz>1 .and. nz<=100 ) l2(nz)='s'
        endif
      endif
-
+
      ! write a line of the printed plot of the history tally pdf.
      if( np(i)<=999999 ) then
        write(iuo,130) hf(1),np(i),hf(2),pl(i),(l2(j),j=1,100)
130   format(a8,i7,a8,f8.3,1x,100a1)
      else
-       write(ha,'(lpe8.1)') real(np(i))
+       write(ha,'(es8.1)') real(np(i))
        he = ha(1:4)//ha(6:8)
        write(iuo,150) hf(1),he,hf(2),pl(i),(l2(j),j=1,100)
150   format(a8,a7,a8,f8.3,1x,100a1)
      endif
      end do DO_160
-
+
      ! print the total line for the printed history tally pdf plot.
      ns = nhSD(nsp+2,it)-nhSD(1,it)-nhSD(nsp,it)
-     write(hb,'(lpe9.2)') float(ns)
+     write(hb,'(es9.2)') real(ns)
      hf(1) = hb(1:5)//hb(7:9)
-     write(hb,'(lpe9.2)') ns*fpi
+     write(hb,'(es9.2)') ns*fpi
      hf(2) = hb(1:5)//hb(7:9)
      if( ns<=9999999 ) then
        write(iuo,170) ns,hf(2),(dl(j),j=1,100)
@@ -182,23 +183,23 @@
        write(iuo,180) hf(1),hf(2),(dl(j),j=1,100)
180   format(2x, "total",2a8,9x,100a1)
      endif
-
+
      ! write any history tallies that were outside the values in hsb.
      kp = 26
      if( no/=0 ) then
        kp = 25
        if( no==1 ) write(iuo,190) nhSD(1,it)
-190 format( " a total of",i10,&
+190 format( " a total of",i12,&
          & " tallies were below the score grid bin boundaries.")
        if( no==2 ) write(iuo,200) nhSD(nsp,it)
-200 format( " a total of",i10,&
+200 format( " a total of",i12,&
          & " tallies were above the score grid bin boundaries.")
        if( no==3 ) write(iuo,210) nhSD(1,it),nhSD(nsp,it)
-210 format( " a total of",i10, " tallies were below and",i10,&

```

```

+210 format( " a total of",i12, " tallies were below and",i12,&
& " tallies were above the score grid bin boundaries.")
endif
if( ink(162)==0 ) return
-
+
! calculate and print the cumulative tally number table.
ch = '1'
if( k<=kp ) then
@@ -208,40 +209,40 @@
endif
write(iuo,250) ch,j1,he,sm,nps
250 format(a1, "cumulative tally number for tally",i4,1x,a7,3x,&
& "nonzero tally mean(m) =",1pe10.3,3x, "nps =",i10,4x,&
+ "nonzero tally mean(m) =",es10.3,3x, "nps =",i12,2x,&
& "print table 162")
write(iuo,260)da
260 format(/ " abscissa",4x, " cum ordinate",3x, " plot of the",&
& " cumulative number of tallies in the tally fluctuation chart",&
& " bin from 0 to 100 percent"/ " tally number cum pct:",&
& a100)
-
+
! loop over k table lines and check for mean(m) line.
n = nhsd(1,it)-nhsd(nsp+1,it)
- do i=1,k
+ do i=1,k
n = n+np(i)
ch = '*'
if( sm>sb(i) .and. sm<=sb(i+1) ) ch='m'
- do j=1,100
+ do j=1,100
l2(j) = h(j)
- end do
- l = nint(100.*n/ni)
- do j=1,l
+ end do
+ l = nint(hundred*n/ni)
+ do j=1,l
if( l2(j)/='|' ) l2(j)=ch
- end do
+ end do
if( n<=9999999 ) then
- write(iuo,290) sb(i+1),n,100.*n/ni, (l2(j),j=1,100)
-290 format(1pe12.5,i9,0pf9.3, "|",100a1)
+ write(iuo,290) sb(i+1),n,hundred*n/ni, (l2(j),j=1,100)
+290 format(es12.5,i9,f9.3, "|",100a1)
else
- write(hb,'(1pe9.2)') float(n)
+ write(hb,'(es9.2)') real(n)
hf(1) = hb(1:5)//hb(7:9)
- write(iuo,310) sb(i+1),hf(1),100.*n/ni, (l2(j),j=1,100)
-310 format(1pe12.5,1x,a8,0pf9.3, "|",100a1)
+ write(iuo,310) sb(i+1),hf(1),hundred*n/ni, (l2(j),j=1,100)
+310 format(es12.5,1x,a8,f9.3, "|",100a1)
endif
- end do
- write(iuo,330) ns,100.*n/nhds(nsp+2,it),da
+ end do
+ write(iuo,330) ns,hundred*n/nhds(nsp+2,it),da
330 format(4x, "total",i12,f9.3, ":",a100)
-
+
! write any history tallies that were outside the values in hsb.
kp = 15
if( no/=0 ) then
@@ -250,7 +251,7 @@
if( no==2 ) write(iuo,200) nhsd(nsp,it)
if( no==3 ) write(iuo,210) nhsd(1,it),nhsd(nsp,it)
endif
-

```



```

+
! calculate and print the cumulative history tally table.
ch = '1'
if( k<=kp ) then
@@ -259,42 +260,42 @@
endif
write(iuo,360) ch,j1,he,sm,nps
360 format(/,a1, "cumulative unnormed tally for tally",i4,1x,a7,1x,&
- & "nonzero tally mean(m) =",1pe10.3,3x, "nps =",i10,4x,&
+ & "nonzero tally mean(m) =",es10.3,3x, "nps =",i10,4x,&
& "print table 162")
write(iuo,370) da
370 format(/ " abscissa",4x, " cum",3x, " ordinate",15x, " plot of",&
& " the cumulative tally in the tally fluctuation chart bin from",&
& " 0 to 100 percent"/ " tally tally/nps cum pct:",a100)
-
+
! loop over k table lines and check for mean(m) line.
- do i=1,k
+ do i=1,k
bg = bg+sp(i)*fpi
ch = '*'
if( sm>sb(i) .and. sm<=sb(i+1) ) ch='m'
- do j=1,100
+ do j=1,100
l2(j) = h(j)
- end do
- l = nint(100.*bg/dn)
- do j=1,l
+ end do
+ l = nint(hundred*bg/dn)
+ do j=1,l
if( l2(j)/='|' ) l2(j)=ch
- end do
- write(iuo,410) sb(i+1),bg,bg/dn,(l2(j),j=1,100)
- end do
-410 format(1pe10.3,e11.3,1x,2pf8.3, "|",100a1)
+ end do
+ write(iuo,410) sb(i+1),bg,hundred*bg/dn,(l2(j),j=1,100)
+ end do
+410 format(es10.3,es11.3,1x,f8.3, "|",100a1)
write(iuo,420) (shsd(nsp+2,it)-shsd(1,it))-&
- & shsd(nsp,it))*fpi,bg/dn,da
-420 format(3x, "total",1pe13.5,1x,2pf8.3, ":",a100)
-
+ & shsd(nsp,it))*fpi,hundred*bg/dn,da
+420 format(3x, "total",es13.5,1x,f8.3, ":",a100)
+
! write any history tallies that were outside the values in hsb.
if( no==0 ) return
if( no==1 ) write(iuo,430) hsb(nsp)*shsd(1,it)*fpi
-430 format( " a total tally/nps of",1pe12.5,&
+430 format( " a total tally/nps of",es12.5,&
& " was below the score grid bin boundaries.")
if( no==2 ) write(iuo,440) hsb(nsp)*shsd(nsp,it)*fpi
-440 format( " a total tally/nps of",1pe12.5,&
+440 format( " a total tally/nps of",es12.5,&
& " was above the score grid bin boundaries.")
if( no==3 ) write(iuo,450) hsb(nsp)*shsd(1,it)*fpi,hsb(nsp)*shsd(nsp,it)*fpi
-450 format( " total tallies/nps of",1pe12.5, " were below and",&
- & es12.5, " were above the score grid bin boundaries.")
+450 format( " total tallies/nps of",es12.5, " were below and",&
+ & es12.5, " were above the score grid bin boundaries.")
return
end subroutine prhpdf
diff -Naurd MCNP5/Source/src/prinv.F90 MCNP5_new/Source/src/prinv.F90
--- MCNP5/Source/src/prinv.F90 2003-04-30 20:12:08.000000000 -0600
+++ MCNP5_new/Source/src/prinv.F90 2004-07-22 15:14:42.000000000 -0600
@@ -8,6 +8,7 @@
use mcnp_global
use mcnp_input

```

```

    use mcnp_debug
+   use erprnt_mod

    implicit real(dknd) (a-h,o-z)
    real(dknd) :: nt(20)
diff -Naurd MCNP5/Source/src/prlost.F90 MCNP5_new/Source/src/prlost.F90
--- MCNP5/Source/src/prlost.F90      2003-04-30 20:12:08.000000000 -0600
+++ MCNP5_new/Source/src/prlost.F90  2004-07-22 15:14:42.000000000 -0600
@@ -14,9 +14,9 @@
    character(len=8) :: hw(2) = ('newcel ', 'track  ' /)
    integer :: ip(29) = (/0,1,2,3,4,0,1,2,3,0,0,0,1,2,3,0,0,0,1,2,3,0,0,1,2,3,1,2,3/)

-   !$OMP ATOMIC
+   !$OMP CRITICAL      (UPDATE_VARCOM)
    nerr = nerr+1
-
+   !$OMP END CRITICAL (UPDATE_VARCOM)
    !$OMP CRITICAL (PRINT_OUTPUT)

    ! once only, send geometry error message to the tty.
@@ -49,7 +49,7 @@
    if( kfq/=0 ) write(hf, '(i6, ".", i1)') jq, kfq
    write(iuo, 50) nerr, npstc, hnp(ip), hf, ncl(icl)
    50 format( "1  lost particle no.", i3, 5x, "no cell found in", &
-   & " subroutine newcel", 5x, "history no.", i9, 2/, " the ", a8, &
+   & " subroutine newcel", 5x, "history no.", i12, 2/, " the ", a8, &
    & " currently being tracked has reached surface", a8, "; there"/&
    & " appears to be no cell on the other side of the surface from", &
    & " cell", i6/ " at that point.")
@@ -93,7 +93,7 @@
    160 format( " the distance to surface", a8, " from the last event is", &
    & lpe12.5/ " the distance to collision from the last event is", &
    & e12.5/ " the number of ", a8, &
-   & " collisions so far in this history is", i6, ".")
+   & " collisions so far in this history is", i12, ".")

    ! print a list of the rejected cells.
    do il = abs(lca(icl)), nlja
@@ -142,7 +142,7 @@
    230 continue
    write(iuo, 240) nerr, npstc
    240 format( "1  lost particle no.", i3, 5x, "no intersection found in", &
-   & " subroutine track", 5x, "history no.", i9)
+   & " subroutine track", 5x, "history no.", i12)
    if( j1==0 ) write(iuo, 250) hnp(ip), ncl(icl), hnp(ip)
    250 format(/ " the ", a8, " currently being tracked is in cell", i5, ".", &
    & " there appears"/ " to be no surface of the cell in the", &
@@ -162,7 +162,7 @@
    & " u,v,w direction cosines:", 3e15.5/&
    & " energy =", e12.5, 4x, "weight =", e12.5, 4x, "time =", e12.5/&
    & " the distance to collision from the last event is", e12.5/&
-   & " the number of collisions so far in this history is", i6, ".")
+   & " the number of collisions so far in this history is", i12, ".")

    ! ***** check for cone vertex. *****

diff -Naurd MCNP5/Source/src/prstat.F90 MCNP5_new/Source/src/prstat.F90
--- MCNP5/Source/src/prstat.F90      2003-04-30 20:12:10.000000000 -0600
+++ MCNP5_new/Source/src/prstat.F90  2004-07-22 15:14:42.000000000 -0600
@@ -14,11 +14,13 @@

    implicit real(dknd) (a-h,o-z)
    character he*7, hf*8, hg*5
+   integer(i8knd) :: j_i8knd
+   integer(i8knd) :: na, nb, ni, nl, np, nq, nu, nx

    ! check if the tally fluctuation chart (tfc) bin has any tallies.
    it = ital+iper*ntal
    nt = nhsd(nsp+2, it)
-   if( nt<=0 ) then
+   if( nt<=0_i8knd ) then

```

```

        write(iuo,10) jptal(1,ital)
10  format(/ " there are no nonzero tallies in the tally fluctuation",&
        & " chart bin for tally",i4)
@@ -121,7 +123,7 @@
        ! print tally information in the tally fluctuation chart bin.
        write(iuo,50) jptal(1,ital),nps
50  format(/ "1analysis of the results in the tally fluctuation",&
-   & " chart bin (tfc) for tally",i4, " with nps =",i10,4x,&
+   & " chart bin (tfc) for tally",i4, " with nps =",i12,2x,&
        & "print table 160")
        if( hsb(nsp)<0. ) write(iuo,60)
60  format( " the empirical history score probability density",&
@@ -160,8 +162,8 @@
        & " change as follows:")
        j = nps-nint(pax(1,1,1))
        if( j>0 .and. nsr==71 ) write(iuo,110) nint(pax(1,1,1)),ikz,j
-110 format( " nps =",i10, " for this table because",i4, " keff cycles",&
-   & " and",i10, " histories were skipped before tally accumulation.")
+110 format( " nps =",i12, " for this table because",i4, " keff cycles",&
+   & " and",i12, " histories were skipped before tally accumulation.")
        if( mct>=0 ) write(iuo,120) t1,t1*(1.+tc),tc,t2,rm,sqrt(1/rr)-1.,t4,&
        & vm,vr,ac,am,am/ac-1.,t3,t3*rr,rr-1.
        if( mct<0 ) write(iuo,120) t1,t1*(1.+tc),tc,t2,rm,sqrt(1/rr)-1.,t4,&
@@ -211,14 +213,14 @@
        ! see if extreme f(x) values decline monotonically last 5 cycles.
        ! skip the check if f(x) appears bounded or has only one bin.
        if( t5==10. .and. np==0 .or. nu==nl ) go to 260
-   do j = nu-min(5,nu-nl-1),nu
-   if( nhsd(j,it)/=0 ) go to 210
+   do j = nu-min(5_i8knd,nu-nl-1_i8knd),nu
+   if( nhsd(j,it)/=0_i8knd ) go to 210
        enddo
        go to 260
210 continue
        nb = nhsd(j,it)
        do k = j+1,nu+1
-   if( nhsd(k,it)==0 ) cycle
+   if( nhsd(k,it)==0_i8knd ) cycle
        if( nb>nhsd(k,it) ) go to 220
        if( nb+nint(6.*sqrt(float(nb)))<nhsd(k,it) ) go to 240
220 continue
@@ -233,7 +235,7 @@

        ! check for holes in the last 5 bins of the high tally tail.
260 continue
-   do j = nu-min(5,nu-nl-1),nu
+   do j = nu-min(5_i8knd,nu-nl-1),nu
        if( nhsd(j,it)==0 ) go to 290
        enddo
        write(iuo,280)
diff -Naurd MCNP5/Source/src/prtfcc.F90 MCNP5_new/Source/src/prtfcc.F90
--- MCNP5/Source/src/prtfcc.F90      2003-04-30 20:12:10.000000000 -0600
+++ MCNP5_new/Source/src/prtfcc.F90  2004-07-22 15:14:42.000000000 -0600
@@ -9,9 +9,11 @@
        use mcnp_global
        use mcnp_debug
        use ra2_mod
+   use erprnt_mod

        implicit real(dknd) (a-h,o-z)
        character ch,fd(4)*3,mc(3)*8,sr(10)*4
+   integer(i8knd) :: nw

        ! set tfc quantities for later use.
        it = ital+iper*ntal
@@ -22,7 +24,7 @@
        if( t5<=1. .and. t5/=0. ) t5 = 10.

        ! set the statistical check parameters to pass all of the tests.
-   nw = 0
+   nw = 0_i8knd

```

```

do i = 1,4
  fd(i) = 'yes'
enddo
@@ -50,7 +52,7 @@
  nk = nskk
  do i=1,nn
    ! Never use the first tfc bin even if npc(1)>nskk (nh always >1)
-   if( npc(i)>nskk ) exit
+   if( npc(i)>int(nskk,i8knd) ) exit
  enddo
  nh = i + (nn-i)/2 + 1
endif
@@ -72,8 +74,8 @@
  if( tfc(1,j+1,it)>tfc(1,j,it) .and. is==1 .or. &
    & tfc(1,j+1,it)<tfc(1,j,it) .and. is==2 ) go to 80
  enddo
-  nw = nw+1
-  nhsd(nsp+8,it) = 2
+  nw = nw+1_i8knd
+  nhsd(nsp+8,it) = 2_i8knd
  sr(1)=' no'
  mc(1)='decrease'
  if(is == 2)mc(1)='increase'
@@ -85,10 +87,10 @@
  80 continue
  if( t2==0. ) go to 140
  if( t2>=rd ) then
-  nw = nw+1
+  nw = nw+1_i8knd
  sr(2) = ' no'
-  nhsd(nsp+8,it) = 3
-  if( jptal(2,ital)==5 ) nhsd(nsp+8,it) = 4
+  nhsd(nsp+8,it) = 3_i8knd
+  if( jptal(2,ital)==5 ) nhsd(nsp+8,it) = 4_i8knd
  endif

  ! check for a decreasing relative error for last half of problem.
@@ -97,7 +99,7 @@
do i = nb+1,nn
  if( tfc(2,i-1,it)==0.) nr = nr+1
  if( tfc(2,i,it)<=tfc(2,i-1,it) ) cycle
-  t = sqrt(float(npc(i-1)-nk)/float(npc(i)-nk))
+  t = sqrt(real(npc(i-1)-int(nk,i8knd),dknd)/real(npc(i)-int(nk,i8knd),dknd))
  s = npc(i-1)-nk-4*nsrck*(mcheck-ikz)
  if( kcheck>0 .and. kc>mcheck .and. mcheck>ikz .and. s>0. )&
    & t = sqrt(s/(s+npc(i)-npc(i-1)))
@@ -106,15 +108,15 @@
enddo
go to 120
110 continue
-  nw = nw+1
-  if( nw==1 ) nhsd(nsp+8,it) = 5
+  nw = nw+1_i8knd
+  if( nw==1_i8knd ) nhsd(nsp+8,it) = 5_i8knd
  sr(3)=' no'
  fd(1)=' no'
  go to 130

  ! check 1/sqrt(nps) rel error for max(5,last half of problem).
120 continue
-  t = sqrt(float(npc(nr)-nk)/(nps-nk))
+  t = sqrt(real(npc(nr)-int(nk,i8knd),dknd)/(nps-int(nk,i8knd)))
  s = npc(nr)-nk-4*nsrck*(mcheck-ikz)
  if( kcheck>0 .and. kc>mcheck .and. mcheck>ikz .and. s>0.)&
    & t = sqrt(.5*s/pax(1,1,1))
@@ -123,8 +125,8 @@
  if( max(r,1./r)<=max(1.05+zero,sqrt(1.+5.*sqrt(t7)+12.5*t7)))&
    & go to 140
130 continue
-  nw = nw+1
-  if( nw==1 ) nhsd(nsp+8,it) = 6

```

```

+ nw = nw+1_i8knd
+ if( nw==1_i8knd )  nhsd(nsp+8,it) = 6_i8knd
  sr(4)=' no'
  fd(2)=' no'

@@ -132,8 +134,8 @@
  140 continue
    if( t4==0. ) go to 200
    if( t4>=0.1 ) then
-   nw = nw+1
-   if( nw==1 )  nhsd(nsp+8,it) = 7
+   nw = nw+1_i8knd
+   if( nw==1_i8knd )  nhsd(nsp+8,it) = 7_i8knd
    sr(5)=' no'
  endif

@@ -145,8 +147,8 @@
  enddo
  go to 180
  170 continue
-   nw = nw+1
-   if( nw==1 )  nhsd(nsp+8,it) = 8
+   nw = nw+1_i8knd
+   if( nw==1_i8knd )  nhsd(nsp+8,it) = 8_i8knd
    sr(6)=' no'
    fd(3)=' no'
  go to 190
@@ -161,8 +163,8 @@
  r = t*tfc(4,nr,it)/t4
  if( max(r,1./r)<1.5 ) go to 200
  190 continue
-   nw = nw+1
-   if( nw==1 )  nhsd(nsp+8,it) = 9
+   nw = nw+1_i8knd
+   if( nw==1_i8knd )  nhsd(nsp+8,it) = 9_i8knd
    sr(7)=' no'
    fd(4)=' no'

@@ -172,8 +174,8 @@
  r = tfc(3,nb,it)/tfc(3,nn,it)
  t7 = max(tfc(4,nb,it),t4)
  if( max(r,1./r)>=max(1.02+zero,min(1.5+zero, 1.+5.*sqrt(t7)+12.5*t7)) ) then
-   nw = nw+1
-   if( nw==1 )  nhsd(nsp+8,it) = 10
+   nw = nw+1_i8knd
+   if( nw==1_i8knd )  nhsd(nsp+8,it) = 10_i8knd
    sr(8) = ' no'
    mc(2) = 'decrease'
    if( r < 1.)mc(2)='increase'
@@ -187,8 +189,8 @@
    if( tfc(3,j+1,it)>tfc(3,j,it) .and. is==1 .or. &
      & tfc(3,j+1,it)<tfc(3,j,it) .and. is==2 ) go to 230
  enddo
-   nw = nw+1
-   if( nw==1 )  nhsd(nsp+8,it) = 11
+   nw = nw+1_i8knd
+   if( nw==1_i8knd )  nhsd(nsp+8,it) = 11_i8knd
    sr(9) = ' no'
    mc(3) = 'decrease'
    if(is == 2)mc(3)='increase'
@@ -198,18 +200,18 @@
  ! check for a steep enough slope in the extreme history tallies.
  230 continue
  if( t5<3. ) then
-   nw = nw+1
+   nw = nw+1_i8knd
    sr(10) = ' no'
-   if( nw<=1 ) then
-     if( t5/=0.) nhsd(nsp+8,it) = 12
-     if( t5==0. .and. nhsd(nsp+5,it)==0) nhsd(nsp+8,it) = 13
-     if( t5==0. .and. nhsd(nsp+5,it)>0) nhsd(nsp+8,it) = 14

```

```

+   if( nw<=1_i8knd ) then
+     if( t5/=0.)   nhsd(nsp+8,it) = 12_i8knd
+     if( t5==0. .and. nhsd(nsp+5,it)==0) nhsd(nsp+8,it) = 13_i8knd
+     if( t5==0. .and. nhsd(nsp+5,it)>0)  nhsd(nsp+8,it) = 14_i8knd
+   endif
endif

! write the table for the 10 statistical checks.
nhsd(nsp+7,it) = nw
- if( nw==0 ) nhsd(nsp+8,it) = 15
+ if( nw==0 ) nhsd(nsp+8,it) = 15_i8knd
  if( nn-nb<=3 ) write(iuo,250) nn-nb+1
  250 format(2/, " ***** the nps-dependent tfc bin check results are",&
    & " suspect because there are only",i3, " nps tally values to",&
@@ -236,7 +238,7 @@
    write(iuo,270) nw
  270 format( 2/, " warning. the tally in the tally fluctuation chart",&
    & " bin did not pass",i3, " of the 10 statistical checks.")
- call erprnt(1,2,2,jptal(1,ital),nw,0,0,-1,"tally",i4,&
+ call erprnt_i8_k2(1,2,2,jptal(1,ital),nw,0,0,-1,"tally",i4,&
    & " tfc bin did not pass",i3, " of 10 statistical checks.")
  return
endif
diff -Naurd MCNP5/Source/src/psurf.F90 MCNP5_new/Source/src/psurf.F90
--- MCNP5/Source/src/psurf.F90      2003-04-30 20:12:12.000000000 -0600
+++ MCNP5_new/Source/src/psurf.F90  2004-07-22 15:14:42.000000000 -0600
@@ -6,6 +6,7 @@
  use mcnp_global
  use mcnp_input
  use mcnp_debug
+ use erprnt_mod

  implicit real(dknd) (a-h,o-z)

diff -Naurd MCNP5/Source/src/ptfc.F90 MCNP5_new/Source/src/ptfc.F90
--- MCNP5/Source/src/ptfc.F90 2003-04-30 20:12:12.000000000 -0600
+++ MCNP5_new/Source/src/ptfc.F90 2004-07-22 15:14:42.000000000 -0600
@@ -6,6 +6,7 @@

  use mcnp_global
  use mcnp_debug
+ use erprnt_mod, only: erprnt

  implicit real(dknd) (a-h,o-z)
  real(dknd) :: t5(3)
@@ -163,7 +164,7 @@
    write(iuo,230) ('tally',jptal(1,i),i=jt,la)
  230 format(/23x,3(a5,i5,32x))
    write(iuo,240) ('mean','error','vov','slope','fom',i=jt,la)
-240 format(7x, "nps",3(6x,a4,5x,a5,3x,a3,2x,a5,4x,a3))
+240 format(10x, "nps",3(6x,a4,5x,a5,3x,a3,2x,a5,4x,a3))
    !
    ! print the npc, tfc table.
    do l=1,nn
@@ -180,7 +181,7 @@
    end do
    write(iuo,270) npc(l),((tfc(j,l,i+k),j=1,2),tfc(4,l,i+k),&
    & t5(i-jt+1),ha(i-jt+1),i=jt,la)
-270 format(i10,3(2x,1pe11.4,0p2f7.4,f5.1,a8))
+270 format(1x,i12,3(2x,1pe11.4,0p2f7.4,f5.1,a8))
    end do
  end do
endif
diff -Naurd MCNP5/Source/src/ptrak.F90 MCNP5_new/Source/src/ptrak.F90
--- MCNP5/Source/src/ptrak.F90      2003-04-30 20:12:14.000000000 -0600
+++ MCNP5_new/Source/src/ptrak.F90  2004-07-22 15:14:42.000000000 -0600
@@ -6,6 +6,7 @@

  use mcnp_global
  use mcnp_debug
+ use erprnt_mod, only: erprnt

```

```

implicit real(dknd) (a-h,o-z)

@@ -15,8 +16,8 @@
&
      19,23,24,25,-2,-3,-7,-8,-10,-11,-12,-13 /)
integer :: il(6) = (/ 8, 7, 6,11, 3, 5 /)
integer :: in(5) = (/ 0, 0, 0, 0, 0 /)
- integer :: ip(nptra+1) = (/ (0,j=1,nptra+1) /)
- integer :: iq(3,5) = reshape( (/ 1, (0,j=1,14) /), (/3,5/) )
+ integer(i8knd) :: ip(nptra+1) = (/ (0,j=1,nptra+1) /)
+ integer(i8knd) :: iq(3,5) = reshape( (/ 1, (0,j=1,14) /), (/3,5/) )
integer :: iv(5) = (/ 0, 0, 2, 9,10 /)
integer :: iw(6) = (/ 1, 2, 3, 4, 5, 6 /)
integer :: iz(25) = (/1,0,0,1,0,0,1,1,1,0,1,1,1,1,0,0,0,0,1,1,1,1,0,0,0/)
@@ -25,7 +26,7 @@
character(len=74) :: hq
character(len=14) :: hf
save hs,ht,ih,il,in,ip,iq,iv,iz,nn
-
+ integer(i8knd) :: l,lp
select case( m )

case( 0 )
@@ -127,11 +128,11 @@
      if( kpt(i)/=0 ) k = i
      n = n+kpt(i)
      enddo
-   if( n==1 ) ip(11) = 1
+   if( n==1 ) ip(11) = 1_i8knd
      if( n/=1 ) k = 0
      il = 6+iptra(13)
      i2 = 3**iptra(13)
-   ip(13) = il+i2
+   ip(13) = int(il+i2,i8knd)
      do i = 1,5
         i(1,i) = il-ip(11)-iq(1,i)
         iq(2,i) = i2-iq(2,i)
@@ -152,7 +153,7 @@
      ! >>>> m=1 through 5 -- filter and write the ptrac events.
      ! m=1 source; m=2 bank; m=3 surface; m=4 collision; m=5 term.
      im = 1
-   if( m==5 ) ip(5) = ip(5)+1
+   if( m==5 ) ip(5) = ip(5)+1_i8knd

      ! apply the various event filters - bank events are special.
      DO 290: do i = 1,6
@@ -191,7 +192,7 @@
      endif
      enddo
      case( 2, 3 )
-   if( ip(il(i))<lp ) cycle DO_290
+   if( ip(il(i))<int(lp,i8knd) ) cycle DO_290
      if( m/=2 .or. il(i)/=5 ) return
      im = -1
      case( 1 )
@@ -204,14 +205,14 @@
      enddo DO_290

      ! eliminate useless bank events, increment the various counters.
-   if( iptra(3)/=0 .or. m/=2 .or. ip(3)/=2 ) then
-   ip(6) = ip(6)+1
-   ip(7) = ip(7)+1
-   ip(1) = ip(1)+1
+   if( iptra(3)/=0 .or. m/=2 .or. ip(3)/=2_i8knd ) then
+   ip(6) = ip(6)+1_i8knd
+   ip(7) = ip(7)+1_i8knd
+   ip(1) = ip(1)+1_i8knd
      endif

      ! write the appropriate event data to the buffer.
-   lp = ip(13)*ip(1)

```

```

+   lp = int(ip(13)*ip(1),i4knd)
   pts(lp+1) = 9000.
   pts(lp+2) = node
   l = 0
@@ -244,7 +245,7 @@
   lp = lp+1
   end select
   pts(lp+4) = ipt
-   if( ip(11)==0 ) lp = lp+1
+   if( ip(11)==0_i8knd ) lp = lp+1
   pts(lp+4) = ncl(icl)
   pts(lp+5) = mat(icl)
   pts(lp+6) = ncp
@@ -257,15 +258,15 @@
   pts(lp+5+i) = udt(i,0)
   enddo
   endif
-   pts(ip(13)*(ip(1)-1)+1) = float(im*(m*1000+1))
+   pts(int(ip(13)*(ip(1)-1)+1,i4knd)) = float(im*(m*1000+1))
   ip(3) = m
   if( ip(1)<=iptra(1) ) return

   ! when full, move the buffer to the scratch file.
-   if( ip(4)==0 ) ip(4) = nint(pts(1))
+   if( ip(4)==0_i8knd ) ip(4) = nint(pts(1),i8knd)
   rp(1) = pts(1)
   do i = 1,iptra(1)
-   lp = ip(13)*i
+   lp = int(ip(13)*i,i4knd)
   n = iq(3,nint(abs(rp(1)))/1000)
   do j = 1,n
     rp(j) = pts(lp+j)
@@ -275,8 +276,8 @@

   ! move the last event to the front of the buffer.
   pts(1) = rp(1)
-   do j = 1,ip(13)
-     pts(ip(13)+j) = pts(lp+ip(13)+j)
+   do j = 1,int(ip(13),i4knd)
+     pts(int(ip(13),i4knd)+j) = pts(lp+int(ip(13),i4knd)+j)
   enddo
   ip(1) = 1

@@ -286,7 +287,7 @@
   do i = 3,4
     l = iv(i)
     lp = abs(iptra(1))
-   if( lp==0 .or. ip(1)/=0 ) go to 470
+   if( lp==0 .or. ip(1)/=0_i8knd ) go to 470
   do j = 1,nint(ptr(lp))
     if( i/=4 .and. nint(ptr(lp+j))==k ) go to 460
     if( i==4 .and. ptr(lp+j)==k+kfq*0.1 ) go to 460
@@ -302,13 +303,13 @@

case( 7 )
! >>>> m=7 -- filter the history and move events to the output file.
-   if( ip(7)==0 ) go to 690
+   if( ip(7)==0_i8knd ) go to 690
   if( abs(iptra)==1 ) go to 570

   if( iptra(2)/=0 ) then
     ! check the cell filters.
-     if( ip(2)==0 ) go to 680
-     ip(2) = ncl(ip(2))
+     if( ip(2)==0_i8knd ) go to 680
+     ip(2) = ncl(int(ip(2),i4knd))
   endif
   if( iptra(9)/=0 ) then
     ! check the surface filters.
@@ -334,9 +335,9 @@
   if( it<=0 ) then

```



```

        ! find the tfc bin value and the appropriate multiplier.
        do l = 1,20
-         if( npc(l)==0 ) exit
+         if( npc(l)==0_i8knd ) exit
        enddo
-         l = max(1,l-1)
+         l = max(1_i8knd,l-1_i8knd)
        tv = tfc(l,l,k)*10.
        if( tv==0. ) cycle
        if( lv/=0 ) tv = tfc(l,l,k)*ptr(lv+i)
@@ -353,8 +354,8 @@

        ! write the nps line to the output file.
570 continue
-         ip(8) = ip(8)+1
-         if( ip(4)==0 ) ip(4) = nint(pts(1))
+         ip(8) = ip(8)+1_i8knd
+         if( ip(4)==0 ) ip(4) = nint(pts(1),i8knd)
        iw(1) = npstc
        iw(2) = ip(4)
        ! check for surface facet for write.
@@ -462,9 +463,9 @@
        ip(6) = ip(6)-ip(7)
690 continue
        rewind(iupc)
-         ip(1:5) = 0
-         ip(7) = 0
-         ip(9) = 0
+         ip(1:5) = 0_i8knd
+         ip(7) = 0_i8knd
+         ip(9) = 0_i8knd
        if( iptr<0 .and. ip(6)>=iptra(6) ) nst = nst+256

        case( 8 )
@@ -473,7 +474,7 @@
        close(iupw)
        write(jtty,720) ht(iptra(4)),ptrac,ip(6),ip(8)
        write(iuo, 720) ht(iptra(4)),ptrac,ip(6),ip(8)
-720 format(1x,a6," file ",a8," written with ",i7," events from ",i7," histories.")
+720 format(1x,a6," file ",a8," written with ",i12," events",/29x," from ",i12,"
histories.")

        end select

diff -Naurd MCNP5/Source/src/ttyin.F90 MCNP5_new/Source/src/ttyin.F90
--- MCNP5/Source/src/ttyin.F90      2003-04-30 20:12:16.000000000 -0600
+++ MCNP5_new/Source/src/ttyin.F90  2004-07-22 15:14:43.000000000 -0600
@@ -1,73 +1,167 @@
-!+ $Id: ttyin.F90,v 1.7 2002/12/03 19:30:08 ljcox Exp $
+!+ $Id: ttyin.F90,v 1.2 2004/04/01 23:48:02 jgoorley Exp $
! Copyright LANL/UC/DOE - see file COPYRIGHT_INFO

-subroutine ttyin(ia,hm)
- ! Description:
- ! Process tty interrupts if irup=1 flag on. hm=message.
- ! The allowed interrupts are
- ! (ctrl-c) status (s) (or nothing) -- return program status.
- ! (ctrl-c) mcplot (m) -- call mcplot. mcrun only.
- ! (ctrl-c) quit (q) -- terminate at history end. mcrun only.
- ! (ctrl-c) kill (k) -- unconditional kill.
+module ttyin_mod

- ! Modules:
- use dmmp, only: dm_term
- use mcnp_global
- use mcnp_debug
- use gxsub, only : gxquit
+ interface ttyin
+ ! ==> specific routines used for generic subroutine:
+ module procedure ttyin_i4, ttyin_i8
+ end interface

```

```

- implicit real(dknd) (a-h,o-z)
- character(len=*) :: hm
- character(len=60) :: ha
- character(len=8) :: hg
- character(len=6) :: is(4) = ('status','mcplot','quit ','kill '/')
- character(len=2) :: js(4) = ('is','im','iq','ik'/)
+ contains

- ! Get the message from the tty.
- irup = 0
- write(jtty,'( " **** interrupt. enter s (status), m (mcplot), "&'&
- & //' "q (quit), k (kill)")')
- read(ittty,'(a8)') hg
- call nxtsym(hg,' ',1,i,j,2)
- do mi = 1,4
-   if( hg==is(mi)(1:1) .or. hg==is(mi) .or. hg==js(mi) .or. hg==' ' ) exit
- enddo
- if( (mi==2 .or. mi==3) .and. iovr/=4 ) mi = 1
+ subroutine qttyin_i4(ia,hm)
+ ! Description:
+ ! Process tty interrupts if irup=1 flag on. hm=message.
+ ! The allowed interrupts are
+ ! (ctrl-c) status (s) (or nothing) -- return program status.
+ ! (ctrl-c) mcplot (m) -- call mcplot. mcrun only.
+ ! (ctrl-c) quit (q) -- terminate at history end. mcrun only.
+ ! (ctrl-c) kill (k) -- unconditional kill.

- select case( mi )
+ ! Modules:
+ use dmmp, only: dm_term
+ use mcnp_global
+ use mcnp_debug
+ use gxsub, only : gxquit

- case( 1 )
- ! >>>> mi=1 -- return the status.
- call secnd(t)
- ha = '( " time =",f9.2,5x,'//hm//)'
- if( ia<0 ) write(jtty,ha) (t)/60.,nps,nch(1)+nch(2)+nch(3)
- if( ia==0 ) write(jtty,ha) (t)/60.
- if( ia>0 ) write(jtty,ha) (t)/60.,ia
- return
+ implicit none

- case( 2 )
- ! >>>> mi=2 -- call mcplot.
- kmplot = 1
- write(jtty,'( " will call plotter after history",i10)') nps
- return
+ integer(i4knd), intent(in) :: ia
+ character(len=*), intent(in) :: hm

- case( 3 )
- ! >>>> mi=3 -- terminate run after this history.
- nst = nst+16
- write(jtty,'( " will quit after history",i10)') nps
- return
+ integer :: i,j,mi
+ real(dknd) :: t

- case( 4 )
- ! >>>> mi=4 -- unconditional kill.
- call gxquit
- if( mcnp_opt multp ) then
-   if( ltasks>1 .and. iovr==4 ) call msgcon(3)
-   if( ltasks>=0 ) call dm_term
- endif
+ character(len=60) :: ha
+ character(len=8) :: hg
+ character(len=6) :: is(4) = ('status','mcplot','quit ','kill '/')

```

```

+ character(len=2) :: js(4) = ('is','im','iq','ik')

- stop
+ ! Get the message from the tty.
+ irup = 0
+ write(jtty,'( " **** interrupt. enter s (status), m (mcplot), ", '&
+ & //' "q (quit), k (kill)"')
+ read(itty,'(a8)') hg
+ call nxtsym(hg,' ',1,i,j,2)
+ do mi = 1,4
+   if( hg==is(mi)(1:1) .or. hg==is(mi) .or. hg==js(mi) .or. hg==' ' ) exit
+ enddo
+ if( (mi==2 .or. mi==3) .and. iovr/=4 ) mi = 1

- end select
+ select case( mi )

- return
-end subroutine qttyin
+ case( 1 )
+ ! >>>> mi=1 -- return the status.
+ call secnd(t)
+ ha = '( " time =",f9.2,5x,'//hm//')'
+ if( ia < 0 ) write(jtty,ha) t/sixty,nps,sum(nch)
+ if( ia == 0 ) write(jtty,ha) t/sixty
+ if( ia > 0 ) write(jtty,ha) t/sixty,ia
+ return
+
+ case( 2 )
+ ! >>>> mi=2 -- call mcplot.
+ kmplot = 1
+ write(jtty,'( " will call plotter after history",i12)') nps
+ return
+
+ case( 3 )
+ ! >>>> mi=3 -- terminate run after this history.
+ nst = nst+16
+ write(jtty,'( " will quit after history",i12)') nps
+ return
+
+ case( 4 )
+ ! >>>> mi=4 -- unconditional kill.
+ call gxquit
+ if( mcnp_opt_multp ) then
+   if( ltasks>1 .and. iovr==4 ) call msgcon(3)
+   if( ltasks>=0 ) call dm_term
+ endif
+
+ stop
+
+ end select
+
+ return
+ end subroutine qttyin_i4
+
+ subroutine qttyin_i8(ia,hm)
+ ! Description:
+ ! Process tty interrupts if irup=1 flag on. hm=message.
+ ! The allowed interrupts are
+ ! (ctrl-c) status (s) (or nothing) -- return program status.
+ ! (ctrl-c) mcplot (m) -- call mcplot. mcrun only.
+ ! (ctrl-c) quit (q) -- terminate at history end. mcrun only.
+ ! (ctrl-c) kill (k) -- unconditional kill.
+
+ ! Modules:
+ use dmmp, only: dm_term
+ use mcnp_global
+ use mcnp_debug
+ use gxsub, only : gxquit
+
+ implicit none

```

```

+
+ integer(i8knd), intent(in) :: ia
+ character(len=*), intent(in) :: hm
+
+ integer :: i,j,mi
+ real(dknd) :: t
+
+ character(len=60) :: ha
+ character(len=8) :: hg
+ character(len=6) :: is(4) = ('status','mcplot','quit ','kill '/')
+ character(len=2) :: js(4) = ('is','im','iq','ik'/)
+
+ ! Get the message from the tty.
+ irup = 0
+ write(jtty,'( " **** interrupt. enter s (status), m (mcplot), "&
+ & //' "q (quit), k (kill)")')
+ read(itty,'(a8)') hg
+ call nxtsym(hg,' ',1,i,j,2)
+ do mi = 1,4
+   if( hg==is(mi)(1:1) .or. hg==is(mi) .or. hg==js(mi) .or. hg==' ' ) exit
+ enddo
+ if( (mi==2 .or. mi==3) .and. iovr/=4 ) mi = 1
+
+ select case( mi )
+
+   case( 1 )
+     ! >>>> mi=1 -- return the status.
+     call secnd(t)
+     ha = '( " time =",f9.2,5x,'//hm//')'
+     if( ia < 0_i8knd ) write(jtty,ha) t/sixty,nps,sum(nch)
+     if( ia == 0_i8knd ) write(jtty,ha) t/sixty
+     if( ia > 0_i8knd ) write(jtty,ha) t/sixty,ia
+     return
+
+   case( 2 )
+     ! >>>> mi=2 -- call mcplot.
+     kmplot = 1
+     write(jtty,'( " will call plotter after history",i12)') nps
+     return
+
+   case( 3 )
+     ! >>>> mi=3 -- terminate run after this history.
+     nst = nst+16
+     write(jtty,'( " will quit after history",i12)') nps
+     return
+
+   case( 4 )
+     ! >>>> mi=4 -- unconditional kill.
+     call gxquit
+     if( mcnp_opt_multp ) then
+       if( ltasks>1 .and. iovr==4 ) call msgcon(3)
+       if( ltasks>=0 ) call dm_term
+     endif
+
+     stop
+
+   end select
+
+   return
+ end subroutine qttyin_i8
+
+end module qttyin_mod
diff -Naurd MCNP5/Source/src/ra2_mod.F90 MCNP5_new/Source/src/ra2_mod.F90
--- MCNP5/Source/src/ra2_mod.F90 2003-04-30 20:12:20.000000000 -0600
+++ MCNP5_new/Source/src/ra2_mod.F90 2004-07-22 15:14:43.000000000 -0600
@@ -6,6 +6,7 @@
     use mcnp_global
     use mcnp_debug
     use mcnp_input
+ use erprnt_mod

```

```

implicit real(dknd) (a-h,o-z)

diff -Naurd MCNP5/Source/src/rdprob.F90 MCNP5_new/Source/src/rdprob.F90
--- MCNP5/Source/src/rdprob.F90      2003-04-30 20:12:20.000000000 -0600
+++ MCNP5_new/Source/src/rdprob.F90  2004-07-22 15:14:43.000000000 -0600
@@ -7,6 +7,7 @@
    use mcnp_global
    use mcnp_debug
    use mcnp_input
+   use erprnt_mod

    implicit real(dknd) (a-h,o-z)
    character(len=80) :: hl
@@ -17,6 +18,12 @@
    if( krq(6,i)==-1 ) krq(6,i) = -mxa
    enddo

+   ! Allocate flag arrays for fm, de df card checks for spdt1
+   allocate ( flag_speed_tally_fm(0:max(1,ntal),1:2) )
+   allocate ( flag_speed_tally_de(0:max(1,ntal),1:2) )
+   flag_speed_tally_fm = 0
+   flag_speed_tally_de = 0
+
    ! process 1 or 3 data blocks, which are separated by blank lines.
    rewind iul
    jui = iui
@@ -114,5 +121,68 @@
    if( kl<=1 ) exit
    enddo
    enddo DO_80

+
+   ! Issue statement about lattice speed tally modifications, if necessary.
+   do i=1,ntal
+     ! Check presence of fm#4 tally cards for spdt
+     if ( flag_speed_tally_fm(i,1) == 0 .and. &
+         & flag_speed_tally_fm(i,2) /= 0 ) then
+       if ( flag_speed_tally_ok == 1) flag_speed_tally_ok = -1
+       if ( flag_speed_tally_force == 1 ) call erprnt(1,3,1,&
+         & flag_speed_tally_fm(i,2),0,0,0,0,&
+         & "need fm card with tally",i4," for lattice speed tally.")
+     endif
+     ! Check presence of de#4 df#4 tally cards for spdt1
+     if ( flag_speed_tally_de(i,1) == 0 .and. & ! check for de# card
+         & flag_speed_tally_de(0,1) == 0 .and. & ! check for de0 card
+         & flag_speed_tally_de(i,2) /= 0 ) then
+       if ( flag_speed_tally_ok == 1) flag_speed_tally_ok = -1
+       if ( flag_speed_tally_force == 1 ) call erprnt(1,3,1,&
+         & flag_speed_tally_de(i,2),0,0,0,0,&
+         & "need de df cards with tally",i4," for lattice speed tally.")
+     endif
+   enddo
+   !
+   if ( flag_speed_tally_ok == 1 .and. &
+       & (flag_speed_tally_force == 0 .or. flag_speed_tally_force == 1) ) then
+     call erprnt(1,2,0,0,0,0,0,0,&
+       & "*****")
+     call erprnt(1,2,0,0,0,0,0,0,"Using lattice speed tally modifications.")
+     call erprnt(1,2,0,0,0,0,0,0,&
+       & " User should review input deck and verify the following are true:")
+     call erprnt(1,2,0,0,0,0,0,0,&
+       & " 1) Nested lattices are not tallied over.")
+     call erprnt(1,2,0,0,0,0,0,0,&
+       & " 2) A cell with the fill keyword does not reference its own universe.")
+     call erprnt(1,2,0,0,0,0,0,0,&
+       & " 3) Lattice index range on tally must match corresponding fill range.")
+     call erprnt(1,2,0,0,0,0,0,0,&
+       & " Failure to meet these criteria may result in silent wrong answers.")
+     call erprnt(1,2,0,0,0,0,0,0,&
+       & " See the Lattice Speed Tally Enhancement report: LA-UR-04-3400")
+     call erprnt(1,2,0,0,0,0,0,0,&
+       & "*****")
+   endif

```

```

+   flag_speed_tally_used=1
+ endif
+ if ( flag_speed_tally_ok == 1 .and. flag_speed_tally_force == -1 ) then
+   call erprnt(1,3,0,0,0,0,0,&
+     & "lattice speed tally modifications ok to use, but have been turned off.")
+   flag_speed_tally_used=-1
+ endif
+ if ( flag_speed_tally_ok == -1 .and. &
+   & (flag_speed_tally_force == -1 .or. flag_speed_tally_force == 0) ) then
+   call erprnt(1,3,0,0,0,0,0,&
+     & "lattice speed tally modifications will not be used.")
+   flag_speed_tally_used=-1
+ endif
+ if( flag_speed_tally_ok == -1 .and. flag_speed_tally_force == 1 ) then
+   call erprnt(1,2,0,0,0,0,0, &
+     & "using lattice speed tally even though not appropriate.")
+   call erprnt(1,2,0,0,0,0,0, &
+     & "      Silent wrong answers or crash may result.")
+   flag_speed_tally_used=1
+ endif
+
+
+   return
end subroutine rdprob
diff -Naurd MCNP5/Source/src/regula.F90 MCNP5_new/Source/src/regula.F90
--- MCNP5/Source/src/regula.F90      2003-04-30 20:12:22.000000000 -0600
+++ MCNP5_new/Source/src/regula.F90  2004-07-22 15:14:43.000000000 -0600
@@ -10,6 +10,7 @@
    use mcnp_global
    use mcnp_debug
    use mcnp_plot
+   use erprnt_mod

    implicit real(dknd) (a-h,o-z)

diff -Naurd MCNP5/Source/src/rhoden.F90 MCNP5_new/Source/src/rhoden.F90
--- MCNP5/Source/src/rhoden.F90     2003-04-30 20:12:22.000000000 -0600
+++ MCNP5_new/Source/src/rhoden.F90  2004-07-22 15:14:43.000000000 -0600
@@ -6,6 +6,7 @@
    use mcnp_global
    use mcnp_debug
    use mcnp_input
+   use erprnt_mod

    implicit real(dknd) (a-h,o-z)
    character(len=82) :: ht
diff -Naurd MCNP5/Source/src/ronge.F90 MCNP5_new/Source/src/ronge.F90
--- MCNP5/Source/src/ronge.F90      2003-04-30 20:12:24.000000000 -0600
+++ MCNP5_new/Source/src/ronge.F90   2004-07-22 15:14:43.000000000 -0600
@@ -15,6 +15,7 @@
    use mcnp_global
    use mcnp_debug
    use mcnp_landau
+   use erprnt_mod

    implicit real(dknd) (a-h,o-z)
    integer, parameter :: km = 5
diff -Naurd MCNP5/Source/src/runtpr.F90 MCNP5_new/Source/src/runtpr.F90
--- MCNP5/Source/src/runtpr.F90     2003-04-30 20:12:26.000000000 -0600
+++ MCNP5_new/Source/src/runtpr.F90  2004-07-22 15:14:43.000000000 -0600
@@ -16,7 +16,7 @@
    ie = 0

    read(iu,end = 10) hk,hv,h1,hi,hc,hp
-   read(iu,end = 10) avarcm,gvarcm,jvarcm,rdum,idum
+   read(iu,end = 10) avarcm,gvarcm,i8varcm,jvarcm,rdum,idum
    call vdac_read(iu)
    call fmesh_runtpr(iu)
    return
diff -Naurd MCNP5/Source/src/runtpw.F90 MCNP5_new/Source/src/runtpw.F90
--- MCNP5/Source/src/runtpw.F90     2003-04-30 20:12:28.000000000 -0600

```

```

+++ MCNP5_new/Source/src/runtpw.F90 2004-07-22 15:14:43.000000000 -0600
@@ -12,7 +12,7 @@
implicit real(dknd) (a-h,o-z)

write(iu) kod,ver,loddat,idtm, chcd,probid
- write(iu) avarcm,gvarcm,jvarcm,rdum,idum
+ write(iu) avarcm,gvarcm,i8varcm,jvarcm,rdum,idum
call vdac_write(iu)
call fmesh_runtpw(iu)

diff -Naurd MCNP5/Source/src/setdas.F90 MCNP5_new/Source/src/setdas.F90
--- MCNP5/Source/src/setdas.F90 2003-11-05 17:23:12.000000000 -0700
+++ MCNP5_new/Source/src/setdas.F90 2004-07-22 15:14:43.000000000 -0600
@@ -465,7 +465,7 @@
allocate( rho( 1:mxal ) )
rho = 0.0
allocate( isef( 1:2, 1:mxal*mt ) ) !***** check
- isef = 0
+ isef = 0_i8knd
allocate( jfq( 1:8, 0:ntal1 ) )
jfq = 0
allocate( laj( 1:(mlaj1+mxal)*mtasks ) )
@@ -560,7 +560,7 @@
allocate( stt( 1:ntp, 1:ntal1*(npert1+1)*mt ) )
stt = 0
allocate( nhsd( 1:nsp12, 1:ntal1*(npert1+1)*mt ) )
- nhsd = 0
+ nhsd = 0_i8knd

! Call routine to allocate mesh tally arrays
if( nmesh>0 ) then
@@ -969,10 +969,10 @@
! call msg_put( wwfa, 1, (mgww1+mipt)*nwwmal)
! call msg_put( swwfa, 1, (mgww1+mipt)*nwwmal)

- call msg_put( pac, 1, mipt*10*mxal)
- call msg_put( pan, 1, 3*8*npn1)
+ call msg_put( pac, lpac+1, mipt*10*mxal)
+ call msg_put( pan, lpan+1, 3*8*npn1)
! call msg_put( pcc, 1, 3*mxal*kpt1(2))
- call msg_put( pwb, 1, mipt*22*mxal)
+ call msg_put( pwb, lpwb+1, mipt*22*mxal)

! if( nsr==71 ) then
! call msg_put( sump, 1, npert1)
@@ -1234,12 +1234,12 @@
call msg_put( sump, 1, npert1)
sump(1:npert1)=zero
endif
-
+
call msg_put( wns, 1, 2*(mxxs1/4))
wns(1:2,1:(mxxs1/4))=zero

call msg_put( isef, 1, 2*mxal)
- isef(1:2,1:mxal)=0
+ isef(1:2,1:mxal)=0_i8knd

call msg_put( maze, 1, 3*nmaz1*sum(kpt))
maze(1:3*nmaz1*sum(kpt))=0
@@ -1249,7 +1249,7 @@

call msg_put( ndr, 1, mxel)
ndr(1:mxel)=0
-
+
if( ntal>0 ) then
call msg_put( shsd, 1, nspt*ntal*(npert1+1))
shsd(1:nspt,1:ntal*(npert1+1))=zero
@@ -1258,7 +1258,7 @@
stt(1:ntp,1:ntal*(npert1+1))=zero

```

```

    call msg_put( nhsd, 1, nspl2*ntal*(npert+1))
-   nhsd(1:nspl2,1:ntal*(npert+1))=0
+   nhsd(1:nspl2,1:ntal*(npert+1))=0_i8knd
endif

return
diff -Naurd MCNP5/Source/src/sfiles.F90 MCNP5_new/Source/src/sfiles.F90
--- MCNP5/Source/src/sfiles.F90      2003-04-30 20:12:32.000000000 -0600
+++ MCNP5_new/Source/src/sfiles.F90  2004-07-22 15:14:43.000000000 -0600
@@ -6,6 +6,7 @@
    use mcnp_global
    use mcnp_debug
    use mcnp_input
+   use erprnt_mod

    implicit real(dknd) (a-h,o-z)

diff -Naurd MCNP5/Source/src/shade.F90 MCNP5_new/Source/src/shade.F90
--- MCNP5/Source/src/shade.F90      2003-04-30 20:12:34.000000000 -0600
+++ MCNP5_new/Source/src/shade.F90  2004-07-22 15:14:43.000000000 -0600
@@ -8,6 +8,7 @@
    use mcnp_debug
    use mcnp_plot
    use gkssim
+   use erprnt_mod
    implicit real(dknd) (a-h,o-z)

    real :: x(4),y(4)
@@ -33,6 +34,7 @@
    case ('tmp')
        sx = maxval(tmp)
        sn = minval(tmp,MASK = tmp.NE.0.0)
+
    case default
        sx = 1.0
        sn = 0.0
@@ -122,7 +124,7 @@
    il = ic
    95 continue
    s2 = extent(1)
-   if( dls<huge ) s2 = min( s+dls, real(extent(1),dknd) )
+   if( dls<huge_float ) s2 = min( s+dls, real(extent(1),dknd) )
    if( mat(ic)==0 .or. lc==1 ) go to 100
    if( lev/=levplt .and. levplt>=0 ) go to 100
    !
@@ -141,6 +143,7 @@
    case ('tmp')
        ik = min(nshades,int(nshades*(tmp(ic)-sn)/(sd))+1)
        ik = nshades + 1 - ik
+
    end select
    call gsfaci(ik,color_mode)
    !
diff -Naurd MCNP5/Source/src/smmp.F90 MCNP5_new/Source/src/smmp.F90
--- MCNP5/Source/src/smmp.F90      2003-04-30 20:12:36.000000000 -0600
+++ MCNP5_new/Source/src/smmp.F90  2004-07-22 15:14:43.000000000 -0600
@@ -22,7 +22,7 @@

    ! Modules used:
    use mcnp_debug
-   use mcnp_params,    only: dknd, IDEF
+   use mcnp_params,    only: dknd,i8knd, IDEF

    implicit none
    public                ! Default PUBLIC for this module.
@@ -36,7 +36,7 @@
    integer, private, parameter :: TWICE = 2 ! locked twice.

    ! Private Variables:
-   integer, private,allocatable :: lock_var(:) ! the lock variable.

```



```

+ integer(i8knd), private,allocatable :: lock_var(:) ! the lock variable.
integer, private :: nlocks=0 ! number of OMP locks.
real(dknd),private,dimension(MAXTASKS) :: btme = 0.0
! time waiting at barriers.
diff -Naurd MCNP5/Source/src/sourcb.F90 MCNP5_new/Source/src/sourcb.F90
--- MCNP5/Source/src/sourcb.F90 2003-04-30 20:12:38.000000000 -0600
+++ MCNP5_new/Source/src/sourcb.F90 2004-07-22 15:14:43.000000000 -0600
@@ -523,7 +523,7 @@

!$OMP CRITICAL (PRINT_OUTPUT)
write(iuo,590) k,isef(kise+1,ji),ncl(ji)
-590 format(/ " only",i8, " successes in",i10, " tries in source cell",i6)
+590 format(/ " only",i8, " successes in",i12, " tries in source cell",i6)
write(jtty,595) ic(1),ksd(1,ivdis(1)),hbln(1,1),xxx,yyy,zzz
write(iuo,595) ic(1),ksd(1,ivdis(1)),hbln(1,1),xxx,yyy,zzz
595 format(/," entry",i5," on SI",i3," for independant variable",a3,&
diff -Naurd MCNP5/Source/src/sprob.F90 MCNP5_new/Source/src/sprob.F90
--- MCNP5/Source/src/sprob.F90 2003-04-30 20:12:40.000000000 -0600
+++ MCNP5_new/Source/src/sprob.F90 2004-07-22 15:14:43.000000000 -0600
@@ -8,6 +8,7 @@
use mcnp_global
use mcnp_debug
use mcnp_input
+ use erprnt_mod

implicit real(dknd) (a-h,o-z)
character ht*75
diff -Naurd MCNP5/Source/src/srcsrf.F90 MCNP5_new/Source/src/srcsrf.F90
--- MCNP5/Source/src/srcsrf.F90 2003-04-30 20:12:42.000000000 -0600
+++ MCNP5_new/Source/src/srcsrf.F90 2004-07-22 15:14:43.000000000 -0600
@@ -8,6 +8,7 @@
use mcnp_global
use mcnp_debug
use mcnp_input
+ use erprnt_mod

implicit real(dknd) (a-h,o-z)

diff -Naurd MCNP5/Source/src/sread.F90 MCNP5_new/Source/src/sread.F90
--- MCNP5/Source/src/sread.F90 2003-04-30 20:12:42.000000000 -0600
+++ MCNP5_new/Source/src/sread.F90 2004-07-22 15:14:43.000000000 -0600
@@ -6,6 +6,9 @@

use mcnp_global
use mcnp_debug
+ use qttyin_mod, only: qttyin
+ use erprnt_mod, only: erprnt
+

implicit real(dknd) (a-h,o-z)
real(dknd) :: aw(0:16)
@@ -26,9 +29,6 @@
if( i>=5 ) read(ht,'(bn,i10)') ly(i-4)
end do
call zaid(2,ht,ixl(1,iex))
-#ifdef PCDOS
- if(lockl)call ptttyin
-#endif
if( irup/=0 ) call qttyin(0,"reading nuclide '//ht//'")

if( ly(1)/=2 ) then
diff -Naurd MCNP5/Source/src/startp.F90 MCNP5_new/Source/src/startp.F90
--- MCNP5/Source/src/startp.F90 2003-04-30 20:12:44.000000000 -0600
+++ MCNP5_new/Source/src/startp.F90 2004-07-22 15:14:43.000000000 -0600
@@ -7,6 +7,7 @@

! Modules:
use mcnp_global
+ use dxtran_mod
use mcnp_debug
use rmc_mod

```

```

@@ -142,7 +143,6 @@
    endif
  endif

-
  ! Report, count, and resample the source if energy > emx.
  if( erg>emx(ipt) ) then
    if( nsr==6 .or. nsr==71 ) then
@@ -159,6 +159,7 @@

    ! Print the initial parameters for the first fifty histories.

+160 continue
  !$OMP CRITICAL (PRINT_OUTPUT)
  ! Facet of macrobody surface source not printed to save space.
  if( npstc<=50 .and. ink(110)/=0 .and. krflg/=2 ) then
@@ -220,14 +221,7 @@
  endif

  ! Mark the particle if it is born inside a dxtran sphere.
-  idx = 0
-  do i = 1,ndx(ipt)
-    if( (dxx(ipt,1,i)-xxx)**2+(dxx(ipt,2,i)-yyy)**2+&
-      & (dxx(ipt,3,i)-zzz)**2<dxx(ipt,5,i) ) then
-      idx = i
-      exit
-    endif
-  enddo
+  idx = inside_dxtran_sphere()

  ! Increment source accounts and save some initial variables.
  paxtc(2,1,ipt) = paxtc(2,1,ipt)+wgt
diff -Naurd MCNP5/Source/src/stuff.F90 MCNP5_new/Source/src/stuff.F90
--- MCNP5/Source/src/stuff.F90      2003-04-30 20:12:46.000000000 -0600
+++ MCNP5_new/Source/src/stuff.F90  2004-07-22 15:14:43.000000000 -0600
@@ -7,15 +7,14 @@
  use mcnp_debug
  use mcnp_input
  use fmesh_mod
+ use qttyin_mod, only: qttyin
+ use erprnt_mod, only: erprnt

  implicit real(dknd) (a-h,o-z)

  character hs*10,ht*10,hb*30,hc*181

  ! change mat from material names to material indexes.
-#ifndef PCDOS
-  if( lock1) call ptttyin
-#endif /*def.pcdos*/
  if( irup/=0 ) call qttyin(0,' "beginning material processing."')
  DO_20: do i = 1,mxa
    do j = 1,nmat
@@ -65,8 +64,13 @@
    enddo
  enddo
  do i = 1,nmesh
-    if( fm(i)%mat /= nmt(mn) ) cycle
-    if( fm(i)%ipt == m ) goto 150
+    if( fm(i)%mat < 0 ) then
+      do j=1,fm(i)%nreact,2
+        if ( fm(i)%react(j) == mn .and. fm(i)%ipt == m ) goto 150
+      enddo
+    else if( fm(i)%mat == mn .and. fm(i)%ipt == m ) then
+      goto 150
+    endif
  enddo
  cycle DO_230

diff -Naurd MCNP5/Source/src/sumary.F90 MCNP5_new/Source/src/sumary.F90

```

```

--- MCNP5/Source/src/summary.F90      2003-04-30 20:12:46.000000000 -0600
+++ MCNP5_new/Source/src/summary.F90  2004-07-22 15:14:43.000000000 -0600
@@ -6,15 +6,17 @@
! Print summaries of problem activity.

use mcnp_global
+ use dxtran_mod
use mcnp_debug
use critl_mod
use fmesh_mod, only: nmesh, fmesh_print
use ral_mod
use ra2_mod
+ use erprnt_mod, only: erprnt, erprnt_i8_k2

implicit real(dknd) (a-h,o-z)
integer(i8knd) :: i8_stride, i8_period
- character(len=88) :: hy
+ character(len=92) :: hy
character(len=26) :: ha(2)
character(len=16) :: hg
character(len=14) :: ht(4)
@@ -67,16 +69,16 @@
if( nsr==6 .and. nrrs>=nrss ) t = npl
if( nsr==6 .and. nrrs<nrss ) t = npsr
fpi = 1./max(one,t)
- write(hy,'(20x, "source particle weight for summary table normalization =",f12.2)')t
- if( nint(t)==nps ) hy=' '
+ write(hy,'(20x, "source particle weight for summary table normalization =",f16.2)')t
+ if( nint(t,i8knd)==nps ) hy=' '
if( kc8<0 .or. kcheck/=0 ) hy(1:20)='(active cycles only)'
- write(iuo,'( "lproblem summary ",a20,14x,a68/)') hy(1:20),hy(21:88)
+ write(iuo,'( "lproblem summary ",a20,14x,a72/)') hy(1:20),hy(21:92)

! If the run is finished, print the reason.
call getidt(idtm)
if( nst/=0 ) then
write(rfq(1)(4:7),'(i4)') ksr
- write(rfq(2)(8:17),'(i10)') nps
+ write(rfq(2)(8:19),'(i12)') nps
write(rfq(3)(11:14),'(i4)') nerr
if( ctme>0.0 .and. ctme<10. ) then
write(rfq(5)(20:24),'(f5.1)') ctme
@@ -85,7 +87,7 @@
endif
write(rfq(7)(8:13),'(i6)') kcy
if( kcheck/=0 ) write(rfq(7)(8:15),'(i6, " a")') kct
- write(rfq(8)(9:18),'(i10)') iptra(6)
+ write(rfq(8)(9:20),'(i12)') iptra(6)
do i = 1,11
if( mod(nst/2**i,2)==0 ) cycle
write(iuo,'(6x, "run terminated ",//rfq(i)//)')
@@ -227,14 +229,14 @@
& "maximum number ever in bank",i10/ " computer time in mcrun",&
& f19.2, " minutes",12x, "bank overflows to backup file",i8/&
& " source particles per minute",lpe22.4,/, " random numbers generated",&
- & Opf26.0,t11, " ",11x, "most random numbers used was",i9,&
- & " in history",i9)
+ & Opf26.0,t11, " ",11x, "most random numbers used was",i12,&
+ & " in history",i12)
endif

! Print conditional comments.
call RN_query( stride = i8_stride, period = i8_period )
- if( nrnh(1)>0 ) then
- call erprnt(1,2,2,int(i8_stride),nrnh(1),0,0,0, &
+ if( nrnh(1)>0_i8knd ) then
+ call erprnt_i8_k2(1,2,2,int(i8_stride),nrnh(1),0,0,0, &
& "' random number stride",i9," exceeded",i9," times."')
endif
if( nps*i8_stride>i8_period ) then
@@ -244,8 +246,8 @@

```

```

240 format(/ " range of sampled source weights =",lpe11.4," to",e11.4)
   ie = 0
   do m = 1,mxa
-   if( isef(1,m)/=0 )   ie = 1
-   if( isef(1,m)/=0 )   write(iuo,260)  1.-isef(2,m)/(isef(1,m)+zero),ncl(m)
+   if( isef(1,m)/=0_i8knd )   ie = 1
+   if( isef(1,m)/=0_i8knd )   write(iuo,260)  1.-
real(isef(2,m),dknd)/real(isef(1,m),dknd),ncl(m)
   enddo
260 format(/ " source efficiency =",f7.4," in cell",i6)
   je = 0
@@ -301,7 +303,7 @@
       else
         write(iuo,390) (nbal(i),i = 1,ltasks+1)
       endif
-390 format(/," number of histories processed by each task"/(10i10))
+390 format(/," number of histories processed by each task"/(10i12))
       endif
     endif

@@ -348,7 +350,7 @@

! Print information about results.
call ra_result( mcheck )
- if( nsr==71 .and. (nst/=0 .or. npp<0) .and. mcheck==0 ) then
+ if( nsr==71 .and. (nst/=0 .or. npp<0_i8knd) .and. mcheck==0 ) then
  call kprint
endif

@@ -363,15 +365,15 @@
endif

! Generate weight-window cards at the end of the run.
- if( iwwg>0 .and. (nst/=0 .or. npp<0) ) then
+ if( iwwg>0 .and. (nst/=0 .or. npp<0_i8knd) ) then
  call avrout
endif
- if( icw/=0 .and. (nst/=0 .or. npp<0) ) then
+ if( icw/=0 .and. (nst/=0 .or. npp<0_i8knd) ) then
  call gmgww
endif

! Print rnr if required, for quick evaluation of test problems.
- if( dbcn(12)==0 .or. nst==0 .and. npp>=0 .or. nps<=0 ) return
+ if( dbcn(12)==0 .or. nst==0 .and. npp>=0_i8knd .or. nps<=0_i8knd ) return
write(ha(1)(1:16),'(f16.0)') dbcn(12)
write(ha(2)(1:16),'(f16.0)') rnr
write(jtty,420) ha(1)(1:15),ha(2)(1:15)
diff -Naurd MCNP5/Source/src/sursrc.F90 MCNP5_new/Source/src/sursrc.F90
--- MCNP5/Source/src/sursrc.F90      2003-04-30 20:12:48.000000000 -0600
+++ MCNP5_new/Source/src/sursrc.F90  2004-07-22 15:14:43.000000000 -0600
@@ -9,6 +9,7 @@
  use mcnp_debug

  implicit real(dknd) (a-h,o-z)
+ integer(i8knd) :: nr, n2

  nr = 0
  nt = 0
@@ -124,7 +125,7 @@
    if( n2/=npsr ) then
      n2 = npsr
      if( rang(>)>snit ) then
-        n2 = -1
+        n2 = -1_i8knd
        nssi(8) = nssi(8)+1
        go to 340
      endif
@@ -200,7 +201,7 @@
    if( nt==0 ) then
      ! save the first accepted particle to start the history with.

```

```

        nt = 1
-       ntss = ntss+1
+       ntss = ntss+1_i8knd
        if( mcnp_opt_multp .and. ns/=0 ) go to 330
        npb = 1
        call savpar(1,0)
@@ -232,12 +233,12 @@
        if( npsr==abs(ssb(1)) ) go to 10

        ! all tracks associated with this history have been read.
-       ngss = ngss+1
+       ngss = ngss+1_i8knd
        n2 = 0
        if( nt==0 ) go to 10
    else
        ! terminate the problem when all tracks are read.
-       ngss = ngss+1
+       ngss = ngss+1_i8knd
        if( twss<=0. ) then
            call expirx(0,'sursrc','no weight is on the '//rssa//' file.')
            return
@@ -248,7 +249,7 @@
        endif
        if( nt==0 ) then
            nomore = 1
-           nps = nps-1
+           nps = nps-1_i8knd
        endif
    endif

diff -Naurd MCNP5/Source/src/tallmg.F90 MCNP5_new/Source/src/tallmg.F90
--- MCNP5/Source/src/tallmg.F90      2003-04-30 20:12:48.000000000 -0600
+++ MCNP5_new/Source/src/tallmg.F90  2004-07-22 15:14:43.000000000 -0600
@@ -13,6 +13,7 @@
    ! Modules:
    use mcnp_global
    use mcnp_debug
+   use erprnt_mod

    implicit real(dknd) (a-h,o-z)

diff -Naurd MCNP5/Source/src/talloc.F90 MCNP5_new/Source/src/talloc.F90
--- MCNP5/Source/src/talloc.F90      2003-04-30 20:12:48.000000000 -0600
+++ MCNP5_new/Source/src/talloc.F90  2004-07-22 15:14:43.000000000 -0600
@@ -7,6 +7,7 @@
    use mcnp_global
    use mcnp_debug
    use mcnp_input
+   use erprnt_mod

    implicit real(dknd) (a-h,o-z)
    integer, parameter :: ki(8,3) = &
diff -Naurd MCNP5/Source/src/tallyd.F90 MCNP5_new/Source/src/tallyd.F90
--- MCNP5/Source/src/tallyd.F90      2003-04-30 20:12:50.000000000 -0600
+++ MCNP5_new/Source/src/tallyd.F90  2004-07-22 15:14:43.000000000 -0600
@@ -10,7 +10,7 @@
    use mcnp_debug

    implicit real(dknd) (a-h,o-z)
-   integer(i8knd) :: i8_count
+   integer(i8knd) :: i8_count,itmp2
    integer          :: ik(8)
    logical          :: test_td

@@ -244,12 +244,12 @@
        if( jptal(8,ital)<4 ) then
            if( ddg(1,idet)<0. ) then
                s = -ddg(1,idet)/(wgt*psc)
-           elseif( ddg(1,idet)>0. .and. npstc>200 ) then
+           elseif( ddg(1,idet)>0. .and. npstc>200_i8knd ) then
                s = ddg(1,idet)*ddn(24,idet)/(wgt*psc)

```

```

endif
if( ipsc/=11 ) s = s*2.*pie*dd**2
else
-   if( jptal(8,ital)==4 .and. npstc>npsmg .and. npsmg/=0 .and. &
+   if( jptal(8,ital)==4 .and. npstc>npsmg .and. npsmg/=0_i8knd .and. &
& (ipsc==3 .or. ipsc==10 .or. ipsc==11 .or. ipsc==12 .or. &
& ipsc==101) ) then
amfp = 0.
@@ -366,7 +366,7 @@
ca = tme+tds(11+1)
cd = tme+tds(11+2)
ibt = 1
-   b = -huge
+   b = -huge_float
endif
320 continue
a = b
@@ -439,10 +439,10 @@
itmp2 = npsout
else
itmp1 = mxfl
-   itmp2 = nps - 1
+   itmp2 = nps - 1_i8knd
endif

-   test_td = jptal(8,ital)==4 .and. npstc>npsmg .and. npsmg/=0 .and. &
+   test_td = jptal(8,ital)==4 .and. npstc>npsmg .and. npsmg/=0_i8knd .and. &
& (ipsc==3 .or. ipsc==10 .or. ipsc==11 .or. ipsc==12 .or. ipsc==101)

is = ibs
diff -Naurd MCNP5/Source/src/tally.F90 MCNP5_new/Source/src/tally.F90
--- MCNP5/Source/src/tally.F90      2003-04-30 20:12:50.000000000 -0600
+++ MCNP5_new/Source/src/tally.F90  2004-07-22 15:14:43.000000000 -0600
@@ -18,6 +18,9 @@
! return if kcode problem is not settled.
if( kc8>0 ) return

+ ! Check for speed tally for lattice usage
+ if ( flag_speed_tally_used == 1 ) goto 800
+
! warn if tally made by both dxtran and non-dxtran particles.
if( idx+1/=itds(lo-1) ) then
if( itds(lo-1)>=0 ) then
@@ -66,7 +69,7 @@
l = jxs(1,mgegbt(1))+2*jgm(1)-1
do ibu_tmp = 1,iptal(3,4,ital)-1
ibu = ibu_tmp
-   if( abs(tds(iptal(3,1,ital)+ibu)-xss(l+jgp))<=.001*xss(l+jgp) ) go to 60
+   if( abs(tds(iptal(3,1,ital)+ibu)-xss(l+jgp))<=.001_dknd*xss(l+jgp) ) go to 60
enddo
ibu = ibu_tmp
go to 700
@@ -89,7 +92,7 @@
t2 = t1**2+rang()**2
if( t2<=1. ) exit
enddo
-   erg = erg + .60056120439322*(tds(1+1)+tds(1+2))*sqrt(max(zero,&
+   erg = erg + .60056120439322_dknd*(tds(1+1)+tds(1+2))*sqrt(max(zero,&
& erg+tds(1+3)*erg**2)))*sqrt(-log(t2)/t2)*t1
endif

@@ -214,7 +217,7 @@
mk = mat(ic1)
if( mcal==0 ) then
do m = jmd(mk),jmd(mk+1)-1
-   h2 = huge
+   h2 = huge_float
i = lme(1,m)
if( jxs(21,i)==0 ) cycle
l = jxs(21,i)
@@ -231,7 +234,7 @@

```

```

        if( npert/=0 ) call pertc(2,mk,m,-6,lx,h2)
        h = h+h2
    enddo
-   if( npert/=0 .and. h2==huge ) call pertc(2,mk,jmd(mk+1)-1,-6,lx,zero)
+   if( npert/=0 .and. h2==huge_float ) call pertc(2,mk,jmd(mk+1)-1,-6,lx,zero)
    else
        ! multigroup fission heating.
        do m = jmd(mk),jmd(mk+1)-1
@@ -299,7 +302,7 @@
        enddo
        db = min(dr,dti(k))
        if( db==dr ) go to 470
-   dti(k) = huge
+   dti(k) = huge_float
        do j = 1,n
            if( abs(lja(abs(lca(ig))+j-1))==iti(k) ) exit
        enddo
@@ -322,7 +325,7 @@
        ca = tme+tds(l1+1)
        cd = tme+tds(l1+2)
        ibt = 1
-   b = -huge
+   b = -huge_float
        if( jptal(2,ital)>=4 ) then
            dt = (dc-da)/vel
            tt = ta*vel
@@ -512,4 +515,27 @@
        tme = tv
        erg = es
        return
+! this is the special speed tally treatment for lattices
+800 lx=lo+2 ! From: do all tallies that include this cell or
surface
+   ta=wtg ! include weight of particle in tally
+   j=-mfl(1,nint(udt(7,lev-1))) ! effectively from do surface or cell bins
+   n8=nint(udt(8,lev-1))
+   n9=nint(udt(9,lev-1))
+   n10=nint(udt(10,lev-1))
+   do ml=1,itds(lo) ! From: do all tallies that include this cell or
surface
+   ital=itds(lx-1)
+   n1=itds(lx)
+   ir=n8-laf(j+1,1)+laf(j+1,2)*(n9-&
+   & laf(j+2,1)+laf(j+2,2)*(n10-laf(j+3,1)))+1
+   j7=ktal+jptal(5,ital)+iptal(2,5,ital)*(itds(lx+ir)-1)+1
+   tb=dosef(ta) ! Include DE, DF cards into tally result
+   td=tb*dr*tds(iptal(5,2,ital)+1)
+   if(tal(j7).eq. 0._dknd)then
+   jtls=jtls+1
+   if(jtls.le. ktls) tal(ktal+nmxf*mx+f+jtls)=j7
+   endif
+   tal(j7)=tal(j7)+td
+   lx=lx+n1+2
+   enddo
+   return
end subroutine tally
diff -Naurd MCNP5/Source/src/tallyh.F90 MCNP5_new/Source/src/tallyh.F90
--- MCNP5/Source/src/tallyh.F90 2003-04-30 20:12:50.000000000 -0600
+++ MCNP5_new/Source/src/tallyh.F90 2004-07-22 15:14:43.000000000 -0600
@@ -5,6 +5,7 @@
! print the tally heading.
use mcnp_global
use mcnp_debug
+ use qttyin_mod

implicit real(dknd) (a-h,o-z)

@@ -51,7 +52,7 @@
if( nps==0 ) write(iuo,10) k
10 format("/!tally",i4,94x, "print table 30")
if( nps>0 ) write(iuo,20) k,nps

```

```

-20 format("/!tally",i4,8x, "nps =",i9)
+20 format("/!tally",i4,8x, "nps =",i12)
  if( l/=0 ) then
    n = itds(1)
    hv = '+'
@@ -69,9 +70,6 @@
  iy = jptal(2,ital)
  js = min(jptal(4,ital),1)
  if( iy==5 ) hk(js+1,5) (20-2*js:24-2*js) = hd(jptal(8,ital))
-#ifndef PCDOS
- if( lockl) call ptttyin
-#endif /*def.pcdos*/
  if( irup/=0 ) call qttyin(iy, ' "processing tally",i5')
  hv = ' '
  if( nps==0 .or. iptal(5,2,ital)/=0 .or. &
diff -Naurd MCNP5/Source/src/tallyp.F90 MCNP5_new/Source/src/tallyp.F90
--- MCNP5/Source/src/tallyp.F90      2003-04-30 20:12:52.000000000 -0600
+++ MCNP5_new/Source/src/tallyp.F90  2004-07-22 15:14:43.000000000 -0600
@@ -26,7 +26,7 @@

  ! find how many lines are in the tfc charts.
  do i=1,20
-   if( npc(i)/=0 ) nn=i
+   if( npc(i)/=0_i8knd ) nn=i
  end do

  ! do all of the tallies in the problem.
@@ -49,9 +49,9 @@
  do i=1,8
    ip(i) = i
  end do
-  nhsd(nsp+8,it) = 1
+  nhsd(nsp+8,it) = 1_i8knd
  do i=4,7
-   nhsd(nsp+5+i,it) = 0
+   nhsd(nsp+5+i,it) = 0_i8knd
  end do
  ac = 0.1
  if( iy==5 ) ac=.05
@@ -146,13 +146,13 @@
  tpp(5+i) = 0.
  vv(i) = 0.
  vv(i+5) = 0.
-  if( tal(j)==0. ) nhsd(nsp+10,it)=nhsd(nsp+10,it)+1
+  if( tal(j)==0. ) nhsd(nsp+10,it)=nhsd(nsp+10,it)+1_i8knd
  if( tal(j)==0. .or. tal(mxf+j)==0. ) cycle DO_80

  ! calculate estimated relative error using first two moments.
  t = tal(j)
  tpp(5+i) = sqrt(max(zero,min(tal(mxf+j)/t**2-fpi,one)))
-  if( tpp(5+i)>=ac ) nhsd(nsp+11,it)=nhsd(nsp+11,it)+1
+  if( tpp(5+i)>=ac ) nhsd(nsp+11,it)=nhsd(nsp+11,it)+1_i8knd

  ! assume a very small rel error is round off and set to zero.
  if( tpp(5+i)<=1.e-7 ) tpp(5+i)=0.
@@ -176,7 +176,7 @@
  if( t2<=0. .or. t1<=0. .or. tal(mxf+j)<=0 ) cycle DO_80
  vv(i+5) = max(zero,min(t2/t1**2,one))
  if( t2<1.e-30 .and. vv(i+5)==one ) vv(i+5)=0.
-  if( vv(i+5)>=0.1 ) nhsd(nsp12,it)=nhsd(nsp12,it)+1
+  if( vv(i+5)>=0.1 ) nhsd(nsp12,it)=nhsd(nsp12,it)+1_i8knd

  ! calculate asymmetric confidence interval shift(w/scale
factor).

  ! see a-1/87-749 for the confidence interval center shift.
@@ -200,13 +200,13 @@
  end do DO_110

  ! print detector diagnostics with the detector if possible.
-  if( ip(1)==1 .and. iy==5 .and. nps/=0 ) call dddiag(i1,0)
+  if( ip(1)==1 .and. iy==5 .and. nps/=0_i8knd ) call dddiag(i1,0)

```



```

end do DO_120

! otherwise print detector diagnostics at the end of the tally.
if( ip(1)==1 ) go to 140
125 continue
- if( iy==5 .and. nps/=0 ) then
+ if( iy==5 .and. nps/=0_i8knd ) then
  do i1=1, iptal(1,3,ital)
    call dddiag(i1,1)
  end do
@@ -242,7 +242,7 @@
  endif
end do
end do
- if( nps<=0 ) return
+ if( nps<=0_i8knd ) return

! print tally fluctuation charts.
call ptfc(nn)
diff -Naurd MCNP5/Source/src/talshf.F90 MCNP5_new/Source/src/talshf.F90
--- MCNP5/Source/src/talshf.F90      2003-04-30 20:12:54.000000000 -0600
+++ MCNP5_new/Source/src/talshf.F90  2004-07-22 15:14:43.000000000 -0600
@@ -9,6 +9,7 @@
! Modules used:
use mcnp_global
use mcnp_debug
+ use hpsort_mod, only: hpsort

implicit real(dknd) (a-h,o-z)

@@ -35,24 +36,24 @@
  j = max(1,min(nsp,int(10.*log10(abs(t))+nhb)))
  if ( t<=0 ) then
    j = 1
-   nhsd(knhs+nsp+1,it) = nhsd(knhs+nsp+1,it)+1
+   nhsd(knhs+nsp+1,it) = nhsd(knhs+nsp+1,it)+1_i8knd
    shsd(kshs+nsp+1,it) = shsd(kshs+nsp+1,it)+t
  end if
-   nhsd(knhs+j,it) = nhsd(knhs+j,it)+1
-   nhsd(knhs+nsp+2,it) = nhsd(knhs+nsp+2,it)+1
+   nhsd(knhs+j,it) = nhsd(knhs+j,it)+1_i8knd
+   nhsd(knhs+nsp+2,it) = nhsd(knhs+nsp+2,it)+1_i8knd
    shsd(kshs+j,it) = shsd(kshs+j,it)+t
    shsd(kshs+nsp+2,it) = shsd(kshs+nsp+2,it)+t

! save the ntp largest,smallest history tallies for each tfc bin.
if( t<=shsd(kshs+nsp+ntp+6,it) ) cycle DO_10_1
if( nhsd(knhs+nsp+6,it)==ntp ) then
-   nhsd(knhs+nsp+7,it) = nhsd(knhs+nsp+7,it)+1
+   nhsd(knhs+nsp+7,it) = nhsd(knhs+nsp+7,it)+1_i8knd
  stt(kstt+nhsd(knhs+nsp+7,it),it) = t
-   if( nhsd(knhs+nsp+7,it)==ntp ) then
+   if( nhsd(knhs+nsp+7,it)==int(ntp,i8knd) ) then
    call hpsort(it, knhs+nsp+5, kshs+nsp+5, ntp, ntp)
  endif
else
-   nhsd(knhs+nsp+6,it) = nhsd(knhs+nsp+6,it)+1
+   nhsd(knhs+nsp+6,it) = nhsd(knhs+nsp+6,it)+1_i8knd
  shsd(kshs+nsp+5+nhsd(knhs+nsp+6,it),it) = t
endif
end do DO_10_1
diff -Naurd MCNP5/Source/src/tekdvvr.F90 MCNP5_new/Source/src/tekdvvr.F90
--- MCNP5/Source/src/tekdvvr.F90      2003-04-30 20:12:56.000000000 -0600
+++ MCNP5_new/Source/src/tekdvvr.F90  2004-07-22 15:14:43.000000000 -0600
@@ -25,9 +25,6 @@
  data np/0,1,3*0,1,4*0,1,1,0,1,4*0,1/,nn/9*0,1,1,0,1,5*0,1/
!
! specify the window and the character expansion factor.
-#ifdef LAHEY
- call IGrAreaClear(0.0,0.0,1.0,1.0)
-#endif /*def.lahey*/

```

```

        et(1) = extent(1)*(1.+2*(1-jvp))
        et(2) = extent(2)*(1.+2*(1-jvp))
        call gswm(1,-et(1)*(5-2*jvp)/3.,et(1),-et(2),et(2))
@@ -110,14 +107,11 @@
! write the legend if the viewport is rectangular.
yv = .96*et(2)
yd = 1.5*sch*et(2)
-#ifndef LAHEY
- if( jgf==0 ) yd = yd*2.0
-#endif /*def.lahey*/
        call gschh(real(sch)*et(2))
        if( jvp/=0 ) go to 110
        call getidt(idtm)
        xv = -1.64*et(1)
- call gtx(xv,yv,idtm)
+ call gtx(xv,yv,idtm)
        i = 33
        do iz = 1,33
            if(aid(iz:iz) == ' ')i=iz
@@ -171,9 +165,7 @@
        110 continue
            xhom = -.33*(5-2*jvp)*et(1)
            yhom = yv-yd
-#ifndef LAHEY
        call gxhome(real(xhom),real(yhom))
-#endif /*-def.lahey*/
        return
    end subroutine tekdv
    #endif /*def.plot*/
diff -Naurd MCNP5/Source/src/tpefil.F90 MCNP5_new/Source/src/tpefil.F90
--- MCNP5/Source/src/tpefil.F90      2003-04-30 20:12:58.000000000 -0600
+++ MCNP5_new/Source/src/tpefil.F90  2004-07-22 15:14:43.000000000 -0600
@@ -52,11 +52,11 @@
! -----
! mm=3 -- Write the fixed data and the first dump.
case( 3 )
- write(iur) aplace,kplace,lplace,gfixcm,jfixcm,i8fixcm
+ write(iur) aplace,kplace,lplace,gfixcm,i8fixcm,jfixcm
  call fdac_write(iur)

! Zero the tfc bin history score arrays and tally blocks.
- nhsd( 1:nspl2, 1:ntal*(npert+1) ) = 0
+ nhsd( 1:nspl2, 1:ntal*(npert+1) ) = 0_i8knd
  shsd( 1:nspt, 1:ntal*(npert+1) ) = 0.
  tal( 1:nmxf*mxmf+ktls ) = 0.

@@ -87,9 +87,9 @@
write(jtty,70) knod,runtpe,nps,hp(1:15),cts/60.,hp(17:31)

60 format(/1x,119('*')/ " dump no.",i5, " on file ",a8,5x, &
- & "nps =",i10,5x, "coll =",a15,5x, "ctm =",f8.2,5x, "nrn =",a15/)
-70 format( " dump",i5, " on file ",a8,3x, "nps =",i10,4x, &
- & "coll =",a15/ 30x, "ctm =",f10.2,5x, "nrn =",a15)
+ & "nps =",i12,5x, "coll =",a15,5x, "ctm =",f12.2,3x, "nrn =",a18/)
+70 format( " dump",i5, " on file ",a8,3x, "nps =",i12,4x, &
+ & "coll =",a15/ 30x, "ctm =",f12.2,3x, "nrn =",a18)

! -----
! mm=5 -- Open existing runtpe and read it for continue run.
@@ -115,7 +115,7 @@
read(iur) id
enddo

- read(iur) aplace,kplace,lplace,gfixcm,jfixcm,i8fixcm
+ read(iur) aplace,kplace,lplace,gfixcm,i8fixcm,jfixcm

! set up dynamic storage
if( allocated( gbnk ) ) deallocate( gbnk )
@@ -127,7 +127,7 @@
mt = 1
endif

```

```

        allocate( gbnk( 1:mbnk*mtasks ) )
-       allocate( ibnk( 1:(nbmx*(lpblcm+2*abs(iunr))+1)*mtasks ) )
+       allocate( ibnk( 0:(nbmx*(lpblcm+2*abs(iunr))+1)*mtasks ) )
        allocate( tal( 1:(nmxf*mx+ktls)*mt ) )
        gbnk = 0.0
        ibnk = 0
@@ -175,10 +175,10 @@
        ! Print comments about starting from the restart dump.
        write(iuo,150) knod,runtpe,nps,cts/60.,probid
-       150 format(/ " starting from dump no.",i5, " from file ",a8,5x,&
+       & "nps =",i10,5x, "ctm =",f8.2,5x, "probid = ",a19/)
+       & "nps =",i12,5x, "ctm =",f12.2,5x, "probid = ",a19/)
        write(jtty,160) knod,runtpe,nps,cts/60.,probid
-       160 format( " starting from dump",i5, " file ",a8, " nps =",i10,&
+       & " ctm =",f8.2/ " probid = ",a19)
+       160 format( " starting from dump",i5, " file ",a8, " nps =",i12,&
+       & " ctm =",f12.2/ " probid = ",a19)

        ! -----
        ! mm=6 -- Make sure of write access to runtpe.
@@ -213,7 +213,7 @@
        do i = 1,mxe
            read(iur) id
        enddo
-       read(iur) aplace,kplace,lplace,gfixcm,jfixcm,i8fixcm
+       read(iur) aplace,kplace,lplace,gfixcm,i8fixcm,jfixcm

        call dyn_allocate

diff -Naurd MCNP5/Source/src/track.F90 MCNP5_new/Source/src/track.F90
--- MCNP5/Source/src/track.F90      2003-04-30 20:12:58.000000000 -0600
+++ MCNP5_new/Source/src/track.F90  2004-07-22 15:14:43.000000000 -0600
@@ -11,18 +11,16 @@

        use mcnp_global
        use mcnp_debug
+       use qttyin_mod, only: qttyin

        implicit real(dknd) (a-h,o-z)
        real(dknd) :: dl(0:mxlv)
        integer    :: jp(0:mxlv)

        ! set up to do the cell in the current level.
-#ifndef PCDOS
-       if( lockl ) call pttysin
-#endif /*def.pcdos*/
        if( irup/=0 ) then
            if( .not.mcnp_opt_multt ) then
-               call qttyin(-1,' "nps =",i9,5x, "collisions =",i6')
+               call qttyin(-1,' "nps =",i12,5x, "collisions =",i6')
            endif
        endif
        ll = lev
@@ -30,7 +28,7 @@

        ! find the distance to boundary, dl, in this cell.
        10 continue
-       dl(ll) = huge
+       dl(ll) = huge_float
        nlt = 0

        ! calculate all intersections with all surfaces of this cell.
@@ -318,11 +316,11 @@
        if( dti(m)<dti(nl) ) nl = m
        enddo
        dl(ll) = dti(nl)
-       if( dl(ll)==huge ) exit
+       if( dl(ll)==huge_float ) exit
        do j1 = j2,j3
            if( abs(lja(j1))==iti(nl) ) lgc(j1-j2+1) = 1-lgc(j1-j2+1)
        enddo

```

```

-      dti(n1) = huge
+      dti(n1) = huge_float
      if( lgeval(lgc,j3-j2+1)==0 ) then
        jp(ll) = iti(n1)
        exit
@@ -370,6 +368,6 @@
      jap = jp(levp)
      !
      ! return with error indicator if no intersection was found.
-      if( dls==huge ) kdb = 2
+      if( dls==huge_float ) kdb = 2
      return
    end subroutine track
diff -Naurd MCNP5/Source/src/trfmat.F90 MCNP5_new/Source/src/trfmat.F90
--- MCNP5/Source/src/trfmat.F90      2003-04-30 20:13:00.000000000 -0600
+++ MCNP5_new/Source/src/trfmat.F90  2004-07-22 15:14:43.000000000 -0600
@@ -7,6 +7,7 @@
      use mcnp_global
      use mcnp_debug
      use mcnp_input
+     use erprnt_mod

      implicit real(dknd) (a-h,o-z)

@@ -18,7 +19,7 @@
      tr = 0.0
      do i=1,14
        tr(i) = trf(i,jt)
-      if( tr(i)/=huge .and. i>=5 .and. i<=13 ) nb=nb+1
+      if( tr(i)/=huge_float .and. i>=5 .and. i<=13 ) nb=nb+1
      end do
      if( tr(14)==0. ) tr(14)=1.

@@ -37,7 +38,7 @@
      ! >>>>> nb=3 -- one vector.
      do k=1,2
        do j=1,3
-          if( tr(3*j+2)/=huge .and. tr(3*j+3)/=huge .and. tr(3*j+4)/=huge ) then
+          if( tr(3*j+2)/=huge_float .and. tr(3*j+3)/=huge_float .and.
tr(3*j+4)/=huge_float ) then
            r = sqrt(tr(3*j+2)**2+tr(3*j+3)**2+tr(3*j+4)**2)
            if( r==0. ) go to 320
            do i=2,4
@@ -67,7 +68,7 @@
      ! >>>>> nb=6 -- two vectors in the same system.
      do k=1,2
        do j=1,3
-          if( tr(3*j+2)==huge .and. tr(3*j+3)==huge .and. tr(3*j+4)==huge ) then
+          if( tr(3*j+2)==huge_float .and. tr(3*j+3)==huge_float .and.
tr(3*j+4)==huge_float ) then
            do l=1,2
              m = mod(j+l-1,3)+1
              r = sqrt(tr(3*m+2)**2+tr(3*m+3)**2+tr(3*m+4)**2)
@@ -99,17 +100,17 @@
      case( 5 )
      ! >>>>> nb=5 -- one vector in each system.
      do il=1,3
-      if( tr(3*il+2)/=huge .and. tr(3*il+3)/=huge .and. tr(3*il+4)/=huge ) then
+      if( tr(3*il+2)/=huge_float .and. tr(3*il+3)/=huge_float .and.
tr(3*il+4)/=huge_float ) then
        do jl=1,3
-          if( tr(jl+4)/=huge .and. tr(jl+7)/=huge .and. tr(jl+10)/=huge ) then
+          if( tr(jl+4)/=huge_float .and. tr(jl+7)/=huge_float .and.
tr(jl+10)/=huge_float ) then
          r = tr(3*il+jl+1)**2
          do i=5,13
-          if( tr(i)/=huge ) r=r+tr(i)**2
+          if( tr(i)/=huge_float ) r=r+tr(i)**2
          end do
          r = sqrt(.5*r)
          if( r==0. ) go to 320

```

```

do i=5,13
-   if( tr(i)/=huge ) tr(i)=tr(i)/r
+   if( tr(i)/=huge_float ) tr(i)=tr(i)/r
end do
if( tr(3*i1+j1+1)**2==1. ) go to 320
i2 = mod(i1,3)+1
diff -Naurd MCNP5/Source/src/trfsrf.F90 MCNP5_new/Source/src/trfsrf.F90
--- MCNP5/Source/src/trfsrf.F90      2003-04-30 20:13:00.000000000 -0600
+++ MCNP5_new/Source/src/trfsrf.F90  2004-07-22 15:14:43.000000000 -0600
@@ -6,6 +6,7 @@
use mcnp_global
use mcnp_debug
use mcnp_input
+ use erprnt_mod

implicit real(dknd) (a-h,o-z)

diff -Naurd MCNP5/Source/src/trnspt.F90 MCNP5_new/Source/src/trnspt.F90
--- MCNP5/Source/src/trnspt.F90      2003-04-30 20:13:00.000000000 -0600
+++ MCNP5_new/Source/src/trnspt.F90  2004-07-22 15:14:43.000000000 -0600
@@ -13,6 +13,7 @@

implicit real(dknd) (a-h,o-z)

+
call utask

call secnd(t1)
@@ -26,7 +27,7 @@
do while( .not. time_to_stop() )

! Run the next history.
- nps = nps+1
+ nps = nps+1_i8knd
npstc = nps

if( ltasks<=1 ) nbal(ktask+1) = nbal(ktask+1)+1
@@ -64,15 +65,15 @@
! see if it's time to stop running histories &
! return to do output, a dump, plotting, handle an
! interrupt, or terminate the problem...
-
logical :: time_to_stop
+ integer(i8knd) :: n,ne

time_to_stop = .false.

! Quit if enough particles have been started from the source.
- if( nsr==6 .and. nrrs>=nrss ) nst = nst+1024
- if( ltasks<=1 .and. nps>=npp .and. npp/=0 ) nst = nst+4
- if( ltasks>1 .and. nps>=npp ) nst = nst+4 ! npp may be 0
+ if( nsr==6 .and. nrrs>=nrss ) nst = nst+1024
+ if( ltasks<=1 .and. nps>=npp .and. npp/=0_i8knd ) nst = nst+4
+ if( ltasks>1 .and. nps>=npp ) nst = nst+4 ! npp may be 0

! Quit if too many particles are lost.
if( nerr>=lost(1) ) nst = nst+8
@@ -113,21 +114,21 @@
endif

! Set output flags at specified histories.
- if( prn>0 .and. mod(n,max(1,int(prn)))==0 ) mpc = 1
- if( dmp>0 .and. mod(n,max(1,int(dmp)))==0 ) mdc = 1
+ if( prn>0 .and. mod(n,int(max(1_i8knd,int(prn,i8knd))),i8knd)==0 ) mpc = 1
+ if( dmp>0 .and. mod(n,int(max(1_i8knd,int(dmp,i8knd))),i8knd)==0 ) mdc = 1
if( kmplot/=0 .or. &
- & (krtm/=0 .and. freq>0 .and. mod(n,max(1,int(freq)))==0 ) mrm = 1
+ & (krtm/=0 .and. freq>0 .and. mod(n,int(max(1,int(freq)),i8knd))==0 ) mrm =
1
30 continue

```

```

! Check the time once a second and for output.
call secnd(t2)
if( nps>=ntc1 .or. nst+jtfc+mpc+mdc+mrm/=0 .or. &
& (nps==npsmg .and. npsmg/=0 .and. npsout/=npsmg) .or. &
- & (nsr==71 .and. nsa==0) .or. (nps==200 .and. npsout/=200) ) then
+ & (nsr==71 .and. nsa==0) .or. (nps==200_i8knd .and. npsout/=200_i8knd) ) then
  if( t2<cp2(ktask+1)-1. ) then
    write(jtty,40) kod,cp2(ktask+1)/60.,t2/60.
    write(iuo,40) kod,cp2(ktask+1)/60.,t2/60.
-40 format( " restarted ",a8,8x, "old time =",f7.2,4x,"new time =",f7.2)
+40 format( " restarted ",a8,8x, "old time =",f9.2,4x,"new time =",f9.2)
    nrc = nrc+1
  else
    cp1 = cp1+(t2-cp2(ktask+1))/ntasks
@@ -155,8 +156,8 @@
    ! set flag to stop running histories if output is required.
    if( (nsr==71 .and. nsa==0) .or. &
& jtfc+nst/=0 .or. &
- & (nps==npsmg .and. npsmg/=0 .and. npsout/=npsmg) .or. &
- & (nps==200 .and. npsout/=200) .or. &
+ & (nps==npsmg .and. npsmg/=0_i8knd .and. npsout/=npsmg) .or. &
+ & (nps==200_i8knd .and. npsout/=200_i8knd) .or. &
& (ltasks<=1 .and. mpc+mdc+mrm/=0) ) time_to_stop = .true.
    endif
  return
diff -Naurd MCNP5/Source/src/tskcom.F90 MCNP5_new/Source/src/tskcom.F90
--- MCNP5/Source/src/tskcom.F90 2003-04-30 20:13:02.000000000 -0600
+++ MCNP5_new/Source/src/tskcom.F90 2004-07-22 15:14:43.000000000 -0600
@@ -10,11 +10,37 @@
  use mcnp_params
  use mcnp_debug
  use fixcom, only : ltskpt
- use varcom, only : nvarsw, lvarsw
+ use varcom, only : nvarsw, l8varsw, lvarsw

  implicit none

- ! Swept tskcom reals - order is important, see varcom.
+
+ -----
+ ! (1) parameters for the length of the 3 portions of /tskcm/
+ ! Swept-tskcom,itskpt lengths and equivalences.
+
+ integer,parameter :: ntskcm = & != Size of floating-point part of /TSKCM/.
+ & nvarsw + 25*(1) + 3*(3) + 1*(5) + 1*(7) + 1*(64) &
+ & + 1*(3*11) + 2*(mipt) + 1*(mlgc) + 1*(3*maxv) + 4*(10*mxlv+10)
+
+ integer,parameter :: l8tskcm = & != Size of INTEGER*8 part of /TSKCM/.
+ & l8varsw + 2*(1)
+
+ integer,parameter :: ltskcm = & != Size of integer part of /TSKCM/.
+ & lvarsw + 43*(1) + 1*(5*(1+mxlv)) + 1*(maxv) &
+ & + 1*(mipt) + 1*(mlgc) + 1*(mlgc+1) + 1*(nlocks)
+
+ !-----
+
+ ! (2) declarations for 3 arrays equivalenced to /tskcm/
+
+ real(dknd) :: gtskcm(ntskcm) != Equivalence to real part of /TSKCM/.
+ integer(i8knd) :: i8tskcm(l8tskcm) != Equivalence to integer*8 part of /TSKCM/.
+ integer :: jtskcm(ltskcm) != Equivalence to integer part of /TSKCM/.
+
+ !-----
+
+ ! (3) declarations for /tskcm/ REALS
+
+ ! Swept tskcom reals - order is important, see varcom - length = nvarsw
  real(dknd) :: colltc(mipt) != Task copy of COLL.
  real(dknd) :: eacctc(4) != Task copy of EACC.
  real(dknd) :: paxtc(6,21,mipt) != Task copy of PAX.

```

```

@@ -25,8 +51,6 @@
real(dknd) :: tmavtc(mipt,3)      != Task copy of TMAV.
real(dknd) :: wgtstc(2)         != Task copy of WGTTS.

- common /tskcm/ colltc, eacctc, paxtc, rlttc, rnrtc, smultc, sumktc, tmavtc, wgtstc
-
! Non-swept tskcom reals.
real(dknd) :: amfp              != Mean free paths to detector or DXTRAN sphere.
real(dknd) :: ang(3)           != Surface normal and cosine of track direction.
@@ -69,21 +93,24 @@
real(dknd) :: ycn              != Temperature-normalized neutron velocity.
real(dknd) :: ztskcm          != Marker after floating-point part of /TSKCM/.

- common /tskcm/&
-   & amfp, ang, cbwf, cmult, colout, ddet, deb, deltas, deltac, &
-   & dti, eg0, ergace, pfp, ple, pmf, psc, ptbtc, qpl, rnb, &
-   & rr0, sff, siga, ssr, stp, totgpl, totm, totpn, tpd, tpp, &
-   & ttn, udt, udtsav, uold, vtr, wcs1tc, wcs2tc, ycn, ztskcm
+ !-----
--
+ ! (4) declarations for /tskcm/ INTEGER*8
+
+ ! Swept integer*8 - order is important, see varcom - length = 18varsw
+ integer(i8knd) :: nrnhtc(3)    != Task copy of NRNH.

+ ! Non-swept Integer*8
+ integer(i8knd) :: npsrtc      != Task copy of nspr
+ integer(i8knd) :: npstc      != Task copy of nps.
+
+ !-----
--
+ ! (5) declarations for /tskcm/ INTEGERS
+ ! Swept tskcom integers - order is important, see varcom.
+ ! Swept tskcom integers - order is important, see varcom.
integer :: nbhwtc              != Task copy of NBHWM.
integer :: nbttc(mipt)        != Task copy of NBT.
- integer :: nrnhtc(3)        != Task copy of NRNH.
integer :: nziytc(8,mxdx,mipt) != Task copy of NZIY.

- common /tskcm/&
-   & nbhwtc, nbttc, nrnhtc, nziytc
- !
! Non-swept tskcom integers.
integer :: iax                != Flag for presence of AXS vector.
integer :: ibc                != Index of the tally cosine bin.
@@ -131,34 +158,47 @@
integer :: nlt                != Number of entries in DTI.
integer :: nmc                != Counter for weight window generator tracking.
integer :: npb                != Number of saved particles in GPB9CM.
- integer :: npsrtc          != Task copy of nspr
- integer :: npstc          != Task copy of nps.
integer :: nter               != Type of termination of the track.
integer :: ntii              != Indicator of multiple time interrupts.
integer :: ntx               != Number of calls of TALLYX in user bins loop.
integer :: nty               != Type of reaction in current collision.
integer :: mtskcm           != Marker after integer part of /TSKCM/.

- common /tskcm/&
+
+ -----
--
+ ! (6) declaration for /tskcm/ (real, interger*8, integer)
+
+ ! REAL
+ common /tskcm/ & ! swept - order important
+   & colltc, eacctc, paxtc, rlttc, rnrtc, smultc, sumktc, tmavtc, wgtstc
+ common /tskcm/ & ! non-swept
+   & amfp, ang, cbwf, cmult, colout, ddet, deb, deltas, deltac, &
+   & dti, eg0, ergace, pfp, ple, pmf, psc, ptbtc, qpl, rnb, &
+   & rr0, sff, siga, ssr, stp, totgpl, totm, totpn, tpd, tpp, &
+   & ttn, udt, udtsav, uold, vtr, wcs1tc, wcs2tc, ycn, ztskcm

```

```

+
+ ! INTEGER*8
+ common /tskcm/ & ! swept
+ & nrrhtc
+ common /tskcm/ & ! non-swept
+ & npsrtc,npstc
+
+ ! INTEGER
+ common /tskcm/& ! swept
+ & nbhwtc,nbttc, nziytc
+ common /tskcm/& ! non-swept
+ & iax, ibc, ibe, ibs, ibt, ibu, ic0, iclp, id0, idet, &
+ & iet, imd, iper, ipsc, irt, isic, ital, iti, iw0, ixcos, &
+ & ixre, jap, jbd, jbnk, jev, jlock, jtls, kdb, kqss, ktask, &
+ & levp, lgc, lsb, mbb, mkc, mpan, nbnk, nch, ngp, nlaj, &
- & nlse, nlt, nmc, npb, npsrtc,npstc, nter, ntii, ntx, ntyn, &
- & mtskcm
-
- ! Swept-tskcom,itskpt lengths and equivalences.
- integer,parameter :: ntskcm = & != Size of floating-point part of /TSKCM/.
- & nvarsw + 25*(1) + 3*(3) + 1*(5) + 1*(7) + 1*(64)&
- & + 1*(3*11) + 2*(mipt) + 1*(mlgc) + 1*(3*maxv) + 4*(10*mxlv+10)
- integer,parameter :: ltskcm = & != Size of integer part of /TSKCM/.
- & lvarsw + 45*(1) + 1*(5*(1+mxlv)) + 1*(maxv) &
- & + 1*(mipt) + 1*(mlgc) + 1*(mlgc+1) + 1*(nlocks)
+ & nlse, nlt, nmc, npb, nter, ntii, ntx, ntyn, mtskcm

- real(dknd) :: gtskcm(ntskcm) != Equivalence to real part of /TSKCM/.
- integer :: jtskcm(ltskcm) != Equivalence to integer part of /TSKCM/.
+ EQUIVALENCE (colltc, gtskcm)
+ EQUIVALENCE (nrrhtc, i8tskcm)
+ EQUIVALENCE (nbhwtc, jtskcm)

- equivalence (colltc,gtskcm), (nbhwtc,jtskcm)
+ !-----
--
+ ! (7) declaration for /itskpt/ - k-pointers for parallel calcs

! Itskpt common -- parallel offset variables.
integer :: kbnk != Task offset for IBNK array.
diff -Naurd MCNP5/Source/src/ttbr.F90 MCNP5_new/Source/src/ttbr.F90
--- MCNP5/Source/src/ttbr.F90 2003-04-30 20:13:02.000000000 -0600
+++ MCNP5_new/Source/src/ttbr.F90 2004-07-22 15:14:43.000000000 -0600
@@ -7,7 +7,9 @@
! d = length of path segment.

use mcnp_global
+ use dxtran_mod
use mcnp_debug
+ use erprnt_mod

implicit real(dknd) (a-h,o-z)

@@ -64,11 +66,7 @@
npa = 1
ncp = 0
jsu = 0
- idx = 0
- do i = 1,ndx(2)
- if( (xxx-dxx(2,1,i))**2+(yyy-dxx(2,2,i))**2+&
- & (zzz-dxx(2,3,i))**2<dxx(2,5,i) ) idx = i
- enddo
+ idx = inside_dxtran_sphere()
ipsc = 13
deb = sqrt(erg*(erg+2.*gpt(3)))/(erg+gpt(3))

diff -Naurd MCNP5/Source/src/ttyint.F90 MCNP5_new/Source/src/ttyint.F90
--- MCNP5/Source/src/ttyint.F90 2003-04-30 20:13:02.000000000 -0600
+++ MCNP5_new/Source/src/ttyint.F90 2004-07-22 15:14:43.000000000 -0600
@@ -6,11 +6,6 @@
! Set up the tty interrupt.

```



```

        use mcnp_debug
-#ifdef PCDOS
-   use mcnp_global
-   implicit none
-   integer :: k
-#endif

        external pttuin

@@ -40,9 +35,5 @@

        #endif /*def.unix.or.dec*/

-#ifdef PCDOS
-   call break(lock1)
-#endif /*def.pcdos*/
-
        return
    end subroutine ttyint
diff -Naurd MCNP5/Source/src/ufiles.F90 MCNP5_new/Source/src/ufiles.F90
--- MCNP5/Source/src/ufiles.F90      2003-04-30 20:13:04.000000000 -0600
+++ MCNP5_new/Source/src/ufiles.F90  2004-07-22 15:14:43.000000000 -0600
@@ -6,6 +6,7 @@
        use mcnp_global
        use mcnp_debug
        use mcnp_input
+   use erprnt_mod

        implicit real(dknd) (a-h,o-z)

diff -Naurd MCNP5/Source/src/unimaz.F90 MCNP5_new/Source/src/unimaz.F90
--- MCNP5/Source/src/unimaz.F90      2003-04-30 20:13:04.000000000 -0600
+++ MCNP5_new/Source/src/unimaz.F90  2004-07-22 15:14:43.000000000 -0600
@@ -9,6 +9,8 @@
        use mcnp_global
        use mcnp_debug
        use dynamic_arrays
+   use erprnt_mod
+
        implicit real(dknd) (a-h,o-z)

diff -Naurd MCNP5/Source/src/utask.F90 MCNP5_new/Source/src/utask.F90
--- MCNP5/Source/src/utask.F90       2003-11-05 17:23:12.000000000 -0700
+++ MCNP5_new/Source/src/utask.F90   2004-07-22 15:14:43.000000000 -0600
@@ -14,14 +14,17 @@

        ! Initialize /tskcom/ and /pblcom/.
        gtskcm(1:ntskcm) = 0.
+   i8tskcm(1:l8tskcm) = 0_i8knd
        jtskcm(1:ltskcm) = 0
+
        gpblcm(1:npblcm+1) = 0.
        gpb9cm(1:mpb,1:npblcm+1) = 0.
        jpblcm(1:lpblcm+1) = 0
        jpb9cm(1:mpb,1:lpblcm+1) = 0
+
        wcs1tc(1:mipt) = wcs1(1:mipt)
        wcs2tc(1:mipt) = wcs2(1:mipt)
-   wgtstc(1) = huge
+   wgtstc(1) = huge_float

        if( mcnp_opt_parallel ) then
            if( ntasks>1 ) jlock = -1
@@ -81,7 +84,7 @@

        ! Clear and reset history score and tally blocks for this task.
        if( itask>=0 ) then
-           nhsd( knhs+1:knhs+nsp12, 1:ntal*(npert+1) ) = 0
+           nhsd( knhs+1:knhs+nsp12, 1:ntal*(npert+1) ) = 0_i8knd

```

```

      shsd( kshs+1:kshs+nspt, 1:ntal*(npert+1) ) = 0.
      ddm( kddm+1, 1:ntal*(npert+1) ) = ddm( 1, 1:ntal*(npert+1) )
      shsd(kshs+nspt-1, 1:ntal*(npert+1)) = shsd(nspt-1, 1:ntal*(npert+1))
diff  -Naurd MCNP5/Source/src/varcom.F90 MCNP5_new/Source/src/varcom.F90
--- MCNP5/Source/src/varcom.F90      2003-04-30 20:13:08.000000000 -0600
+++ MCNP5_new/Source/src/varcom.F90  2004-07-22 15:14:43.000000000 -0600
@@ -22,23 +22,41 @@
! varcom tag:
character(len=64), parameter, private :: fx_tag = "varcom 11-01-2002"

- ! Varcom length parameters:
- integer, parameter :: nvarsw =& != Number of swept variable common
+ !-----
--
+ ! (1) parameters for the length of the 3 portions of /varcm/
+
+ integer, parameter :: nvarsw =& != Number of swept REALS
+ & 1*(1) + 1*(2) + 1*(3) + 1*(4) + 1*(7) + 1*(4*2)&
+ & + 1*(6*21*mipt) + 1*(mipt) + 1*(mipt*3)
+
- integer, parameter :: nvarcm =& != Size of floating-point part of
+ integer, parameter :: nvarcm =& != Size of REAL part of /varcm/
+ & nvarsw + 12*(1) + 2*(3) + 1*(4) + 1*(10) &
+ & + 1*(30) + 1*(50) + 1*(2*3) + 2*(3*3) + 2*(mipt)
+
- integer, parameter :: lvarsw =& != Number of swept variable common
+ integer, parameter :: l8varsw = & != Number of swept INTEGER*8
+ & 1*(3)
+
+ integer, parameter :: l8varcm =& != Size of INTEGER*8 part of /VARCM/.
+ & l8varsw + 13*(1) + 1*(20)
+
+ integer, parameter :: lvarsw =& != Number of swept INTEGERS
+ & 1*(1) + 1*(8*mxdx*mipt) + 1*(mipt) + 1*(3)
+
integer, parameter :: lvarcm =& != Size of integer part of /VARCM/.
- & lvarsw + 47*(1) + 2*(2) + 1*(3) + 1*(10)&
- & + 1*(20) + 1*(50) + 1*(2*99) + 1*(100)
+ & lvarsw + 34*(1) + 2*(2) + 1*(3) + 1*(10)&
+ & + 1*(50) + 1*(2*99) + 1*(100)
+
- ! Real variables swept from tskcom:
+ !-----
--
+ ! (2) declarations for 3 arrays equivalenced to /varcm/
+
+ real(dknd) :: gvarcm(nvarcm)
+ integer(i8knd) :: i8varcm(l8varcm)
+ integer :: jvarcm(lvarcm)
+
+ !-----
--
+ ! (3) declarations for /varcm/ REALS
+
+ ! Real variables swept from tskcom - length = nvarsw
real(dknd) :: coll(mipt) != Number of collisions in problem.
real(dknd) :: eacc(4) != Weight and energy of electrons above EMAX.
real(dknd) :: pax(6,21,mipt) != Ledger of creation and loss. See App. E.
@@ -75,10 +93,35 @@
real(dknd) :: wt0 != Weight of each KCODE source point.
real(dknd) :: zvarcm != Marker after floating-point part of /VARCM/.

+ !-----
--
+ ! (4) declarations for /varcm/ INTEGER*8
+
+ ! swept Integer*8 variables
+ integer(i8knd) :: nrnh(3) != Information about number of random numbers used.
+
+ ! non-swept INTEGER*8
+ integer(i8knd) :: nps != Count of source particles started.

```

```

+ integer(i8knd) :: npsmg      != Number of source particles that contribute
+                               != to image grid (2nd nps card entry).
+ integer(i8knd) :: npsout    != NPS when output was last done.
+ integer(i8knd) :: npc(20)   != NPS for tally fluctuation charts. See App. E.
+ integer(i8knd) :: npd       != NPS step in tally fluctuation chart.
+ integer(i8knd) :: npp       != Number of histories to run, from NPS card.
+ integer(i8knd) :: npsr      != History number last read from surface source.
+ integer(i8knd) :: nqss      != Number of histories read from surface source.
+ integer(i8knd) :: nqsw      != Number of histories written to surface source.
+ integer(i8knd) :: nrrs      != Number of tracks read from surface source.
+ integer(i8knd) :: nrsw      != Number of tracks written to surface source.
+ integer(i8knd) :: ntc       != Control variable for time check.
+ integer(i8knd) :: ntcl      != Second control variable for time check.
+ integer(i8knd) :: ntss      != Number of surface source tracks accepted.
+
+ !-----
--
+ ! (5) declarations for /varcm/ INTEGERS
+
+ ! Integer variables swept from tskcom:
integer :: nbhwm      != Largest number of particles ever in the bank.
integer :: nbt(mipt) != Total numbers particles banked.
- integer :: nrnh(3)  != Information about number of random numbers used.
integer :: nziy(8,mxdx,mipt) != DXTRANS lost to zero importance.

! Non-swept integer variables:
@@ -111,21 +154,9 @@
integer :: notrn      != Flag to only calculate direct source
                               != to point detector tallies
                               != (no particles are transported).
- integer :: npc(20)  != NPS for tally fluctuation charts. See App. E.
- integer :: npd      != NPS step in tally fluctuation chart.
integer :: npsnm      != Count of times neutron-reaction MT not found.
- integer :: npp      != Number of histories to run, from NPS card.
integer :: nppm      != Count of times photon-production MT not found.
- integer :: nps      != Count of source particles started.
- integer :: npsmg     != Number of source particles that contribute
                               != to image grid (2nd nps card entry).
-                               != NPS when output was last done.
- integer :: npsr      != History number last read from surface source.
integer :: npum      != Flag for Photonuclear production failure.
- integer :: nqss      != Number of histories read from surface source.
- integer :: nqsw      != Number of histories written to surface source.
- integer :: nrrs      != Number of tracks read from surface source.
- integer :: nrsw      != Number of tracks written to surface source.
integer :: nsa       != Source particles yet to be done in this cycle.
integer :: nsa0      != Saved NSA value to rerun lost history.
integer :: nskk      != Number of histories in first IKZ KCODE cycles.
@@ -135,12 +166,9 @@
integer :: nss       != Count of source points stored for the next cycle.
integer :: nss0      != Saved NSS value to rerun lost history.
integer :: nssi(10)  != Numbers of rejected surface source tracks.
- integer :: ntc      != Control variable for time check.
- integer :: ntcl     != Second control variable for time check.
integer :: ntprt(100) != List of tally numbers on talnp card that
                               != will not have bin values printed
                               != to the outp file.
- integer :: ntss     != Number of surface source tracks accepted.
integer :: nwer      != Count of warning messages printed.
integer :: nwsb      != Count of source weights below cutoff.
integer :: nwse      != Count of source energies below cutoff.
@@ -149,10 +177,9 @@
integer :: nwws(2,99) != Like NWSS and NWSL but binned.
integer :: mvarcm    != Marker variable at end of /VARCM/.

- real(dknd)      ::      gvarcm(nvarcm)
- EQUIVALENCE      (coll,gvarcm)
- integer ::      jvarcm(lvarcm)
- EQUIVALENCE      (nbhwm,jvarcm)
+

```

```

+ !-----
--
+ ! (6) declaration for /varcm/ (real, interger*8, integer)

! real variables swept from tskcom - order important, see tskcom.
common /varcm/ &
@@ -164,151 +191,30 @@
& rrmc, rkk, rssp, rsum, rsum2, snit, swtm, twac, twss, &
& wcs1, wcs2, wssi, wt0, zvarcm

+ ! INTEGER*8
+ common /varcm/ & ! swept - order important, see tskcom.
+ & nrnh
+ common /varcm/ & ! non-swept
+ & nps, npsmg, npsout, npc, npd, npp, npsr, nqss, nqsw, &
+ & nrns, nrsw, ntc, ntcl, ntss
+
! int variables swept from tskcom - order important, see tskcom.
common /varcm/ &
- & nbhwm, nbt, nrnh, nziy
+ & nbhwm, nbt, nziy

! non-swept integer variables.
common /varcm/ &
& irmc, ist, ist0, ixak, ixak0, jrad, kc8, kcz, kcsf, &
- & kct, kcy, knod, ksdef, lost, monod, nbov, ndmp, &
- & nerr, nesm, netb, nfer, notal, notrn, npc, npd, npnm, &
- & npp, nppm, nps, npsmg, npsout, npsr, npum, nqss, nqsw, &
- & nrns, nrsw, nsa, nsa0, nskk, nsom, nss, nss0, nssi, &
- & ntc, ntcl, ntprt, ntss, nwer, nwsb, nwse, nwsg, nwst, &
& nwws, mvarcm
-
-
-contains
-
- !-----
- subroutine vr_write (iu,ierr)
- ! description:
- ! write varcom data to pre-positioned file.
-
- ! argument declarations:
- integer, intent(in) :: iu ! file unit number.
- integer, intent(out) :: ierr ! status.
-
- ! local declarations:
- logical :: lopen
- character(len=11) :: hformat
-
- ! file must be opened and unformatted.
- inquire(UNIT = iu, OPENED = lopen, FORM = hformat)
-
- if( lopen .and. hformat == "UNFORMATTED") then
- ierr = 0
-
- ! write tag.
- write(iu) fx_tag
-
- ! write swept reals.
- write(iu) &
& avarcm, coll, eacc, pax, rlt, rnr, smul, sumk, tmav, wgts
-
- ! write non-swept reals.
- write(iu) &
& bcw, cpk, cts, dbcn, dmp, osum, osum2, pptme, prn, &
& rrmc, rkk, rssp, rsum, rsum2, snit, swtm, twac, twss, &
& wcs1, wcs2, wssi, wt0, zvarcm
-
- ! write swept integers.
- write(iu) &
& nbhwm, nbt, nrnh, nziy
-
-

```

```

-      ! write non-swept integers.
-      write(iu)&
-        & irmc,ist,ist0,ixak,ixak0,jrad,&
-        & kc8,kcz,kcsf,kct,kcy,knod,ksdef,lost,monod,&
-        & nbov,ndmp,nerr,nesm,netb,nfer,notal,notrn,npc,npd,&
-        & nprm,npp,nppm,nps,npsmg,npsout,npsr,npum,nqss,nqsw,nrrs,nrsw,&
-        & nsa,nsa0,nskk,nsom,nss,nss0,nssi,ntc,ntcl,ntpvt,ntss,nwer,&
-        & nwsb,nwse,nwsg,nwst,nwws,mvarcm
-
-      else                                ! either not open or not unformatted.
-        ierr = -1                          ! return an error.
-
-      endif
-      return
-    end subroutine vr_write
-
-    !-----
-
-    subroutine vr_read(iu,ierr)
-      ! description:
-      ! read varcom data from pre-positioned file. Position verified
-      ! by module tag.
-
-      ! argument declarations:
-      integer, intent(in)  :: iu          ! file unit number.
-      integer, intent(out) :: ierr       ! status.
-
-      ! local declarations:
-      logical              :: lopen
-      character(len=11)   :: hformat
-      character(len=64)   :: tag
-
-      ! file must be opened and unformatted.
-      inquire(UNIT = iu, OPENED = lopen, FORM = hformat)
-
-      if ( .not. lopen .or. hformat/"UNFORMATTED" ) then
-        ierr = -1 ! return error
-
-      else
-        ! read tag and verify it against module tag parameter.
-        read(iu) tag
-        if( tag/=fx_tag ) then
-          ierr = -2 ! return error
-
-        else
-          ierr = 0
-
-          ! read swept reals.
-          read(iu)&
-            & avarcm,coll,eacc,pax,rlt,rnr,smul ,sumk,tmav,wgts
-
-          ! read non-swept reals.
-          read(iu)&
-            & bcw,cpk,cts,dbcn,dmp,osum,osum2,pptme,prn,&
-            & rrmc,rkk,rssp,rsum,rsum2,snit,swtm,twac,twss,&
-            & wcs1,wcs2,wssi,wt0,zvarcm
-
-          ! read swept integers.
-          read(iu)&
-            & nbhwm,nbt,nrn,nziy
-
-          ! read non-swept integers.
-          read(iu)&
-            & irmc,ist,ist0,ixak,ixak0,jrad, &
-            & kc8,kcz,kcsf,kct,kcy,knod,ksdef,lost,monod,&
-            & nbov,ndmp,nerr,nesm,netb,nfer,notal,notrn,npc,npd,&
-            & nprm,npp,nppm,nps,npsmg,npsout,npsr,npum,nqss,nqsw,nrrs,nrsw,&
-            & nsa,nsa0,nskk,nsom,nss,nss0,nssi,ntc,ntcl,ntpvt,ntss,nwer,&
-            & nwsb,nwse,nwsg,nwst,nwws,mvarcm
-
-        endif
-      endif

```

```

-
-   endif
-
-   return
- end subroutine vr_read
-
- !-----
-
- subroutine vr_cast(mh,mx,ie)
-   ! Description:
-   ! DMMP bcast of varcom data.
-   ! Arguments:
-   integer,intent(in)    :: mh ! action flag, 0 -> sender.
-   integer,intent(in)    :: mx ! message chunk size (max).
-   integer,intent(inout) :: ie ! return status.
+   & kct,  kcy,  knod,  ksdef,  lost,  monod,  nbov,  ndmp,  nerr,  &
+   & nesm,  netb,  nfer,  notal,  notrn,  nprm,  nppm,  npum,  nsa,  &
+   & nsa0,  nskk,  nsom,  nss,   nss0,  nssi,  ntprt,  nwer,  nwsb,  &
+   & nwse,  nwsq,  nwst,  nwsw,  mvarcm
-
-   call dm_bcast(mh,gvarcm,nvarcm,mx,ie)
-   call dm_bcast(mh,jvarcm,lvarcm,mx,ie)
+   EQUIVALENCE      (coll,  gvarcm)
+   EQUIVALENCE      (nrnh,  i8varcm)
+   EQUIVALENCE      (nbhwm, jvarcm)
-
-   return
- end subroutine vr_cast
+ !-----
--

end module varcom
!-
diff -Naurd MCNP5/Source/src/viewz.F90 MCNP5_new/Source/src/viewz.F90
--- MCNP5/Source/src/viewz.F90      2003-04-30 20:13:08.000000000 -0600
+++ MCNP5_new/Source/src/viewz.F90  2004-07-22 15:14:43.000000000 -0600
@@ -148,8 +148,8 @@
    nn = nint(2.*a+.5)
    coe(1,1,jsu) = coe(1,1,jsu)-ii*d1
    coe(4,1,jsu) = coe(4,1,jsu)-ii*d2
-   udt(2*ku-1,lev) = huge
-   udt(2*ku,lev) = -huge
+   udt(2*ku-1,lev) = huge_float
+   udt(2*ku,lev) = -huge_float
    do j=1,nn
        coe(1,1,jsu) = coe(1,1,jsu)+d1
        coe(4,1,jsu) = coe(4,1,jsu)+d2
@@ -198,8 +198,8 @@
    a = (e1*d1+e2*d2)/(e1**2+e2**2)
    g1 = d1-e1*a
    g2 = d2-e2*a
-   u = huge
-   v = -huge
+   u = huge_float
+   v = -huge_float
    do i=-1,1,2
        do j=-1,1,2
            a = (i-st(1,1))*g1+(j-st(1,2))*g2
@@ -210,8 +210,8 @@
    a = 1./(g1**2+g2**2)
    mm = (v-u)*a+3.
    ii = -u*a+2.
-   u = huge
-   v = -huge
+   u = huge_float
+   v = -huge_float
    do i=-1,1,2
        do j=-1,1,2
            a = (i-st(1,1))*f1+(j-st(1,2))*f2
@@ -226,10 +226,10 @@
    coe(1,1,jn(i)) = coe(1,1,jn(i))-ii*d1-jj*e1

```

```

        coe(4,1,jn(i)) = coe(4,1,jn(i))-ii*d2-jj*e2
    end do
-   udt(1,lev) = huge
-   udt(2,lev) = -huge
-   udt(3,lev) = huge
-   udt(4,lev) = -huge
+   udt(1,lev) = huge_float
+   udt(2,lev) = -huge_float
+   udt(3,lev) = huge_float
+   udt(4,lev) = -huge_float
    lx = abs(lca(lc+1))-lca(lc)-6
    do j=1,nn
        do k=1,6
diff -Naurd MCNP5/Source/src/voidcd.F90 MCNP5_new/Source/src/voidcd.F90
--- MCNP5/Source/src/voidcd.F90      2003-04-30 20:13:08.000000000 -0600
+++ MCNP5_new/Source/src/voidcd.F90  2004-07-22 15:14:43.000000000 -0600
@@ -7,6 +7,7 @@
    use mcnp_global
    use mcnp_debug
    use mcnp_input
+   use erprnt_mod

    implicit real(dknd) (a-h,o-z)

diff -Naurd MCNP5/Source/src/volume.F90 MCNP5_new/Source/src/volume.F90
--- MCNP5/Source/src/volume.F90      2003-11-05 17:23:12.000000000 -0700
+++ MCNP5_new/Source/src/volume.F90  2004-07-22 15:14:43.000000000 -0600
@@ -7,6 +7,8 @@
    use mcnp_global
    use mcnp_debug
    use mcnp_input
+   use qttyin_mod, only: qttyin
+   use erprnt_mod, only: erprnt

    implicit real(dknd) (a-h,o-z)
    character(len=23) :: hh
@@ -32,9 +34,6 @@
    50 format( "1",5x, "details of volume and area calculations")
    DO_250: do icl_tmp=1,mtx
        icl = icl_tmp
-#ifdef PCDOS
-   if(lockl)call ptttyin
-#endif /*def.pcdos*/
    if( irup/=0 ) call qttyin(ncl(icl),' "calculating volume in cell",i5')
    if( dbcn(7)/=0. ) write(iuo,60)ncl(icl)
    60 format(2/" cell",i6,4x,104( ""))
diff -Naurd MCNP5/Source/src/vtask.F90 MCNP5_new/Source/src/vtask.F90
--- MCNP5/Source/src/vtask.F90      2003-11-05 17:23:12.000000000 -0700
+++ MCNP5_new/Source/src/vtask.F90  2004-07-22 15:14:43.000000000 -0600
@@ -10,6 +10,7 @@
    use mcnp_global
    use mcnp_debug
    use fmesh_mod, only: nmesh, fmesh_vtask
+   use hpsort_mod, only: hpsort

    implicit real(dknd) (a-h,o-z)
    real(dknd) :: ar(ntp)
@@ -17,7 +18,7 @@
    ! Multiprocessing - use mynum and itask to determine action.

    ! define a multiplier which is 1 if mynum>0, 0 otherwise
-   lfix = 0
+   lfix=0
    if( mynum>0 ) then
        lfix = 1
    endif
@@ -31,7 +32,7 @@
    !$ call sm_loff(jlock,1)

    do it = 1,ntal*(npert+1)
-   if( nhsd(knhs+nsp+6,it)>1 ) then

```

```

+      if( nhsd(knhs+nsp+6,it)>1_i8knd ) then
+        call hpsort( it, knhs+nsp+5, kshs+nsp+5,&
+          & nhsd(knhs+nsp+6,it), nhsd(knhs+nsp+7,it) )
+      endif
@@ -72,19 +73,19 @@
+      ! Combine global and task largest tally points into global array.
+      if( ntal>0 ) then
+        do it = 1,ntal*(npert+1)
-         if( nhsd(knhs+nsp+2,it)==0 ) cycle
+         if( nhsd(knhs+nsp+2,it)==0_i8knd ) cycle

+         ln = 0
+         ls = 0
+         nhsd(ln+1:ln+nsp+5,it) = nhsd(ln+1:ln+nsp+5,it)+nhsd(knhs+1:knhs+nsp+5,it)
+         shsd(ls+1:ls+nsp+5,it) = shsd(ls+1:ls+nsp+5,it)+shsd(kshs+1:kshs+nsp+5,it)

-         if( nhsd(knhs+nsp+6,it)==0 ) cycle
+         if( nhsd(knhs+nsp+6,it)==0_i8knd ) cycle

+         ! Do extreme tally merge only if this task has large points.
+         nk = nhsd(knhs+nsp+6,it)+kshs+nsp+5
+         nl = nhsd(ln +nsp+6,it)+ls +nsp+5
-         np = min( ntp, nhsd(knhs+nsp+6,it)+nhsd(ln+nsp+6,it) )
+         np = min( int(ntp,i8knd), nhsd(knhs+nsp+6,it)+nhsd(ln+nsp+6,it) )

+         ! Merge global and task extreme tallies and keep sorted.
+         do k = np,1,-1
@@ -209,7 +210,7 @@

+         l = 0
+         isef(l +1:l +2,1:mxa) = isef(l+1:l+2,1:mxa)+isef(kise+1:kise+2,1:mxa)
-         isef(kise+1:kise+2,1:mxa) = 0
+         isef(kise+1:kise+2,1:mxa) = 0_i8knd

+         l = 0
+         n = 3*nmaz*(kpt(1)+kpt(2)+kpt(3))
diff -Naurd MCNP5/Source/src/wgtul.F90 MCNP5_new/Source/src/wgtul.F90
--- MCNP5/Source/src/wgtul.F90      2003-04-30 20:13:10.000000000 -0600
+++ MCNP5_new/Source/src/wgtul.F90  2004-07-22 15:14:43.000000000 -0600
@@ -39,15 +39,15 @@
+         a = 0.
+         b = 0.
+         if( sqq(2,n)<sqc(5,n) ) then
-         a = huge
-         b = huge
+         a = huge_float
+         b = huge_float
+         endif
+         if( sqq(6,n)/=0. ) a = abs(sqq(6,n))**(sqq(2,n)-sqq(5,n))
+         if( sqq(7,n)/=0. ) b = abs(sqq(7,n))**(sqq(2,n)-sqq(5,n))
+         wl = wl*sqq(3,n)*min(a,b)
+         w = max(a,b)
-         if( w==huge ) then
-         wu = huge
+         if( w==huge_float ) then
+         wu = huge_float
+         else
+         wu = wu*sqq(3,n)*w
+         endif
@@ -94,11 +94,11 @@
+         if( spf(ksd(13,n)+3,m)==0. ) go to 80
+         if( ksd(19,n)*ksd(18,n)/=0 ) w=w*spf(ksd(13,n)+2,m)/spf(ksd(13,n)+3,m)
+         w1 = w1*w
-         if( w2/=huge ) w2=w2*w
+         if( w2/=huge_float ) w2=w2*w
+         70 continue
+         w1 = min(w1,w1)
-         if( w2==huge ) wu=huge
-         if( wu/=huge ) wu=max(wu,w2)
+         if( w2==huge_float ) wu=huge_float
+         if( wu/=huge_float ) wu=max(wu,w2)

```



```

80 continue
   m = m+1
   if( m<=ksd(4,n) ) go to 40
diff  -Naurd MCNP5/Source/src/wrwsa.F90 MCNP5_new/Source/src/wrwsa.F90
--- MCNP5/Source/src/wrwsa.F90      2003-04-30 20:13:12.000000000 -0600
+++ MCNP5_new/Source/src/wrwsa.F90  2004-07-22 15:14:43.000000000 -0600
@@ -10,6 +10,7 @@

   real(dknd) :: rs(6), rg(11)
   character hq*80, hf*9
+ integer(i8knd) :: np

   ! create wssa and write general information and table lengths.
   call unique(wssa,jtty)
@@ -59,9 +60,9 @@
   endif
   rewind iusw
   write(jtty,70) wssa,nrsw
-70 format( " surface-source file ",a8, " written with",i8, " tracks.")
+70 format( " surface-source file ",a8, " written with",i12, " tracks.")
   write(iuo,80) wssa,np,nrsw
-80 format( " surface-source file ",a8, " with nps =",i7, " and",i8,&
+80 format( " surface-source file ",a8, " with nps =",i12, " and",i12,&
& " tracks was written for")

   ! write surfaces without facets.
diff  -Naurd MCNP5/Source/src/wtcalc.F90 MCNP5_new/Source/src/wtcalc.F90
--- MCNP5/Source/src/wtcalc.F90      2003-04-30 20:13:12.000000000 -0600
+++ MCNP5_new/Source/src/wtcalc.F90  2004-07-22 15:14:43.000000000 -0600
@@ -28,8 +28,8 @@
   ! Case of no biased dependent variables.
   call wgtul(wl,wu,ivdis(iv),jf)
   w1 = w1*w1
-   if( wu==huge ) w2=huge
-   if( w2/=huge ) w2=w2*wu
+   if( wu==huge_float ) w2=huge_float
+   if( w2/=huge_float ) w2=w2*wu
   cycle DO_140

   ! Case of biased dependent variables.
@@ -64,15 +64,15 @@
   if( ksd(6,jd)==0 ) cycle
   call wgtul(wl,wu,int(spf(ksd(13,jd)+1,i)),jf)
   wp = wp*w1
-   if( wu==huge ) wq=huge
-   if( wq/=huge ) wq=wq*wu
+   if( wu==huge_float ) wq=huge_float
+   if( wq/=huge_float ) wq=wq*wu
   end do
   wa = min(wa,wp)
   wb = max(wb,wq)
   end do
   w1 = w1*wa
-   if( wb==huge ) w2=huge
-   if( w2/=huge ) w2=w2*wb
+   if( wb==huge_float ) w2=huge_float
+   if( w2/=huge_float ) w2=w2*wb
   cycle DO_140

   ! Case of dependent variables with q option.
@@ -102,15 +102,15 @@
   if( wu==w1 .or. ksd(8,jd)==0 ) cycle
   call wgtul(wl,wu,int(spf(ksd(13,jd)+1,i)),jf)
   wp = wp*w1
-   if( wu==huge ) wq=huge
-   if( wq/=huge ) wq=wq*wu
+   if( wu==huge_float ) wq=huge_float
+   if( wq/=huge_float ) wq=wq*wu
   end do
   wa = min(wa,wp)
   wb = max(wb,wq)

```

```

        end do
        w1 = w1*wa
-       if( wb==huge ) w2=huge
-       if( w2/=huge ) w2=w2*wb
+       if( wb==huge_float ) w2=huge_float
+       if( w2/=huge_float ) w2=w2*wb
        cycle DO_140
    end if
130 continue
@@ -124,8 +124,8 @@
    if( swtm==-1. ) swtm=0.

    ! Print the minimum and maximum source weights.
-   w = huge
-   if( w2<.01*huge ) w=w2*srvc(1,17)
+   w = huge_float
+   if( w2<.01*huge_float ) w=w2*srvc(1,17)
    write(iuo,150) w1*srvc(1,17),w
    150 format(/4x, "minimum source weight =",1p11.4,&
        & 4x, "maximum source weight =",1p11.4)
diff -Naurd MCNP5/Source/src/wwfile.F90 MCNP5_new/Source/src/wwfile.F90
--- MCNP5/Source/src/wwfile.F90      2003-04-30 20:13:14.000000000 -0600
+++ MCNP5_new/Source/src/wwfile.F90  2004-07-22 15:14:43.000000000 -0600
@@ -6,6 +6,7 @@
    use mcnpc_global
    use mcnpc_debug
    use rmc_mod
+   use erprnt_mod

    implicit real(dknd) (a-h,o-z)

diff -Naurd MCNP5/Source/src/xsgen.F90 MCNP5_new/Source/src/xsgen.F90
--- MCNP5/Source/src/xsgen.F90      2003-04-30 20:13:16.000000000 -0600
+++ MCNP5_new/Source/src/xsgen.F90  2004-07-22 15:14:43.000000000 -0600
@@ -7,6 +7,8 @@

    use mcnpc_global
    use mcnpc_debug
+   use qttyin_mod, only : qttyin
+   use erprnt_mod, only : erprnt

    implicit real(dknd) (a-h,o-z)
    real(dknd) :: p(243,4)
@@ -208,14 +210,8 @@
    end do

    ! calculate range, straggling, and scattering tables.
-#ifndef PCIDOS
-   if(lockl) call ptttyin
-#endif
    if( irup/=0 ) call qttyin(mkc,' "get electron range, mat",i5')
    call ronge(az,aa,.00001d0*q/aa,nd)
-#ifndef PCIDOS
-   if(lockl) call ptttyin
-#endif
    if( irup/=0 ) call qttyin(mkc,' "get electron scat. xsec, mat",i5')
    call scatt(az)

@@ -256,14 +252,8 @@
    if( xnum>=0. ) xnm(mkc)=xnum

    ! calculate bremsstrahlung cross sections.
-#ifndef PCIDOS
-   if(lockl) call ptttyin
-#endif
    if( irup/=0 ) call qttyin(mkc,' "get bremsstrahlung xsec, mat",i5')
    call brem
-#ifndef PCIDOS
-   if(lockl) call ptttyin
-#endif /*def.pcdos*/
    if( irup/=0 ) call qttyin(mkc,' "get bremsstrahlung scat, mat",i5')

```

```

call brang

diff -Naurd MCNP5/Source/src/ybssp.F90 MCNP5_new/Source/src/ybssp.F90
--- MCNP5/Source/src/ybssp.F90      2003-04-30 20:13:16.000000000 -0600
+++ MCNP5_new/Source/src/ybssp.F90  2004-07-22 15:14:43.000000000 -0600
@@ -4,6 +4,7 @@
subroutine ybssp
! start a banked surface-source particle.
use mcnp_global
+ use dxtran_mod
use mcnp_debug

implicit real(dknd) (a-h,o-z)
diff -Naurd MCNP5/Testing/config/test_options.mk
MCNP5_new/Testing/config/test_options.mk
--- MCNP5/Testing/config/test_options.mk      2003-04-30 20:13:40.000000000 -0600
+++ MCNP5_new/Testing/config/test_options.mk  2004-07-22 15:06:14.000000000 -0600
@@ -169,6 +169,17 @@
ifeq (OSF1,$(OS))
PRUN      := prun -n $(NMPI) -c $(NTRD)
PRUNSEQ   := prun -n 1
+ # ----special syntax for lampi. This procedure for mixed mode
+ # only works for 1 MPI task per node (=4 threads on Q machine)
+ ifneq (,$(findstring lampi, $(CONFIG)))
+   ifeq (1,$(NTRD))
+     PRUN := mpirun -n $(NMPI)
+   else
+     PRUN := mpirun -n $(NMPI) -N $(NMPI)
+   endif
+   PRUNSEQ := mpirun -n 1
+ endif
+
else
PRUN      := mpirun -np $(NMPI)
PRUNSEQ   := mpirun -np 1

```