### LA-UR-12-22259

Approved for public release; distribution is unlimited.

Title:	Continuous-Estimator Representation for Monte Carlo Criticality Diagnostics	
Author(s):	Kiedrowski, Brian C. Brown, Forrest B.	
Intended for:	2012 ANS Annual Meeting, 2012-06-24/2012-06-28 (Chicago, Illinois, United States)	



Disclaimer:

Disclaimer: Los Alamos National Laboratory, an affirmative action/equal opportunity employer, is operated by the Los Alamos National Security, LLC for the National NuclearSecurity Administration of the U.S. Department of Energy under contract DE-AC52-06NA25396. By approving this article, the publisher recognizes that the U.S. Government retains nonexclusive, royalty-free license to publish or reproduce the published form of this contribution, or to allow others to do so, for U.S. Government purposes. Los Alamos National Laboratory requests that the publisher identify this article as work performed under the auspices of the U.S. Departmentof Energy. Los Alamos National Laboratory strongly supports academic freedom and a researcher's right to publish; as an institution, however, the Laboratory does not endorse the viewpoint of a publication or guarantee its technical correctness.

### Continuous-Estimator Representation for Monte Carlo Criticality Diagnostics

Brian C. Kiedrowski Forrest B. Brown

Los Alamos National Laboratory

June 26, 2012



Operated by Los Alamos National Security, LLC for the U.S. Department of Energy's NNSA LA-UR-12-XXXXX



An alternate means of computing diagnostics for Monte Carlo criticality calculations is proposed. Overlapping spherical regions or estimators are placed covering the fissile material with a minimum center-to-center separation of the "fission distance", which is defined herein, and a radius that is some multiple thereof. Fission neutron production is recorded based upon a weighted average of proximities to centers for all the spherical estimators. These scores are used to compute the Shannon entropy, and shown to reproduce the value, to within an additive constant, determined from a well-placed mesh by a user. The spherical estimators are also used to assess statistical coverage.





- Towards Automating Diagnostics
- Spherical Estimators
- Shannon Entropy Results
- Coverage and Sampling Results





# **Diagnostics in Criticality Calculations**

- Modern analysis often requires detailed spatial- and energy-resolved results.
- Source convergence necessary to get the correct answers.
- Is the local fission source sufficiently sampled for a well-behaved solution?
- Many diagnostics available, e.g., Shannon Entropy.
- Some automation for users, but improvements desirable.





# **Shannon Entropy Requirements**

• Shannon entropy provides a measure of how "spread out" a distribution is.

$$H = -\sum_{j=1}^{J} p_j \log(p_j)$$

- User of program must define J spatial regions.
- Uniform grid in MCNP with specified or estimated extent.
- Automated spacing based on total population of particles no physics.
- Generally robust, but possible to get bad meshes, especially for problems with separated discrete regions.





# **Sampling Diagnostics**

- Good local tally results depends on sufficiently sampling nearby fission source.
- For high dominance ratio problems, are all higher modes activated by stochastic noise either sufficiently suppressed or sampled?
- No automatic diagnostic currently in MCNP.
- Shannon entropy mesh may not be suitable because of "small corners" or other non-conformality.



Operated by Los Alamos National Security, LLC for the U.S. Department of Energy's NNSA LA-UR-12-XXXXX



# **Spherical Estimator**

- Approach: Instead of a regular mesh, overlay a collection of spheres for tallying fission source points.
- Properties:
  - 1. Center of spheres guaranteed to be in fissionable material.
  - 2. All regions with fissionable material covered by a sphere.
  - 3. Have a physics-based radius and minimum separation distances.
  - 4. May overlap, and then fission source points contribute based on proximity to center.





### **Fission Distance**

- Define the *fission distance* as some average straight-line distance between source and fission site.
- Empirically determined that square of the average of square-root of distances appears to work well.

$$L = \left[\frac{1}{M}\sum_{i=1}^{M}||\mathbf{r}_s - \mathbf{r}_f||^{1/2}\right]^2,$$



Operated by Los Alamos National Security, LLC for the U.S. Department of Energy's NNSA

LA-UR-12-XXXXX



# **Placement Algorithm**

- 1. Bounding box is defined to cover the problem, and a temporary regular "scaffolding" mesh with approximate edge length 2*L*.
- 2. In a random order for each scaffolding mesh, randomly sample points until one lies in fissionable material or some maximum samples exceeded.
- 3. If/when a point is found:
  - Check to see if it is within distance *L* of another (previously placed) estimator center.
  - If it is not, create a new spherical estimator centered at that point.
  - Store this element as a candidate for more elements and continue to the next element.
- 4. Go back to 2 if new estimators were added, else end.





# **Scoring the Estimators**

- If fission source point *i* in only one estimator, score 1 to that estimator.
- Otherwise score a fraction to each estimator *j*, *w<sub>ji</sub>*, based upon proximity to center using a 3-D tent function.

$$\tau_{ji} = 1 - \left|\left|\mathbf{r}_{i} - \mathbf{r}_{j}\right|\right| / 2L$$

$$w_{ji} = \frac{\tau_{ji}}{\sum_{j;\tau_{ji}>0}\tau_{ji}}$$



Operated by Los Alamos National Security, LLC for the U.S. Department of Energy's NNSA

LA-UR-12-XXXXX



# **Calculating Shannon Entropy**

• Entropy computed similarly, except that fission source points may have more than one "state".

$$H = -\sum_{j=1}^{J} p_j \log(p_j)$$

$$p_j = rac{1}{M}\sum_{i=1}^M w_{ji}$$



Operated by Los Alamos National Security, LLC for the U.S. Department of Energy's NNSA

LA-UR-12-XXXXX



### **Test Problems**

- 1. Godiva: Bare HEU sphere.
- 2. <u>3-D Full Core PWR:</u> Hoogenboom-Martin benchmark.
- 3. <u>k-eff of the World:</u>  $9 \times 9 \times 9$  array of Pu-239 spheres.
- 4. OECD Fuel Storage Pool: Source convergence benchmark (very hard).

• Each calculation uses 20,000 neutrons per cycle.



Operated by Los Alamos National Security, LLC for the U.S. Department of Energy's NNSA LA-UR-12-XXXXX



Table: Estimator Placement Information.

	<i>L</i> (cm)	Number
Godiva	3.10	88
PWR	13.66	10,762
<i>k</i> -Eff World	12.10	729
Fuel Pool	8.81	8,153



Operated by Los Alamos National Security, LLC for the U.S. Department of Energy's NNSA

LA-UR-12-XXXXX



### **Estimators Illustrated**




Figure: PWR Mid-Plane Slice of the Estimator Spheres.




Operated by Los Alamos National Security, LLC for the U.S. Department of Energy's NNSA

LA-UR-12-XXXXX



### **Estimators Illustrated**



### Figure: Fuel Pool Estimator Spheres.



Operated by Los Alamos National Security, LLC for the U.S. Department of Energy's NNSA

LA-UR-12-XXXXX



# Shannon Entropy




Figure: Shannon Entropy User-Defined Mesh Versus Automated Spherical Estimators



Operated by Los Alamos National Security, LLC for the U.S. Department of Energy's NNSA

LA-UR-12-XXXXX



# **Sampling Diagnostics**

Table: Number of Histories Required to Satisfy Sampling Thresholds.

	>99.9% Sampled	>99% Error $<$ 10%
Godiva	< 20k	960k
PWR	440k	8.8M
<i>k</i> -Eff World	< 20k	6.6M
Fuel Pool	>> 100M	>> 100M



Operated by Los Alamos National Security, LLC for the U.S. Department of Energy's NNSA

LA-UR-12-XXXXX



- Automated placement algorithm for spherical estimators developed.
- Distance is "physics based".
- Able to reproduce Shannon entropy to within additive constant.
- More research needed on sampling diagnostics, but provides a basis.





### **Questions?**



Operated by Los Alamos National Security, LLC for the U.S. Department of Energy's NNSA

LA-UR-12-XXXXX

